The kaucollection class*

Stefan Berthold stefan.berthold@kau.se

November 21, 2012

1 Introduction

The kaucollection class provides LATEX defaults and macros which you might find useful during this process.

2 Usage

Load the class without options.

3 Implementation

No class options are accepted.

1 \ProcessOptions\relax

For simplicity, we'll derive everything from the standard article class.

2 \LoadClass{article}

Load dependencies.

- 3 \RequirePackage{kauclear}
- 4 \RequirePackage{kaustudies}
- 5 \RequirePackage{kaumeta}
- 6 \RequirePackage{kaupaper}
- 7 \RequirePackage{kauenvironments}
- 8 \RequirePackage{tikz}

\kuk@maketitle Preserve the previous definition of \maketitle.

9 \AtBeginDocument{\let\kuk@maketitle\maketitle}

\maketitle Make sure that the title page has a white backside.

- 10 \renewcommand\maketitle{%
- 11 \kuk@maketitle%12 \cleardoublepage%
- 13 }

^{*}This document corresponds to kaucollection v1.1, dated 2011/05/06.

```
Make sure that the table of contents starts on an odd page.
                  14 \let\kuk@tableofcontents\tableofcontents
                  15 \renewcommand\tableofcontents{%
                      \cleardoublepage%
                  17
                       \kuk@tableofcontents%
                  18 }
                      Preserve the old abstract environment for later usage in the appended papers.
                  19 \let\kuk@abstract\abstract%
                  20 \let\kuk@endabstract\endabstract%
                 Start the frontmatter, beginning with page iii and redefining the abstract environ-
    \frontmatter
                  ment so that it generates an own section.
                  21 \newcommand*\frontmatter{\%}
                  22
                      \clearpage%
                       \verb|\setcounter{page}{3}||
                  23
                       \renewcommand\thepage{\roman{page}}%
                  24
                       \renewenvironment{abstract}{%
                  25
                         \newcommand\keywords{\paragraph{Keywords:}}%
                  26
                         \cleardoublepage%
                  27
                  28
                         \section*{\@title}%
                  29
                         \textsc{\@author}\par%
                  30
                         \noindent\textit{\@institute}%
                  31
                         \section*{Abstract}%
                         %\addcontentsline{toc}{section}{Abstract}%
                  32
                  33
                      }{%
                  34
                         \cleardoublepage%
                  35
                      }%
                  36 }
                  Acknowledgements section.
{\tt acknowledgements}
                  37 \newenvironment{acknowledgements}{%
                      \cleardoublepage%
                  38
                      \section*{Acknowledgements}%
                  39
                  40 %\addcontentsline{toc}{section}{Acknowledgements}%
                  41 }{%
                       \par\bigskip\bigskip\noindent\@place, \@date\hfill \@author%
                  42
                  43
                       \cleardoublepage%
                  44 }
     \mainmatter Start the mainmatter with the part 'Introductory Summary' on page 1.
                  45 \newcommand\mainmatter[1][]{%
                  46 \cleardoublepage%
                  47 \renewenvironment{abstract}{\kuk@abstract}{\kuk@endabstract}
                      \setcounter{page}{1}%
                  48
                      \renewcommand\thepage{\arabic{page}}%
                  49
                  50
                       \kaupart*[body={#1}]{Introductory Summary}%
                  51 }
                 Typeset quotes on cover pages.
    \vanityquote
                  52 \newcommand\vanityquote[2]{%
                       \begin{tikzpicture}[remember picture,overlay]%
                  54
                         \path (current page.south east) +(-3,3.5)%
                  55
                           node%
```

Change History

v1.0 v1.1 General: SBe's licentiate version . . . 1 General: Initial public release 1

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

${f Symbols}$	${f F}$	\normalfont 60
\@author 29, 42	\frontmatter 21	
\@date 42		P
\@institute 30	\mathbf{H}	\par 29, 42, 60
\@place 42	\hfill 42	\paragraph 26
\@title 28		\path 54
	${f I}$	\ProcessOptions 1
\mathbf{A}	\itshape 60	-
\abstract 19		$\mathbf R$
acknowledgements (en-	K	\raggedleft 59
vironment) 37	\kaupart 50	\relax 1
\addcontentsline 32, 40	\keywords 26	\renewcommand
\arabic 49	\kuk@abstract 19, 47	\dots 10, 15, 24, 49
\AtBeginDocument 9	\kuk@endabstract 20,47	\renewenvironment 25, 47
_	\kuk@maketitle 9 , 11	\RequirePackage 3-8
${f B}$	\kuk@tableofcontents	\rlap 59
\begin 53	$\dots \dots 14, 17$	\roman 24
\bigskip 42		
	${f L}$	${f S}$
${f C}$	\large 57	\section 28, 31, 39
\cleardoublepage	\let $9, 14, 19, 20$	\setcounter 23, 48
$\dots 12, 16,$	\LoadClass 2	
27, 34, 38, 43, 46		${f T}$
\clearpage 22	${f M}$	\t tableofcontents 14, 15
	\mainmatter $\underline{45}$	\textit 30
${f E}$	\maketitle $9, \underline{10}$	\textsc 29
\end 61	\medskip 60	\thepage 24, 49
\endabstract 20		
environments:	N	${f V}$
acknowledgements 37	\noindent $\dots 30, 42$	\vanityquote $\underline{52}$