

The kaumeeting class*

Stefan Berthold
stefan.berthold@kau.se

December 14, 2012

1 Introduction

The `kaumeeting` class is part of the `kauthesis` package. The class provides macros for writing meeting records. The latest version can be obtained from

`http://github.com/ZjMNZHgG5jMXw/kauthesis` .

This class requires the URW Garamond font. The latest version can be obtained from

`http://www.ctan.org/pkg/urw-garamond` .

This class also requires the logo of Karlstad Univerity. The latest version can be obtained from

`http://www.kau.se/om-universitetet/pressinformation/ladda-hem-logotyp` .

2 Usage

The following example can be found in `kaumeetingtemplate.tex`.

After loading the class, complete the meta data with `\metadata{<data>}`.

```
1 \documentclass{kaumeeting}
2 \metadata{<data>}
```

The subject of the meeting, e.g., a course name.

```
3 { meeting={}
```

The person who is writing the protocol.

```
4 , protocol={}
```

The place of the meeting.

```
5 , place={}
```

The calendar date of the meeting.

```
6 , date={}
```

The time when the meeting began.

```
7 , start={}
```

*This document corresponds to `kaumeeting` v1.0, dated 2011/11/18.

The time when the meeting was over.

```
8   , end={}
```

The persons who attended the meeting.

```
9   , participants={}
```

Persons excused from the meeting.

```
10  , excused=none
```

Persons missing from the meeting without excuse.

```
11  , missing={}
```

The distribution list of the meeting records.

```
12  , distribution={}
```

The faculty and department names.

```
13  , faculty={Faculty of Health, Science and Technology}%
14  , department={Department of Mathematics and Computer Science}%
```

The name (or location) of Karlstad University's logo.

```
15  , logfile={kau-logo-tryck}
16  }
```

The macro `\maketitle` creates the record header from the meta data.

```
17 \begin{document}
18 \maketitle
```

After `\maketitle`, content can be added like in a \LaTeX article.

```
19 \end{document}
```

3 Implementation

3.1 Class options and dependencies

Class options are neither parsed nor passed to the underlying article class.

```
1 \ProcessOptions\relax
```

`kaumeeting` derives all macros from the standard article class.

```
2 \LoadClass{article}
```

Garamond is chosen as default font.

```
3 \RequirePackage[urw-garamond]{mathdesign}
```

A4 is set as the default page layout.

```
4 \RequirePackage[paper=a4,pagesize]{typearea}
```

```
5 \RequirePackage{xkeyval}
```

```
6 \RequirePackage{graphicx}
```

```
7 \RequirePackage{tikz}
```

```
8 \RequirePackage{tabularx}
```

```
9 \RequirePackage{ragged2e}
```

```
10 \RequirePackage{xifthen}
```

3.2 Meta data

`\metadata`

```

11 \define@cmdkeys[kaumet]{general}[kaumet@]%
12 { meeting, protocol, place%
13 , date, start, end%
14 , participants, excused, missing%
15 , distribution%
16 , faculty, department%
17 , logfile%
18 }
19 \newcommand\metadata[1]{\setkeys[kaumet]{general}{#1}}
20 \setkeys[kaumet]{general}%
21 { meeting=, protocol=, place=
22 , date=\today, start=, end=
23 , participants=, excused=, missing=
24 , distribution=
25 , faculty={Faculty of Health, Science and Technology}%
26 , department={Department of Mathematics and Computer Science}%
27 , logfile={kau-logo-tryck}
28 }
```

3.3 Title page

`\kaumet@maketitle` The definition of `\maketitle` in the article class creates a title without creating a separate page. `kaumeeting` redefines the macro and preserves the original definition in `\kaumas@maketitle`.

```

29 \let\kaumet@maketitle\maketitle
```

`\maketitle`

```

30 \renewcommand\maketitle{
31   \thispagestyle{empty}
32   \begin{tikzpicture}[overlay,remember picture]
33     % top
34     \path (current page.north)
35       node[below=5mm, text centered, text width=\textwidth] (top)
36       {\includegraphics[width=33mm]{\kaumet@logfile}\[5mm]%
37        \kaumet@faculty\\%
38        \kaumet@department}
39     ;
40   \end{tikzpicture}
41   \vspace{1.5cm}\\
42   \mbox{}\hfill\kaumet@date\\
43   \centering \Large\scshape Meeting Record\\
44   \justifying\normalfont\bigskip\small\noindent
45   \begin{tabularx}{\textwidth}{@{}>{\bfseries\phantom{Xy}}rX}
46     subject & \kaumet@meeting\\
47     place & \kaumet@place\\
48     start & \kaumet@start\\
49     end & \kaumet@end\\
50     participants & \kaumet@participants\\
51     recording & \kaumet@protocol\\
52     excused & \kaumet@excused\\

```

```

53   missing & \kaumet@missing\\
54   distribution & \kaumet@distribution
55   \end{tabularx}\smallskip
56   \justifying\normalfont\normalsize
57 }

```

Change History

v1.0

General: Initial public release 1

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	<code>\kaumet@department</code> . 38	<code>\normalsize</code> 56
<code>\</code> . 36, 37, 41–43, 46–53	<code>\kaumet@distribution</code> 54	
	<code>\kaumet@end</code> 49	P
B	<code>\kaumet@excused</code> . . . 52	<code>\path</code> 34
<code>\begin</code> 17, 32, 45	<code>\kaumet@faculty</code> . . . 37	<code>\ProcessOptions</code> 1
<code>\bfseries</code> 45	<code>\kaumet@logfile</code> . . 36	
<code>\bigskip</code> 44	<code>\kaumet@maketitle</code> . <u>29</u>	R
	<code>\kaumet@meeting</code> . . . 46	<code>\relax</code> 1
C	<code>\kaumet@missing</code> . . . 53	<code>\renewcommand</code> 30
<code>\centering</code> 43	<code>\kaumet@participants</code> 50	<code>\RequirePackage</code> . . 3–10
	<code>\kaumet@place</code> 47	
D	<code>\kaumet@protocol</code> . . 51	S
<code>\define@cmdkeys</code> . . . 11	<code>\kaumet@start</code> 48	<code>\scshape</code> 43
<code>\documentclass</code> 1		<code>\setkeys</code> 19, 20
E	L	<code>\small</code> 44
<code>\end</code> 19, 40, 55	<code>\Large</code> 43	<code>\smallskip</code> 55
	<code>\let</code> 29	
H	<code>\LoadClass</code> 2	T
<code>\hfill</code> 42		<code>\textwidth</code> 35, 45
I	M	<code>\thispagestyle</code> 31
<code>\includegraphics</code> . . 36	<code>\maketitle</code> . . 18, 29, <u>30</u>	<code>\today</code> 22
	<code>\mbox</code> 42	
J	<code>\metadata</code> 2, <u>11</u>	V
<code>\justifying</code> 44, 56	N	<code>\vphantom</code> 45
K	<code>\noindent</code> 44	<code>\vspace</code> 41
<code>\kaumet@date</code> 42	<code>\normalfont</code> 44, 56	