

# The kauprotocol bundle\*

Stefan Berthold  
stefan.berthold@kau.se

May 28, 2013

## 1 Introduction

The `kauhead` package, the `kaunote` class, and the `kaumeeting` class are part of the `kauthesis` package. The classes provide macros for writing notes and meeting records. The latest version can be obtained from

<http://github.com/ZjMNZHgG5jMXw/kauthesis> .

This package and the classes require the URW Garamond font. The latest version can be obtained from

<http://www.ctan.org/pkg/urw-garamond> .

This package and the classes also require the logo of Karlstad University. The latest version can be obtained from

<http://www.kau.se/om-universitetet/pressinformation/ladda-hem-logotyp> .

## 2 Usage

The following example can be found in `kaumeetingtemplate.tex`.

After loading the class, complete the meta data with `\metadata{<data>}`.

```
1 <*meetingtemplate>
2 \documentclass{kaumeeting}
3 \metadata{
```

The subject of the meeting, e. g., a course name.

```
4 { meeting={}
```

The person who is writing the protocol.

```
5 , protocol={}
```

The place of the meeting.

```
6 , place={}
```

The calendar date of the meeting.

```
7 , date={}
```

---

\*This document corresponds to `kauprotocol` v1.10, dated 2013/05/28.

The time when the meeting began.

```
8   , start={}
```

The time when the meeting was over.

```
9   , end={}
```

The persons who attended the meeting.

```
10  , participants={}
```

Persons excused from the meeting.

```
11  , excused=none
```

Persons missing from the meeting without excuse.

```
12  , missing={}
```

The distribution list of the meeting records.

```
13  , distribution={}
```

The faculty and department names.

```
14  , faculty={Faculty of Health, Science and Technology}%
15  , department={Department of Mathematics and Computer Science}%
```

The name (or location) of Karlstad University's logo.

```
16  , logfile={kau_2012_cmyk_eps_14679}
17  }
```

The macro `\maketitle` creates the record header from the meta data.

```
18 \begin{document}
19 \maketitle
```

After `\maketitle`, content can be added like in a L<sup>A</sup>T<sub>E</sub>X article.

```
20 \end{document}
21 \</meetingtemplate>
```

### 3 kauhead package

#### 3.1 Package options and dependencies

Package options are neither parsed nor passed to the underlying article class.

```
1 <*head>
2 \ProcessOptions\relax
```

Garamond is chosen as default font.

```
3 \RequirePackage[urw-garamond]{mathdesign}
```

A4 is set as the default page layout.

```
4 \RequirePackage[paper=a4,pagesize]{typearea}

5 \RequirePackage{xkeyval}
6 \RequirePackage{graphicx}
7 \RequirePackage{tikz}
8 \RequirePackage{ragged2e}
```

## 3.2 Meta data

```
\headdata
    9 \define@cmdkeys[kauhed]{general}[kauhed@]%
   10 { title, date%
   11   , faculty, department%
   12   , logfile%
   13 }
   14 \newcommand\headdata[1]{\setkeys[kauhed]{general}{#1}}
   15 \setkeys[kauhed]{general}%
   16 { title=, date=\today%
   17   , faculty={Faculty of Health, Science and Technology}%
   18   , department={Department of Mathematics and Computer Science}%
   19   , logfile={kau_2012_cmyk_eps_14679}%
   20 }
```

## 3.3 Title page

`\kauhed@maketitle` kauhead redefines the macro and preserves the original definition in `\kauhed@maketitle`.

```
21 \let\kauhed@maketitle\maketitle
```

```
\maketitle
22 \renewcommand\maketitle{
23   \thispagestyle{empty}
24   \begin{tikzpicture}[overlay,remember picture]
25     \path (current page.north)
26       node[below=5mm, text centered, text width=\textwidth] (top)
27       {\includegraphics[width=33mm]{\kauhed@logfile}\[3mm]%
28       \kauhed@faculty\\%
29       \kauhed@department}
30   ;
31   \end{tikzpicture}
32   \vspace{1.5cm}\\
33   \mbox{\hfill\kauhed@date\\
34   \centering\Large\scshape\kauhed@title\\
35   \justifying\normalfont\bigskip\normalsize
36 }
37 \end{head}
```

## 4 kaunote class

### 4.1 Class options and dependencies

Class options are neither parsed nor passed to the underlying article class.

```
1 (*note)
2 \ProcessOptions\relax
```

kaunote derives all macros from the standard article class.

```
3 \LoadClass{article}
```

kauhead package is loaded.

```
4 \RequirePackage{kauhead}
```

## 4.2 Meta data

```
\metadata
5 \newcommand\metadata[1]{\setkeys[kauhed]{general}{#1}}
```

## 4.3 Title page

```
\kaunot@title kaunote redefines the macro \title and preserves the original definition in
\kaunot@title.
6 \let\kaunot@title\title
```

```
\title
7 \renewcommand\title[1]{\setkeys[kauhed]{general}{title={#1}}}
```

```
\kaunot@maketitle kaunote redefines the macro \maketitle and preserves the original definition in
\kaunot@maketitle.
8 \let\kaunot@maketitle\maketitle
```

```
\maketitle
9 \renewcommand\maketitle{%
10 \kaunot@maketitle\par\medskip\@afterindentfalse\@afterheading%
11 }
12 </note>
```

## 5 kaumeeting class

### 5.1 Class options and dependencies

Class options are neither parsed nor passed to the underlying article class.

```
1 <*meeting>
2 \ProcessOptions\relax
```

kaumeeting derives all macros from the standard article class.

```
3 \LoadClass{article}
```

kauhead package is loaded.

```
4 \RequirePackage{kauhead}
5 \RequirePackage{tabularx}
```

### 5.2 Meta data

```
\metadata
6 \define@cmdkeys[kamet]{general}[kamet@]{%
7 { meeting, protocol, place%
8 , start, end%
9 , participants, excused, missing%
10 , distribution%
11 }
12 \define@cmdkey[kamet]{general}[kamet@]{date}%
13 {\setkeys[kauhed]{general}{date={#1}}}
14 \define@cmdkey[kamet]{general}[kamet@]{faculty}%
15 {\setkeys[kauhed]{general}{faculty={#1}}}
```

```

16 \definecmdkey[kaumet]{general}[kaumet@]{department}%
17   {\setkeys[kauhed]{general}{department={#1}}}
18 \definecmdkey[kaumet]{general}[kaumet@]{logfile}%
19   {\setkeys[kauhed]{general}{logfile={#1}}}
20 \newcommand\metadata[1]{\setkeys[kaumet]{general}{#1}}
21 \setkeys[kauhed]{general}{title=Meeting record}%
22 \setkeys[kaumet]{general}%
23   { meeting=, protocol=, place=
24     , date=\today, start=, end=
25     , participants=, excused=, missing=
26     , distribution=
27     , faculty={Faculty of Health, Science and Technology}%
28     , department={Department of Mathematics and Computer Science}%
29     , logfile={kau_2012_cmyk_eps_14679}%
30   }

```

### 5.3 Title page

`\kaumet@maketitle` kaumeeting redefines the macro and preserves the original definition in `\kaumet@maketitle`.

```

31 \let\kaumet@maketitle\maketitle

```

`\maketitle`

```

32 \renewcommand\maketitle{
33   \kaumet@maketitle%
34   \noindent\small%
35   \begin{tabularx}{\textwidth}{@{}>{\bfseries\vphantom{Xy}}rX}
36     subject & \kaumet@meeting\\
37     place & \kaumet@place\\
38     start & \kaumet@start\\
39     end & \kaumet@end\\
40     participants & \kaumet@participants\\
41     recording & \kaumet@protocol\\
42     excused & \kaumet@excused\\
43     missing & \kaumet@missing\\
44     distribution & \kaumet@distribution
45   \end{tabularx}\smallskip
46   \justifying\normalfont\normalsize
47 }
48 \</meeting>

```

## Change History

v1.0	thesis bundle as protocol bundle with classes kaunote and kaumeeting . . . . . 1
v1.10	General: Initial public release . . . . 1
	General: Integration in the kau-

# Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	K	N
\@afterheading .... 10	\kauhed@date ..... 33	\noindent ..... 34
\@afterindentfalse . 10	\kauhed@department . 29	\normalfont ..... 35, 46
\\ . 27, 28, 32–34, 36–43	\kauhed@faculty ... 28	\normalsize ..... 35, 46
	\kauhed@logfile .. 27	
	\kauhed@maketitle . <u>21</u>	<b>P</b>
<b>B</b>	\kauhed@title ..... 34	\par ..... 10
\begin ..... 18, 24, 35	\kaumet@distribution 44	\path ..... 25
\bfseries ..... 35	\kaumet@end ..... 39	\ProcessOptions .... 2
\bigskip ..... 35	\kaumet@excused ... 42	
	\kaumet@maketitle <u>31</u> , 33	<b>R</b>
<b>C</b>	\kaumet@meeting ... 36	\relax ..... 2
\centering ..... 34	\kaumet@missing ... 43	\renewcommand 7, 9, 22, 32
	\kaumet@participants 40	\RequirePackage ... 3–8
<b>D</b>	\kaumet@place ..... 37	
\define@cmdkey ....	\kaumet@protocol .. 41	<b>S</b>
.... 12, 14, 16, 18	\kaumet@start ..... 38	\scshape ..... 34
\define@cmdkeys .. 6, 9	\kaunot@maketitle <u>8</u> , 10	\setkeys ..... 5,
\documentclass ..... 2	\kaunot@title ..... <u>6</u>	7, 13–15, 17, 19–22
		\small ..... 34
<b>E</b>	<b>L</b>	\smallskip ..... 45
\end ..... 20, 31, 45	\Large ..... 34	
	\let ..... 6, 8, 21, 31	<b>T</b>
<b>H</b>	\LoadClass ..... 3	\textwidth ..... 26, 35
\headdata ..... <u>9</u>		\thispagestyle .... 23
\hfill ..... 33	<b>M</b>	\title ..... 6, <u>7</u>
	\maketitle ..... 8,	\today ..... 16, 24
<b>I</b>	<u>9</u> , 19, 21, <u>22</u> , 31, <u>32</u>	
\includegraphics .. 27	\mbox ..... 33	<b>V</b>
	\medskip ..... 10	\vphantom ..... 35
<b>J</b>	\metadata ..... 3, <u>5</u> , <u>6</u>	\vspace ..... 32
\justifying ..... 35, 46		