

# The `kaumeta` package\*

Stefan Berthold  
`stefan.berthold@kau.se`

November 21, 2012

## 1 Introduction

The `kaumeta` package defines three macros, `\subject`, `\institute`, and `\place`, for providing additional meta data about the document and its author. This meta data can be used, e. g., on the title page of the document.

## 2 Usage

Load the package without options.

## 3 Implementation

No package options are accepted.

```
1 \ProcessOptions\relax
```

Load dependencies.

```
2 \usepackage{ifthen}
```

`\subject` The macro `\subject{<subject>}` can be used to set the subject of the document.  
`\@subject` The last `<subject>` set will be available in the macro `\@subject`.

```
3 \newcommand*\@subject{}
```

```
4 \newcommand\subject[1]{\renewcommand*\@subject{#1}}
```

`\institute` The macro `\institute[<short>]{<institute>}` can be used to set the institute of the document's author. It is possible to provide a shorter version of the institute in the optional argument `<short>`. If not explicitly set, the short version is the same as the long version `<institute>`. The values are available in the macros `\@institute` and `\@shortinstitute`.

`\@institute`  
`\@shortinstitute`

```
5 \newcommand*\@institute{}
```

```
6 \newcommand*\@shortinstitute{}
```

```
7 \newcommand\institute[2][]{\%
```

```
8   \renewcommand*\@institute{#2}%
```

```
9   \ifthenelse{\equal{#1}{} }{\%
```

```
10     \renewcommand*\@shortinstitute{#2}%
```

```
11   }{\%
```

---

\*This document corresponds to `kaumeta` v1.1, dated 2011/05/06.

```

12 \renewcommand*\@shortinstitute{#1}%
13 }%
14 }

```

`\place` The macro `\place{<place>}` can be used to set the place of the document's author.  
`\@place` The last `<place>` set will be available in the macro `\@place`.

```

15 \newcommand*\@place{}
16 \newcommand\place[1]{\renewcommand*\@place{#1}}

```

## Change History

v1.0		v1.1
General: SBe's licentiate version . . .	1	General: Initial public release . . . . . 1

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	I	R
<code>\@institute</code> . . . . . <i>1</i> , 5, 8	<code>\ifthenelse</code> . . . . . 9	<code>\relax</code> . . . . . 1
<code>\@place</code> . . . . . <i>2</i> , 15, 16	<code>\institute</code> . . . . . <u>5</u>	
<code>\@shortinstitute</code> . . . . . <i>1</i> , 6, 10, 12		<b>S</b>
<code>\@subject</code> . . . . . <i>1</i> , 3, 4	<b>P</b>	<code>\subject</code> . . . . . <u>3</u>
<b>E</b>	<code>\place</code> . . . . . <u>15</u>	<b>U</b>
<code>\equal</code> . . . . . 9	<code>\ProcessOptions</code> . . . . . 1	<code>\usepackage</code> . . . . . 2