

CSE 101 Homework 6

Brian Masse, Kreshiv Chawla, Taira Sakamoto, Emily Xie, Annabelle Coles

November 25, 2025

1. Recurrence Relations

(a) $T(n) = 4T(\lfloor n/4 \rfloor) + cn^3, n \geq 2, T(1) = c$

(b) $T(n) = 2 * T(n - 3)$ for $n \geq 4, T(1) = c$

(c) $T(n) = T(\lfloor n/4 \rfloor) + c, T(1) = c$

(d) $T(n) = (\log n)T(\lfloor n/2 \rfloor), n \geq 2; T(1) = c.$

2. High Frequency Element

Say we have an array of numbers $A[1..n]$. x is *high frequency* in A if it occurs more than $n/2$ times in A , i.e., there are strictly more than $n/2$ many indices $1 \leq i \leq n$ with $A[i] = x$. Here's an algorithm that finds a high frequency element if one exists (it may return an element if no high frequency element exists):

HF($A[1..n]$)

- (a) If $n = 0$ return "No HF element".
- (b) If $n = 1$ return $A[1]$.
- (c) If n is odd do:
- (d) $Count = 0$
- (e) FOR $I = 1$ to n IF $A[I] = A[n]$ THEN $Count++$
- (f) IF $Count > n/2$ THEN Return $A[n]$
- (g) Initialize an array $B[1.. \lfloor n/2 \rfloor]$.
- (h) $I = 1, J = 1$.
- (i) While $I < n$ do:
- (j) IF $A[I] == A[I + 1]$ THEN $B[J] = A[I], J++$
- (k) $I = I + 2$.
- (l) Return HF($B[1..J - 1]$).

Questions:

- (a) Give the recursive calls the algorithm would make on input $A[1..7] = (1, 4, 3, 3, 2, 3, 3)$.
- (b) Prove that if x is a high-frequency element in $A[1..n]$, then x is a high frequency element in $B[1..J - 1]$ at the end of the loop. (Hint: look at the number of times each of the following occur for consecutive elements of A : Both are x , both are some $y \neq x$, exactly one is x , neither is x and are not equal.)
- (c) Use this to prove that if x is a high-frequency element in $A[1..n]$, then $HF(A[1..n]) = x$.
- (d) Give a worst-case time analysis for this algorithm.

3. Weighted Median

Say that we are given a list of pairs of values and weights, with weights greater than 0, $(v_1, w_1), \dots, (v_n, w_n)$. Let $W = \sum_{1 \leq i \leq n} w_i$ be the total weight. The weighted median is a value v_j with $\sum_{1 \leq i \leq n, v_i < v_j} w_i \leq W/2$ and $\sum_{1 \leq i \leq n, v_i > v_j} w_i \leq W/2$.

For example, if the list had elements $(2, .1), (4, .2), (-3, .2), (1, .4), (5, .1)$, we can compute $W = 1$, so $W/2 = .5$. A weighted median is 1, because the sum of the weights of values less than 1 is .2 and the sum of the weights larger than 1 is $.1 + .2 + .1 = .4$.

Give an efficient algorithm (faster than sorting the list) to compute a weighted median.

```
// pass in the list of pairs, the size of the list, and half the total weight
// The final piece can be precomputed in linear time.
weighted_median(list L, size n, WM):

    // Find the median of the given list (by value, not weight)
    // Using the select algorithm from class
    median = select_lowest(L, n / 2)

    // create 3 sub array for pairs with a value <, =, > the median
    // keep track of their cumulative weight
    SL = []; WL = 0;
    SM = []
    SR = []; WR = 0;

    // loop through the list to build sub arrays.
    for pair in L:
        if pair.value < median.value:
            SL.add(pair)
            WL += pair.weight
        elif pair.value > median.value:
            SR.add(pair)
            WR += pair.weight
        else:
            SM.add(pair)

    // if both sides are less than the target weight, that value is the weighted median
    if (WL < WM && WR < WM):
        return median

    // run the algorithm recursively on whichever subset was greater than the target
    // weight
    if (WL > WM):
        return weighted_median(WL, WL.size(), WM)
    else:
        return weighted_median(WR, WR.size(), WM)
```

Short Correctness Proof

The algorithm recursively calls the select median algorithm discussed in class. It is assumed that, for any set, it correctly returns the median. Once the median is found, the algorithm uses it as a pivot to create 3 partitions: values less than the median, equal to the median, and greater than the median, and calculates the total weight of each partition.

There are 2 outcomes:

- The weight of both subsets are less than $W/2$. This implies the median is the weighted median and returns
- The weight of one of the subsets is greater than $W/2$. In this case, the weighted median must be in the heavier subset, since being in either other subset implies values above or below it sum above $W/2$, violating the definition of the weighted median. Thus, the algorithm runs itself on the smaller subset.

Note: Only 1 subset can have a weight $> W/2$, since all others must have weight $w < W/2$ to all sum to W

Note: A recursive call will never contain an empty set. If there are no numbers above or below the median returned by select, that number is the weighted median.

Analysis / Efficiency

This algorithm can be determined using the master theorem. First note:

- Calculating target weight $\in O(n)$
- Select (from class) $\in O(n \cdot \log(n))$
- partitioning into subsets $\in O(n)$
- The partitions will always be roughly $n/2$ elements large, since they use the median as the pivot, which by definition is in the center of the set.

Together this implies the total time complexity, $T(n)$:

$$T(n) = 1 \cdot T(n/2) + O(n \cdot \log(n))$$

- (a) Only 1 subset is recursively called on \implies 1 subroutine
- (b) With median as input, subroutines are roughly $n/2$
- (c) The total time complexity of each call is dominated by the select median $\implies \in O(n \cdot \log n)$

By the master theorem:

$$\begin{aligned} f(n) &= n \cdot \log(n) \\ &\in \Omega(n^{\log_b(a)}) = \Omega(1) \\ &\implies T(n) \in O(f(n)) \end{aligned}$$

Thus, the total runtime complexity is $O(n \cdot \log n)$

4. Weighted Independent Set for Trees

A subset S of vertices in an undirected graph is an *independent set* if it doesn't contain both ends of any edge. If we assign every vertex a weight $w(x) > 0$, the *maximum weight independent set* is to find the independent set of the graph that has maximum possible total weight of its vertices. While the maximum weight independent set problem is *NP*-hard, some special cases can be solved efficiently. In particular, consider the special case when the underlying graph is a complete binary tree of depth k , so $|V| = 2^{k+1} - 1$. Give a divide-and-conquer algorithm for this problem that runs in polynomial time. (Hint: have your algorithm return not just the weight of the maximum weighted independent set, but both of the values for the two cases, the root is in S and the root is not in S . This problem can be solved using dynamic programming, but it is not required and the dynamic programming solution will not be given any credit for this assignment.) (5 points clear algorithm description, 5 points for short correctness argument, 5 points for correct time analysis, and 5 points for efficiency; the best algorithm is $O(|V|)$ time.)

5. Karatsuba implementation

This problem is designed to teach you an idea that makes divide-and-conquer algorithms that only improve time for huge inputs into ones that give substantial improvements even for moderate sized inputs.

Implement both the Karatsuba method for multiplying polynomials from the ungraded problems above and a straight-forward $O(n^2)$ polynomial multiplication algorithm. Collect average running times for a wide range of input sizes n , say powers of 2 until the algorithm is taking over 15 minutes to run, for random polynomials with coefficients 0 or 1. Graph these on a log-log scale, $\log n$ vs. \log (algorithm time). How big are inputs where the Karatsuba method is faster, or how big would you interpolate such inputs to be from your data (if there are no actual data points where Karatsuba is better)? Then try a hybrid algorithm, where we use the Karatsuba recursion when $n > T$ and the quadratic time method in recursive calls when $n \leq T$. For a wide range of possible T 's, starting with rather small values such as $T = 16$, graph the hybrid's performance and compare to the other two. What do you conclude from this experiment?

(2 points clearly describing features of implementation and experiment, such as PL, libraries, type of computer, etc. For each of Karatsuba, quadratic algorithm and hybrid, 2 points for running experiment with adequate variety of input sizes and 2 points for clearly presenting results. 6 points for conclusions based on comparing results.)