

## 11. A bit of C++

# Roadmap

- > C++ vs C
- > C++ vs Java
- > References vs pointers
- > C++ classes: Orthodox Canonical Form
- > A quick look at STL — The Standard Template Library



# Roadmap

- > **C++ vs C**
- > C++ vs Java
- > References vs pointers
- > C++ classes: Orthodox Canonical Form
- > A quick look at STL — The Standard Template Library




## Essential C++ Texts

- > Bjarne Stroustrup, *The C++ Programming Language* (Special Edition), Addison Wesley, 2000.
- > Stanley B. Lippman and Josee LaJoie, *C++ Primer*, Third Edition, Addison-Wesley, 1998.
- > Scott Meyers, *Effective C++*, 2d ed., Addison-Wesley, 1998.
- > James O. Coplien, *Advanced C++: Programming Styles and Idioms*, Addison-Wesley, 1992.
- > David R. Musser, Gilmer J. Derge and Atul Saini, *STL Tutorial and Reference Guide*, 2d ed., Addison-Wesley, 2000.
- > Erich Gamma, Richard Helm, Ralph Johnson and John Vlissides, *Design Patterns*, Addison Wesley, Reading, MA, 1995.

P2 — A bit of C++


# Object-oriented language genealogy

1950



# What is C?

- > C is a general purpose, procedural, imperative language developed in 1972 by Dennis Ritchie at Bell Labs for the Unix Operating System.
  - Low-level access to memory
  - Language constructs close to machine instructions
  - Used as a “*machine-independent assembler*”



# My first C Program

A preprocessor directive

Include standard io  
declarations

```
#include <stdio.h>
```

```
int main(void)  
{
```

Write to  
standard  
output

```
    printf("hello, world\n");  
    return 0;
```

char array

Indicate correct termination


```
}
```

# What is C++?



A “*better C*” (<http://www.research.att.com/~bs/C++.html>) that supports:

- > Systems programming
- > Object-oriented programming (*classes* & *inheritance*)
- > Programming-in-the-large (*namespaces*, *exceptions*)
- > Generic programming (*templates*)
- > Reuse (large class & template libraries)





# C++ vs C


**Most C programs are also C++ programs.**

*Nevertheless, good C++ programs usually do not resemble C:*

- > avoid macros (use inline)
- > avoid pointers (use references)
- > avoid malloc and free (use new and delete)
- > avoid arrays and char\* (use vectors and strings) ...
- > avoid structs (use classes)

*C++ encourages a different style of programming:*

- > avoid procedural programming
  - *model your domain* with classes and templates



# Roadmap

- > C++ vs C
- > **C++ vs Java**
- > References vs pointers
- > C++ classes: Orthodox Canonical Form
- > A quick look at STL — The Standard Template Library



# Hello World in Java

```
package p2;  
// My first Java program!  
public class HelloMain {  
    public static void main(String[] args) {  
        System.out.println("hello world!");  
        return 0;  
    }  
}
```

# “Hello World” in C++

Use the standard namespace

Include standard  
iostream classes

A C++ comment

cout is an  
instance of  
ostream

```
using namespace std;  
#include <iostream>  
// My first C++ program!  
int main(void)  
{  
    cout << "hello world!" << endl;  
    return 0;  
}
```

operator overloading  
(two *different* argument types!)

# Makefiles / Managed Make in CDT

You could compile it all together by hand:

```
c++ helloWorld.cpp -o helloWorld
```


Or you could use a *Makefile* to manage dependencies:

```
helloWorld : helloWorld.cpp
```

```
c++ $@.cpp -o $@
```

```
make helloWorld
```

Or you could use *cdt with eclipse* to create a standard managed make project



# C++ Design Goals

*“C with Classes” designed by Bjarne Stroustrup in early 1980s:*

- > Originally a translator to C
  - Initially difficult to debug and inefficient
- > Mostly *upward compatible* extension of C
  - “As close to C as possible, but no closer”
  - Stronger type-checking
  - Support for object-oriented programming
- > Run-time efficiency
  - Language primitives close to machine instructions
  - *Minimal cost for new features*

# C++ Features

<b><i>C with Classes</i></b>	Classes as structs Inheritance; virtual functions Inline functions
<b><i>C++ 1.0 (1985)</i></b>	Strong typing; function prototypes new and delete operators
<b><i>C++ 2.0</i></b>	Local classes; protected members Multiple inheritance
<b><i>C++ 3.0</i></b>	Templates Exception handling
<b><i>ANSI C++ (1998)</i></b>	Namespaces RTTI (Runtime Type Information)

# Java and C++ — Similarities and Extensions

## ***Similarities:***

- > primitive data types (in Java, platform independent)
- > syntax: control structures, exceptions ...
- > classes, visibility declarations (public, private)
- > multiple constructors, this, new
- > types, type casting (safe in Java, not in C++)
- > comments

## ***Some Java Extensions:***

- > garbage collection
- > standard abstract machine
- > standard classes (came later to C++)
- > packages (now C++ has namespaces)
- > final classes
- > autoboxing
- > generics instead of templates



# Java Simplifications of C++

- > no pointers — **just references**
- > no functions — can declare **static** methods
- > no global variables — use **public static** variables
- > no destructors — **garbage collection** and **finalize**
- > no linking — **dynamic class loading**
- > no header files — can define **interface**
- > no operator overloading — **only method overloading**
- > no member initialization lists — call **super** constructor
- > no preprocessor — **static final constants** and automatic inlining
- > no multiple inheritance — **implement multiple interfaces**
- > no structs, unions, enums — **typically not needed**

# New Keywords

In addition the **keywords** inherited from C, C++ **adds**:

<b><i>Exceptions</i></b>	<code>catch, throw, try</code>
<b><i>Declarations:</i></b>	<code>bool, class, enum, explicit, export, friend, inline, mutable, namespace, operator, private, protected, public, template, typename, using, virtual, volatile, wchar_t</code>
<b><i>Expressions:</i></b>	<code>and, and_eq, bitand, bitor, compl, const_cast, delete, dynamic_cast, false, new, not, not_eq, or, or_eq, reinterpret_cast, static_cast, this, true, typeid, xor, xor_eq</code>

(**see** <http://www.glenmccl.com/glos.htm>)

# Roadmap


- > C++ vs C
- > C++ vs Java
- > **References vs pointers**
- > C++ classes: Orthodox Canonical Form
- > A quick look at STL — The Standard Template Library



# Memory Layout

*The address space consists of (at least):*

<b>Text:</b>	executable program text (not writable)
<b>Static:</b>	static data
<b>Heap:</b>	dynamically allocated global memory (grows upward)
<b>Stack:</b>	local memory for function calls (grows downward)



# Pointers in C++


```
int i;  
int *iPtr; // a pointer to an integer  
  
iPtr = &i; // iPtr contains the address of I  
*iPtr = 100;
```

variable	value	Address in hex
i	...	456FD4
	100	
iPtr	456FD4	456FD0
	...	

# References

A reference is an **alias** for another variable:

```
int i = 10;  
int &ir = i;  // reference (alias)  
ir = ir + 1;  // increment i
```



*Once initialized, references cannot be changed.*

References are especially useful in **procedure calls** to avoid the overhead of passing arguments by value, without the clutter of explicit pointer dereferencing ( `y = *ptr;` )

```
void refInc(int &n)  
{  
    n = n+1; // increment the variable n refers to  
}
```

# References vs Pointers

*References should be preferred to pointers **except** when:*

- > manipulating dynamically allocated objects
  - **new** returns an object pointer
- > a variable must range over a set of objects
  - use a **pointer** to walk through the set

# C++ Classes

C++ classes may be instantiated either *automatically* (on the stack):

```
MyClass oVal;           // constructor called  
                        // destroyed when scope ends
```

or *dynamically* (in the heap)

```
MyClass *oPtr;          // uninitialized pointer  
  
oPtr = new MyClass;     // constructor called  
                        // must be explicitly deleted
```



# Constructors and destructors

Include standard iostream and string classes

```
#include <iostream>
#include <string>

using namespace std;
class MyClass {
private:
    string name;
public:
    MyClass(string name) : name(name) {
        cout << "create " << name << endl;
    }
    ~MyClass() {
        cout << "destroy " << name << endl;
    }
};
```

Use initialization list in constructor

Specify cleanup in destructor

# Automatic and dynamic destruction

```

MyClass& start() {                                // returns a reference
    MyClass a("a");                             // automatic
    MyClass *b = new MyClass("b");               // dynamic
    return *b;                                    // returns a reference (!) to b
}                                                  // a goes out of scope

void finish(MyClass& b) {
    delete &b;                                    // need pointer to b
}

```

```

#include "MyClass.h"
using namespace std;
int main (int argc, char **argv) {
    MyClass aClass("d");
    finish(start());
    return 0;
}

```

*create d*  
*create a*  
*create b*  
*destroy a*  
*destroy b*  
*destroy d*

# Roadmap

- > C++ vs C
- > C++ vs Java
- > References vs pointers
- > **C++ classes: Orthodox Canonical Form**
- > A quick look at STL — The Standard Template Library



# Orthodox Canonical Form

*Most of your classes should look like this:*

```
class myClass {  
public:  
    myClass(void);           // default constructor  
    myClass(const myClass& copy); // copy constructor  
    ...                     // other constructors  
    ~myClass(void);         // destructor  
    myClass& operator=(const myClass&); // assignment  
    ...                     // other public member functions  
private:  
    ...  
};
```

# Why OCF?

If you don't define these four member functions, *C++ will generate them*:

- > ***default constructor***
  - will call default constructor for each data member
- > ***destructor***
  - will call destructor of each data member
- > ***copy constructor***
  - will *shallow copy* each data member
  - pointers will be copied, not the objects pointed to!
- > ***assignment***
  - will *shallow copy* each data member

## Example: A String Class

We would like a `String` class that protects C-style strings:

- > strings are indistinguishable from `char` pointers
- > string updates may cause memory to be corrupted

*Strings should support:*

- > creation and destruction
- > initialization from `char` arrays
- > copying
- > safe indexing
- > safe concatenation and updating
- > output
- > length, and other common operations ...

# A Simple String.h

```

class String
{
    friend ostream& operator<<(ostream&, const String&);
public:
    String(void);           // default construct
    ~String(void);          // destructor
    String(const String& copy); // copy constructor
    String(const char*s);    // char* constructor
    String& operator=(const String&); // assignment
    inline int length(void) const { return ::strlen(_s); }
    char& operator[](const int n) throw(exception);
    String& operator+=(const String&) throw(exception); // concatenation
private:
    char *_s; // invariant: _s points to a null-terminated heap string
    void become(const char*) throw(exception); // internal copy function
};

```

Returns a  
reference  
to ostream

Operator  
overloading

A friend function  
prototype  
declaration of the  
String class

Operator  
overloading of =

inline


# Default Constructors

Every constructor should *establish the class invariant*:

```
String::String(void)
{
    _s = new char[1];
    _s[0] = '\\0';
}
```

Allocate memory  
for the string

*// allocate a char array*  
*// NULL terminate it!*



The *default constructor* for a class is called when a new instance is declared without any initialization parameters:

```
String anEmptyString;           // call String::String()
String stringVector[10];        // call it ten times!
```



# Destructors

The `String` destructor must *explicitly free* any memory allocated by that object.

```
String::~~String (void)
{
    delete [] _s;
}
```

free memory



*Every new must be matched somewhere by a delete!*

- > use `new` and `delete` for *objects*
- > use `new[ ]` and `delete[ ]` for *arrays*!

# Copy Constructors

Our String copy constructor must create a *deep copy*:

```
String::String(const String& copy)
{
    become(copy._s);           // call helper
}

void String::become(const char* s) throw (exception)
{
    _s = new char[sizeof(s) + 1];
    if (_s == 0) throw(logic_error("new failed"));
    ::strcpy(_s, s);
}
```

From std

## A few remarks ...

- > We **must** define a copy constructor,  
... else copies of Strings will *share the same representation!*
  - Modifying one will modify the other!
  - Destroying one will invalidate the other!
  
- > We **must** declare copy as `const`,  
... else we won't be able to construct a copy of a `const String!`
  - Only `const` (*immutable*) operations are permitted on `const` values
  
- > We **must** declare copy as `String&`, not `String`,  
... else a *new copy* will be made before it is passed to the constructor!
  - Functions arguments are always passed by value in C++
  - The “value” of a pointer is a pointer!
  
- > **The abstraction boundary is a class, *not an object*.** Within a class, **all private members are visible** (as is `copy._s`)

## Other Constructors

Class constructors may have arbitrary arguments, as long as their signatures are unique and unambiguous:

```
String::String(const char* s)
{
    become(s);
}
```

Since the argument is not modified, we can declare it as **const**. This will allow us to construct `String` instances from constant `char` arrays.

# Assignment Operators

Assignment is different from the copy constructor because *an instance already exists*:

```
String& String::operator=(const String& copy)
{
    if (this != &copy) {           // take care!
        delete [] _s;
        become(copy._s);
    }
    return *this;                  // NB: a reference, not a copy
}
```

- > Return **String&** rather than void so the result *can be used in an expression*
- > Return **String&** rather than String so the result *won't be copied!*
- > **this** is a pseudo-variable whose value is a pointer to the current object
  - so **\*this** is the value of the current object, which is *returned by reference*

# Implicit Conversion

When an argument of the “wrong” type is passed to a function, the C++ compiler looks for a constructor that will convert it to the “right” type:

```
str = "hello world";
```

*is implicitly converted to:*

```
str = String("hello world");
```

***NB: compare to autoboxing in Java***

# Operator Overloading (indexing)

Not only assignment, but other useful operators can be “overloaded” provided their signatures are unique:

```
char& String::operator[] (const int n) throw(exception)
{
    if ((n<0) || (length()<=n)) {
        throw(logic_error("array index out of bounds"));
    }
    return _s[n];
}
```

*NB: a non-const reference is returned, so can be used as an **lvalue** in an assignment.*

# Overloadable Operators

The following operators may be overloaded:

+	-	*	/	%	^	&	
-	!	,	=	<	>	<=	>=
++	--	<<	>>	==	!=	&&	
+=	-=	/=	%=	^=	&=	=	*=
<<=	>>=	[ ]	( )	->	->*	new	delete

*NB: arity and precedence are fixed by C++*



# Friends

We would like to be able to write:

```
cout << String("TESTING ... ") << endl;
```

But:

- It can't be a member function of `ostream`, since we can't extend the standard library.
- It can't be a member function of `String` since the target is `cout`.
- But it must have access to `String`'s **private data**

So ... we need a binary *function* `<<` that takes a `cout` and a `String` as arguments, and is a *friend* of `String`.

## Friends ...

*We declare:*

```
class String
{
    friend ostream&
        operator<<(ostream&, const String&);
    ...
};
```

*And define:*

```
ostream&
operator<<(ostream& outStream, const String& s)
{
    return outStream << s._s;
}
```

# Roadmap

- > C++ vs C
- > C++ vs Java
- > References vs pointers
- > C++ classes: Orthodox Canonical Form
- > **A quick look at STL — The Standard Template Library**



# Standard Template Library

*STL is a general-purpose C++ library of generic algorithms and data structures.*

1. Containers store *collections of objects*
  - vector, list, deque, set, multiset, map, multimap
2. Iterators *traverse containers*
  - random access, bidirectional, forward/backward ...
3. Function Objects encapsulate *functions as objects*
  - arithmetic, comparison, logical, and user-defined ...
4. Algorithms implement *generic procedures*
  - search, count, copy, random\_shuffle, sort, ...
5. Adaptors provide an *alternative interface* to a component
  - stack, queue, reverse\_iterator, ...

# An STL Line Reverser

```
#include <iostream>
#include <stack>           // STL stacks
#include <string>          // Standard strings












void rev(void)
{
    typedef stack<string> IOStack; // instantiate the template
    IOStack ioStack;              // instantiate the template class
    string buf;

    while (getline(cin, buf)) {
        ioStack.push(buf);
    }
    while (ioStack.size() != 0) {
        cout << ioStack.top() << endl;
        ioStack.pop();
    }
}
```







## What we didn't have time for ...

- > virtual member functions, pure virtuals
- > public, private and multiple inheritance
- > default arguments, default initializers
- > method overloading
- > const declarations
- > enumerations
- > smart pointers
- > static and dynamic casts
- > Templates, STL
- > template specialization
- > namespaces
- > RTTI
- > ...

## *What you should know!*

-  *What **new features** does C++ add to C?*
-  *What **does Java remove** from C++?*
-  *How should you use C and C++ **commenting styles**?*
-  *How does a **reference** differ from a **pointer**?*
-  *When should you use **pointers** in C++?*
-  *Where do **C++ objects** live in memory?*
-  *What is a **member initialization list**?*
-  *Why does C++ need **destructors**?*
-  *What is **OCF** and why is it **important**?*
-  *What's the difference between **delete** and **delete[]**?*
-  *What is **operator overloading**?*

## *Can you answer these questions?*

-  *Why doesn't C++ support garbage collection?*
-  *Why doesn't Java support multiple inheritance?*
-  *What trouble can you get into with references?*
-  *Why doesn't C++ just make deep copies by default?*
-  *How can you declare a class without a default constructor?*
-  *Why can objects of the same class access each others private members?*



# License

<http://creativecommons.org/licenses/by-sa/2.5/>



**You are free:**

- to copy, distribute, display, and perform the work
- to make derivative works
- to make commercial use of the work

**Under the following conditions:**



**Attribution.** You must attribute the work in the manner specified by the author or licensor.



**Share Alike.** If you alter, transform, or build upon this work, you may distribute the resulting work only under a license identical to this one.

- For any reuse or distribution, you must make clear to others the license terms of this work.
- Any of these conditions can be waived if you get permission from the copyright holder.

**Your fair use and other rights are in no way affected by the above.**