



MPPT NEW GENERATION

PRODUCTION DETAILS: USE THIS TO REPORT PROBLEMS TO: +41 (32) 332 79 31

MPPT No.: D0206-074

Title, First Name, Name: Donnie Jones

Team / Organization: Donnie Jones / University of Kentucky Solar Car Team

Address: Company: University of Kentucky

Street 1: Mechanical Engineering

Street 2: 151 RGAN Bldg.

ZIP: 40506-0503 City: Lexington, KY

Country: USA

e-mail: donnie@darthik.com phone: 001 859 257 6336 fax: 001 859 257 3304

ORDER INFORMATION:

5 pcs. of New Generation MPPT's CAN version each US\$ 900.-.

INPUT VOLTAGE RANGE:

Minimum input voltage:	59.9 [V]
Maximum input voltage:	98.2 [V]

OUTPUT VOLTAGE RANGE:

Nominal battery voltage:	103.6 [V]
Type of Batteries:	Li-Polymer

Minimum output voltage:	80 [V]
Maximum output voltage:	115 [V]

INPUT CURRENT:

Maximum input MPP current:	5.54 [A]
Maximum input short circuit current:	6.5 [A]

DELIVERY DETAILS:

Desired date of delivery (DD/MM/YY):	ASAP
Actual date of shipment (DD/MM/YY):	ASAP





MPPT NEW GENERATION

TECHNICAL SPECIFICATION FOR THE MPPT No.: D0206-074

We try to respect the limits given by the customer. Due to the nominal values of the available resistors and capacitors, as well as to the limited possibilities with the given core sizes and core material, the actual values can be different.

Nevertheless: In the software implementation we will always use the values given by the customers.

SERIAL NUMBER:

Serial number: D0206-074

INPUT VOLTAGE RANGE:

Input voltage range: 153,95 [V]

OUTPUT VOLTAGE RANGE:

Output voltage range: 201.5 [V] Shutdown voltage range: 234.9 [V]

INPUT CURRENT RANGE:

Input MPP current range: 5.996 [A]

CAN CONVERSION FACTORS:

Input voltage multiplication factor:150.49 [mV/LSB]Output voltage multiplication factor:208.79 [mV/LSB]Input MPP current multiplication factor:5.86 [mA/LSB]

SOFTWARE:

Software Version: V 6.0