Phase 4: Discovering Internal Neural Representations

Dissecting Latent Geometry across Baseline, LeWM, and H-JEPA for FPGA Acceleration

Brian A. Hadian

Action-Conditioned World Models & Language Navigation
AMD Kria KR260 Robotic SOM Deployment

November 6, 2026

1. Sparse Autoencoders Expose Low-Rank Collapse vs High Capacity

Core Insight: *Baseline policies collapse into an extremely low-rank latent subspace, whereas predictive world models utilize full dictionary capacity without dead features.*

Dictionary Learning Formulation

For representation $h \in \mathbb{R}^{32}$:

$$\mathbf{z} = \mathrm{ReLU}(W_e(h - \mathbf{b}_d) + \mathbf{b}_e), \quad \hat{h} = W_d\mathbf{z} + \mathbf{b}_d$$

$$\mathcal{L} = \|h - \hat{h}\|_2^2 + \lambda\|\mathbf{z}\|_1, \quad \|W_d[:, j]\|_2 = 1$$

- Trained across $d \in \{64, 128, 256\}$ on 12,595 frames.
- Baseline exhibits $> 81\%$ dead features across all dictionary dimensions ($L_0 \approx 2$–4).
- World models (LeWM, H-JEPA) exhibit **0.0% dead features** with near-perfect reconstruction ($R^2 > 0.98$).

Empirical SAE Reconstruction & Sparsity

Model Latent	Dict d	Recon R^2	Active L_0	Dead %
Baseline (z)	64	0.874	2.2	81.2%
Baseline (z)	128	0.870	3.5	86.7%
Baseline (z)	256	0.872	1.4	87.5%
LeWM (s_t)	64	0.978	18.3	**0.0%**
LeWM (s_t)	128	0.981	25.0	**0.0%**
LeWM (s_t)	256	0.979	29.3	**0.0%**
H-JEPA (s_t)	64	**0.987**	15.9	**0.0%**
H-JEPA (s_t)	128	**0.988**	20.9	**0.0%**
H-JEPA (s_t)	256	**0.987**	23.8	**0.8%**

Hardware Implication: World model state spaces possess rich, uncollapsed geometric rank suitable for structured sub-circuit extraction.

2. Diagnostic Probes Confirm Egocentric Frame Representation

Core Insight: *Neural agents represent environment geometry strictly in robot-centric body coordinates rather than world coordinates.*

Allocentric vs Egocentric Probing

Closed-form ridge regression diagnostic probes ($N = 2,885$ test transitions):

$$W^* = (X_{\text{train}}^T X_{\text{train}} + \alpha I)^{-1} X_{\text{train}}^T Y_{\text{train}}$$

- **Allocentric Failure:** World-frame object position $(x_{\text{obj}}, y_{\text{obj}})$ is entirely undecodable across all models ($R^2 \approx 0.00$).
- **Egocentric Encoding:** Relative displacement $(dx_{\text{rel}}, dy_{\text{rel}})$ in the robot's heading frame is decodable at $R^2 = 0.4262$.
- Validates that spatial reasoning circuits operate on polar/body vectors rather than absolute spatial

Decodability Comparison Across Frames

Probing Target	Base (z)	LeWM (s)	H-JEPA (s)
World Object (x, y)	0.021	0.000	0.000
Relative Vector (dx, dy)	0.151	0.379	**0.426**
Robot Position (x, y)	0.252	0.273	**0.352**
Goal Direction $(\Delta\theta)$	0.013	**0.236**	0.211
Future State (x_{t+1}, y_{t+1})	0.252	0.270	**0.346**
Action Identity (v, ω)	0.047	**0.153**	0.148

Epistemological Rule: Information decodability proves availability of variables in early activations, not causal utilization by the motor head.


3. World Models Quadruple Latent Obstacle Capacity

Core Insight: *Joint-embedding and predictive state transitions force latent representations to heavily dedicate capacity to collision proximity and obstacle boundaries.*

Obstacle Decodability Quadrupling

- In Baseline policy, obstacle clearance ($d_{\min}$) achieves only $R^2 = 0.3256$ ($\mathrm{RMSE} = 0.303\,\mathrm{m}$).
- In LeWM, latent state s_t decodes clearance at $R^2 = 0.6473$ ($2.0\times$ higher).
- In H-JEPA, latent state s_t decodes clearance at $R^2 = \mathbf{0.7161}$ ($\mathrm{RMSE} = 0.197\,\mathrm{m}$, $2.2\times$ higher).
- Joint predictive training naturally establishes an internal obstacle boundary manifold without auxiliary supervision.

Obstacle Probing & Collision Avoidance



Causal Link: The $2.2\times$ increase in internal obstacle decodability directly underpins the $2.0\times$ reduction in physical collisions verified in Phase 2.

4. H-JEPA Discards Visual Nuisance for Physical Invariants

Core Insight: *H-JEPA completely suppresses surface appearance (allocating only 3.1% of latent space to color), compressing almost purely into geometry and heading.*

Counterfactual Interventions (E1–E7)

Sensitivity measured on 350 matched pairs:

$$S_k(E) = \frac{1}{N} \sum_{p=1}^{N} \frac{|h_k^{(E_0)} - h_k^{(E_i)}|}{\sigma(h_k) + \epsilon}$$

- **Baseline Policy Vulnerability:** 23 of 32 dimensions (71.9%) respond dominantly to color and lighting shifts (E2).
- **H-JEPA Semantic Invariance:** Exactly 1 dimension (3.1%) responds to color shifts; **96.9%** of neurons encode geometry, orientation, and clearance.

Dominant Latent Selectivity Profiles

Semantic Category	Base (z)	LeWM (s)	H-JEPA (s)
Visual Color / Shading	71.9% (23)	28.1% (9)	**3.1% (1)**
Geometry / Landmark	3.1% (1)	31.2% (10)	**37.5% (12)**
Global Starting Pose	15.6% (5)	9.4% (3)	**34.4% (11)**
Egocentric Heading	9.4% (3)	31.2% (10)	**25.0% (8)**

Theoretical Confirmation: Directly confirms LeCun's JEPA principle: predictive latent architectures filter out non-predictable pixel variance.

5. World Models Converge; Single SAE Features Are Polysemantic

Core Insight: *LeWM and H-JEPA representations converge to a shared geometric manifold, while individual SAE dictionary features exhibit rotational under-specification across seeds.*

Centered Kernel Alignment (CKA)

Linear CKA across 2,911 validation frames:

- Baseline diverges from both world models (CKA $= 0.34$–0.37).
- LeWM and H-JEPA achieve high cross-model geometric alignment: CKA $= \mathbf{0.6231}$.
- H-JEPA Micro state s_t and Macro prediction S_{t+5} achieve near-identity alignment: CKA $= \mathbf{0.9792}$.

SAE Dictionary Cross-Seed Stability

Bipartite column cosine alignment (Seed 42 vs 1337):

- Mean max cosine similarity is moderate (≈ 0.53–0.61).
- Strict column reproducibility ($|\cos| \geq 0.85$) is $< 5\%$ in world models.

Design Warning for Architecture Extraction

Single SAE dictionary atoms rotate across seeds. Circuit extraction in Phase 7 must target **functional weight sub-manifolds and causal pathways**, not fragile individual dictionary columns.

6. Dynamic Range Profiling Confirms Q8.8 FPGA Readiness

Core Insight: *All layers across all three architectures operate strictly within* $[-10.75, +10.75]$*, guaranteeing zero saturation and 3+ guard bits in signed Q8.8 arithmetic.*

Hardware Quantization Safety Profile

- Target FPGA format: Signed **Q8.8** (range: $[-128.0, +127.996]$).
- Maximum absolute activation observed across all layers: **10.75** (H-JEPA flatten).
- Integer bits required: ≤ 5 bits (including sign).
- Fixed-point headroom: **3 full guard bits** before saturation.
- Saturation overflow rate: **0.000%** across 100% of test tokens.

Layer Dynamic Range & Sparsity

Layer / Activation	Range	Peak	Zero %	Q8.8
Baseline `conv1`	$[-1.39, 0.89]$	1.39	0.0%	**PASS**
Baseline `latent_z`	$[-3.35, 2.20]$	3.35	0.0%	**PASS**
Baseline `fc1`	$[-1.54, 3.68]$	3.68	0.0%	**PASS**
LeWM `conv3`	$[-5.79, 2.15]$	5.79	0.0%	**PASS**
LeWM `flatten`	$[0.00, 1.89]$	1.89	**92.3%**	**PASS**
LeWM `latent_s`	$[-4.20, 3.48]$	4.20	0.0%	**PASS**
H-JEPA `flatten`	$[0.00, 10.75]$	10.75	**84.1%**	**PASS**
H-JEPA `latent_s`	$[-2.92, 3.36]$	3.36	0.0%	**PASS**

RTL DSP Optimization: Post-ReLU sparsity (**84.1%–92.3%**) enables zero-skipping logic to bypass up to 90% of DSP multiplier cycles on the AMD KR260.