


Structural Rounding

Brian Lavallee

18 October 2022

Approximations for Real-World Networks




- ▶ **Structural rounding** gives better approximations by assuming networks are *close* to a structural class.

Outline


- ▶ Structural Rounding Framework
- ▶ Extending to Realistic Classes
 - ▶ Editing to Bounded Expansion
- ▶ Empirical Evaluation
 - ▶ Vertex Cover in Near-Bipartite Graphs
 - ▶ Dominating Set in Near-Bounded Treewidth Graphs
- ▶ Summary and Open Questions

Structural Rounding




Edit: Use ψ to edit G to be in \mathcal{C}_λ .

Structural Rounding



Edit: Use ψ to edit G to be in \mathcal{C}_λ .


Structural Rounding



Edit: Use ψ to edit G to be in \mathcal{C}_λ .

Solve: Run an exact or approximate algorithm on the edited instance in polynomial time.


Structural Rounding



Edit: Use ψ to edit G to be in \mathcal{C}_λ .

Solve: Run an exact or approximate algorithm on the edited instance in polynomial time.

Structural Rounding




Edit: Use ψ to edit G to be in \mathcal{C}_λ .

Solve: Run an exact or approximate algorithm on the edited instance in polynomial time.

Lift: Extend the partial solution to G .

Structural Rounding




Edit: Use ψ to edit G to be in \mathcal{C}_λ . A problem is c' -**stable** w.r.t. ψ if ψ_1, \dots, ψ_d cannot increase $\text{opt}(G)$ by more than $c' \cdot d$.

Solve: Run an exact or approximate algorithm on the edited instance in polynomial time.

Lift: Extend the partial solution to G .

Structural Rounding




Edit: Use ψ to edit G to be in \mathcal{C}_λ . A problem is c' -**stable** w.r.t. ψ if ψ_1, \dots, ψ_d cannot increase $\text{opt}(G)$ by more than $c' \cdot d$.

Solve: Run an exact or approximate algorithm on the edited instance in polynomial time.

Lift: Extend the partial solution to G . A problem can be c -**lifted** w.r.t. ψ if any partial solution S can be extended to G by undoing ψ_1, \dots, ψ_d without increasing $\text{cost}(S)$ by more than $c \cdot d$.

Structural Rounding



Edit

Solve

Lift

Theorem (Demaine, L et al, 2019)

Let Π be a problem

- ▶ that is c' -stable under ψ and
- ▶ that can be c -lifted w.r.t. ψ .

If Π has a poly-time $\rho(\lambda)$ -approximation in \mathcal{C}_λ and
(\mathcal{C}_λ , ψ)-EDITING has a poly-time (α, β) -approximation, then
there is a poly-time $((1 + c'\alpha\delta) \cdot \rho(\beta\lambda) + c\alpha\delta)$ -approximation for
 Π on graphs that are $(\delta \cdot \text{opt}_\Pi(G))$ -close to \mathcal{C}_λ .

Extending to Realistic Classes

- ▶ Editing to Bounded Expansion
- ▶ Generalized Coloring Numbers

Why Editing?




image credit: Felix Reidl

Why Editing?

Smaller Edit Sets




image credit: Felix Reidl

Why Editing?

Smaller Edit Sets



Faster/Better
Approximations





image credit: Felix Reidl

Why Bounded Expansion?

Smaller Edit Sets



Faster/Better Approximations




image credit: Felix Reidl

Why Bounded Expansion?


Smaller Edit Sets



Excluding a topological minor



Excluding a minor



Bounded treedepth



Star forests



Faster/Better Approximations

Nowhere dense



Locally bounded expansion



Locally excluding a minor



Locally bounded treewidth



Bounded genus



Planar



Outerplanar



Forests




Linear forests

image credit: Felix Reidl

Why Bounded Expansion?

Smaller Edit Sets




Faster/Better
Approximations

image credit: Felix Reidl

Generalized Coloring Numbers


- ▶ extend degeneracy to larger r -neighborhoods
- ▶ classes with bounded expansion have $\text{col}_r(G) \leq f(r)$



$$\sigma = [9, 8, 7, 0, \mathbf{6}, 5, 3, 4, 2, 1]$$

Generalized Coloring Numbers


- ▶ extend degeneracy to larger r -neighborhoods
- ▶ classes with bounded expansion have $\text{col}_r(G) \leq f(r)$



$\sigma = [9, 8, 7, 0, \mathbf{6}, 5, 3, 4, 2, 1]$
▶ $R_1(6, G_\sigma) = \{3, 5\}$

Generalized Coloring Numbers

- ▶ extend degeneracy to larger r -neighborhoods
- ▶ classes with bounded expansion have $\text{col}_r(G) \leq f(r)$




$$\sigma = [9, 8, 7, 0, \mathbf{6}, 5, 3, 4, 2, 1]$$

$$\blacktriangleright R_1(6, G_\sigma) = \{3, 5\}$$

$$\blacktriangleright R_2(6, G_\sigma) = \{2, 3, 5\}$$

Generalized Coloring Numbers

- ▶ extend degeneracy to larger r -neighborhoods
- ▶ classes with bounded expansion have $\text{col}_r(G) \leq f(r)$




$$\sigma = [9, 8, 7, 0, \mathbf{6}, 5, 3, 4, 2, 1]$$

- ▶ $R_1(6, G_\sigma) = \{3, 5\}$
- ▶ $R_2(6, G_\sigma) = \{2, 3, 5\}$
- ▶ $R_3(6, G_\sigma) = \{1, 2, 3, 5\}$

Generalized Coloring Numbers

- ▶ extend degeneracy to larger r -neighborhoods
- ▶ classes with bounded expansion have $\text{col}_r(G) \leq f(r)$



$$\sigma = [9, 8, 7, 0, \mathbf{6}, 5, 3, 4, 2, 1]$$

- ▶ $R_1(6, G_\sigma) = \{3, 5\}$
- ▶ $R_2(6, G_\sigma) = \{2, 3, 5\}$
- ▶ $R_3(6, G_\sigma) = \{1, 2, 3, 5\}$

$$\text{col}_r(G) := \min_{\sigma \in \pi} \max_{u \in V} |R_r(u, G_\sigma)|$$

Generalized Coloring Numbers

Theorem (Breen-McKay, L, Sullivan, 2022)

There is a greedy $(k - 1)^{r-1}$ approximation for $\text{col}_r(G)$ in graphs with r -admissibility at most k .

- ▶ $\text{adm}_r(G) \leq \text{col}_r(G)$

Theorem (Breen-McKay, L, Sullivan, 2022)

It is NP-hard to determine if $\text{col}_r(G) \leq 6$ when $r \geq 2$.

Implications:

- ▶ No polynomial time $\frac{7}{6}$ -approximation.
- ▶ No $O(n^{f(t)})$ time algorithm to check if $\text{col}_r(G) \leq t$.

Coloring Number Deletion

r -COLORING NUMBER DELETION

Input: a graph $G = (V, E)$ and a target t .

Problem: find a set of vertices $X \subseteq V$ of minimum size such that $\text{col}_r(G \setminus X) \leq t$.

Theorem (Breen-McKay, Kloster, L, Sullivan, 2019)

There exists a constant c such that it is NP-hard to approximate r -COLORING NUMBER DELETION within a factor of $c \cdot \log \frac{n}{r+t}$.

Coloring Number Deletion

r -COLORING NUMBER DELETION

Input: a graph $G = (V, E)$ and a target t .

Problem: find a set of vertices $X \subseteq V$ of minimum size such that $\text{col}_r(G \setminus X) \leq t$.

Theorem (Breen-McKay, Kloster, L, Sullivan, 2019)

There exists a constant c such that it is NP-hard to approximate r -COLORING NUMBER DELETION within a factor of $c \cdot \log \frac{n}{r+t}$.


SET COVER

Input: a universe of elements \mathcal{U} and a family of sets \mathcal{F} .

Problem: find a set $S \subseteq \mathcal{F}$ of minimum size such that $\bigcup_{s_i \in S} s_i = \mathcal{U}$.


Coloring Number Deletion

$$\mathcal{U} = \{e_1, e_2, e_3, e_4, e_5\} \quad \mathcal{F} = \{(e_1, e_2, e_3), (e_1, e_3), (e_2, e_4), (e_3, e_5)\}$$




Coloring Number Deletion

$$\mathcal{U} = \{e_1, e_2, e_3, e_4, e_5\} \quad \mathcal{F} = \{(e_1, e_2, e_3), (e_1, e_3), (e_2, e_4), (e_3, e_5)\}$$



Coloring Number Deletion


$$\mathcal{U} = \{e_1, e_2, e_3, e_4, e_5\} \quad \mathcal{F} = \{(e_1, e_2, e_3), (e_1, e_3), (e_2, e_4), (e_3, e_5)\}$$



- ▶ Implies DEGENERACY DELETION is $\tilde{o}(\log \frac{n}{t})$ inapproximable.

Coloring Number Deletion


$$\mathcal{U} = \{e_1, e_2, e_3, e_4, e_5\} \quad \mathcal{F} = \{(e_1, e_2, e_3), (e_1, e_3), (e_2, e_4), (e_3, e_5)\}$$



Caveat: The NP-hardness of computing $\text{col}_r(G)$ implies that no multiplicative approximation exists.

Coloring Number Deletion

$$\mathcal{U} = \{e_1, e_2, e_3, e_4, e_5\} \quad \mathcal{F} = \{(e_1, e_2, e_3), (e_1, e_3), (e_2, e_4), (e_3, e_5)\}$$





Optimistic view: Still applies when $\text{col}_r(G) > t$ is guaranteed.

Structural Rounding in Practice

- ▶ Vertex Cover in Near-Bipartite Graphs
- ▶ Dominating Set in Near-Bounded Treewidth Graphs

Graph Corpuses

- ▶ vc-synth: 1,620 graphs generated with preferential attachment restricted by random labels (E, L, R)
- ▶ ds-synth: 750 graphs generated by taking a random subgraph of a random k -tree



Graph Corpuses

- ▶ vc-synth: 1,620 graphs generated with preferential attachment restricted by random labels (E, L, R)
- ▶ ds-synth: 750 graphs generated by taking a random subgraph of a random k -tree
- ▶ pace: 200 graphs used by 2019 PACE Challenge to assess exact VERTEX COVER algorithms
- ▶ networks: 207 graphs collected from scientific domains

Graph Corpuses

- ▶ vc-synth: 1,620 graphs generated with preferential attachment restricted by random labels (E, L, R)
- ▶ ds-synth: 750 graphs generated by taking a random subgraph of a random k -tree
- ▶ pace: 200 graphs used by 2019 PACE Challenge to assess exact VERTEX COVER algorithms
- ▶ networks: 207 graphs collected from scientific domains

corpus	vertices	edges
vc-synth	10K	39K - 4M
ds-synth	4K - 10K	6K - 4M
pace	153 - 138K	1K - 454K
networks	9 - 935K	16 - 17M


Structural Rounding in Practice

- ▶ Vertex Cover in Near-Bipartite Graphs
- ▶ Dominating Set in Near-Bounded Treewidth Graphs

Vertex Cover in Near-Bipartite Graphs

Edit: ODD CYCLE TRANSVERSAL


- ▶ greedy-edit: builds from maximal cut.
- ▶ indset-edit: builds from two maximal independent sets.
- ▶ bfs-edit: builds from layers of BFS tree.



Vertex Cover in Near-Bipartite Graphs

Edit: ODD CYCLE TRANSVERSAL

- ▶ greedy-edit: builds from maximal cut.
- ▶ indset-edit: builds from two maximal independent sets.
- ▶ bfs-edit: builds from layers of BFS tree.




Vertex Cover in Near-Bipartite Graphs

Edit: ODD CYCLE TRANSVERSAL

- ▶ greedy-edit: builds from maximal cut.
- ▶ indset-edit: builds from two maximal independent sets.
- ▶ bfs-edit: builds from layers of BFS tree.

Solve: VERTEX COVER

- ▶ Hopcroft-Karp: exact algorithm for VC in bipartite graphs.



Vertex Cover in Near-Bipartite Graphs

Edit: ODD CYCLE TRANSVERSAL


- ▶ greedy-edit: builds from maximal cut.
- ▶ indset-edit: builds from two maximal independent sets.
- ▶ bfs-edit: builds from layers of BFS tree.

Solve: VERTEX COVER

- ▶ Hopcroft-Karp: exact algorithm for VC in bipartite graphs.

Lift: VC-LIFT (minimum completion of a partial solution)

- ▶ greedy-lift
- ▶ apx-lift
- ▶ oct-lift
- ▶ bip-lift
- ▶ recursive-lift



Vertex Cover in Near-Bipartite Graphs

Edit: ODD CYCLE TRANSVERSAL


- ▶ greedy-edit: builds from maximal cut.
- ▶ indset-edit: builds from two maximal independent sets.
- ▶ bfs-edit: builds from layers of BFS tree.

Solve: VERTEX COVER


- ▶ Hopcroft-Karp: exact algorithm for VC in bipartite graphs.

Lift: VC-LIFT (minimum completion of a partial solution)

- ▶ greedy-lift
- ▶ apx-lift
- ▶ oct-lift
- ▶ bip-lift
- ▶ recursive-lift




Vertex Cover in Near-Bipartite Graphs




- ▶ indset-edit results in better solutions even though it finds larger edit sets.

Vertex Cover in Near-Bipartite Graphs




- Guaranteeing the lifting constant matters.

Vertex Cover in Near-Bipartite Graphs



- Guaranteeing the lifting constant matters.

Vertex Cover in Near-Bipartite Graphs



- ▶ Better performance even with large edit sets ($> 40\%$).
- ▶ About 1.8x slower than standard approximations/heuristics.
- ▶ Real-world networks aren't exactly *close* to bipartite.


Structural Rounding in Practice

- ▶ Vertex Cover in Near-Bipartite Graphs
- ▶ Dominating Set in Near-Bounded Treewidth Graphs

Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION



- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.



Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION



- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.



Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION



- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.



Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION

- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.




Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION

- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.

Solve: DOMINATING SET

- ▶ DP: $O(4^t n)$ exact algorithm for DS in graphs with treewidth t .



Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION


- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.

Solve: DOMINATING SET

- ▶ DP: $O(4^t n)$ exact algorithm for DS in graphs with treewidth t .

Lift: DS-LIFT (minimum completion of a partial solution)

- ▶ greedy-lift
- ▶ apx-lift



Dominating Set in Near-Treewidth Graphs

Edit: TREewidth DELETION


- ▶ greedy-edit: finds a tree decomposition and removes vertices until it has width t .
- ▶ root-edit: removes vertex separators until $\text{tw}(G) \leq t$.

Solve: DOMINATING SET


- ▶ DP: $O(4^t n)$ exact algorithm for DS in graphs with treewidth t .

Lift: DS-LIFT (minimum completion of a partial solution)

- ▶ greedy-lift
- ▶ apx-lift




Dominating Set in Near-Bounded Treewidth Graphs




- ▶ greedy-edit produces smaller edit sets than root-edit.

Dominating Set in Near-Bounded Treewidth Graphs




- ▶ greedy-edit produces smaller edit sets than root-edit.
- ▶ final algorithm has runtime quadratic in treewidth of input.

Dominating Set in Near-Bounded Treewidth Graphs




- ▶ Guaranteeing the lifting constant still matters.

Dominating Set in Near-Bounded Treewidth Graphs



- ▶ Improved performance for small ($< 5\%$) edit sets.
- ▶ Comparable performance overall, but 60x slower.
- ▶ Real-world networks are closer to treewidth 8 than bipartite.

Dominating Set in Near-Bounded Treewidth Graphs



- ▶ Improved performance for small ($< 5\%$) edit sets.
- ▶ Comparable performance overall, but 60x slower.
- ▶ Real-world networks are closer to treewidth 8 than bipartite.

Summary

- ▶ Structural Rounding is a viable technique for approximating NP-hard problems in real-world networks.
 - ▶ SR outperforms standard VERTEX COVER algorithms with only 1.8x slowdown.
 - ▶ SR finds small dominating sets in graphs close to $\text{tw}/8$ (< 5%).

Summary

- ▶ Structural Rounding is a viable technique for approximating NP-hard problems in real-world networks.
 - ▶ SR outperforms standard VERTEX COVER algorithms with only 1.8x slowdown.
 - ▶ SR finds small dominating sets in graphs close to tw-8 (< 5%).
- ▶ r -COLORING NUMBER DELETION is $o(\log \frac{n}{r+t})$ inapprox.

Summary

- ▶ Structural Rounding is a viable technique for approximating NP-hard problems in real-world networks.
 - ▶ SR outperforms standard VERTEX COVER algorithms with only 1.8x slowdown.
 - ▶ SR finds small dominating sets in graphs close to $\text{tw-8} (< 5\%)$.
- ▶ r -COLORING NUMBER DELETION is $o(\log \frac{n}{r+t})$ inapprox.
- ▶ It is NP-hard to decide $\text{col}_r(G) \leq 6$.
 - ▶ No $\frac{7}{6}$ approximation.
 - ▶ No $n^{f(t)}$ algorithm to check $\text{col}_r(G) \leq t$.

Summary

- ▶ Structural Rounding is a viable technique for approximating NP-hard problems in real-world networks.
 - ▶ SR outperforms standard VERTEX COVER algorithms with only 1.8x slowdown.
 - ▶ SR finds small dominating sets in graphs close to $\text{tw-8} (< 5\%)$.
- ▶ r -COLORING NUMBER DELETION is $o(\log \frac{n}{r+t})$ inapprox.
- ▶ It is NP-hard to decide $\text{col}_r(G) \leq 6$.
 - ▶ No $\frac{7}{6}$ approximation.
 - ▶ No $n^{f(t)}$ algorithm to check $\text{col}_r(G) \leq t$.
- ▶ The generalized coloring numbers admit a $(k-1)^{r-1}$ approximation in graphs with r -admissibility at most k .

Open Questions

- ▶ Performance of structural rounding using edge deletions
 - ▶ DOMINATING SET has better stability and lifting constant w.r.t. edge deletion

Open Questions

- ▶ Performance of structural rounding using edge deletions
 - ▶ DOMINATING SET has better stability and lifting constant w.r.t. edge deletion
- ▶ Precise approximation bounds for $\text{col}_r(G)$
 - ▶ Large gap between $\frac{7}{6}$ and $(k - 1)^{r-1}$
 - ▶ Constant factor approximation for $\text{col}_2(G)$?

Open Questions

- ▶ Performance of structural rounding using edge deletions
 - ▶ DOMINATING SET has better stability and lifting constant w.r.t. edge deletion
- ▶ Precise approximation bounds for $\text{col}_r(G)$
 - ▶ Large gap between $\frac{7}{6}$ and $(k - 1)^{r-1}$
 - ▶ Constant factor approximation for $\text{col}_2(G)$?
- ▶ Bicriteria inapproximability
 - ▶ Inapproximability results for editing to classes with NP-hard parameters when class parameter is approximate

Thanks!

- ▶ Blair Sullivan
- ▶ Erik Demaine
- ▶ Drew van der Poel
- ▶ Ali Vakilian
- ▶ Mike Breen-McKay
- ▶ Quanquan Liu
- ▶ Kyle Kloster
- ▶ Tim Goodrich
- ▶ Hayley Russell
- ▶ Felix Reidl
- ▶ Madi Cooley
- ▶ Mike O'Brien
- ▶ Cole Perschon
- ▶ Andrew Fraser



GORDON AND BETTY
MOORE
FOUNDATION

