

Forårets valgfag

Sæt kryds i kalenderen – **onsdag den 16. november, kl. 12-45-13:15**

De udbudte valgfag er:

1. **Frameworks** (Morten Mathiasen)
2. **Mobile Development, Android** (Martin Knudsen)
3. **Mobile Development, iOS** (Kaj Schermer Didriksen)

Efter præsentation får I mulighed for at vælge jer ind på fagene i prioriteret rækkefølge. I skal følge 2 af 3.

Today's Agenda


- Introduction to Entity Framework
 - What Is Entity Framework?
 - Entity Framework Workflows
 - Installation of EF
 - Release History
- Answer Questions in Groups
- Exercises
- An introduction to LINQ and Lambda Expressions
- Exercises (continued)

Entity Framework


An Introduction

What is Entity Framework?


- Entity framework is an ORM (object-relational mapper) that enables us to **connect** to the DB (SQL server) and **map** DB to our models and vice versa.
- One of the core capabilities of the Entity Framework is generation of **SELECT, UPDATE, INSERT** and **DELETE** commands.
- The focal point of the Entity Framework is the **Entity Data Model (EDM)**, a **conceptual model** that describes an application's domain objects (which is normally in the **Models** folder).




The Entity Framework lets developers express **queries against the model** rather than concern themselves with details of the database.



The **DbContext** object gives you access to the model



Entity Framework Workflows



Application Design Strategies

1. Domain Centric Approach (**Domain Driven Design**)
 - In this approach we design our models in such a way that they can be stored/persisted anywhere -> **Entity Framework Code First**
2. Data Centric Applications (**Data Driven Design**)
 - Data Model comes first -> Entity Framework Database First or **Code First with an Existing Database** (since EF 6.1)

Essential EF Classes

- **`System.Data.Entity.DbContext`**

- A class that represents a session with the database, allowing you to query and save data. A context derives from the **`DbContext`** or **`ObjectContext`** class
- The primary class that is responsible for interacting with data as objects

- **Fluent API**

- An API that can be used to **configure a Code First model** (e.g. relationships)

POCO data classes

- Custom data classes that only contain properties (no attributes or methods) that maps to entities and relationships in EF
- They are Plain Old CLR (Common Language Runtime) Objects (**POCO**)
- POCO are classes that **remain free from a backing infrastructure**, such as Entity Framework
- A POCO class is known as persistence-ignorant object

Model class Customer as an example of a **POCO** class

```
public class Customer {  
    public int ID { get; set; }  
    public string FirstName { get; set; }  
    public string LastName { get; set; }  
    public string Address { get; set; }  
    public string City { get; set; }  
    public string Zip { get; set; }  
    public string Phone { get; set; }  
    public string Email { get; set; }  
}
```


DbContext Class Example

```
namespace Lesson08.DAL {  
    public class MbmStoreContext : DbContext {  
        public MbmStoreContext() : base("PetHotelContext") { }  
        public DbSet<Customer> Customers { get; set; }  
        public DbSet<OrderItem> OrderItems { get; set; }  
        public DbSet<Invoice> Invoices { get; set; }  
  
        protected override void OnModelCreating(DbModelBuilder modelBuilder) {  
            modelBuilder.Conventions.Remove<PluralizingTableNameConvention>();  
        }  
    }  
}
```

DbContext

Entity

A class or object that represents **application data** such as Customers, Products, and Orders: **DbSet<TEntity>**



web.config

```
<configuration>
  <connectionStrings>
    <add name="PetHotelContext"
      connectionString="Data Source=(localdb)\v11.0;
      Integrated Security=True;
      AttachDbFilename=|DataDirectory|MbmStoreContext.mdf"
      providerName="System.Data.SqlClient" />
  </connectionStrings>
</configuration>
```

Using EF from the Controller

```
public class CustomerController : Controller {  
    private MbmStoreContext db = new MbmStoreContext();  
  
    // GET: Customers from DB  
    public ActionResult Index() {  
        return View(db.Customers.ToList());  
    }  
}
```

Installation

EntityFramework 6.1.1

Entity Framework is Microsoft's recommended data access technology for new applications.


To install EntityFramework, run the following command in the [Package Manager Console](#)

```
PM> Install-Package EntityFramework -Version 6.1.1
```


Entity Framework Release History

- **EF v1** released on 11 August **2008**. This version was widely criticized
- **EF v4** (next version) released as part of .NET 4.0 on 12 April 2010 and addressed many of the criticisms made of version 1
- **EF 4.1** released on April 12, 2011, with **Code First** support
- **4.3.1** released on February 29, 2012. There were a few updates, like support for **migration**
- **EF 5.0** released on August 11, 2012 and is targeted at .NET framework 4.5. Without any runtime advantages over version 4
- **EF 6.0** released on October 17, 2013 and is now an **open source project**. This version has a number of **improvements for code-first support**
- **EF 6.1.** released on March 17, 2014. **Code First reverse engineering** from an existing database.
- **EF 6.1.2** released on June 20, 2014. Mainly bug fixes.
- **EF 6.1.3** released on March 10, 2015. Bug fixes. <https://github.com/aspnet/EntityFramework6>
- **EF Core 1.0** released on June 27, 2016. <https://github.com/aspnet/EntityFramework>

Entity Framework in a nutshell



Other ORM (Object/Relational Mapper) Tools


- Dapper.NET ORM ([StackExchange/dapper-dot-net](https://stackoverflow.com/questions/10309152/dapper-net))
- NHibernate (sourceforge.net/projects/nhibernate)
- NET ORM tool (www.telerik.com/data-access)

Questions

Q1: Naming conventions

- Table names are *pluralized*
E.g. Entity class name `Student` -> table name `Students`
- Entity property names are used for column names
E.g. Entity `Student` class property `FirstName` -> table column `FirstName`
- Entity properties that are named `ID` or *classnameID* are recognized as primary key properties
- A property is interpreted as a foreign key property if it's named *<navigation property name><primary key property name>* (for example, `StudentID` for the `Student` navigation property since the `Student` entity's primary key is `ID`).
Foreign key properties can also be named the same simply *<primary key property name>* (for example, `EnrollmentID` since the `Enrollment` entity's primary key is `EnrollmentID`).

Q2: What is a navigation property?



Q2: Navigational properties

- **Navigation properties** are typically defined as virtual. Please explain why?
 - To enable **lazy loading** (loads only object when needed)
- A navigation property that holds multiple entities must be a list. Which type must that list be??

```
public class Student {  
    public int ID { get; set; }  
    public string LastName { get; set; }  
    public string FirstMidName { get; set; }  
    public DateTime EnrollmentDate { get; set; }  
    public string Secret { get; set; }  
    public virtual ICollection<Enrollment> Enrollments { get; set; }  
}
```

Q3: Override conventions

- You can use:
 - Data Annotations
 - The Fluent API

- Primary key?

```
[Key]  
public string CourseCode {get; set}
```

- Avoid DB automatic generation of primary key values

```
[DatabaseGenerated(DatabaseGeneratedOption.None)]  
public string CourseID {get; set}
```


Q3: Foreign key?

```
public class Course {  
    public int CourseID { get; set; }  
    public string CourseName { get; set; }  
  
    //Foreign key for Department  
    public int DepartmentRefId { get; set; }  
  
    [ForeignKey("DepartmentRefId")]  
    public Department Department { get; set; }  
}
```

```
public class Department {  
    public int DepartmentId { get; set; }  
    public string DepartmentName { get; set; }  
    public ICollection<Course> Courses { get; set; }  
}
```

Q4: Explain this code

```
using ContosoUniversity.Models;
using System.Data.Entity;
using System.Data.Entity.ModelConfiguration.Conventions;

namespace ContosoUniversity.DAL {

    public class SchoolContext : DbContext {
        public SchoolContext() : base("SchoolContext") {}

        public DbSet<Student> Students { get; set; }
        public DbSet<Enrollment> Enrollments { get; set; }
        public DbSet<Course> Courses { get; set; }

        protected override void OnModelCreating(DbModelBuilder modelBuilder) {
            modelBuilder.Conventions.Remove<PluralizingTableNameConvention>();
        }
    }
}
```

Q5: The Seed method

- in the **SchoolInitializer.cs** class

- The purpose of the seed method?
 - Insert example data
- How do you tell the EF to use the initializer class?
 - **web.config** file (or **global.asax** in Application_Start)
- When is the Seed method inside the initializer class called?
 - Whenever the model is changed
- What happens when the Seed method is called?
 - The database is dropped and recreated (drop/recreate) (default behavior – can be changed)
- Where should the seed method be located
 - Inside the DAL folder (maybe)

Q6: LocalDB

- What is LocalDB?
 - Lightweight SQLExpress instance. LocalDB is created specifically for developers.
 - It is very easy to install - developers no longer have to install and manage a full instance of SQL Server Express on their laptops
 - Offers the same T-SQL language, programming surface and client-side providers as the regular SQL Server Express.
- How do you specify the name and location of you LocalDB database file?
 - Inside the `web.config` file (inside the `connectionStrings` node)
- What is the preferred location for LocalDB database files for ASP.NET MVC web development?
 - Inside the `/App_Data` folder

Q6: Connection String, please explain

```
<connectionStrings>
  <add name="SchoolContext"

    connectionString="Data Source=(localdb)\MSSQLLocalDB;
    Integrated Security=True;
    MultipleActiveResultSets=True;
    AttachDbFilename=|DataDirectory|ContosoUniversity.mdf"

    providerName="System.Data.SqlClient" />
</connectionStrings>
```

Q8: Which files and methods does the scaffolder *MVC 5 Controller with Views, using Entity Framework* create?

Action Method	View
Index()	Index.cshtml – list of students
Details(int? id)	Details.cshtml – detailed student view
Create()	Create.cshtml – empty student form
[HttpPost] Create(Student student)	Create.cshtml – form if error, else student list
Edit(int? id)	Edit.cshtml – populated student form
[HttpPost] Edit(Student student)	Edit.cshtml – form if error, else student list
Delete(int? id)	Delete.cshtml – detailed student view
[HttpPost] Delete(int id)	Index.cshtml – list of students



Q8: MVC 5 Controller with views, using Entity Framework

The first time you run the scaffolder **MVC 5 Controller with views, using Entity Framework** in a project it also:

1. Installs Entity Framework
2. Creates a DbContext class in the Models folder
3. Adds a connection string to the Web.config file
4. Adds a reference to the DbContext class in Web.config file

Q9: What is **Lazy Loading**?


- When the entity is first read, **related data isn't retrieved**. However, the first time you attempt to access a navigation property, the data required for that navigation property is automatically retrieved. The **DbContext** class enables lazy loading by default

```
departments = context.Departments
foreach (Department d in departments)  Query: all Department rows
{
    foreach (Course c in d.Courses)  Query: Course rows related to
    {                                     Department d
        courseList.Add(d.Name + c.Title);
    }
}
```


Q9: What is Eager Loading?


- When the entity is read, **related data is retrieved along with it**. This typically results in a single join query that retrieves all of the data that's needed. You specify eager loading by using the **Include** method.

```
departments = context.Departments.Include(x => x.Courses)
foreach (Department d in departments)
{
    foreach (Course c in d.Courses)
    {
        courseList.Add(d.Name + c.Title);
    }
}
```

 **Query: all Department rows and related Course rows**

Q9: Force Immediate Query Execution

```
departments = context.Departments.Include(x => x.Courses).ToList();  
foreach (Department d in departments)  
{  
    foreach (Course c in d.Courses)  
    {  
        courseList.Add(d.Name + c.Title);  
    }  
}
```


**Query: all Department
rows and related
Course rows**

LINQ Methods that Force Entity Framework to return the result from the DB

Enumerables

- ToList
- ToArray
- ToDictionary

Singleton

- Average
- Count
- First
- FirstOrDefault
- Max
- Single
- SingleOrDefault


Q10: Securing the code

In the view

```
@Html.AntiForgeryToken()
```

```
[ValidateAntiForgeryToken]
public ActionResult Create([Bind(Include = "LastName,
FirstMidName, EnrollmentDate")]Student student) {
    try {
        if (ModelState.IsValid) {
            db.Students.Add(student);
            db.SaveChanges();
            return RedirectToAction("Index");
        }
    }
    catch (DataException /* dex */) {
        //Log the error
    }
    return View(student);
}
```

With a tool like Fiddler (or JavaScript) a hacker can POST extra form values



Q10: How does the Edit method differ from **Create** method

```
[ValidateAntiForgeryToken]
public ActionResult Edit([Bind(Include = "LastName,
FirstMidName, EnrollmentDate")]Student student) {
    try {
        if (ModelState.IsValid) {
            db.Books.Add(book) ;
            db.SaveChanges();
            return RedirectToAction("Index");
        }
    }
    catch (DataException /* dex */) {
        //Log the error
    }
    return View(student);
}
```

Q10: How does the **Edit** method differ from **Create** method

```
[ValidateAntiForgeryToken]
public ActionResult Edit([Bind(Include = "ID, LastName,
FirstMidName, EnrollmentDate")]Student student) {
    try {
        if (ModelState.IsValid) {
            db.Entry(student).State = EntityState.Modified;
            db.SaveChanges();
            return RedirectToAction("Index");
        }
    }
    catch (DataException /* dex */) {
        //Log the error
    }
    return View(student);
}
```

Exercises 1-10

An adaption of Tom Dykstra and Rick Anderson: *Getting Started with Entity Framework 6 Code First using MVC 5 for the **MbmStore** project*

LINQ & Lamda Expressions


The purpose of LINQ

- Making data access easier by **integrating querying capabilities** into a programming language like C#
- Linq to objects (from collections)
- Linq to XML
- Linq to SQL
- Linq to Entity

LINQ expressions are supported by intellisense

```
6 namespace LinqIntro
7 {
8     public class Employee
9     {
10         public int ID { get; set; }
11         public string Name { get; set; }
12         public DateTime HireDate { get; set; }
13     }
14 }
15
```

```
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```



The screenshot shows a Visual Studio code editor with a C# file named `LinqIntro.cs`. The code defines a `namespace LinqIntro` containing a `public class Employee` with properties `ID`, `Name`, and `HireDate`. Below the class definition, there is a LINQ query: `IEnumerable<Employee> employees = new List<Employee>() { new Employee { ID=1, Name="Scott", HireDate=new DateTime(2002, 3, 5) }, new Employee { ID=2, Name="Poonam", HireDate=new DateTime(2002, 10, 15) }, new Employee { ID=3, Name="Paul", HireDate=new DateTime(2007, 10, 11) } };` followed by another LINQ query: `IEnumerable<Employee> query = from e in employees where e.HireDate.Year < 2005 orderby e.Name select e`. An intellisense dropdown menu is open over the `select e` line, showing a list of suggestions including `do`, `double`, `Double`, `DuplicateWaitObjectException`, `e` (highlighted), `else`, `Employee`, `employees`, `EntryPointNotFoundException`, and `enum`. The background of the code editor is light blue, and the text is in a monospaced font. The Visual Studio logo is visible in the bottom right corner.

LINQ Query Expressions

- The same standard query operators work everywhere
 - Objects
 - Relational data
 - XML data
- More than 50 operators defined
 - Projection
 - Filtering
 - Joining
 - Ordering
 - Agregating
- Similar to
 - Select, Where, From, Join, OrderBy, GroupBy

Deferred execution:

Queries are **not executed** until we access the result

The Controller

```
public class Example01Controller : Controller
{
    // GET: Example01
    public ActionResult Index()
    {
        IEnumerable<Employee> employees = new List<Employee>() {
            new Employee {Id = 1, Name = "Peter Sorensen", HireDate = new DateTime(2008, 10, 10) },
            new Employee {Id = 1, Name = "Torsten Peterson", HireDate = new DateTime(2002, 1, 2) },
            new Employee {Id = 1, Name = "Liza Thompson", HireDate = new DateTime(2011, 12, 4) }
        };

        IEnumerable<Employee> query =
            from e in employees
            where e.HireDate.Year < 2010
            orderby e.Name
            select e;

        return View(query);
    }
}
```

← LINQ query expression

The View

```
@using lesson08_linq_example.Models;
@model IEnumerable<Employee>
@{
    ViewBag.Title = "Index";
}

<h2>Index</h2>

<ul>
    @foreach (Employee e in Model) {
        <li>@e.Name</li>
    }
</ul>
```

← Query sent

Comprehensive query syntax in LINQ


```
string[] cities = { "Boston", "Los Angeles",  
                    "Seattle", "London", "Hyderabad" };  
  
IEnumerable<string> filteredCities =  
    from city in cities  
    where city.StartsWith("L") && city.Length < 15  
    orderby city  
    select city;
```

- Begins with a *from* clause, ends with a *select* or *group*
- Looks like a SQL query
 - *from* logically comes first (also helps Intellisense)

Sweet and Sugary Syntax

- Compiler transfers query expressions into a series of LINQ method calls with lamda expressions

```
string[] cities = { "Boston", "Los Angeles",  
                    "Seattle", "London", "Hyderabad" };  
  
IEnumerable<string> filteredCities =  
    from city in cities  
    where city.StartsWith("L") && city.Length < 15  
    orderby city  
    select city;
```



```
IEnumerable<string> filteredCities =  
    cities.Where(c => c.StartsWith("L") && c.Length < 15)  
           .OrderBy(c => c)  
           .Select(c => c);
```

Live example

```
public ActionResult Index()
{
    IEnumerable<Employee> employees = new List<Employee>() {
        new Employee {Id = 1, Name = "Peter Sorensen", HireDate = new DateTime(2008, 10, 10) },
        new Employee {Id = 1, Name = "Torsten Peterson", HireDate = new DateTime(2002, 1, 2) },
        new Employee {Id = 1, Name = "Liza Thompson", HireDate = new DateTime(2011, 12, 4) }
    };

    IEnumerable<Employee> query1 =
        from e in employees
        where e.HireDate.Year < 2010
        orderby e.Name
        select e;

    IEnumerable<Employee> query2 =
        employees.Where(e => e.HireDate.Year < 2010)
            .OrderBy(e => e.Name)
            .Select(e => e);

    return View(query2);
}
```


Select a single object

```
public ActionResult Index()
{
    IEnumerable<Employee> employees = new List<Employee>() {
        new Employee {Id = 1, Name = "Peter Sorensen", HireDate = new DateTime(2008, 10, 10) },
        new Employee {Id = 2, Name = "Torsten Peterson", HireDate = new DateTime(2002, 1, 2) },
        new Employee {Id = 3, Name = "Liza Thompson", HireDate = new DateTime(2011, 12, 4) }
    };

    Employee query1 =
        (from e in employees
         where e.Id == 3
         select e).First();

    Employee query2 =
        employees.Where(e => e.Id == 3)
            .OrderBy(e => e.Name)
            .Select(e => e)
            .First();

    return View(query2);
}
```

Comprehensive Query syntax versus Lamda Query

- Comprehensive Query
 - If you already know SQL, you'll probably find that easier to grasp
- Lamda query
 - Generally offers more control and flexibility
 - Chaining of query operators looks like a pipeline
 - Select operator is optional (when not doing a projection)
 - Many query operators have no comprehensive query equivalent
- It is possible to mix syntaxes

Exercises 1-10

Continued ...