

Arrays and Useful R functions

Introduction to R for Public Health Researchers

Data Frames versus Matrices

You will likely use `data.frame` class for a lot of data cleaning and analysis. However, some operations that rely on matrix multiplication (like performing many linear regressions) are (much) faster with matrices. Also, as we will touch on later, some functions for iterating over data will return the matrix class, or will be placed in empty matrices that can then be converted to `data.frames`

Data Frames versus Matrices

There is also additional summarization functions for matrices (and not data.frames) in the `matrixStats` package, like `rowMins()`, `colMaxs()`, etc.

```
library(matrixStats,quietly = TRUE)
```

```
##  
## Attaching package: 'matrixStats'  
  
## The following object is masked from 'package:dplyr':  
##  
##      count
```

```
avgs = select(circ, ends_with("Average"))  
rowMins(as.matrix(avgs),na.rm=TRUE) [500:510]
```

```
## [1] 3538.5 3402.5 3862.5 3347.5 2837.5 2704.0 3138.5 3287.5 3275.0 3917.5  
## [11] 3046.0
```

Data Classes

Extensions of “normal” data classes:

- N-dimensional classes:
- Arrays: any extension of matrices with more than 2 dimensions, e.g. 3x3x3 cube
- Lists: more flexible container for R objects.

Arrays

These are just more flexible matrices - you should just be made aware of them as some functions return objects of this class, for example, cross tabulating over more than 2 variables and the `tapply` function.

Arrays

Selecting from arrays is similar to matrices, just with additional commas for the additional slots.

```
ar = array(1:27, c(3,3,3))  
ar[, , 1]
```

```
##      [,1] [,2] [,3]  
## [1,]    1    4    7  
## [2,]    2    5    8  
## [3,]    3    6    9
```

```
ar[, 1, ]
```

```
##      [,1] [,2] [,3]  
## [1,]    1   10   19  
## [2,]    2   11   20  
## [3,]    3   12   21
```

Splitting Data Frames

The `split()` function is useful for splitting `data.frames`

“`split` divides the data in the vector `x` into the groups defined by `f`. The replacement forms replace values corresponding to such a division. `unsplit` reverses the effect of `split`.”

```
> dayList = split(circ,circ$day)
```

Splitting Data Frames

Here is a good chance to introduce `lapply`, which performs a function within each list element:

```
> # head(dayList)
> lapply(dayList, head, n=2)
```

```
$Friday
  day      date orangeBoardings orangeAlightings orangeAverage
5 Friday 01/15/2010          1645           1643          1644.0
12 Friday 01/22/2010          1401           1388          1394.5
  purpleBoardings purpleAlightings purpleAverage greenBoardings
5              NA              NA              NA              NA
12             NA              NA              NA              NA
  greenAlightings greenAverage bannerBoardings bannerAlightings
5              NA              NA              NA              NA
12             NA              NA              NA              NA
  bannerAverage daily
5              NA 1644.0
12             NA 1394.5

$Monday
  day      date orangeBoardings orangeAlightings orangeAverage
1 Monday 01/11/2010           877           1027           952.0
8 Monday 01/18/2010           999           1000           999.5
  purpleBoardings purpleAlightings purpleAverage greenBoardings
1              NA              NA              NA              NA
8              NA              NA              NA              NA
  greenAlightings greenAverage bannerBoardings bannerAlightings
1              NA              NA              NA              NA
8              NA              NA              NA              NA
  bannerAverage daily
1              NA 952.0
8              NA 999.5

$Saturday
  day      date orangeBoardings orangeAlightings orangeAverage
6 Saturday 01/16/2010          1457           1524          1490.5
13 Saturday 01/23/2010          1202           1210          1206.0
  purpleBoardings purpleAlightings purpleAverage greenBoardings
6              NA              NA              NA              NA
13             NA              NA              NA              NA
  greenAlightings greenAverage bannerBoardings bannerAlightings
6              NA              NA              NA              NA
13             NA              NA              NA              NA
  bannerAverage daily
6              NA 1490.5
13             NA 1206.0

$Sunday
  day      date orangeBoardings orangeAlightings orangeAverage
7 Sunday 01/17/2010           839           938           888.5
14 Sunday 01/24/2010           715           711           713.0
  purpleBoardings purpleAlightings purpleAverage greenBoardings
7              NA              NA              NA              NA
14             NA              NA              NA              NA
  greenAlightings greenAverage bannerBoardings bannerAlightings
7              NA              NA              NA              NA
14             NA              NA              NA              NA
  bannerAverage daily
7              NA 888.5
14             NA 713.0

$Thursday
  day      date orangeBoardings orangeAlightings orangeAverage
4 Thursday 01/14/2010          1194           1233          1213.5
11 Thursday 01/21/2010          1303           1307          1305.0
  purpleBoardings purpleAlightings purpleAverage greenBoardings
```



```
> # head(dayList)
> lapply(dayList, dim)
```

```
$Friday
[1] 164 15
```

```
$Monday
[1] 164 15
```

```
$Saturday
[1] 163 15
```

```
$Sunday
[1] 163 15
```

```
$Thursday
[1] 164 15
```

```
$Tuesday
[1] 164 15
```

```
$Wednesday
[1] 164 15
```

Website

[Website](#)