IoT challenges

State of the art

Aghiles DJOUDI

PhD student
LIGM/ESIEE Paris & SIC/ECE Paris

September 8, 2019

Outline

Context

What is IoT ?



Figure 1: IoT platform.

Figure 2: IoT challenges.

Context

Introduction

- IoT Applications
  - Health care
  - **Transportation**
  - Industry
  - Market
  - Scool
  - Vehicles
  - Smart Home
  - Agriculture

Figure ??: IoT Applications

Problematic

Where is the problem ?



Figure 3: Key barriers in adopting the Industrial Internet [**industrialinternetofthings_executive_**].

Problematic

Where is the problem ?

- Some network configuration are static and not adptive to the application
  - Decision and optimisation problem..
  - Various network acces
  - Various configuration of each network acces
  - Lake of selection tools

- Users have to select the network and the application
  - How to select the **best** network.
  - How to select the network required by the application.

Motivations

Who & why cares with such problems ?

- ➟ a
  - ➟ Lake of selective tools
  - ➟ How to select the **best** access point

- ➟ QoS Analysis
  - ➟ a
  - ➟ Lake of selective tools
  - ➟ How to select the **best** access point

- ➟ Threats
  - ➟ a
  - ➟ Lake of selective tools
  - ➟ How to select the **best** access point



Figure 4: Communication diversity.

Goal

What is the goal ?

- Allow heterogeneous network to communicate
  - QoS Analysis
  - Threats
- How to select the **best** access point
  - Allow heterogeneous network to communicate
  - QoS Analysis
  - Threats

Figure 5: wsn-IoT.

Goal

What is the goal ?

- Allow heterogeneous network to communicate
- QoS Analysis
- Threats

- How to select the **best** access point
  - Allow heterogeneous network to communicate
  - QoS Analysis
  - Threats

Figure 5: wsn-IoT.

How to adapt the network to applications ?

Challenges

Where is the difficulty ?

- Reasonable and acceptable delay before the decision appears.
- Cope with the different view points and goals of the operators and the users.
- React to the changing environment conditions.
- Allow any type of inputs and to be applicable to any type of ANs.
- Handle the increasing number of RATs and the large number of criteria.

Contributions

Contributions

- Use cases (Requirements)
  - Smart building: Videos, Voice, Text.
  - Smart trafic: Videos, Voice, Text
- Environnements
  - Rural/Urban
  - Static/Mobile
  - Tempirature
- Senarios
  - For each application protocol (MQTT, COAP, XMPP)
  - For each network protocol (Start, Mesh)
  - For each MAC protocol (LoraWan, Sigfox, ...)
- Algorithms
  - Input:
    - Service QoS metrics requiremnts
    - MAC configuration (SF, CR, BW, ...)
    - Network QoS metrics
  - Method:
    - MADM, Game, Neural
  - Outputs:
    - Ranked networks

Contributions

Contributions

- Use cases (Requirements)
  - Smart building: Videos, Voice, Text.
  - Smart trafic: Videos, Voice, Text
- Environnements
  - Rural/Urban
  - Static/Mobile
  - Tempirature
- Senarios
  - For each application protocol (MQTT, COAP, XMPP)
  - For each network protocol (Start, Mesh)
  - For each MAC protocol (LoraWan, Sigfox, ...)
- Algorithms
  - Input:
    - Service QoS metrics requiremnts
    - MAC configuration (SF, CR, BW, ...)
    - Network QoS metrics
  - Method:
    - MADM, Game, Neural
  - Outputs:
    - Ranked networks

Theoretical, Simulation & Real environnement

Outline

Outline

1. Related work
2. Contagion process
3. Experimentation
4. Results exploitation
5. Discussion

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 1: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 2: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison

Table 3

Outline

Experimentation

Experimentation

- a
- b



Figure 6: .

Outline

Results

Comparison

- a
- b



Figure 7: .

Outline

Discussion

- a
- b



Figure 8: .

Outline

1. Problem statement
2. Related work
3. Contagion process
4. Experimentation
5. Results exploitation
6. Discussion

Outline

Problem statement

Introduction

- a
- b



Figure 9: .

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 4: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 5: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 6

Outline

Experimentation

Experimentation

- a
- b



Figure 10: .

Outline

Results

Comparison

- a
- b



Figure 11: .

Outline

Discussion

- a
- b



Figure 12: .

Outline

Outline

Problem statement

Introduction

- a
- b



Figure 13: .

Outline

Paper	A1	A2	A3	A4

Table 7: An example table.

Paper	A1	A2	A3	A4

Table 8: An example table.

Outline

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison

Table 9

Outline

Experimentation

Experimentation

- a
- b



Figure 14: .

Outline

Results

Comparison

- a
- b



Figure 15: .

Outline

Discussion

- a
- b



Figure 16: .

Outline

Outline

Problem statement

Introduction

- a
- b



Figure 17: .

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 10: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 11: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 12

Outline

Experimentation

Experimentation

- a
- b



Figure 18: .

Outline

Results

Comparison

- a
- b



Figure 19: .

Outline

Discussion

- a
- b



Figure 20: .

Outline

Outline

Problem statement

Introduction [2] ?

Bandwidth (*BW*) Spreading Factor (*SF*) Coding Rate (*CR*) Transmission Power (*Tx*) Receiver Sensitivity (*RS*) Signal Noise Rate (*SNR*) Data Rate (*DR*) ,Air Time (*AT*), Payload length (*PktL*)

Setting	Values	Rewards	Costs
BW	$7.8 \rightarrow 500kHz$	*DR*	*RS*, Range
SF	$2^6 \rightarrow 2^{12}$	*RS*, Range	*DR*, *SNR*, *PktL*, *Tx*
CR	$4/5 \rightarrow 4/8$	Resilience	*PktL*, *Tx*, *AT*
Tx	$-4 \rightarrow 20dBm$	*SNR*	*Tx*

Table 13: [1]

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 14: An example table.

Outline

Multi-Armed-Bandit Algorithm

Related work

- Arms: K = 1, ... , K
- Decision: T = 1, ... , T
- Reward: X_t^k with $\mu_t^k = \mathrm{E}\,[X_t^k]$
  - Best reward: X_t^* with $\mu_t^* = \max\, \mu_t^k$, k$\in$K

Binary code analysis: Why?









Outline

Genetic Algorithm

Related work [**alkhawlani_access_2008a**]

- Heterogeneous wireless network: (RAT 1 ,RAT 2 ,...,RAT n)
- Criteria up to i (c 1 ,c 2 ,...,c i) the operators, the applications, and the network conditions.
-
- The different sets of scores (d 1 , d 2 ,...,d i) are sent to the MCDM in the second component.
- GA component assigns a suitable weight (w 1 ,w 2 ,...,w i)

Genetic Algorithm

Related work

- S = SF12, BW125, 4/8, 17 dBm
- Input:
  - Problem: f(x) = max(x^2), x $\in$[0,32]
    - $x_1 : 01101_b$
    - $x_2 : 11000_b$
    - $x_3 : 01000_b$
    - $x_4 : 10011_b$
- Method: Genetic algorithm
  - Generate a set of random possible solution
  - Test each solution and see how good it is (ranking)
    - Remove some bad solutions
    - Duplicate some good solutions
    - Make small changes to some of them (Crossover, Mutation)
- Output:
  - x_1: 01101 (169) (14.4)

Outline

Marcov chain

Related work

$$V(s,\pi) = \mathbb{E}_s^{\pi}\left(\sum_{k=0}^{\inf} \gamma^k \cdot r(s_k, a_k)\right), s \in \mathbb{S} \tag{1}$$

$$r(s_k, a_k) = G_k \cdot PRR(a_k) \tag{2}$$

$$\pi^* = \arg\max_{\pi} V(s,\pi) \tag{3}$$

$$PRR = (1 - BER)^L \tag{4}$$

$$BER = 10^{\alpha e^{\beta\, SNR}} \tag{5}$$

Marcov chain

Related work

HGHGJ

$$V(s,\pi) = \mathbb{E}_s^{\pi}\left(\sum_{k=0}^{\inf} \gamma^k \cdot r(s_k, a_k)\right), s \in \mathbb{S} \tag{1}$$

$$r(s_k, a_k) = G_k \cdot PRR(a_k) \tag{2}$$

$$\pi^* = \arg\max_{\pi} V(s,\pi) \tag{3}$$

$$PRR = (1 - BER)^L \tag{4}$$

$$BER = 10^{\alpha e^{\beta\, SNR}} \tag{5}$$

Marcov chain

Related work

Learning Iterative Steps:

- **Choose** action $a_k(t) \sim \pi_k(t)$.
- **Observe** game outcome, e.g., $\boldsymbol{a}_{-k}(t)$ $u_k(a_k(t), \boldsymbol{a}_{-k}(t))$.
- **Improve** $\pi_k(t+1)$.



Thus, we can expect that: $\forall k \in \mathcal{K}$,

$$\pi_k(t) \xrightarrow{t\to\infty} \pi_k^* \tag{1}$$

$$\bar{u}_k(\pi_k(t), \pi_{-k}(t)) \xrightarrow{t\to\infty} \bar{u}_k(\pi_k^*, \pi_{-k}^*) \tag{2}$$

where, $\pi^* = (\pi_1^*, \ldots, \pi_K^*)$ is a NE strategy profile.

Figure 21: .

Outline

Game theory

Related work

- Players: $K = \{1, \ldots, K\}$
- Strategies: $S = S_1 \times \ldots \times S_K$
  - S_k is the strategy set of the k^{th} player.

- Rewards: $u_k : S \longrightarrow R_+$ and is denoted by $r_k(s_k, s_{-k})$
  - $s_{-k} = (s_1, \ldots, s_{k-1}, s_{k+1}, \ldots, s_K) \in S_1 \times \ldots \times S_{k-1} \times S_{k+1} \times \ldots \times S_K$

Related work

Comparison

Paper	A1	A2	A3	A4

Table 15: An example table.

Outline

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 16

Outline

Technical choice

Implementation

- ZOLERTIA RE-MOTE
  - Low consumption component
  - ADC port for placing sensors on it
- CONTIKI OS
  - Operating system for wireless and low power development
  - Support for newer standards (6LowPAN, RPL, CoAP, MQTT)
- 6LowPAN
  - Based on IPv6 and IEEE 802.15.4
  - IPv6-based network with low power consumption
  - Ability to create a mesh network
- Sending packages
  - UDP in the 6LowPAN network
  - MQTT between the cloud platform and the router

Experimentation

Experimentation

- a
- b



Figure 22: .

Outline

Results

Comparison

- a
- b



Figure 23: .

Outline

Discussion

- a
- b



Figure 24: .

Outline

Outline

Problem statement

Introduction

- a
- b



Figure 25: .

Outline

Paper	A1	A2	A3	A4

Table 17: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 18: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 19

Outline

Experimentation

Experimentation

- a
- b



Figure 26: .

Outline

Results

Comparison

- a
- b



Figure 27: .

Outline

Discussion

- a
- b



Figure 28: .

Outline

Outline

Problem statement

Introduction

- a
- b



Figure 29: .

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 20: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 21: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 22

Outline

Experimentation

Experimentation

- a
- b



Figure 30: .

Outline

Results

Comparison

- a
- b



Figure 31: .

Outline

Discussion

- a
- b



Figure 32: .

Outline

Conclusion

Our main goal was

Our main contribution was

Our main results was

Future Challenges

Conclusion

Our future goal was

Future Challenges

Conclusion

Our future goal was

Thank you !

Outline

Outline

Related work

Comparison

Works	Contribution	Goal
[3] **Protect U**	Classification of interlocutors	Friends lists management
[4] **Privacy Wizard**	Friends Classification	Permission Configuration
[5] **SocialMarket**	Common Interests	Assessment of Trust Relationships
[6] **PARE**	Information Leakage	Evaluation of Information Dissemination
[7] **LENS**	Spam Protection	Trusted Emitters Evaluation
[8] **SocialEmail**	Classify msg by paths	Evaluate message reliability
[9] **Privacy Index**	Visibility, sensitivity	Msg exposure assessment

Table 23: Contributions from existing work.

Outline

Step 1: Individual vulnerability measurement

Method

Parameter	Value	
Network connection	Private, Public	1,2
Technology	Ethernet, 5G, 4G, Wifi	[1:4]
Operating system	Windows, Unix, Mac	[1:3]
Web browser	Firefox, Chrome, Opera, ...	[1:10]
Password strength	low, medium, strength	[1:3]
Sessions opened	counter	[1:10]
TLS version	v1.0, v1.1, v1.2, v1.3	[1:4]

Table 24: Individual Vulnerability parameter

$$Y = \sum_{i}^{n} \frac{w * V}{n} \quad (6)$$

- **Y:** Individual vulnerability
- **w:** Weight of each vulnerability
- **V:** Scores mentioned above



Figure 33: Individual vulnerability level.

Step 2: Users reputation estimation

Method

Parameter	Value	
Frequency of msg exchanged	continuous	N
Discussion time	continuous	N
% of messages exchanged	cipher, signed or clear	[1:3]
Message type exchanged	Text, images, videos, script	[1:4]

Table 25: Trust grant features

$$\alpha = P(\textit{reputation}) = P(X \geq 1) \; = \; 1 \; - \; (1 \; - \; P(\textit{trust}))^{n} \qquad (7)$$

- Where,
  - **X**: trust grant, random variable, X ∼B(n,p)
  - **n**: deg(node)
  - **P(X=1)**: The probability of being assigned one trust grant by an interlocutor



Figure 34: Reputation level.

Step 3: Social vulnerability measurement

Freidkin's theory of social influence

- Input (Features):
  - $Y^{(1)}$ = Vector of the individual vulnerabilities of N users (eq 9)
  - α= The level of reputation (influence) of each user (eq 10)
  - M = Adjacency matrix N x N
- Model:

$$Y^{(t)} = \alpha M Y^{(t-1)} + (1-\alpha) Y^{(t-1)} \tag{8}$$

- Output:
  - $Y^{(t)}$ = Vector of the social vulnerabilities of the N users



Figure 35: Social vulnerability.

Step 3: Social vulnerability measurement

Freidkin's theory of social influence

Formal properties of the model:

- When a user's influence is high, the model is reduced to:
  - average vulnerabilities of his friends weighted by their trust levels.

$$Y^{(t)} = 1 * MY^{(t-1)} + (1-1)Y^{(t-1)} \quad (11)$$

$$Y^{(t)} = MY^{(t-1)}$$

- In the absence of influence, the model is reduced to:
  - his own vulnerability weighted by the level of mistrust of his friends

$$Y^{(t)} = 0 * MY^{(t-1)} + (1-0)Y^{(t-1)} \quad (11)$$

$$Y^{(t)} = Y^{(t-1)}$$



Figure 36: Social vulnerability.

Outline

Email datasets

Experimentation

Parameter	Value
Users	958
Messages	6966
Diameter	958
# of msg on average	2.413361
Msg density	0.00252
Modularity	0.654600
Average distance	3.042114

Table 26: Enron dataset properties.

Figure 37: Enron logo.

Parameter	Value
Users	5885
Messages	26547
Diameter	2096
# of msg on average	9.02192
Msg density	0.001533
Modularity	0.86526
Average distance	3.914097

Table 27: Caliopen dataset properties.

Figure 38: Caliopen logo.

Outline

Results

Comparison

Initial values:

- generated randomly (normal distribution)
- represent individual vulnerabilities.
- dark color = highly infected

Final values:

- obtained after convergence.
- represent social vulnerabilities.



(a) Individual privacy vulnerability.

(b) Social privacy vulnerability.

Figure 39: Individual & Social privacy vulnerabilities.

User ID	Individual Vul	Social Vul
34	0.84	0.67
67	0.12	0.87
206	0.76	0.33
588	0.23	0.78

Table 28: Individual and social privacy vulnerabilities.

Results exploitation



(a) Enron dataset.



(b) Caliopen dataset.

Figure 40: Cumulative distribution function of infected users.

- Figures shows the CDF of the vulnerability diffusion process.
- The vulnerability diffusion process increases as the reputation level of vulnerable users increases.
- Users with high reputation values contribute significantly to the diffusion
  - They spread their vulnerabilities quickly and widely through the network.

Results exploitation



(a) Enron dataset.



(b) Caliopen dataset.

Figure 41: Convergence of the diffusion process.

- The process converge when the mean distance between social vulnerability scores is the minimum.
- Assigning trust to vulnerable users allows them to achieve a high level of reputation.
- Consequently, they infect all other vulnerability values.

Outline

Discussion

- The purpose of this work is to simulate a diffusion process of individual vulnerabilities.
  - The vulnerability of one user is the vulnerability of all users.
  - At the end of the diffusion (convergence), all users gets their social vulnerability scores.

- Future work
  - To propose mechanisms to improve the reputation of non-vulnerable users.
    - Suggest well known interlocutors with acceptable vulnerability scores.
  - To propose mechanisms to improve the vulnerability of reputed users.
    - recommend configurations and softwares.

Discussion

- The purpose of this work is to simulate a diffusion process of individual vulnerabilities.
  - The vulnerability of one user is the vulnerability of all users.
  - At the end of the diffusion (convergence), all users gets their social vulnerability scores.

- Future work
  - To propose mechanisms to improve the reputation of non-vulnerable users.
    - Suggest well known interlocutors with acceptable vulnerability scores.
  - To propose mechanisms to improve the vulnerability of reputed users.
    - recommend configurations and softwares.

Thank you

Outline

1. Travaux connexes
2. Processus de diffusion
3. Expérimentation
4. Exploitation des résultats

Outline

Travaux connexes

Comparaison

Travaux	Contribution	Performance
[3] Protect U	Classification des interlocuteurs	Configuration des listes d'amis
[4] Privacy Wizard	Classification des interlocuteurs	Configuration des permissions
[5] SocialMarket	Intérêt communs	Évaluation des relation de confiance
[6] TAPE	Fuite d'information	Évaluation de la diffusion de l'info
[7] LENS	Protection anti-spam	Évaluation des émetteurs de confiance
[8] SocialEmail	Classer les chemins des msg	Évaluation de la fiabilité du message
[9] Privacy Index	Visibilité, sensibilité	Évaluation de l'exposition des msg

Table 29: Contributions des travaux existants.

Outline

Etape 1: Calcule de la vulnérabilité individuelle

Méthode

- Entrée:
  - Vulnérabilité de la machine utilisée:
    - Connexion réseaux (privé (1) ou publique (2))
    - Type d'architecture: Ethernet, 5G, 4G, Wifi (1:4)
    - Système d'exploitation (Windows, Unix) (1:2)
    - Navigateur web (1:10)
  - Vulnérabilité du compte utilisé
    - Mdp utilisé, mode de récupération des mdp (1:5)
    - Nombre de sessions ouvertes en même temps.(1:nbr)
    - Mode de chiffrement, signature, version TLS
- Sortie:

$$Pi = \sum_{i}^{n} \frac{w * V}{n} \tag{9}$$

Etape 2: Calcule de la réputation des utilisateurs

Méthode

- Entrée:
  - Fréquence d'utilisation de la messagerie.
  - Horaire, durée des échanges (1:5)
  - % des échanges chiffrés, signés, claires (1:3)
  - Importance des interlocuteurs: Liste favoris (2), noir(1)
  - Type de données: Texte, images, vidéos, script (1:4)

- Méthode:
  - Loi binomiale

- Output:

$$P(reputation) = P(X \geq 1) = 1 - (1 - P(trust))^n \quad (10)$$

  - Where,
    - X: Niveau de confiance, X ∼B(n,p)
    - n: deg(noeud)



Figure 42: Niveau de réputation.

Etape 3: Calcule de la vulnérabilité sociale

Théorie de l'influence sociale de Freidkin

- Entrée:
  - $Y^{(1)}$ = Vecteur des vulnérabilités individuelles de N utilisateurs (eq 9)
  - α= Le niveau de réputation (d'influence) de chaque utilisateur (eq 10)
  - M = Matrice d'adjacence N x N

- Modèle:

$$Y^{(t)} = \alpha M Y^{(t-1)} + (1-\alpha) Y^{(t-1)} \qquad (11)$$



Figure 43: Vulnérabilité Sociale.

- Sortie:
  - $Y^{(t)}$ = Vecteur des vulnérabilités sociales des N utilisateurs

Etape 3: Calcule de la vulnérabilité sociale

Théorie de l'influence sociale de Freidkin

Propriétés formelles du modèle:

- Lorsque l'influence d'un utilisateur est élevé, le modèle se réduit aux:
  - vulnérabilités moyennes de ses amis pondérées par leur niveaux de confiances.

$$Y^{(t)} = 1 * MY^{(t-1)} + (1-1)Y^{(t-1)} \qquad (11)$$

$$Y^{(t)} = MY^{(t-1)}$$



Figure 44: Vulnérabilité sociale.

- En absence d'influence, le modèle se réduit à:
  - sa propre vulnérabilité pondérée par le niveau de méfiance de ses amis

$$Y^{(t)} = 0 * MY^{(t-1)} + (1-0)Y^{(t-1)} \qquad (11)$$

$$Y^{(t)} = Y^{(t-1)}$$

Outline

Paramètre	Valeur
Utilisateurs	958
Messages	6966
Diamètre	958
# de msg en moyenne	2.413361
Densité des msg	0.00252
Modularité	0.654600
Distance moyenne	3.042114

Table 30: Propriétés des données Enron.

Figure 45: Enron logo.

Paramètre	Valeur
Utilisateurs	5885
Messages	26547
Diamètre	2096
# de msg en moyenne	9.02192
Densité des msg	0.001533
Modularité	0.86526
Distance moyenne	3.914097

Table 31: Propriétés des données Caliopen.

Figure 46: Caliopen logo.

Outline

Résultats

Comparaison

Valeurs initiales:

- générées aléatoirement (distribution normale)
- représentent les vulnérabilités individuelles.
- couleur foncée = vulnérabilité élevé

Valeurs finales:

- obtenu après convergence.
- représentent les vulnérabilités sociales.



(a) Vulnérabilité individuelle.

(b) Vulnérabilité Sociale.

Figure 47: Vulnérabilité individuelle & sociale.

User ID	Vul individuel	Vul sociale
34	0.84	0.67
67	0.12	0.87
206	0.76	0.33
588	0.23	0.78

Table 32: Différence entre les vulnérabilités individuelles et sociales en matière de protection de la vie privée.

Exploitation des résultats



(a) Les données de Enron.

(b) Les données de Caliopen.

Figure 48: Fonction de distribution cumulative des utilisateurs infectés.

- Les utilisateurs avec des valeurs de réputation élevées contribuent considérablement à la diffusion
- Ils diffusent leur vulnérabilités rapidement et largement dans la messagerie.

Exploitation des résultats



(a) Les données de Enron.

(b) Les données de Caliopen.

Figure 49: Convergence du processus de diffusion.

- Attribuer une confiance à des utilisateurs vulnérables leur permet d'obtenir un niveau de réputation élevé.
- Par conséquent, infecter l'ensemble des valeurs de vulnérabilité de la messagerie.

Outline

Outline

Related work

Comparison

Paper	A1	A2	A3	A4

Table 33: An example table.

Related work

Comparison

Paper	A1	A2	A3	A4

Table 34: An example table.

Outline

... (step 1)

Methods

... (step 2)

Methods

... (step 3)

Methods

... (step 4)

Methods

Results

Comparison



Table 35

Outline

Experimentation

Experimentation

- a
- b



Figure 50: .

Outline

Results

Comparison

- a
- b



Figure 51: .

Outline

Discussion

- a
- b



Figure 52: .

References

[1] Marco Cattani, Carlo Boano, and Kay Römer. “ An Experimental Evaluation of the Reliability of Lora Long-Range Low-Power Wireless Communication ”. In: *Journal of Sensor and Actuator Networks* 6.2 (2017). 00042, p. 7.

[2] B. Di Martino et al. “ Internet of Things Reference Architectures, Security and Interoperability: A Survey ”. In: *Internet of Things* 1-2 (Sept. 2018). 00006, pp. 99–112.

[3] Ala Eddine Gandouz. “ PROTECT_U: Un Systeme Communautaire Pour La Protection Des Usagers de Facebook ”. In: (2012). 00001, p. 77.

[4] Lujun Fang and Kristen LeFevre. “ Privacy Wizards for Social Networking Sites ”. In: 00397. ACM Press, 2010, p. 351.

[5] Davide Frey, Arnaud Jégou, and Anne-Marie Kermarrec. “ Social Market: Combining Explicit and Implicit Social Networks ”. In: *Stabilization, Safety, and Security of Distributed Systems*. Symposium on Self-Stabilizing Systems. Lecture Notes in Computer Science. 00019. Springer, Berlin, Heidelberg, Oct. 10, 2011, pp. 193–207.

[6] Yongbo Zeng et al. “ A Study of Online Social Network Privacy Via the TAPE Framework ”. In: *IEEE Journal of Selected Topics in Signal Processing* 9.7 (Oct. 2015). 00003, pp. 1270–1284.

[7] Sufian Hameed et al. “ LENS: Leveraging Social Networking and Trust to Prevent Spam Transmission ”. In: *Network Protocols (ICNP), 2011 19th IEEE International Conference On*. 00019. IEEE, 2011, pp. 13–18.

[8] Thomas Tran, Jeff Rowe, and S. Felix Wu. “ Social Email: A Framework and Application for More Socially-Aware Communications ”. In: *Social Informatics*. Ed. by Leonard Bolc, Marek Makowski, and Adam Wierzbicki. Vol. 6430. 00000. Berlin, Heidelberg: Springer Berlin Heidelberg, 2010, pp. 203–215.

[9] Raj Kumar Nepali and Yong Wang. “ SONET: A SOcial NETwork Model for Privacy Monitoring and Ranking ”. In: 00021. IEEE, July 2013, pp. 162–166.