

Week 8 Tutorial Sheet

(To be completed during the Week 8 tutorial class)

Objectives: The tutorials, in general, give practice in problem solving, in analysis of algorithms and data structures, and in mathematics and logic useful in the above.

Instructions to the class: Aim to attempt these questions before the tutorial! It will probably not be possible to cover all questions unless the class has prepared them in advance. There are marks allocated towards active participation during the class. You **must** attempt the problems under **Assessed Preparation** section **before** your tutorial class and give your worked out solutions to your tutor at the start of the class – this is a hurdle and failing to attempt these problems before your tutorial will result in 0 mark for that class even if you actively participate in the class.

Instructions to Tutors:

1. The purpose of the tutorials is not to solve the practical exercises!
2. The purpose is to check answers, and to discuss particular sticking points, not to simply make answers available.

Supplementary problems: The supplementary problems provide additional practice for you to complete after your tutorial class, or as pre-exam revision. Problems that are marked as (**Advanced**) difficulty are beyond the difficulty that you would be expected to complete in the exam, but are nonetheless useful practice problems as they will teach you skills and concepts that you can apply to other problems.

Assessed Preparation

Problem 1. Write the suffix array for the string ACACIA\$ and compute its Burrows-Wheeler transform.

Problem 2. Show the steps in the inverse Burrows-Wheeler transform for the string N\$RSOOCIMPSE.

Tutorial Problems

Problem 3. Write the suffix array for the string GATTACA\$ and compute its Burrows-Wheeler transform.

Problem 4. Show the steps in the inverse Burrows-Wheeler transform for the string TWOIPPR\$ENQ.

Problem 5. Compute the Burrows-Wheeler transform of the string woolloomooloo\$, and show the steps taken by the pattern matching algorithm for the following patterns:

- (a) olo
- (b) oll
- (c) oo
- (d) wol

Problem 6. Consider the prefix doubling algorithm applied to computing the suffix array of JARARAKA\$. Write the partially-sorted suffix array after the length two prefixes have been sorted. Write the corresponding rank

array and perform the next iteration of prefix doubling, showing the partially-sorted suffix array for the length four prefixes.

Problem 7. The *minimum lexicographical rotation* problem is the problem of finding, for a given string, its cyclic rotation that is lexicographically least. For example, given the string `banana`, its cyclic rotations are `banana`, `ananab`, `nanaba`, `anaban`, `nabana`, `abanan`. The lexicographically (alphabetically) least one is `abanan`. Describe how to solve the minimum lexicographical rotation problem using a suffix array.

Supplementary Problems

Problem 8. A string S of length n is called k -periodic if S consists of n/k repeats of the string $S[1..k]$. For example, the string `abababab` is two-periodic since it is made up of four copies of `ab`. Of course, all strings are n -periodic (they are made of one copy of themselves!) The *period* of a string is the minimum value of k such that it is k -periodic. Describe an efficient algorithm for determining the period of a string using a suffix array.

Problem 9. Write pseudocode for an algorithm that converts the suffix tree of a given string into the suffix array in $O(n)$ time.

Problem 10. (Advanced) Recall the pattern-matching algorithm that uses the Burrows-Wheeler transform of the text string. One downside of this algorithm is the large memory requirement if we decide to store the occurrences $\text{Occ}(c, i)$ explicitly for every position i and every character c . In this problem we will explore some space-time tradeoffs using *milestones*. Suppose that instead of storing $\text{Occ}(c, i)$ for all values of i , we decide to store it for every k^{th} position only, i.e. we store $\text{Occ}(c, 0)$, $\text{Occ}(c, k)$, $\text{Occ}(c, 2k)$, $\text{Occ}(c, 3k)$, ... for all characters c .

- (a) What is the space complexity of storing the preprocessed statistics in this case?
- (b) What is the time complexity of performing the preprocessing?

To compute $\text{Occ}(c, i)$, we will take the value of $\text{Occ}(c, j)$ where j is the nearest multiple of k up to i and then manually count the rest of the occurrences in $S[j + 1..i]$

- (c) What is the time complexity of performing a query for a pattern of length m ?
- (d) Describe how bitwise operations can be exploited to reduce the space complexity of the preprocessed statistics to $O\left(\frac{\lfloor \Sigma \rfloor n}{w}\right)$ where w is the number of bits in a machine word, while retaining the ability to perform pattern searches in $O(m)$.

Problem 11. (Advanced) A given suffix array could have come from many strings. For example, the suffix array 7, 6, 4, 2, 1, 5, 3 could have come from `banana$`, or from `dbxbxa$`, or many other possible strings.

- (a) Devise an algorithm that given a suffix array, determines any string that would produce that suffix array. You can assume that you have as large of an alphabet as you need.
- (b) Devise an algorithm that given a suffix array, determines the lexicographically least string that would produce that suffix array. You can assume that you have as large of an alphabet as required. Your algorithm should run in $O(n)$ time