Not Secure brie.mycybersecurityclass.com Relaunch to update

Apache2 Debian Default Page

debian

It works!

This is the default welcome page used to test the correct operation of the Apache2 server after installation on Debian systems. If you can read this page, it means that the Apache HTTP server installed at this site is working properly. You should **replace this file** (located at `/var/www/html/index.html`) before continuing to operate your HTTP server.

If you are a normal user of this web site and don't know what this page is about, this probably means that the site is currently unavailable due to maintenance. If the problem persists, please contact the site's administrator.

Configuration Overview

Debian's Apache2 default configuration is different from the upstream default configuration, and split into several files optimized for interaction with Debian tools. The configuration system is **fully documented in /usr/share/doc/apache2/README.Debian.gz**. Refer to this for the full documentation. Documentation for the web server itself can be found by accessing the **manual** if the apache2-doc package was installed on this server.

The configuration layout for an Apache2 web server installation on Debian systems is as follows:

```
/etc/apache2/
|-- apache2.conf
|       `--  ports.conf
|-- mods-enabled
|       |-- *.load
|       `-- *.conf
|-- conf-enabled
|       `-- *.conf
|-- sites-enabled
|       `-- *.conf
```

- `apache2.conf` is the main configuration file. It puts the pieces together by including all remaining configuration files when starting up the web server.
- `ports.conf` is always included from the main configuration file. It is used to determine the listening ports for incoming connections, and this file can be customized anytime.
- Configuration files in the `mods-enabled/`, `conf-enabled/` and `sites-enabled/` directories contain particular configuration snippets which manage modules, global configuration fragments, or

☐	✓	brie	us-central1-c	192.168.200.7 (nic0)	34.45.149.163 (nic0)	SSH

```
devweb@brie:~$ sudo -
```

```
root@brie:/home/devweb# uname -a
Linux brie 6.1.0-43-cloud-amd64 #1 SMP PREEMPT_DYNAMIC Debian 6.1.162-1 (2026-02-08) x86_64 GNU/Linux
```

```
root@brie:/home/devweb# ip addr
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
       valid_lft forever preferred_lft forever
2: ens4: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1460 qdisc mq state UP group default qlen 1000
    link/ether 42:01:c0:a8:c8:07 brd ff:ff:ff:ff:ff:ff
    altname enp0s4
    inet 192.168.200.7/32 metric 100 scope global dynamic ens4
       valid_lft 2303sec preferred_lft 2303sec
    inet6 fe80::4001:c0ff:fea8:c807/64 scope link
       valid_lft forever preferred_lft forever
```

```
root@brie:/home/devweb# systemctl status apache2
● apache2.service - The Apache HTTP Server
     Loaded: loaded (/lib/systemd/system/apache2.service; enabled; preset: enabled)
     Active: active (running) since Thu 2026-02-26 16:30:20 UTC; 28min ago
       Docs: https://httpd.apache.org/docs/2.4/
   Main PID: 3579 (apache2)
      Tasks: 55 (limit: 2344)
     Memory: 9.4M
        CPU: 233ms
     CGroup: /system.slice/apache2.service
             ├─3579 /usr/sbin/apache2 -k start
             ├─3580 /usr/sbin/apache2 -k start
             └─3581 /usr/sbin/apache2 -k start

Feb 26 16:30:20 brie systemd[1]: Starting apache2.service - The Apache HTTP Server...
Feb 26 16:30:20 brie systemd[1]: Started apache2.service - The Apache HTTP Server.
```

	brie	brie.mycybersecurityclass.com.	Off	Public

DNS name	Type	TTL (seconds)	Record data
brie.mycybersecurityclass.com.	NS	21600	ns-cloud-a1.googledomains.com.
brie.mycybersecurityclass.com.	SOA	21600	ns-cloud-a1.googledomains.com. cloud-dns-hostmaster.google.com. 1 21600
brie.mycybersecurityclass.com.	A	0	34.45.149.163

```
briellathompson@Kaylas-MacBook-Air-3 ~ % nslookup brie.mycybersecurityclass.com
Server:         205.118.215.90
Address:        205.118.215.90#53

Non-authoritative answer:
Name:   brie.mycybersecurityclass.com
Address: 34.45.149.163
```

```
<p>
    1. What are the biggest security risks in your current setup?
    In the current setup you can see a tab at the top saying the site is not secure. This would mean
    that if anyone were to access the site or input any personal information, the site is prone
    to attackers and hackers. This is because the site is not using HTTPS, which encrypts data
    between the user's browser and the server.



    3. What does NAT protect you from?
    It protects your internal network from external threats by hiding your internal IP addresses.

    4. What would you change to make this production-ready?
    I would change the site to use HTTPS instead of HTTP to ensure that data is encrypted and secure.
    I would also add security measures to ensure users are not vulnerable to attacks.

    5. If you were an attacker, what would you target first?
    I would want to try and access any users personal information escpecially their login and passwords to make
    sure I can access their accounts and cause harm.
</p>
```