CWL in ARCs

DataPLANT Data Steward Circle – Feb 5th, 2025 Dominik Brilhaus








Example tool: FastQC

First step in RNASeq data analysis: QC of read files (e.g. *.fastq)











FastQC has a GUI











Are we FAIR yet?







Command line tool

- Some tool that you can run ... on the command line
- Example:
 - CLI: ARC Commander
 - (GUI: ARCitect)
- Takes arguments or parameters as **inputs**
- Generates **outputs**







FastQC via command line

```
fastqc --version
fastqc --help
```








FastQC via command line

fastqc assays/rnaseq/dataset/blau1_CGATGT_L005_R1_002.fastq.gz









Materials & Methods

```
fastqc assays/rnaseq/dataset/sample1
fastqc assays/rnaseq/dataset/sample2
fastqc assays/rnaseq/dataset/ ...
```

"FastQC v0.12.1 was employed for read quality control using default parameters."







Installing bioinformatic tools



- From source:
 - https://www.bioinformatics.babraham.ac.uk/projects/download.html#fastqc
- Docker: docker pull quay.io/biocontainers/fastqc:0.11.9—hdfd78af_1
- Conda: conda install fastqc







Why CWL and ARCs

- Reproducibility / Replicability of the data
 - Rerunning the same analysis on the **same** dataset
- Reusability of the analysis
 - Applying the same (type of) analysis on another dataset







Some factors affecting reproducibility & reusability

- Operating system (linux, win, mac) and version
- Version of tool / software
- Version of package/library and interpreter (python, R, F#, etc.)
- ...







Approaches towards CWL in ARCs

- 1. Wrap a script
- 2. Wrap a CLI tool
- 3. Reuse an existing CWL document (command line tool or full workflow)
- 4. ...







Demo: CWL-Wrapping the CommandLineTool FastQC







Step 1

- Without in/out
- Local tool installed

```
#!/usr/bin/env cwl-runner
cwlVersion: v1.2
class: CommandLineTool

baseCommand: ["fastqc", "--help"]
inputs: []
outputs: []
```







Step 2: Add a docker container

```
#!/usr/bin/env cwl-runner
cwlVersion: v1.2
class: CommandLineTool
hints:
  DockerRequirement:
    dockerPull: quay.io/biocontainers/fastqc:0.11.9--hdfd78af_1
baseCommand: ["fastqc", "--help"]
inputs: []
outputs: []
```







Step 3: Define inputs

```
#!/usr/bin/env cwl-runner
cwlVersion: v1.2
class: CommandLineTool
hints:
  DockerRequirement:
    dockerPull: quay.io/biocontainers/fastqc:0.11.9--hdfd78af_1
baseCommand: ["fastqc"]
inputs:
  reads:
    type: File[]
    inputBinding:
      position: 1
arguments:
  - valueFrom: $(runtime.outdir)
    prefix: "-o"
outputs: []
```







Step 4: Define outputs

```
#!/usr/bin/env cwl-runner
cwlVersion: v1.2
class: CommandLineTool
hints:
 DockerRequirement:
    dockerPull: quay.io/biocontainers/fastqc:0.11.9--hdfd78af_1
baseCommand: ["fastqc"]
inputs:
  reads:
    type: File[]
    inputBinding:
      position: 1
arguments:
  - valueFrom: $(runtime.outdir)
    prefix: "-o"
outputs:
 fastqc_out:
      type: File[]
      outputBinding:
        glob:
          - "*_fastqc.zip"
          - "*_fastqc.html"
```








Step 4: Define outputs

```
#!/usr/bin/env cwl-runner
cwlVersion: v1.2
class: CommandLineTool
hints:
  DockerRequirement:
    dockerPull: quay.io/biocontainers/fastqc:0.11.9--hdfd78af_1
baseCommand: ["fastqc"]
inputs:
  reads:
    type: File[]
    inputBinding:
      position: 1
arguments:
  - valueFrom: $(runtime.outdir)
    prefix: "-o"
outputs:
  fastqc_out:
      type: File[]
      outputBinding:
        qlob:
          - "*_fastqc.zip"
- "*_fastqc.html"
```









Run the workflow

You can provide arguments via another file:

```
run.yml
```

```
reads:
    - class: File
    path: ../../assays/rnaseq/dataset/blau1_CGATGT_L005_R1_002.fastq.gz
    - class: File
    path: ../../assays/rnaseq/dataset/blau2_TGACCA_L005_R1_002.fastq.gz
```







Reusability: Simply import an existing CWL


• e.g. from one ARC to another







Example workflow: First steps RNASeq pipeline









CWL is a time investment at first

There's a *tiny* learning curve and some dependencies

- JavaScript
- Docker
- Conda and the cwltool (reference runner)







Resources

- Specification v1.2: https://www.commonwl.org/v1.2/CommandLineTool.html
- Published Workflows: https://view.commonwl.org/workflows
- CWL repos: https://www.commonwl.org/repos/
- bio-cwl-tools: https://github.com/common-workflow-library/bio-cwl-tools/tree/release
- EBI-Metagenomics: https://github.com/EBI-Metagenomics/workflow-is-cwl/tree/master/tools
- Scatter example: https://github.com/Gibbsdavidl/CWL_scatter_example
- CWL tool: https://github.com/common-workflow-language/cwltool





