| **Exp No: 12** | **End-End Communication at Transport Layer - Echo Client Server and Chat** |
|---|---|

## AIM:

To implement (a) an echo client-server using TCP and UDP sockets and (b) a chat program using socket programming, for end-to-end communication at the transport layer.

## ALGORITHM / PROCEDURE:

### (a1) TCP echo server and client

1. **Server**: create a TCP socket with `socket(AF_INET, SOCK_STREAM)`, `bind()` it to an IP address and port (5000), call `listen()` and wait in `accept()` for the client.
2. **Client**: create a TCP socket and call `connect()` with the IP address and port of the server.
3. The client sends a message using `send()`. The server reads it with `recv()`, displays it and sends the same data back using `sendall()`.
4. The client receives the echoed message and displays it. This is repeated for each message.
5. Close the sockets using `close()`.

### (a2) UDP echo server and client

1. **Server**: create a UDP socket with `SOCK_DGRAM` and `bind()` it to port 6000. No `listen()` / `accept()` is needed because UDP is connectionless.
2. **Client**: create a UDP socket and send the message to the server address with `sendto()`.
3. The server receives the datagram and the client address with `recvfrom()` and sends it back using `sendto()`.
4. The client receives the echo with `recvfrom()` and displays it. Close the sockets.

### (b) Chat program

1. The chat server creates a TCP socket on port 7000 and waits for a client. The client connects to it.
2. The client types a message and sends it. The server displays it, then the server user types the reply and sends it back.
3. Messages are exchanged alternately until either side sends the word `exit`. Then both sockets are closed.

| **Point** | **TCP** | **UDP** |
|---|---|---|
| Socket type | SOCK_STREAM | SOCK_DGRAM |
| Connection | Connection oriented (3-way handshake) | Connectionless |
| Reliability | Reliable, ordered delivery | No guarantee |
| Server calls | bind, listen, accept, recv, send | bind, recvfrom, sendto |
| Used in | HTTP, FTP, SMTP | DNS, DHCP, streaming |

**`echo_tcp_client.py`**

```
import socket c = socket.socket(socket.AF_INET,
socket.SOCK_STREAM)
c.connect(("127.0.0.1", 5000)) for msg in ["Hello Server",
"Computer Networks Lab", "bye"]:
```

# DIAGRAM:





**Fig 1: Socket calls in TCP client-server communication**





**Fig 2: Socket calls in UDP client-server communication**

# PROGRAM:

**echo_tcp_server.py**

```
import socket s = socket.socket(socket.AF_INET,
socket.SOCK_STREAM)
s.bind(("127.0.0.1", 5000))
s.listen(1) print("TCP Echo Server listening on
port 5000 ...") conn, addr = s.accept()
print("Connected by", addr) while True:
    data =
conn.recv(1024)     if
not data:         break
    print("Received :", data.decode())
conn.sendall(data)               # echo back
conn.close()
s.close()
print("Connection
closed.")
```

**echo_tcp_client.py (contd.)**

```
    c.sendall(msg.encode())       print("Sent
:",  msg)            print("Echoed       :",
c.recv(1024).decode())
c.close()
```

**echo_udp_server.py**

```
import socket s = socket.socket(socket.AF_INET,
socket.SOCK_DGRAM)
s.bind(("127.0.0.1", 6000)) print("UDP Echo
Server waiting on port 6000 ...") for _ in
range(2):
    data, addr = s.recvfrom(1024)
print("Received from", addr, ":", data.decode())
    s.sendto(data, addr)
s.close()
```

**echo_udp_client.py**

```
import socket c = socket.socket(socket.AF_INET,
socket.SOCK_DGRAM) for msg in ["Hello UDP",
"Datagram test"]:
    c.sendto(msg.encode(), ("127.0.0.1",
6000))     data, _ = c.recvfrom(1024)
print("Sent     :", msg)     print("Echoed
:", data.decode())
c.close()
```

**chat_server.py**

**chat_client.py**

```
import socket c =
socket.socket()
c.connect(("127.0.0.1", 7000)) print("Connected to
chat server. Type 'exit' to quit.") while True:
    msg = input("Client : ")
    c.send(msg.encode())
if msg.lower() == "exit":
        break
    reply = c.recv(1024).decode()
if reply.lower() == "exit":
        break
print("Server :", reply)
c.close()
print("Chat
ended.")
```

```
import socket s =
socket.socket()
s.bind(("127.0.0.1", 7000))
s.listen(1) print("Chat server started. Waiting
for client ...") conn, addr = s.accept()
print("Client connected:", addr) while True:
    msg = conn.recv(1024).decode()
if not msg or msg.lower() == "exit":
        break
print("Client :", msg)
reply = input("Server : ")
conn.send(reply.encode())
if reply.lower() == "exit":
        break
conn.close()
s.close()
print("Chat
ended.")
```

# OUTPUT:

## (a1) TCP echo

**balaji@balaji-VirtualBox: ~ (Terminal 1 - Server)**

```
balaji@balaji-VirtualBox:~$ python3 echo_tcp_server.py
TCP Echo Server listening on port 5000 ...
Connected by ('127.0.0.1', 46248)
Received : Hello Server
Received : Computer Networks Lab
Received : bye
Connection closed.
```

**balaji@balaji-VirtualBox: ~ (Terminal 2 - Client)**

```
balaji@balaji-VirtualBox:~$ python3 echo_tcp_client.py
Sent     : Hello Server
Echoed   : Hello Server
Sent     : Computer Networks Lab
Echoed   : Computer Networks Lab
Sent     : bye
Echoed   : bye
```

## (a2) UDP echo

**balaji@balaji-VirtualBox: ~ (Terminal 2 - Chat Client)**

```
balaji@balaji-VirtualBox:~$ python3 chat_client.py
Connected to chat server. Type 'exit' to quit.
Client : Hi Server, this is Balaji
Server : Hello Balaji, how can I help?
Client : Is the CN lab record ready?
Server : Yes, the lab record is due on Friday.
Client : Thanks, bye
Chat ended.
```

**balaji@balaji-VirtualBox: ~ (Terminal 1 - Server)**

```
balaji@balaji-VirtualBox:~$ python3 echo_udp_server.py
UDP Echo Server waiting on port 6000 ...
Received from ('127.0.0.1', 53205) : Hello UDP
Received from ('127.0.0.1', 53205) : Datagram test
```

**balaji@balaji-VirtualBox: ~ (Terminal 2 - Client)**

```
balaji@balaji-VirtualBox:~$ python3 echo_udp_client.py
Sent     : Hello UDP
Echoed   : Hello UDP
Sent     : Datagram test
Echoed   : Datagram test
```

### (b) Chat program

**balaji@balaji-VirtualBox: ~ (Terminal 1 - Chat Server)**

```
balaji@balaji-VirtualBox:~$ python3 chat_server.py
Chat server started. Waiting for client ...
Client connected: ('127.0.0.1', 43260)
Client : Hi Server, this is Balaji
Server : Hello Balaji, how can I help?
Client : Is the CN lab record ready?
Server : Yes, the lab record is due on Friday.
Client : Thanks, bye
Server : exit
Chat ended.
```

## RESULT:

Thus the echo client-server programs using TCP and UDP sockets and the chat program using socket programming were implemented and executed successfully.