



Full Database Schema

PostgreSQL-compatible relational schema mapped from the BrisConnect Firestore collections.

Generated: 2026-08-09

Total tables: 42 | Total indexes: 45+

Table of Contents

1. Auth / Users
2. Businesses
3. Attractions & Discover
4. Events
5. Business Events & Promotions
6. Reviews & Recommendations
7. Social & Engagement
8. Reports & Feedback
9. Notifications & Messaging
10. Payments & Subscriptions
11. Curated Content
12. System / Config

Complete SQL Schema

The full schema is reproduced below. Each table includes primary keys, foreign keys, indexes, and default values.

```
-- =====  
-- BrisConnect+ Full Database Schema (Firestore → PostgreSQL compatible SQL)
```

```
-- =====
-- This file maps every Firestore collection referenced in the BrisConnect
-- Flutter app and Cloud Functions into a normalized relational schema.
--
-- Conventions:
--   - Primary keys are UUID/SERIAL unless a Firestore doc ID is semantic
--     (e.g. admins.email, local_users.email).
--   - JSONB is used for flexible maps/history objects that Firestore stores
--     as nested maps (socialMedia, viewHistory, businessHours, etc.).
--   - TIMESTAMP WITH TIME ZONE is used for all date/time fields.
--   - Soft deletes use deleted_at / deleted_by columns.
```

```

-- =====
-- -----
-- 1. AUTH / USERS
-- -----

CREATE TABLE admins (
  email          VARCHAR(255) PRIMARY KEY,
  username       VARCHAR(255) NOT NULL,
  name           VARCHAR(255),
  role           VARCHAR(50)  NOT NULL DEFAULT 'admin',
  active         BOOLEAN      NOT NULL DEFAULT TRUE,
  profile_image_url TEXT,
  last_login_at  TIMESTAMPTZ,
  updated_at     TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

CREATE TABLE local_users (
  email          VARCHAR(255) PRIMARY KEY,
  username       VARCHAR(255) NOT NULL,
  name           VARCHAR(255) NOT NULL,
  phone          VARCHAR(50),
  suburb         VARCHAR(255),
  role           VARCHAR(50)  NOT NULL DEFAULT 'local',
  account_type   VARCHAR(50)  NOT NULL DEFAULT 'local',
  approval_status VARCHAR(50) NOT NULL DEFAULT 'pending',
  password_hash  TEXT         NOT NULL,
  interested_event_ids TEXT[]  DEFAULT '{}',
  interest_categories TEXT[]  DEFAULT '{}',
  notifications_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  event_reminders_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  reminder_timing VARCHAR(50) NOT NULL DEFAULT '24h',
  event_updates_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  nearby_events_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  recommended_events_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  use_current_location BOOLEAN NOT NULL DEFAULT TRUE,
  location_radius_km INT      NOT NULL DEFAULT 20,
  location_access_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  theme_preference VARCHAR(50) NOT NULL DEFAULT 'system',
  text_scale_factor DECIMAL(3,2) NOT NULL DEFAULT 1.00,
  profile_image_base64 TEXT,
  profile_image_url TEXT,
  profile_image_storage_path TEXT,
  notify_trending_promotion BOOLEAN NOT NULL DEFAULT TRUE,
  notify_offer_expiry   BOOLEAN NOT NULL DEFAULT TRUE,
  notify_new_review     BOOLEAN NOT NULL DEFAULT TRUE,
  notify_business_updates BOOLEAN NOT NULL DEFAULT TRUE,
  created_at            TIMESTAMPTZ NOT NULL DEFAULT NOW(),
  password_updated_at   TIMESTAMPTZ,
  updated_at            TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

CREATE TABLE visitor_users (
  email          VARCHAR(255) PRIMARY KEY,
  username       VARCHAR(255) NOT NULL,
  name           VARCHAR(255) NOT NULL,
  phone          VARCHAR(50),
  role           VARCHAR(50)  NOT NULL DEFAULT 'visitor',
  password_hash  TEXT         NOT NULL,
  interested_event_ids TEXT[]  DEFAULT '{}',
  saved_attraction_ids TEXT[]  DEFAULT '{}',
  saved_business_ids  TEXT[]  DEFAULT '{}',
  interest_categories TEXT[]  DEFAULT '{}',
  interest_priorities TEXT[]  DEFAULT '{}',
  notifications_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  event_reminders_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  reminder_timing VARCHAR(50) NOT NULL DEFAULT '24h',
  event_updates_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  nearby_events_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  recommended_events_enabled BOOLEAN NOT NULL DEFAULT TRUE,
  email_notifications_enabled BOOLEAN NOT NULL DEFAULT TRUE,

```

```

    use_current_location      BOOLEAN      NOT NULL DEFAULT TRUE,
    location_radius_km        INT           NOT NULL DEFAULT 20,
    location_access_enabled   BOOLEAN      NOT NULL DEFAULT TRUE,
    theme_preference          VARCHAR(50)   NOT NULL DEFAULT 'system',
    text_scale_factor         DECIMAL(3,2)  NOT NULL DEFAULT 1.00,
    language                  VARCHAR(10)   NOT NULL DEFAULT 'en',
    profile_image_base64      TEXT,
    profile_image_url         TEXT,
    profile_image_storage_path TEXT,
    created_at                TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    password_updated_at       TIMESTAMPTZ,
    updated_at                TIMESTAMPTZ   NOT NULL DEFAULT NOW()
);

```

```
-- FCM push tokens (subcollection of local_users in Firestore)
```

```

CREATE TABLE local_user_fcm_tokens (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    local_user_email  VARCHAR(255) NOT NULL REFERENCES local_users(email) ON DELETE CASCADE,
    token            TEXT          NOT NULL,
    platform         VARCHAR(50),
    created_at       TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    updated_at       TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    UNIQUE(local_user_email, token)
);

```

```
-- In-app notifications for business owners (subcollection of local_users)
```

```

CREATE TABLE local_user_notifications (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    local_user_email  VARCHAR(255) NOT NULL REFERENCES local_users(email) ON DELETE CASCADE,
    title            VARCHAR(500) NOT NULL,
    body            TEXT,
    type            VARCHAR(100),
    read            BOOLEAN        NOT NULL DEFAULT FALSE,
    data            JSONB,
    created_at       TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    updated_at       TIMESTAMPTZ   NOT NULL DEFAULT NOW()
);

```

``` -- ----- -- 2. BUSINESSES -- ----- ```

```

CREATE TABLE businesses (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    owner_id          VARCHAR(255) NOT NULL REFERENCES local_users(email) ON DELETE CASCADE,
    business_name     VARCHAR(500) NOT NULL,
    category          VARCHAR(255) NOT NULL,
    description       TEXT,
    address           TEXT,
    lat               DECIMAL(10, 8),
    lng               DECIMAL(11, 8),
    contact_number    VARCHAR(100),
    website           TEXT,
    social_media      JSONB,
    logo_url          TEXT,
    cover_image_url   TEXT,
    business_hours    JSONB,
    price_range       VARCHAR(50),
    audio_guide_url   TEXT,
    audio_guide_narration TEXT,
    photos            TEXT[],
    is_verified       BOOLEAN        NOT NULL DEFAULT FALSE,
    rating            INT,
    average_rating    DECIMAL(3, 2),
    buzz_rating       DECIMAL(3, 2),
    buzz_score        DECIMAL(5, 2) NOT NULL DEFAULT 0.00,
    is_trending       BOOLEAN        NOT NULL DEFAULT FALSE,
    view_count        INT           NOT NULL DEFAULT 0,
    saved_count       INT           NOT NULL DEFAULT 0,
    review_count      INT           NOT NULL DEFAULT 0,
    view_history      JSONB         DEFAULT '{}',

```

```

        save_history          JSONB          DEFAULT '{}',
        is_active             BOOLEAN        NOT NULL DEFAULT TRUE,
        deleted_at            TIMESTAMPTZ,
        deleted_by            VARCHAR(255),
        duplicate_of          UUID           REFERENCES businesses(id),
        created_at            TIMESTAMPTZ    NOT NULL DEFAULT NOW(),
        updated_at            TIMESTAMPTZ    NOT NULL DEFAULT NOW()
    );

CREATE INDEX idx_businesses_owner ON businesses(owner_id);
CREATE INDEX idx_businesses_category ON businesses(category);
CREATE INDEX idx_businesses_active_deleted ON businesses(is_active, deleted_at);

CREATE TABLE business_menu_items (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id       UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    name              VARCHAR(500) NOT NULL,
    description        TEXT,
    price             DECIMAL(10, 2),
    image_url         TEXT,
    tags              TEXT[],
    sort_order        INT NOT NULL DEFAULT 0,
    created_at        TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at        TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-- Soft-deleted business archive (mirrors businesses)
CREATE TABLE business_archive (
    id                UUID PRIMARY KEY,
    payload           JSONB NOT NULL,
    archived_at       TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    archived_by       VARCHAR(255)
);

-- Admin verification audit log
CREATE TABLE business_verification_log (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id       UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    admin_email       VARCHAR(255) NOT NULL REFERENCES admins(email),
    action            VARCHAR(100) NOT NULL,
    reason            TEXT,
    verified_at       TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-- Legacy seeded food/drink businesses (imported/demo data)
CREATE TABLE food_businesses (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name              VARCHAR(500) NOT NULL,
    description        TEXT,
    address            TEXT,
    phone              VARCHAR(100),
    website            TEXT,
    cuisine_types      TEXT[],
    image_url         TEXT,
    latitude           DECIMAL(10, 8),
    longitude          DECIMAL(11, 8),
    average_rating     DECIMAL(3, 2),
    review_count       INT DEFAULT 0,
    operating_hours    TEXT,
    email              VARCHAR(255),
    facebook_url       TEXT,
    instagram_url      TEXT,
    online_order_url   TEXT,
    created_at         TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at         TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-----
-- 3. ATTRACTIONS & DISCOVER
-----
CREATE TABLE attractions (

```



```

    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name              VARCHAR(500) NOT NULL,
    title             VARCHAR(500),
    description        TEXT,
    location           TEXT,
    latitude           DECIMAL(10, 8),
    longitude          DECIMAL(11, 8),
    category           VARCHAR(255),
    accessibility_details TEXT,
    web_link           TEXT,
    image_url          TEXT,
    image_storage_path TEXT,
    audio_url          TEXT,
    audio_storage_path TEXT,
    approval_status    VARCHAR(50) NOT NULL DEFAULT 'pending',
    is_approved        BOOLEAN NOT NULL DEFAULT FALSE,
    created_at         TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at         TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE TABLE attraction_details (
    attraction_id      UUID PRIMARY KEY REFERENCES attractions(id) ON DELETE CASCADE,
    history            TEXT,
    address            TEXT,
    opening_hours      TEXT,
    special_schedule   TEXT,
    entry_requirements TEXT,
    ticket_price       VARCHAR(255),
    booking_label      VARCHAR(255),
    booking_url        TEXT,
    rating             DECIMAL(3, 2),
    review_count       INT DEFAULT 0,
    facilities         TEXT,
    amenities          TEXT,
    accessibility      TEXT,
    visit_duration     VARCHAR(255),
    best_time_to_visit TEXT,
    live_update        TEXT,
    nearby_attractions TEXT,
    nearby_services    TEXT,
    languages          TEXT,
    audio_features     TEXT
);

```

-- Approved attractions web view (denormalized)

```

CREATE TABLE approved_attractions (
    id                UUID PRIMARY KEY REFERENCES attractions(id),
    payload           JSONB NOT NULL,
    approved_at       TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

-- Denormalized discover catalog

```

CREATE TABLE discover_items (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    title             VARCHAR(500) NOT NULL,
    section           VARCHAR(100),
    category           VARCHAR(255),
    location           TEXT,
    venue             VARCHAR(500),
    suburb            VARCHAR(255),
    event_date        VARCHAR(50),
    event_time        VARCHAR(50),
    date_time         TIMESTAMPTZ,
    description        TEXT,
    approval_status    VARCHAR(50) NOT NULL DEFAULT 'pending',
    source            VARCHAR(100),
    source_provider    VARCHAR(255),
    source_place_id    VARCHAR(255),
    source_url         TEXT,
    created_by_local_email VARCHAR(255) REFERENCES local_users(email),
    image_url          TEXT,

```

```

        audio_url          TEXT,
        video_url          TEXT,
        updated_at         TIMESTAMPTZ NOT NULL DEFAULT NOW()
    );

```

```

CREATE INDEX idx_discover_items_section ON discover_items(section);
CREATE INDEX idx_discover_items_category ON discover_items(category);

```

-- 4. EVENTS

```

CREATE TABLE events (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    title             VARCHAR(500) NOT NULL,
    event_date        VARCHAR(50),
    event_time        VARCHAR(50),
    date_time         TIMESTAMPTZ,
    category          VARCHAR(255),
    location          TEXT,
    venue             VARCHAR(500),
    suburb            VARCHAR(255),
    description        TEXT,
    created_by_local_email VARCHAR(255) REFERENCES local_users(email),
    review_status      VARCHAR(50),
    approval_status    VARCHAR(50) NOT NULL DEFAULT 'pending',
    status            VARCHAR(50) NOT NULL DEFAULT 'pending',
    is_approved        BOOLEAN NOT NULL DEFAULT FALSE,
    report_count       INT NOT NULL DEFAULT 0,
    flagged_for_admin_review BOOLEAN NOT NULL DEFAULT FALSE,
    source            VARCHAR(100),
    source_provider    VARCHAR(255),
    source_url         TEXT,
    latitude           DECIMAL(10, 8),
    longitude          DECIMAL(11, 8),
    created_at         TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at         TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_events_created_by ON events(created_by_local_email);
CREATE INDEX idx_events_status ON events(status);
CREATE INDEX idx_events_category ON events(category);

```

-- Many-to-many: locals and visitors interested in events

```

CREATE TABLE event_interests (
    event_id          UUID NOT NULL REFERENCES events(id) ON DELETE CASCADE,
    user_email        VARCHAR(255) NOT NULL,
    user_type          VARCHAR(50) NOT NULL CHECK (user_type IN ('local', 'visitor')),
    created_at         TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    PRIMARY KEY (event_id, user_email, user_type)
);

```

-- 5. BUSINESS EVENTS & PROMOTIONS

```

CREATE TABLE business_events (
    id                UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id        UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    owner_id           VARCHAR(255) NOT NULL REFERENCES local_users(email),
    owner_email        VARCHAR(255) NOT NULL,
    title             VARCHAR(500) NOT NULL,
    event_date        VARCHAR(50) NOT NULL,
    event_time        VARCHAR(50) NOT NULL,
    location          TEXT NOT NULL,
    description        TEXT,
    image_url          TEXT,
    image_storage_path TEXT,
    status            VARCHAR(50) NOT NULL DEFAULT 'published',
    created_at         TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at         TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

);

CREATE INDEX idx_business_events_business ON business_events(business_id);
CREATE INDEX idx_business_events_status ON business_events(status);

CREATE TABLE promotions (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  business_id UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
  owner_id    VARCHAR(255) NOT NULL REFERENCES local_users(email),
  title       VARCHAR(500) NOT NULL,
  description  TEXT,
  scheduled_at TIMESTAMPTZ,
  end_at       TIMESTAMPTZ,
  end_date     DATE,
  is_active   BOOLEAN      NOT NULL DEFAULT FALSE,
  status       VARCHAR(50)  NOT NULL DEFAULT 'draft',
  created_at   TIMESTAMPTZ  NOT NULL DEFAULT NOW(),
  updated_at   TIMESTAMPTZ  NOT NULL DEFAULT NOW()
);

CREATE INDEX idx_promotions_business ON promotions(business_id);
CREATE INDEX idx_promotions_owner ON promotions(owner_id);
CREATE INDEX idx_promotions_status ON promotions(status);

-- AI-generated posts (drafts and published)
CREATE TABLE ai_generated_posts (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  business_id UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
  business_name VARCHAR(500),
  owner_id     VARCHAR(255) NOT NULL REFERENCES local_users(email),
  post_type    VARCHAR(100) NOT NULL,
  title        VARCHAR(500) NOT NULL,
  description   TEXT,
  price         VARCHAR(255),
  discount      VARCHAR(255),
  event_date    TIMESTAMPTZ,
  location      TEXT,
  generated_content TEXT      NOT NULL,
  image_url     TEXT,
  status        VARCHAR(50)  NOT NULL DEFAULT 'draft',
  created_at    TIMESTAMPTZ  NOT NULL DEFAULT NOW(),
  updated_at    TIMESTAMPTZ  NOT NULL DEFAULT NOW()
);

CREATE INDEX idx_ai_generated_posts_owner ON ai_generated_posts(owner_id);
CREATE INDEX idx_ai_generated_posts_status ON ai_generated_posts(status);

-- -----
-- 6. REVIEWS & RECOMMENDATIONS
-- -----

CREATE TABLE reviews (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  business_id UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
  visitor_id   VARCHAR(255) NOT NULL,
  visitor_name  VARCHAR(500) NOT NULL DEFAULT 'Anonymous',
  visitor_photo_url TEXT,
  rating       INT          NOT NULL CHECK (rating BETWEEN 1 AND 5),
  buzz_rating  INT          NOT NULL DEFAULT 0 CHECK (buzz_rating BETWEEN 0 AND 5),
  comment      TEXT        NOT NULL,
  photos       TEXT[],
  helpful_count INT        NOT NULL DEFAULT 0,
  visible      BOOLEAN      NOT NULL DEFAULT TRUE,
  is_reported  BOOLEAN      NOT NULL DEFAULT FALSE,
  report_reason TEXT,
  reported_by  VARCHAR(255),
  severity     VARCHAR(50)  NOT NULL DEFAULT 'medium',
  is_flagged   BOOLEAN      NOT NULL DEFAULT FALSE,
  deleted_at   TIMESTAMPTZ,
  deleted_by   VARCHAR(255),
  created_at   TIMESTAMPTZ  NOT NULL DEFAULT NOW(),

```

```

        updated_at      TIMESTAMPTZ  NOT NULL DEFAULT NOW()
    );

CREATE INDEX idx_reviews_business ON reviews(business_id);
CREATE INDEX idx_reviews_visitor ON reviews(visitor_id);
CREATE INDEX idx_reviews_visible ON reviews(visible, deleted_at);

CREATE TABLE review_reports (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    review_id     UUID NOT NULL REFERENCES reviews(id) ON DELETE CASCADE,
    reporter_email VARCHAR(255) NOT NULL,
    reason        TEXT,
    comments      TEXT,
    status        VARCHAR(50) NOT NULL DEFAULT 'open',
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    reviewed_at   TIMESTAMPTZ
);

CREATE INDEX idx_review_reports_review ON review_reports(review_id);
CREATE INDEX idx_review_reports_status ON review_reports(status);

-- Nested reviews subcollection under businesses (legacy / dev)
CREATE TABLE business_nested_reviews (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id   UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    visitor_id    VARCHAR(255),
    comment       TEXT,
    rating        INT,
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at    TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

-- -----
-- 7. SOCIAL & ENGAGEMENT
-- -----

CREATE TABLE social_shares (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    visitor_id    VARCHAR(255) NOT NULL,
    visitor_name  VARCHAR(500),
    business_id   UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    business_name VARCHAR(500),
    content_id    VARCHAR(255) NOT NULL,
    content_type  VARCHAR(100) NOT NULL,
    platform      VARCHAR(100) NOT NULL,
    share_kind    VARCHAR(100) NOT NULL,
    title         VARCHAR(500) NOT NULL,
    description   TEXT,
    image_url     TEXT,
    share_url     TEXT,
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

CREATE INDEX idx_social_shares_business ON social_shares(business_id);
CREATE INDEX idx_social_shares_visitor ON social_shares(visitor_id);
CREATE INDEX idx_social_shares_created ON social_shares(created_at DESC);

CREATE TABLE post_engagements (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    post_type     VARCHAR(100) NOT NULL,
    post_id       VARCHAR(255) NOT NULL,
    action        VARCHAR(50) NOT NULL CHECK (action IN ('like', 'save', 'buzzVote')),
    visitor_id    VARCHAR(255) NOT NULL,
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    UNIQUE(post_type, post_id, action, visitor_id)
);

CREATE INDEX idx_post_engagements_post ON post_engagements(post_type, post_id);
CREATE INDEX idx_post_engagements_visitor ON post_engagements(visitor_id);

CREATE TABLE post_comments (

```

```

        id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
        post_type      VARCHAR(100) NOT NULL,
        post_id        VARCHAR(255) NOT NULL,
        visitor_id     VARCHAR(255) NOT NULL,
        visitor_name    VARCHAR(500) NOT NULL,
        text            TEXT          NOT NULL,
        created_at     TIMESTAMPTZ   NOT NULL DEFAULT NOW()
    );

```

```
CREATE INDEX idx_post_comments_post ON post_comments(post_type, post_id);
```

```

CREATE TABLE audience_interactions (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id   UUID NOT NULL REFERENCES businesses(id) ON DELETE CASCADE,
    owner_id      VARCHAR(255) NOT NULL,
    visitor_hash  VARCHAR(255) NOT NULL,
    type          VARCHAR(100) NOT NULL,
    timestamp     TIMESTAMPTZ   NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_audience_interactions_business ON audience_interactions(business_id);
CREATE INDEX idx_audience_interactions_owner ON audience_interactions(owner_id);

```

```

CREATE TABLE visitor_photos (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    business_id   UUID REFERENCES businesses(id) ON DELETE CASCADE,
    event_id      UUID REFERENCES events(id) ON DELETE CASCADE,
    visitor_id    VARCHAR(255) NOT NULL,
    visitor_name  VARCHAR(500) NOT NULL DEFAULT 'Anonymous',
    image_url     TEXT          NOT NULL,
    storage_path  TEXT          NOT NULL,
    mime_type     VARCHAR(100) NOT NULL DEFAULT 'image/jpeg',
    file_size     INT           NOT NULL DEFAULT 0,
    caption       TEXT,
    status        VARCHAR(50)   NOT NULL DEFAULT 'pending',
    created_at    TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    updated_at    TIMESTAMPTZ
);

```

```

CREATE INDEX idx_visitor_photos_business ON visitor_photos(business_id);
CREATE INDEX idx_visitor_photos_event ON visitor_photos(event_id);

```

```

-----
-- 8. REPORTS & FEEDBACK
-----

```

```

CREATE TABLE event_reports (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    event_id      UUID NOT NULL REFERENCES events(id) ON DELETE CASCADE,
    visitor_email VARCHAR(255) NOT NULL,
    reason        TEXT          NOT NULL,
    comments      TEXT,
    status        VARCHAR(50)   NOT NULL DEFAULT 'open',
    created_at    TIMESTAMPTZ   NOT NULL DEFAULT NOW(),
    reviewed_at   TIMESTAMPTZ
);

```

```

CREATE INDEX idx_event_reports_event ON event_reports(event_id);
CREATE INDEX idx_event_reports_status ON event_reports(status);

```

```

CREATE TABLE app_feedback (
    id            UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    reference_id  VARCHAR(255) NOT NULL UNIQUE,
    reporter_role VARCHAR(100) NOT NULL,
    reporter_email VARCHAR(255) NOT NULL,
    reporter_name VARCHAR(500),
    subject       VARCHAR(500) NOT NULL,
    details       TEXT          NOT NULL,
    category      VARCHAR(255),
    severity      VARCHAR(50),
    status        VARCHAR(50) NOT NULL DEFAULT 'open',

```

```

        considered_for_fix      BOOLEAN      NOT NULL DEFAULT FALSE,
        maintenance_window_days INT,
        resolution_due_at       TIMESTAMPTZ,
        admin_reply_at          TIMESTAMPTZ,
        reply_read_by_reporter  BOOLEAN      NOT NULL DEFAULT FALSE,
        image_url               TEXT,
        image_storage_path      TEXT,
        created_at              TIMESTAMPTZ  NOT NULL DEFAULT NOW(),
        updated_at              TIMESTAMPTZ  NOT NULL DEFAULT NOW()
    );

CREATE INDEX idx_app_feedback_status ON app_feedback(status);
CREATE INDEX idx_app_feedback_reporter ON app_feedback(reporter_email);

```

```

CREATE TABLE moderation_audit_log (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    admin_email VARCHAR(255) NOT NULL REFERENCES admins(email),
    content_type VARCHAR(100) NOT NULL,
    content_id   VARCHAR(255) NOT NULL,
    decision     VARCHAR(255) NOT NULL,
    reason       TEXT,
    created_at   TIMESTAMPTZ  NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_moderation_audit_content ON moderation_audit_log(content_type, content_id);

```

```

CREATE TABLE crowd_reports (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    event_id    UUID NOT NULL REFERENCES events(id) ON DELETE CASCADE,
    level       VARCHAR(100) NOT NULL,
    weight      INT          NOT NULL,
    timestamp   TIMESTAMPTZ  NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_crowd_reports_event ON crowd_reports(event_id);

```

----- -- 9. NOTIFICATIONS & MESSAGING QUEUES -----

```

CREATE TABLE user_notifications (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    user_email   VARCHAR(255) NOT NULL,
    user_type    VARCHAR(50)  NOT NULL,
    event_id     UUID REFERENCES events(id) ON DELETE CASCADE,
    event_title   VARCHAR(500),
    event_date_time VARCHAR(255),
    event_location TEXT,
    schedule_type VARCHAR(100),
    is_read      BOOLEAN      NOT NULL DEFAULT FALSE,
    created_at   TIMESTAMPTZ  NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_user_notifications_user ON user_notifications(user_email, user_type);
CREATE INDEX idx_user_notifications_read ON user_notifications(is_read);

```

```

CREATE TABLE mail_queue (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    recipient   VARCHAR(255) NOT NULL,
    subject     VARCHAR(500),
    body        TEXT,
    message     JSONB,
    meta        JSONB,
    status      VARCHAR(50) NOT NULL DEFAULT 'pending',
    sent_at     TIMESTAMPTZ,
    created_at  TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_mail_queue_status ON mail_queue(status);

```

```

CREATE TABLE sms_queue (

```

```

        id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
        recipient   VARCHAR(255) NOT NULL,
        body        TEXT,
        message     JSONB,
        meta        JSONB,
        status      VARCHAR(50) NOT NULL DEFAULT 'pending',
        sent_at     TIMESTAMPTZ,
        created_at  TIMESTAMPTZ NOT NULL DEFAULT NOW()
    );

```

```

CREATE INDEX idx_sms_queue_status ON sms_queue(status);

```

```

CREATE TABLE notification_health_checks (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    check_type  VARCHAR(100) NOT NULL,
    result      JSONB NOT NULL,
    status      VARCHAR(50),
    created_at  TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

-- -----
-- 10. PAYMENTS & SUBSCRIPTIONS
-- -----

```

```

CREATE TABLE subscription_plans (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name        VARCHAR(500) NOT NULL,
    plan_type   VARCHAR(100) NOT NULL,
    description  TEXT,
    price_cents INT          NOT NULL,
    duration_days INT        NOT NULL,
    features    TEXT[],
    stripe_product_id VARCHAR(255),
    stripe_price_id  VARCHAR(255),
    is_active     BOOLEAN    NOT NULL DEFAULT TRUE,
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at    TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_subscription_plans_active ON subscription_plans(is_active);

```

```

CREATE TABLE business_subscriptions (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    owner_id    VARCHAR(255) NOT NULL REFERENCES local_users(email) ON DELETE CASCADE,
    stripe_subscription_id VARCHAR(255),
    status      VARCHAR(100) NOT NULL DEFAULT 'incomplete',
    current_period_start TIMESTAMPTZ,
    current_period_end  TIMESTAMPTZ,
    plan_id          UUID REFERENCES subscription_plans(id),
    cancel_at_period_end BOOLEAN NOT NULL DEFAULT FALSE,
    created_at       TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at       TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_business_subscriptions_owner ON business_subscriptions(owner_id);
CREATE INDEX idx_business_subscriptions_status ON business_subscriptions(status);

```

```

CREATE TABLE promotion_plans (
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name        VARCHAR(500) NOT NULL,
    plan_type   VARCHAR(100) NOT NULL,
    description  TEXT,
    price_cents INT          NOT NULL,
    duration_days INT        NOT NULL,
    features    TEXT[],
    stripe_product_id VARCHAR(255),
    stripe_price_id  VARCHAR(255),
    is_active     BOOLEAN    NOT NULL DEFAULT TRUE,
    created_at    TIMESTAMPTZ NOT NULL DEFAULT NOW(),
    updated_at    TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE TABLE business_payments (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  owner_id    VARCHAR(255) NOT NULL REFERENCES local_users(email),
  type        VARCHAR(100) NOT NULL,
  status       VARCHAR(100) NOT NULL,
  amount_cents INT,
  currency     VARCHAR(10) NOT NULL DEFAULT 'aud',
  stripe_payment_intent_id VARCHAR(255),
  stripe_checkout_session_id VARCHAR(255),
  stripe_subscription_id VARCHAR(255),
  plan_id      UUID REFERENCES subscription_plans(id),
  promotion_plan_id UUID REFERENCES promotion_plans(id),
  paid_at      TIMESTAMPTZ,
  expires_at   TIMESTAMPTZ,
  payload      JSONB,
  created_at   TIMESTAMPTZ NOT NULL DEFAULT NOW(),
  updated_at   TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_business_payments_owner ON business_payments(owner_id);
CREATE INDEX idx_business_payments_status ON business_payments(status);
CREATE INDEX idx_business_payments_type ON business_payments(type);

```

```

CREATE TABLE admin_activity (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  admin_email VARCHAR(255) NOT NULL REFERENCES admins(email),
  action       VARCHAR(255) NOT NULL,
  target_type  VARCHAR(100),
  target_id    VARCHAR(255),
  details      JSONB,
  created_at   TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_admin_activity_admin ON admin_activity(admin_email);

```

```

-- -----
-- 11. CURATED CONTENT
-- -----

```

```

CREATE TABLE brisbane_stories (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  title       VARCHAR(500) NOT NULL,
  description  TEXT,
  image_url   TEXT,
  category    VARCHAR(255),
  content     TEXT,
  latitude    DECIMAL(10, 8),
  longitude   DECIMAL(11, 8),
  location_name VARCHAR(500),
  approval_status VARCHAR(50) NOT NULL DEFAULT 'pending',
  published_at TIMESTAMPTZ,
  created_at   TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

CREATE INDEX idx_brisbane_stories_status ON brisbane_stories(approval_status);

```

```

CREATE TABLE brisbane_voices (
  id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),
  name        VARCHAR(500) NOT NULL,
  quote       TEXT NOT NULL,
  profile_image_url TEXT,
  approval_status VARCHAR(50) NOT NULL DEFAULT 'pending',
  created_at   TIMESTAMPTZ NOT NULL DEFAULT NOW()
);

```

```

-- -----
-- 12. SYSTEM / CONFIG
-- -----

```

```

CREATE TABLE config (
  id          VARCHAR(255) PRIMARY KEY,

```



```
    payload JSONB NOT NULL,  
    updated_at TIMESTAMPTZ NOT NULL DEFAULT NOW()  
);
```

```
CREATE TABLE event_categories (  
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    name        VARCHAR(255) NOT NULL UNIQUE,  
    label       VARCHAR(255),  
    color       VARCHAR(50),  
    icon        VARCHAR(100),  
    sort_order  INT NOT NULL DEFAULT 0,  
    is_active   BOOLEAN NOT NULL DEFAULT TRUE  
);
```

```
CREATE TABLE counters (  
    id          VARCHAR(255) PRIMARY KEY,  
    count       BIGINT NOT NULL DEFAULT 0  
);
```

```
CREATE TABLE seed_metadata (  
    id          UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    version     INT NOT NULL,  
    source_provider VARCHAR(255),  
    discover_item_count INT DEFAULT 0,  
    attraction_count INT DEFAULT 0,  
    event_count INT DEFAULT 0,  
    write_count INT DEFAULT 0,  
    seeded_at   TIMESTAMPTZ NOT NULL DEFAULT NOW(),  
    last_synced_at TIMESTAMPTZ  
);
```

```
CREATE TABLE connectivity_probe (  
    id          VARCHAR(255) PRIMARY KEY,  
    payload     JSONB,  
    checked_at TIMESTAMPTZ NOT NULL DEFAULT NOW()  
);
```

```
-- =====  
-- END OF SCHEMA
```

