

BrisConnect Firestore Schema

This document provides the full Firestore schema currently used by BrisConnect. It is based on security rules and implemented write/read paths in the codebase.

1) admins

- Document path: admins/{emailLowercase}
- Purpose: Admin identity and role metadata
- Common fields:
 - email: string
 - username: string
 - name: string
 - role: string (admin)
 - active: boolean
 - profileImageUrl: string
 - profileImageStoragePath: string
 - lastLoginAt: timestamp
 - updatedAt: timestamp

2) local_users

- Document path: local_users/{emailLowercase}
- Purpose: Local user account, profile, preferences, and approval state
- Common fields:
 - name: string
 - email: string
 - username: string
 - role: string (local)
 - accountType: string (local)
 - phone: string
 - suburb: string
 - approvalStatus: string (pending, approved, rejected)
 - passwordHash: string
 - passwordUpdatedAt: timestamp
 - interestedEventIds: array
 - interestCategories: array
 - notificationsEnabled: boolean
 - eventRemindersEnabled: boolean
 - reminderTiming: string
 - eventUpdatesEnabled: boolean
 - nearbyEventsEnabled: boolean
 - recommendedEventsEnabled: boolean
 - useCurrentLocation: boolean
 - locationRadiusKm: number
 - locationAccessEnabled: boolean
 - themePreference: string
 - textScaleFactor: number
 - profileImageBase64: string|null
 - profileImageUrl: string|null

- profileImagePath: string|null
- authFallback: boolean
- createdAt: timestamp
- updatedAt: timestamp

3) visitor_users

- Document path: visitor_users/{emailLowercase}
- Purpose: Visitor account, profile, interests, and preferences
- Common fields:
 - name: string
 - email: string
 - username: string
 - role: string (visitor)
 - phone: string
 - passwordHash: string
 - passwordUpdatedAt: timestamp
 - interestedEventIds: array
 - savedAttractionIds: array
 - interestCategories: array
 - interestPriorities: array
 - notificationsEnabled: boolean
 - eventRemindersEnabled: boolean
 - reminderTiming: string
 - eventUpdatesEnabled: boolean
 - nearbyEventsEnabled: boolean
 - recommendedEventsEnabled: boolean
 - emailNotificationsEnabled: boolean
 - useCurrentLocation: boolean
 - locationRadiusKm: number
 - locationAccessEnabled: boolean
 - themePreference: string
 - textScaleFactor: number
 - profileImageBase64: string|null
 - profileImageUrl: string|null
 - profileImagePath: string|null
 - createdAt: timestamp
 - updatedAt: timestamp

4) events

- Document path: events/{eventId}
- Purpose: Event catalog (seeded, imported, and local-submitted events)
- Common fields:
 - id: string
 - title: string
 - date: string
 - time: string
 - dateTime: string
 - category: string
 - location: string

- venue: string
- suburb: string
- description: string
- createdByLocalEmail: string
- reviewStatus: string
- approvalStatus: string
- status: string
- badge: string
- isApproved: boolean
- reportCount: number
- flaggedForAdminReview: boolean
- lastReportedAt: timestamp
- source: string
- sourceProvider: string
- sourceUrl: string
- imageUrl: string
- imageStoragePath: string
- videoUrl: string
- videoStoragePath: string
- audioUrl: string
- audioStoragePath: string
- aiNarration: string
- latitude: number
- longitude: number
- createdAt: timestamp
- updatedAt: timestamp

5) attractions

- Document path: attractions/{attractionId}
- Purpose: Approved attractions and admin-managed attraction records
- Common fields:
 - id: string
 - name: string
 - title: string
 - description: string
 - location: string
 - latitude: number
 - longitude: number
 - category: string
 - accessibilityDetails: array
 - webLink: string
 - imageUrl: string
 - imageStoragePath: string
 - audioUrl: string
 - audioStoragePath: string
 - aiNarration: string
 - approvalStatus: string
 - reviewStatus: string
 - status: string
 - isApproved: boolean

- sourceProvider: string
- sourcePlaceId: string
- createdAt: timestamp
- updatedAt: timestamp

6) attraction_details

- Document path: attraction_details/{attractionId}
- Purpose: Extended detail page content for attractions
- Common fields:
 - history: string
 - address: string
 - openingHours: array
 - specialSchedule: string
 - entryRequirements: string
 - ticketPrice: string
 - bookingLabel: string
 - bookingUrl: string
 - media: array
 - virtualTourUrl: string
 - rating: number
 - reviewCount: number
 - ratingBreakdown: object
 - reviews: array
 - phone: string
 - website: string
 - email: string
 - facilities: array
 - amenities: array
 - accessibility: array
 - visitDuration: string
 - bestTimeToVisit: string
 - liveUpdate: object
 - nearbyAttractions: array
 - nearbyServices: array
 - languages: array
 - audioFeatures: array
 - personalisedSuggestions: array

7) event_reports

- Document path: event_reports/{eventId__visitorEmailEncoded}
- Purpose: Visitor reports against events
- Common fields:
 - eventId: string
 - visitorEmail: string
 - reason: string
 - comments: string|null
 - status: string (pending, reviewing, resolved, dismissed)
 - createdAt: timestamp
 - reviewedAt: timestamp|null

8) app_feedback

- Document path: app_feedback/{referenceIdLowercase}
- Purpose: User app feedback and admin response workflow
- Common fields:
 - referenceId: string (for example FB-0001)
 - reporterRole: string
 - reporterEmail: string
 - reporterName: string
 - subject: string
 - details: string
 - category: string
 - severity: string
 - status: string (pending_triage, in_progress, resolved, wont_fix)
 - consideredForFix: boolean
 - maintenanceWindowDays: number
 - resolutionDueAt: timestamp
 - adminReply: string|null
 - adminReplyAt: timestamp|null
 - replyReadByReporter: boolean
 - imageUrl: string|null
 - imageStoragePath: string|null
 - createdAt: timestamp
 - updatedAt: timestamp

9) user_notifications

- Document path: user_notifications/{notificationId}
- Purpose: In-app notification records for users
- Common fields:
 - eventId: string
 - userEmail: string
 - userType: string (visitor, local)
 - eventTitle: string
 - eventDateTime: string
 - eventLocation: string
 - scheduleType: string (event_time, fallback, unknown)
 - isRead: boolean
 - createdAt: timestamp

10) mail

- Document path: mail/{queueId}
- Purpose: Outbound email queue consumed by Firebase extension/worker
- Common fields:
 - to: string
 - message: object
 - meta: object
 - createdAt: timestamp

11) sms_queue

- Document path: sms_queue/{queueId}
- Purpose: Outbound SMS queue
- Common fields:
 - to: string
 - message: string
 - meta: object
 - createdAt: timestamp

12) brisbane_stories

- Document path: brisbane_stories/{storySlug}
- Purpose: Curated story content
- Common fields:
 - title: string
 - description: string
 - imageUrl: string
 - category: string
 - content: string
 - latitude: number
 - longitude: number
 - locationName: string
 - approvalStatus: string
 - publishedAt: timestamp
 - createdAt: timestamp

13) brisbane_voices

- Document path: brisbane_voices/{voiceSlug}
- Purpose: Curated voices/quotes
- Common fields:
 - name: string
 - quote: string
 - profileImageUrl: string
 - approvalStatus: string
 - createdAt: timestamp

14) discover_items

- Document path: discover_items/{discoverItemId}
- Purpose: Unified discovery feed (events, historical, food, stadium/venues)
- Common fields:
 - id: string
 - title: string
 - section: string
 - category: string
 - location: string
 - venue: string
 - suburb: string
 - date: string

- time: string
- dateTime: string
- description: string
- approvalStatus: string
- source: string
- sourceProvider: string
- sourcePlaceld: string
- sourceUrl: string
- createdByLocalEmail: string
- imageUrl: string
- imageStoragePath: string
- videoUrl: string
- videoStoragePath: string
- audioUrl: string
- audioStoragePath: string
- aiNarration: string
- updatedAt: timestamp

15) seed_metadata

- Document path: seed_metadata/{seedName}
- Purpose: Seed/sync bookkeeping
- Common fields:
 - version: number
 - sourceProvider: string
 - discoverItemCount: number
 - attractionCount: number
 - eventCount: number
 - historicalCount: number
 - writeCount: number
 - seededAt: timestamp
 - lastSyncedAt: timestamp

16) counters

- Document path: counters/{counterName}
- Purpose: Incremental counters for human-readable IDs
- Common fields:
 - count: number

17) config

- Document path: config/{configKey}
- Purpose: Admin-managed app configuration
- Common fields:
 - payload: object (shape varies by config key)

18) _connectivity_probe

- Document path: _connectivity_probe/{probeld}
- Purpose: Connectivity probe for online/offline UX handling

- Common fields:
 - payload: object

Firestore Indexes

- Composite index:
 - Collection: event_reports
 - Fields:
 - status ascending
 - createdAt descending

Access Model Summary

- Signed-in users can read most business collections.
- Admin users can write admin-controlled collections.
- Users can create and update their own profile documents keyed by email.
- Event updates/deletes are restricted to event owner or admin.