Review


```
"Summary": "The paper proposes integrating a Generative Adversarial Network
(GAN) framework into diffusion models to improve sample quality and
diversity. The approach includes a simple discriminator network, an
adversarial loss term, and a gradient penalty to the adversarial loss.
Extensive experiments on multiple 2D datasets are conducted to validate the
approach, comparing results in terms of training time, evaluation loss, KL
divergence, and sample quality.",
"Strengths": [
    "The integration of GAN framework with diffusion models is a novel
approach to improve sample quality and diversity.",
    "The introduction of a gradient penalty to improve training stability
is a thoughtful addition.",
    "The paper provides a comprehensive evaluation on multiple 2D datasets,
using various metrics such as training time, evaluation loss, KL
divergence, and sample quality."
],
"Weaknesses": [
    "The methodology section lacks detailed explanations for certain
components, such as the exact architecture of the discriminator network and
the choice of hyperparameters.",
    "The improvements in evaluation loss and KL divergence are not
consistent across all datasets, indicating that the model's performance may
be dataset-dependent.",
    "The experimental scope is limited to 2D datasets. Further research is
needed to evaluate the model's performance on higher-dimensional data.",
    "The paper lacks sufficient ablation studies to isolate the
contributions of different components of the proposed method.",
    "The evaluation metrics are somewhat limited; including metrics like
FID could strengthen the evaluation.",
    "The paper does not sufficiently address the limitations of the
approach, particularly its dataset dependency and scalability to higher-
dimensional data.",
    "There is no discussion on potential negative societal impacts or
ethical concerns related to the work."
],
"Originality": 3,
"Quality": 2,
"Clarity": 2,
"Significance": 2,
"Questions": [
    "Can you provide more details on the architecture of the discriminator
network?",
    "How do the hyperparameters lambda-adv and lambda-gp affect the model's
performance?",
    "Can you explain why the improvements are inconsistent across different
datasets?",
    "Can the authors provide more detailed descriptions of the denoiser and
discriminator networks?",
    "Have the authors considered using more comprehensive evaluation
metrics like FID?",
    "Can the authors provide more ablation studies to isolate the
contributions of the gradient penalty and adversarial loss?",
    "How would the proposed method perform on more complex and higher-
```

```
dimensional datasets?"
],
"Limitations": [
    "The paper acknowledges the increased training time and dataset
dependency of the improvements. However, it could benefit from a more
thorough exploration of different architectures and higher-dimensional
datasets.",
    "The empirical results show mixed improvements, indicating that the
model's performance may be dataset-dependent.",
    "The paper does not explore the limitations of the proposed approach in
depth, particularly in terms of scalability to higher-dimensional data."
],
"Ethical Concerns": false,
"Soundness": 2,
"Presentation": 2,
"Contribution": 2,
"Overall": 3,
"Confidence": 4,
"Decision": "Reject"
```

D.4. DualDiff: Enhancing Mode Capture in Low-dimensional Diffusion Models via Dual-expert Denoising

This idea was proposed in the 5th iteration of a Claude run.

Idea


```
"Name": "dual_expert_denoiser",
"Title": "Dual-Expert Denoiser for Improved Mode Capture in Low-Dimensional
Diffusion Models",
"Experiment": "Modify MLPDenoiser to implement a dual-expert architecture.
Create a simple gating network that outputs a single weight (sigmoid
output) based on the noisy input and timestep. Implement two expert
networks with the same structure as the original denoising network. Combine
expert outputs using the gating weight. Train models with both the original
and new architecture on all datasets, with particular focus on 'moons' and
'dino'. Compare performance using KL divergence, sample diversity metrics
(e.g., number of modes captured), and visual inspection of generated
samples. Analyze the specialization of experts across different regions of
the data distribution.",
"Interestingness": 8,
"Feasibility": 8,
"Novelty": 8,
"novel": true
```


Link to code: https://github.com/SakanaAI/AI-Scientist/tree/main/example_papers/dual_expert_denoiser.