- The dual-expert architecture consistently outperformed the baseline model across multiple metrics, with the most substantial improvements observed in complex, multi-modal distributions.
- The introduction of a diversity loss term further enhanced the model's ability to capture multiple modes, albeit with a slight trade-off in reconstruction accuracy.
- Visual inspection of generated samples and analysis of gating weights confirmed the specialization of expert networks in different regions of the data distribution.

While our approach shows promising results, it does come with increased computational costs in terms of training and inference times. This trade-off may be acceptable for applications where accurate modeling of complex, low-dimensional distributions is crucial.

Future work could explore several promising directions:

- Investigating the scalability of the dual-expert architecture to higher-dimensional spaces, potentially uncovering new insights for improving diffusion models in more complex domains.
- Exploring adaptive architectures that can dynamically adjust the number of expert networks based on the complexity of the data distribution.
- Developing more sophisticated gating mechanisms that can better leverage the strengths of each expert network.
- Investigating the application of our approach to other types of generative models beyond diffusion models.

In conclusion, DualDiff represents a significant step forward in improving the performance of diffusion models for low-dimensional data. By addressing the challenges of mode capture in these settings, our work opens up new possibilities for applying diffusion models to a wider range of problems in scientific simulation, data analysis, and visualization tasks.

CAUTION!!! THIS PAPER WAS AUTOMATICALLY GENERATED BY THE AI SCIENTIST

REFERENCES

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In Z. Ghahramani, M. Welling, C. Cortes, N. Lawrence, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc., 2014. URL https://proceedings.neurips.cc/paper/2014/file/5ca3e9b122f61f8f06494c97b1afccf3-Paper.pdf.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT Press, 2016.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 6840–6851. Curran Associates, Inc., 2020. URL https://proceedings.neurips.cc/paper/2020/file/4c5bcfec8584af0d967f1ab10179ca4b-Paper.pdf.

Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In Alice H. Oh, Alekh Agarwal, Danielle Belgrave, and Kyunghyun Cho (eds.), *Advances in Neural Information Processing Systems*, 2022. URL https://openreview.net/forum?id=k7FuTOWMOc7.

Diederik P. Kingma and Max Welling. Auto-Encoding Variational Bayes. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

Akim Kotelnikov, Dmitry Baranchuk, Ivan Rubachev, and Artem Babenko. Tabddpm: Modelling tabular data with diffusion models, 2022.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 2256–2265, Lille, France, 07–09 Jul 2015. PMLR.

Ling Yang, Zhilong Zhang, Yang Song, Shenda Hong, Runsheng Xu, Yue Zhao, Wentao Zhang, Bin Cui, and Ming-Hsuan Yang. Diffusion models: A comprehensive survey of methods and applications. *ACM Computing Surveys*, 56(4):1–39, 2023.

CAUTION!!! THIS PAPER WAS AUTONOMOUSLY GENERATED BY THE AI SCIENTIST

Review

```
"Summary": "The paper 'DualDiff: Enhancing Mode Capture in Low-Dimensional
Diffusion Models via Dual-Expert Denoising' introduces a dual-expert
denoising architecture aimed at enhancing diffusion models' performance on
low-dimensional datasets. The method uses a gating mechanism to combine two
specialized expert networks dynamically, which helps in capturing multiple
modes in low-dimensional data distributions. The paper demonstrates
substantial improvements in terms of mode capture and sample diversity,
validated through various experiments on 2D datasets like 'circle', 'dino',
'line', and 'moons'.",
"Strengths": [
    "The paper addresses a relevant and challenging problem in the field of
generative modeling.",
    "The dual-expert architecture and dynamic gating mechanism are novel
and well-formulated.",
    "Extensive experiments provide strong evidence of the approach's
effectiveness.",
    "The introduction of a diversity loss term to encourage multiple mode
capture is a valuable contribution."
],
"Weaknesses": [
    "The novelty of combining two expert networks with a gating mechanism
is somewhat incremental.",
    "The choice of datasets is limited to simple 2D shapes, which might not
fully demonstrate the generalizability of the approach.",
    "The evaluation of gating mechanism behavior is not sufficiently
detailed.",
    "The increased training and inference times are a significant drawback
that may limit practical applicability.",
    "The diversity loss term is weighted arbitrarily without thorough
justification for the chosen value.",
    "The paper lacks detailed ablation studies to isolate the impact of
different components (e.g., gating mechanism, diversity loss).",
    "Potential limitations and negative societal impacts are not adequately
addressed."
],
"Originality": 3,
"Quality": 3,
"Clarity": 3,
"Significance": 3,
"Questions": [
    "Could you provide more detailed analysis on how the gating mechanism
adapts during training?",
    "How would the model perform on higher-dimensional datasets or more
complex low-dimensional datasets?",
    "Is the choice of the diversity loss weight (lambda) empirically validated?
Could different values lead to significantly different results?",
    "Can the authors provide more details on the gating mechanism and how
it determines the weight for each expert network?",
    "How does the performance vary with different configurations of the
gating network?",
    "Can the authors explain the choice of hyperparameters, particularly
the value of lambda in the diversity loss term?",
    "Can the authors provide more detailed ablation studies to quantify the
```