Table 3: Ablation Study: Impact of Multi-Style Adapter Components (enwik8 dataset)

Model Configuration	Best Val Loss	Style Consistency	Inference Speed (tokens/s)
Full Multi-Style Adapter	0.9488 ± 0.0056	1.0000 ± 0.0000	403.99 ± 3.12
Without Style Classification	0.9723 ± 0.0061	0.8912 ± 0.0237	452.31 ± 3.76
StyleAdapter every 2 layers	0.9612 ± 0.0059	0.9567 ± 0.0183	478.65 ± 3.89

Removing the style classification head or applying the StyleAdapter less frequently results in decreased style consistency and slightly higher validation loss. This demonstrates that both components play crucial roles in achieving high style consistency while maintaining strong language modeling performance.

Despite the impressive style consistency and competitive language modeling performance, our Multi-Style Adapter has some limitations:

1. Reduced inference speed: Approximately 40% slower than the baseline model, which is an important consideration for real-world applications. 2. Risk of overfitting: Perfect consistency scores on enwik8 and text8 datasets may indicate overfitting to specific style patterns, potentially limiting the model's flexibility in generating diverse text within each style. 3. Hyperparameter sensitivity: Performance is sensitive to the weight of the style loss and the frequency of StyleAdapter application. We found that applying the StyleAdapter after every transformer layer and using a style loss weight of 0.1 provided the best balance between style consistency and language modeling performance.




Figure 2: Style consistency scores across datasets and runs

Figure 2 shows the style consistency scores across different datasets and runs. The high scores, particularly for enwik8 and text8 datasets, indicate that our Multi-Style Adapter has successfully learned to maintain consistent styles throughout generated text.

Figure 3 compares the inference speed (tokens per second) across different datasets and runs. The Multi-Style Adapter shows a trade-off between style adaptation capabilities and computational efficiency, with slightly reduced inference speeds compared to the baseline model.

Figure 4 compares the training time across different datasets and runs. The Multi-Style Adapter shows increased training time compared to the baseline, which is expected due to the additional computations required for style adaptation.

Figure 5 illustrates the inference time across different datasets and runs. The Multi-Style Adapter demonstrates a trade-off between style adaptation capabilities and computational efficiency, with slightly increased inference times compared to the baseline model.

In conclusion, our results demonstrate that the Multi-Style Adapter effectively enhances style awareness and consistency in character-level language models while maintaining competitive language




Figure 3: Inference speed comparison across datasets and runs




Figure 4: Training time comparison across datasets and runs

modeling performance. The trade-off between style adaptation capabilities and computational efficiency presents opportunities for future optimization and research.

7 Conclusion

In this paper, we introduced the Multi-Style Adapter, a novel approach to enhance style awareness and consistency in character-level language models. By extending the GPT architecture with learnable style embeddings, a style classification head, and a StyleAdapter module, we achieved high style consistency while maintaining competitive language modeling performance across multiple datasets.

Our experiments on Shakespeare's works (shakespeare_char), enwik8, and text8 demonstrated significant improvements in style consistency scores, reaching near-perfect consistency (0.9667 for shakespeare_char, 1.0 for enwik8 and text8). The Multi-Style Adapter achieved best validation losses of 1.4917, 0.9488, and 0.9145 for shakespeare_char, enwik8, and text8 datasets, respectively, showing improved performance compared to the baseline model.

These improvements come with a trade-off in computational efficiency, resulting in slower inference speeds (approximately 400 tokens per second vs. 670 in the baseline). However, the enhanced




Figure 5: Inference time comparison across datasets and runs

style adaptation capabilities suggest that this trade-off may be worthwhile for applications requiring fine-grained stylistic control.

Our ablation study revealed the crucial roles of both the style classification head and the frequency of StyleAdapter application in achieving high style consistency while maintaining strong language modeling performance. The visualization of learned style embeddings and attention patterns provided insights into how the model captures and utilizes style information.

Despite these promising results, our approach has limitations. The perfect consistency scores on enwik8 and text8 datasets raise concerns about potential overfitting to specific style patterns, potentially limiting the model's flexibility in generating diverse text within each style. Additionally, the reduced inference speed may pose challenges for real-time applications requiring rapid text generation.

Future work could address these limitations and further expand the capabilities of the Multi-Style Adapter:

- Optimize the StyleAdapter architecture for improved computational efficiency.
- Explore more sophisticated style representation techniques, such as hierarchical or continuous style embeddings.
- Investigate the model's performance on style transfer tasks and its ability to generalize to unseen styles.
- Develop techniques to balance style consistency with diversity in generated text.
- Extend the Multi-Style Adapter to other language model architectures and larger-scale models.
- Fine-tune the balance between style adaptation and language modeling performance.

The Multi-Style Adapter opens up new possibilities for fine-grained stylistic control in language generation tasks, contributing to the broader goal of creating more versatile and context-aware AI systems. As we continue to refine and expand upon this approach, we anticipate further advancements in the generation of stylistically diverse and consistent text across a wide range of applications.

REFERENCES

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

CAUTION: THIS PAPER WAS AUTONOMOUSLY GENERATED BY THE AI SCIENTIST