



# Session 4

Tristan Brindle


# Feedback



- We love to hear from you!
- The easiest way is via the *cpplang* channel on Slack — we have our own chatroom, *#ug\_uk\_cpplondonuni*
- Go to <https://cpplang.now.sh/> for an “invitation”

# Textbook

- We'll be using  
*"Programming Principles  
and Practice Using C++"* by  
Bjarne Stroustrup
- Please pick up a copy if you  
haven't already



# Last week...



- Getting set up with a compiler and CLion
- The C++ compilation model
  - What compilers do
  - Using the compiler from the command line
  - The C++ compilation process
  - Separate compilation
  - Using libraries
  - Header files and `#include`

# This week



- Value semantics
- Pass by value
- Scope
- Basic object lifetimes
- Basic control flow
  - If statements
  - Loops

# Value semantics



- Unlike many other programming languages, C++ uses *value semantics* rather than *reference semantics* by default
- This means (roughly) that copies of variables are distinct; changing the value of a copy will not affect the original variable (i.e. copies are “deep”).
- We’ll see next week how we can use references in C++

# Value semantics example

```
int a = 1;
```

```
int b = a;  
// b has value 1
```

```
a = 42;  
// a has value 42  
// b still has value 1
```

```
std::string s = "Hello";  
std::string s2 = "World";
```

```
s += s2;  
// s now has value "HelloWorld"  
// s2 still has value "World"
```

# Passing by value



- By default, C++ passes arguments to functions *by value*
- This means that the function receives an independent *copy* of the object passed to it
- Modifying a function parameter taken by value will not change the original object
- Similarly, C++ (conceptually) *returns a copy* of an object from a function by default



# Passing by value example



```
/* declaration in a header file */  
int add_one(int i);
```

```
/* ..somewhere else... */
```

```
int j = 42;  
// call our add_one function  
auto ret = add_one(j);  
// add_one operates on a *copy* of j  
// our j still has value 42  
// ret has value 43
```

```
/* definition of add_one, in an implementation file */  
int add_one(int i)  
{  
    i += 1;  
    return i;  
}
```

# Exercise



- Create a new project in CLion
- Write a function named `say_hello` which takes a parameter of type `std::string` called *name*, and returns a `std::string`
- Your function `say_hello` should modify *name* by adding the string “Hello “ to the front of it, and then return *name*
- In main, create a `std::string` variable named *me*, initialised with your name. Call your `say_hello` function with *me* as an argument
- Use `std::cout` to show that calling the function has not modified the original variable

# My solution



```
#include <iostream>
#include <string>

std::string say_hello(std::string name)
{
    name = "Hello " + name;
    return name;
}

int main()
{
    std::string me = "Tristan";
    std::string hello_me = say_hello(me);

    std::cout << hello_me << '\n';
    std::cout << me << '\n';
}
```

**Any questions before  
we move on?**

# Variable scope

- A *scope* is a region of source text in our program
- Every variable has a *scope* in which it lives
- The scope of a variable generally lasts from the point at which we declare it until we leave the *block* (pair of curly braces) it was declared in
- We cannot access a variable outside of its *scope*

# Variable scope example

```
void func(int i) // i is in scope
{
    i = 0;
    int j = 1; // j is in scope

    { // open new scope
        int k = 42; // k is in scope

        i = k; // i is still in scope
        j = k + 1; // j is still in scope
    } // k's scope ends

    k = 0; // ERROR - k is no longer in scope
} // i, j scope ends
```

# Variable lifetimes



- Unlike many other languages, C++ does not use *garbage collection* to manage memory
- Instead, resources like memory are usually managed using *scopes*
- This is a central concept in modern C++, and goes by the silly acronym *RAII*

# Variable lifetimes



- When we declare a variable inside a function, it is called an *automatic variable*
- An automatic variable is *destroyed* when we leave the *scope* in which it is declared
- Function parameters are also automatic variables
- Later, we'll see how to declare special functions called *destructors* which can be used to “clean up” when a variable is destroyed



# Lifetimes example



```
void function(int i)
{
    int j = i; // j's lifetime begins

    {
        int k = j + 1; // k's lifetime begins

        if (k == 1) {
            // if we leave the function here,
            // i, j and k are destroyed
            return;
        }
    } // k is destroyed here

} // i and j are destroyed here
```

**Any questions before  
we move on?**

# If statements

- One of the basic building blocks of programs is the if statement
- The basic form of an if statement is

```
if (condition) {  
    // do something  
}
```

# If statements

- We can also add `else if` to test a second condition

```
if (condition) {  
    // do something  
} else if (other condition) {  
    // do something else  
}
```

- We can have as many `else if` statements as we like
- Conditions are tested in the order that they appear

# If statements

- Finally, we can add an else statement as a fallback if none of the other conditions are true

```
if (condition) {  
    // do something  
} else if (other condition) {  
    // do something else  
} else {  
    // do a third thing  
}
```

# Exercise: FizzBuzz



- The modulus operator % returns the *remainder* after dividing one integer by another
- This can be used to test whether one integer is divisible by another
- For example

```
const int i = 16;

if (i % 2 == 0) {
    std::cout << "i is even\n";
} else {
    std::cout << "i is odd\n";
}
```

# Exercise: Fizzbuzz



- In CLion, create a new project called `fizzbuzz`
- Create a new source file `fizzbuzz.cpp` and an accompanying header file
- In `fizzbuzz.cpp`, write a function `void fizzbuzz(int i)` which performs the following using `if` statements:
  - If `i` is divisible by 3, print “fizz”.
  - If `i` is divisible by 5, print “buzz”.
  - If `i` is divisible by both 3 and 5, print “fizzbuzz”.
  - If `i` is not divisible by either 3 or 5, print “not fizzy or buzzy”
- Add a declaration of your `fizzbuzz` function to the `fizzbuzz` header
- In your `main()` function, test calling `fizzbuzz()` with a variety of inputs

# Fizzbuzz: solution



```
// fizzbuzz.hpp  
  
void fizzbuzz(int i);
```

```
// fizzbuzz.cpp  
  
#include "fizzbuzz.hpp"  
#include <iostream>  
  
void fizzbuzz(int i)  
{  
    if (i % 15 == 0) {  
        std::cout << "fizzbuzz\n";  
    } else if (i % 3 == 0) {  
        std::cout << "fizz\n";  
    } else if (i % 5 == 0) {  
        std::cout << "buzz\n";  
    } else {  
        std::cout << "not fizzy or buzzy\n";  
    }  
}
```

```
// main.cpp  
  
#include "fizzbuzz.hpp"  
  
int main()  
{  
    fizzbuzz(9999);  
    fizzbuzz(125);  
    fizzbuzz(225);  
    fizzbuzz(1024);  
}
```



# Loops

- Another of the fundamental building blocks of programs are *loops*
- A *loop* tells the program to keep repeating some action until a *condition* fails
- C++'s loop keywords are very similar to those found in other languages

# While loops

- The simplest form of loop uses the `while` keyword
- We write this as

```
while (some_condition) {  
    // do_something  
}
```

- The program keeps repeating the *body* of the loop until the *condition* is `false`
- If the condition is `false` to start with, we will never enter the loop

# Do-while loops

- Similar to a while loop is a do-while loop. This is written

```
do {  
    // something  
} while (condition);
```

- Unlike a plain while loop, the body of **do** is executed once *before the condition is checked*
- This means that a do-while loop will execute at least once

# For loops

- The most common type of loop is the *for loop*
- This has the form

```
for (init ; condition ; increment) {  
    // do something  
}
```

- First the *init* part is run, then the *condition* is checked
- If the *condition* is **true**, the body of the loop is executed, followed by the *increment* step
- This is repeated until the *condition* is **false**

# For loop example

```
int main()
{
    for (int i = 0; i < 10; i++) {
        std::cout << "i is " << i << "\n";
    }
}
```

# Range-for loops



- C++ also has range-for loops, which can be used to loop over collections (*ranges*)
- This has the form

```
for (declaration : range) {  
    // do something  
}
```

- This is extremely useful when dealing with vectors and strings!
- A range-for loop can be used with any type that meets the *range concept* requirements, including all standard library collections

# Range-for example



```
int main()
{
    std::vector<int> vec{1, 2, 3, 4, 5};

    for (int i : vec) {
        std::cout << i << '\n';
    }
}
```

# Exercise

- Complete exercise 8 of chapter 4 of the textbook
- This is a bit tricky! Try working out the problem with a pen and paper before you start coding
- Don't worry if you don't finish it today



# Summary

- Today we've learned about
  - Pass by value
  - Scope
  - Automatic lifetime
  - If statements
  - Loops

# Next time

- References and const references
- Pointers and when (not) to use them

# Homework

- Read chapter 4 of the book if you have not already done so
- Finish the last exercise if you didn't have time today
- Complete the “drill” from the end of chapter 4
- Read chapter 7 to get a head start on references

# Online resources



- <https://isocpp.org/get-started>
- [cppreference.com](http://cppreference.com) — The bible, but aimed at experts
- [cplusplus.com](http://cplusplus.com) — Another reference site, also has a tutorial section
- [learncpp.com](http://learncpp.com) — Free online tutorial, very up-to-date
- <https://www.pluralsight.com/authors/kate-gregory> - Comprehensive set of courses from an experienced C++ trainer (free trial)
- [reddit.com/r/cpp\\_questions](https://reddit.com/r/cpp_questions)
- Cpplang Slack channel — <https://cpplang.now.sh/> for an “invite”
- StackOverflow (but...)

# Thanks for coming!



C++ London Uni:

- Website: [cpplondonuni.com](http://cpplondonuni.com)
- Github: [github.com/CPPLondonUni](https://github.com/CPPLondonUni)

Where to find Tom Breza:

- On Slack: [#cpplang.slack.com](https://cpplang.slack.com) #learn #ug\_uk\_cpplondonuni
- E-mail: [tom@PCServiceGroup.co.uk](mailto:tom@PCServiceGroup.co.uk)
- Mobile: 07947451167

My stuff:

- Website: [tristanbrindle.com](http://tristanbrindle.com)
- Twitter: @tristanbrindle
- Github: [github.com/tcbrindle](https://github.com/tcbrindle)

See you next time! 😊