

Version 0.2

21-Apr-2016

Contents

1	1 OVERVIEW		3
2	DELI	VERABLES	4
	2.1	Date of Delivery	4
	2.2	DISTRIBUTION METHOD	4
	2.3	ITEMS INCLUDED IN THIS RELEASE	4
	2.4	ITEMS NOT INCLUDED IN THIS RELEASE	4
3	PLAT	FFORM SUPPORT	5
4	TEST	TING	5
5	ISSUI	ES RESOLVED	6
6	KNOV	WN ISSUES	6
7	PREV	VIOUS RELEASES	6

1 Overview

This document provides a general description of the OpenNSL release. It also describes the supported platforms, API additions or changes, resolved issues and any relevant open issues.

OpenNSL 3.1.0.10 release adds the following new features:

• Support for Resource Manager

For product documentation, please refer to the 'doc/html/index.html' file in the OpenNSL package, or access the following URL: http://broadcom-switch.github.io/OpenNSL/doc/html/index.html.

2 Deliverables

2.1 Date of Delivery

OpenNSL version 3.1.0.10 is released on 19th April 2016. This is based on SDK version 6.4.10.

2.2 Distribution Method

OpenNSL is distributed via Broadcom's DOCSAFE and Broadcom's GitHub forums.

2.3 Items included in this release

Following are the items included in this release:

- OpenNSL library for supported platforms
- OpenNSL header files
- OpenNSL documentation
- OpenNSL example applications and supporting software.

2.4 Items Not Included in this release

The following items are specifically not included in this delivery and will be considered for future releases:

• None

3 Platform Support

This release contains support for the following platforms:

Platform	Broadcom Switching Silicon
Interface Masters Niagara 2948-6XL switch	Trident-II (BCM56850_A1)
Wedge Switch	Trident-II (BCM56850_A1)
Celestica Redstone-XP	Trident-II (BCM56850_A1)
Accton AS5712	Trident-II (BCM56854_A2)
Dell S6000	Trident-II (BCM56850_A1)

4 Testing

The following table lists the high level testing done on OpenNSL API's using the sample applications.

Sample Application	Test description
L2 firewall	Verified L2 entry addition and deletion by
	checking the traffic from/to a destination.
	This application is also tested by booting it
	in warm boot mode.
Routing	Created host and default routes and
	verified that traffic is routed as per the
	routes added. This application is also
	tested by booting it in warm boot mode.
Trunk	Added few ports to a trunk and verified
	that the traffic is distributed across the
	trunk members. This application is also
	tested by booting it in warm boot mode.
KNET	Created a Linux interface that maps to a
	front panel port with a specified IP and net
	mask and verified the configured
	parameters from the Linux shell.
BST	Verified display and clearing of basic BST
	counters.
sFlow	Verified configuration, display of sFlow
	sampling rate along with the sampling of
	packets to CPU at configured rate.
Warm Boot	Verified restarting of OpenNSL driver in
	Warm Boot mode and ensured that the L2,
	VLAN, Port and L3 state is retained
	without impacting data forwarding.
Field Processor	Verified configuration of Field process

	QSET, rules, and actions to block traffic
	from specific range of source IPv4
	addresses.
VxLAN	Verified configuration of VxLAN tunnel,
	encapsulation and de-capsulation of a
	packet by sending traffic.
Statistics	Verified updating of port counters on
	sending traffic.
Packet Transmit	Transmitted desired number of pre-defined
	packets onto a port and verified that the
	packets are received correctly on the traffic
	generator connected to it.

5 Issues resolved

ID	Description

6 Known Issues

ID	Description	
FP-230782	QSFP ports on Accton AS5712 platform are not supported	
FP-233309	Warmboot feature is not supported on Accton AS5712	

7 Previous Releases

Date	Release Number	Feature Set	
11 th Apr 3.1.0.9		Adds support for the following.	
2016		 Support for additional API's in Field module Support for additional API's in Packet module Support for an API to get OpenNSL revision 	
24 th Mar 2016	3.1.0.8	Adds the following new features: Support for CoS module. Support for CoS API's Support for L2 table activity API's Support for additional port management API's 	
9 th Mar 2016	3.1.0.7	 SDK upgrade to version 6.4.10 Support for customizing platform initialization 	

		 Support for VXLAN, Mirroring, Field Processor, QoS, Flex Statistics and Tunnel modules Support for Dell S6000 Switch Support for L2 cache management APIs Support for Trunk failover Increased the number of KNET filters from 128 to 256. Support for additional Spanning Tree APIs Support for additional L2 callback events Licensing changes for specific OpenNSL modules.
4 th Dec 2015	3.0.0.4	 SDK upgrade to 6.4.8 Support for Accton AS5712 Switch Support for Broadcom reference platform with Tomahawk B0 switching silicon Support for sFlow Added API's to support for L3 statistics and resilient ECMP Pruning reserved fields from structures and enumerations