

API Documentation

API Documentation

July 28, 2013

Contents

Contents	1
1 Package lotto	3
1.1 Modules	3
1.2 Variables	3
2 Package lotto.dialog	4
2.1 Modules	4
2.2 Variables	4
3 Module lotto.dialog.show_drawing	5
3.1 Variables	5
3.2 ClassDlgShowDrawing	5
3.2.1 Methods	6
3.2.2 Properties	8
3.2.3 Class Variables	8
4 Module lotto.lotto_gui1	9
4.1 Functions	9
4.2 Variables	9
4.3 ClassMeinDialog	9
4.3.1 Methods	10
4.3.2 Properties	12
4.3.3 Class Variables	13
5 Module lotto.lottokugeln_rc	14
5.1 Functions	14
5.2 Variables	14
6 Module lotto.zufallszahl	15
6.1 Functions	15
6.2 Variables	15
Index	17

1 Package lotto

1.1 Modules

- **dialog** (*Section 2, p. 4*)
 - **show_drawing**: pyLottoSimu (*Section 3, p. 5*)
- **lotto_gui1**: The signals for the GUI (*Section 4, p. 9*)
- **lottokugeln_rc** (*Section 5, p. 14*)
- **zufallszahl**: Erzeugen einer Zufallszahl, mit Modultest beim direkten Aufruf (*Section 6, p. 15*)

1.2 Variables

Name	Description
<code>__package__</code>	Value: None

2 Package `lotto.dialog`

2.1 Modules

- `show__drawing`: `pyLottoSimu`
(Section 3, p. 5)

2.2 Variables

Name	Description
<code>__package__</code>	Value: <code>None</code>

3 Module lotto.dialog.show__drawing

pyLottoSimu

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of pyLottoSimu.

pyLottoverwaltung is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.


pyLottoSimu is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with pyLottoSimu. If not, see <<http://www.gnu.org/licenses/>>.

3.1 Variables

Name	Description
__package__	Value: 'lotto.dialog'

3.2 Class DlgShowDrawing



Show the numbers in a dialog box

3.2.1 Methods

__init__ (self, draw_number, highest_number)	
x.__init__(...) initializes x; see help(type(x)) for signature	
Parameters	
draw_number:	the number of draw (type=tuple of int)
highest_number:	the number of the PushButtons (type=int)
Return Value	
none	
Overrides: object.__init__	

Inherited from PyQt4.QtGui.QDialog

accept(), accepted(), closeEvent(), contextMenuEvent(), done(), eventFilter(), exec_(), extension(), finished(), isSizeGripEnabled(), keyPressEvent(), minimumSizeHint(), open(), orientation(), reject(), rejected(), resizeEvent(), result(), setExtension(), setModal(), setOrientation(), setResult(), setSizeGripEnabled(), setVisible(), showEvent(), showExtension(), sizeHint()

Inherited from PyQt4.QtGui.QWidget

acceptDrops(), accessibleDescription(), accessibleName(), actionEvent(), actions(), activateWindow(), addAction(), addActions(), adjustSize(), autoFillBackground(), backgroundRole(), baseSize(), changeEvent(), childAt(), childrenRect(), childrenRegion(), clearFocus(), clearMask(), close(), contentsMargins(), contentsRect(), contextMenuPolicy(), create(), cursor(), customContextMenuRequested(), destroy(), devType(), dragEnterEvent(), dragLeaveEvent(), dragMoveEvent(), dropEvent(), effectiveWinId(), enabledChange(), ensurePolished(), enterEvent(), event(), find(), focusInEvent(), focusNextChild(), focusNextPrevChild(), focusOutEvent(), focusPolicy(), focusPreviousChild(), focusProxy(), focusWidget(), font(), fontChange(), fontInfo(), fontMetrics(), foregroundRole(), frameGeometry(), frameSize(), geometry(), getContentsMargins(), grabGesture(), grabKeyboard(), grabMouse(), grabShortcut(), graphicsEffect(), graphicsProxyWidget(), handle(), hasFocus(), hasMouseTracking(), height(), heightForWidth(), hide(), hideEvent(), inputContext(), inputMethodEvent(), inputMethodHints(), inputMethodQuery(), insertAction(), insertActions(), isActiveWindow(), isAncestorOf(), isEnabled(), isEnabledTo(), isEnabledToTLW(), isFullScreen(), isHidden(), isLeftToRight(), isMaximized(), isMinimized(), isModal(), isRightToLeft(), isTopLevel(), isVisible(), isVisibleTo(), isWindow(), isWindowModified(), keyReleaseEvent(), keyboardGrabber(), languageChange(), layout(), layoutDirection(), leaveEvent(), locale(), lower(), mapFrom(), mapFromGlobal(), mapFromParent(), mapTo(), mapToGlobal(), mapToParent(), mask(), maximumHeight(), maximumSize(), maximumWidth(), metric(), minimumHeight(),

minimumSize(), minimumWidth(), mouseDoubleClickEvent(), mouseGrabber(), mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), move(), moveEvent(), nativeParentWidget(), nextInFocusChain(), normalGeometry(), overrideWindowFlags(), overrideWindowState(), paintEngine(), paintEvent(), palette(), paletteChange(), parentWidget(), pos(), previousInFocusChain(), raise_(), rect(), releaseKeyboard(), releaseMouse(), releaseShortcut(), removeAction(), render(), repaint(), resetInputContext(), resize(), restoreGeometry(), saveGeometry(), scroll(), setAcceptDrops(), setAccessibleDescription(), setAccessibleName(), setAttribute(), setAutoFillBackground(), setBackgroundRole(), setBaseSize(), setContentsMargins(), setContextMenuPolicy(), setCursor(), setDisabled(), setEnabled(), setFixedHeight(), setFixedSize(), setFixedWidth(), setFocus(), setFocusPolicy(), setFocusProxy(), setFont(), setForegroundRole(), setGeometry(), setGraphicsEffect(), setHidden(), setInputContext(), setInputMethodHints(), setLayout(), setLayoutDirection(), setLocale(), setMask(), setMaximumHeight(), setMaximumSize(), setMaximumWidth(), setMinimumHeight(), setMinimumSize(), setMinimumWidth(), setMouseTracking(), setPalette(), setParent(), setShortcutAutoRepeat(), setShortcutEnabled(), setShown(), setSizeIncrement(), setSizePolicy(), setStatusTip(), setStyle(), setStyleSheet(), setTabOrder(), setToolTip(), setUpdatesEnabled(), setWhatsThis(), setWindowFilePath(), setWindowFlags(), setWindowIcon(), setWindowIconText(), setWindowModality(), setWindowModified(), setWindowOpacity(), setWindowRole(), setWindowState(), setWindowTitle(), show(), showFullScreen(), showMaximized(), showMinimized(), showNormal(), size(), sizeIncrement(), sizePolicy(), stackUnder(), statusTip(), style(), styleSheet(), tabletEvent(), testAttribute(), tooltip(), topLevelWidget(), underMouse(), ungrabGesture(), unsetCursor(), unsetLayoutDirection(), unsetLocale(), update(), updateGeometry(), updateMicroFocus(), updatesEnabled(), visibleRegion(), whatsThis(), wheelEvent(), width(), winId(), window(), windowActivationChange(), windowFilePath(), windowFlags(), windowIcon(), windowIconText(), windowModality(), windowOpacity(), windowRole(), windowState(), windowTitle(), windowType(), x(), x11Info(), x11PictureHandle(), y()

Inherited from PyQt4.QtCore.QObject

__getattr__(), blockSignals(), childEvent(), children(), connect(), connectNotify(), customEvent(), deleteLater(), destroyed(), disconnect(), disconnectNotify(), dumpObjectInfo(), dumpObjectTree(), dynamicPropertyNames(), emit(), findChild(), findChildren(), inherits(), installEventFilter(), isWidgetType(), killTimer(), metaObject(), moveToThread(), objectName(), parent(), property(), pyqtConfigure(), receivers(), removeEventFilter(), sender(), senderSignalIndex(), setObjectName(), setProperty(), signalsBlocked(), startTimer(), thread(), timerEvent(), tr(), trUtf8()

Inherited from PyQt4.QtGui.QPaintDevice

colorCount(), depth(), heightMM(), logicalDpiX(), logicalDpiY(), numColors(), paintingActive(), physicalDpiX(), physicalDpiY(), widthMM()

Inherited from sip.simplewrapper

__new__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __reduce__(),
__reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __sub-
classhook__()

3.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

3.2.3 Class Variables

Name	Description
<i>Inherited from PyQt4.QtGui.QDialog</i>	
Accepted, Rejected	
<i>Inherited from PyQt4.QtGui.QWidget</i>	
DrawChildren, DrawWindowBackground, IgnoreMask	
<i>Inherited from PyQt4.QtCore.QObject</i>	
staticMetaObject	
<i>Inherited from PyQt4.QtGui.QPaintDevice</i>	
PdmDepth, PdmDpiX, PdmDpiY, PdmHeight, PdmHeightMM, PdmNumColors, PdmPhysicalDpiX, PdmPhysicalDpiY, PdmWidth, PdmWidthMM	

4 Module *lotto.lotto_gui1*

The signals for the GUI


4.1 Functions

gui()
open the GUI

4.2 Variables

Name	Description
<code>__doc__</code>	Value: "The signals for the GUI"
<code>__package__</code>	Value: 'lotto'

4.3 Class *MeinDialog*



4.3.1 Methods**__init__**(*self*)

x.__init__(...) initializes x; see help(type(x)) for signature

Overrides: object.__init__ extit(inherited documentation)

ontimer(*self*)

start time to show a number

NaechsteZahl(*self*)

Display the draw

onbtn_start(*self*)

start simultion with the first drawing init timer with the valve from the Scrollbar the next drawing starts with the timer event

actionLottosim(*self*)

Changing the layout for simulation or generation Move the textedit and change the visible

onZufallsgenerator(*self*)

Show the output from the random number generator

onAusfeldLeeren(*self*)

clear the TextEdit

onInfo(*self*)

Infoscreen

onClose(*self*)***Inherited from PyQt4.QtGui.QMainWindow***

addDockWidget(), addToolBar(), addToolBarBreak(), centralWidget(), contextMenuEvent(), corner(), createPopupMenu(), dockOptions(), dockWidgetArea(), documentMode(), event(), iconSize(), iconSizeChanged(), insertToolBar(), insertToolBarBreak(), isAnimated(), isDockNestingEnabled(), isSeparator(), menuBar(), menuWidget(), removeDockWidget(), removeToolBar(), removeToolBarBreak(), restoreDockWidget(), restoreState(), saveState(), setAnimated(), setCentralWidget(), setCorner(), set-

`DockNestingEnabled()`, `setDockOptions()`, `setDocumentMode()`, `setIconSize()`, `setMenuBar()`, `setMenuWidget()`, `setStatusbar()`, `setTabPosition()`, `setTabShape()`, `setToolButtonStyle()`, `setUnifiedTitleAndToolBarOnMac()`, `splitDockWidget()`, `statusBar()`, `tabPosition()`, `tabShape()`, `tabifiedDockWidgets()`, `tabifyDockWidget()`, `toolBarArea()`, `toolBarBreak()`, `toolButtonStyle()`, `toolButtonStyleChanged()`, `unifiedTitleAndToolBarOnMac()`

Inherited from PyQt4.QtGui.QWidget

`acceptDrops()`, `accessibleDescription()`, `accessibleName()`, `actionEvent()`, `actions()`, `activateWindow()`, `addAction()`, `addActions()`, `adjustSize()`, `autoFillBackground()`, `backgroundRole()`, `baseSize()`, `changeEvent()`, `childAt()`, `childrenRect()`, `childrenRegion()`, `clearFocus()`, `clearMask()`, `close()`, `closeEvent()`, `contentsMargins()`, `contentsRect()`, `contextMenuPolicy()`, `create()`, `cursor()`, `customContextMenuRequested()`, `destroy()`, `devType()`, `dragEnterEvent()`, `dragLeaveEvent()`, `dragMoveEvent()`, `dropEvent()`, `effectiveWinId()`, `enabledChange()`, `ensurePolished()`, `enterEvent()`, `find()`, `focusInEvent()`, `focusNextChild()`, `focusNextPrevChild()`, `focusOutEvent()`, `focusPolicy()`, `focusPreviousChild()`, `focusProxy()`, `focusWidget()`, `font()`, `fontChange()`, `fontInfo()`, `fontMetrics()`, `foregroundRole()`, `frameGeometry()`, `frameSize()`, `geometry()`, `getContentsMargins()`, `grabGesture()`, `grabKeyboard()`, `grabMouse()`, `grabShortcut()`, `graphicsEffect()`, `graphicsProxyWidget()`, `handle()`, `hasFocus()`, `hasMouseTracking()`, `height()`, `heightForWidth()`, `hide()`, `hideEvent()`, `inputContext()`, `inputMethodEvent()`, `inputMethodHints()`, `inputMethodQuery()`, `insertAction()`, `insertActions()`, `isActiveWindow()`, `isAncestorOf()`, `isEnabled()`, `isEnabledTo()`, `isEnabledToTLW()`, `isFullScreen()`, `isHidden()`, `isLeftToRight()`, `isMaximized()`, `isMinimized()`, `isModal()`, `isRightToLeft()`, `isTopLevel()`, `isVisible()`, `isVisibleTo()`, `isWindow()`, `isWindowModified()`, `keyPressEvent()`, `keyReleaseEvent()`, `keyboardGrabber()`, `languageChange()`, `layout()`, `layoutDirection()`, `leaveEvent()`, `locale()`, `lower()`, `mapFrom()`, `mapFromGlobal()`, `mapFromParent()`, `mapTo()`, `mapToGlobal()`, `mapToParent()`, `mask()`, `maximumHeight()`, `maximumSize()`, `maximumWidth()`, `metric()`, `minimumHeight()`, `minimumSize()`, `minimumSizeHint()`, `minimumWidth()`, `mouseDoubleClickEvent()`, `mouseGrabber()`, `mouseMoveEvent()`, `mousePressEvent()`, `mouseReleaseEvent()`, `move()`, `moveEvent()`, `nativeParentWidget()`, `nextInFocusChain()`, `normalGeometry()`, `overrideWindowFlags()`, `overrideWindowState()`, `paintEngine()`, `paintEvent()`, `palette()`, `paletteChange()`, `parentWidget()`, `pos()`, `previousInFocusChain()`, `raise_()`, `rect()`, `releaseKeyboard()`, `releaseMouse()`, `releaseShortcut()`, `removeAction()`, `render()`, `repaint()`, `resetInputContext()`, `resize()`, `resizeEvent()`, `restoreGeometry()`, `saveGeometry()`, `scroll()`, `setAcceptDrops()`, `setAccessibleDescription()`, `setAccessibleName()`, `setAttribute()`, `setAutoFillBackground()`, `setBackgroundRole()`, `setBaseSize()`, `setContentsMargins()`, `setContextMenuPolicy()`, `setCursor()`, `setDisabled()`, `setEnabled()`, `setFixedHeight()`, `setFixedSize()`, `setFixedWidth()`, `setFocus()`, `setFocusPolicy()`, `setFocusProxy()`, `setFont()`, `setForegroundRole()`, `setGeometry()`, `setGraphicsEffect()`, `setHidden()`, `setInputContext()`, `setInputMethodHints()`, `setLayout()`, `setLayoutDirection()`, `setLocale()`, `setMask()`, `setMaximumHeight()`, `setMaximumSize()`, `setMaximumWidth()`, `setMinimumHeight()`, `setMinimumSize()`,

setMinimumWidth(), setMouseTracking(), setPalette(), setParent(), setShortcutAutoRepeat(), setShortcutEnabled(), setShown(), setSizeIncrement(), setSizePolicy(), setStatusTip(), setStyle(), setStyleSheet(), setTabOrder(), setToolTip(), setUpdatesEnabled(), setVisible(), setWhatsThis(), setWindowFilePath(), setWindowFlags(), setWindowIcon(), setWindowIconText(), setWindowModality(), setWindowModified(), setWindowOpacity(), setWindowRole(), setWindowState(), setWindowTitle(), show(), showEvent(), showFullScreen(), showMaximized(), showMinimized(), showNormal(), size(), sizeHint(), sizeIncrement(), sizePolicy(), stackUnder(), statusTip(), style(), styleSheet(), tabletEvent(), testAttribute(), toolTip(), topLevelWidget(), underMouse(), ungrabGesture(), unsetCursor(), unsetLayoutDirection(), unsetLocale(), update(), updateGeometry(), updateMicroFocus(), updatesEnabled(), visibleRegion(), whatsThis(), wheelEvent(), width(), winId(), window(), windowActivationChange(), windowFilePath(), windowFlags(), windowIcon(), windowIconText(), windowModality(), windowOpacity(), windowRole(), windowState(), windowTitle(), windowType(), x(), x11Info(), x11PictureHandle(), y()

Inherited from PyQt4.QtCore.QObject

__getattr__(), blockSignals(), childEvent(), children(), connect(), connectNotify(), customEvent(), deleteLater(), destroyed(), disconnect(), disconnectNotify(), dumpObjectInfo(), dumpObjectTree(), dynamicPropertyNames(), emit(), eventFilter(), findChild(), findChildren(), inherits(), installEventFilter(), isWidgetType(), killTimer(), metaObject(), moveToThread(), objectName(), parent(), property(), pyqtConfigure(), receivers(), removeEventFilter(), sender(), senderSignalIndex(), setObjectName(), setProperty(), signalsBlocked(), startTimer(), thread(), timerEvent(), tr(), trUtf8()

Inherited from PyQt4.QtGui.QPaintDevice

colorCount(), depth(), heightMM(), logicalDpiX(), logicalDpiY(), numColors(), paintingActive(), physicalDpiX(), physicalDpiY(), widthMM()

Inherited from sip.simplewrapper

__new__()

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(), __str__(), __subclasshook__()

4.3.2 Properties

continued on next page

Name	Description
Name	Description
<i>Inherited from object</i>	
<u>__class__</u>	

4.3.3 Class Variables

Name	Description
<i>Inherited from PyQt4.QtGui.QMainWindow</i>	
AllowNestedDocks, AllowTabbedDocks, AnimatedDocks, ForceTabbedDocks, VerticalTabs	
<i>Inherited from PyQt4.QtGui.QWidget</i>	
DrawChildren, DrawWindowBackground, IgnoreMask	
<i>Inherited from PyQt4.QtCore.QObject</i>	
staticMetaObject	
<i>Inherited from PyQt4.QtGui.QPaintDevice</i>	
PdmDepth, PdmDpiX, PdmDpiY, PdmHeight, PdmHeightMM, PdmNumColors, PdmPhysicalDpiX, PdmPhysicalDpiY, PdmWidth, PdmWidthMM	

5 Module `lotto.lottokugeln_rc`

5.1 Functions

<code>qInitResources()</code>

<code>qCleanupResources()</code>

5.2 Variables

Name	Description
<code>qt_resource_data</code>	Value: '\x00\x01\x94\x94\x89PNG\r\n\x1a\n\x00\x00\x00\rIHDR\x00\.
<code>qt_resource_name</code>	Value: '\x00\x0e\x00\xc9\x8e\xe7\x001\x00o\x00t\x00t\x00o\x00k\x.
<code>qt_resource_struct</code>	Value: '\x00\x00\x00\x00\x00\x02\x00\x00\x00\x01\x00\x00\x00\x01.
<code>__package__</code>	Value: 'lotto'

6 Module *lotto.zufallszahl*

Erzeugen einer Zufallszahl, mit Modultest beim direkten Aufruf

pyLottoSimu

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of pyLottoverwaltung.

pyLottoverwaltung is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

pyLottoverwaltung is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with pyLottoverwaltung. If not, see <<http://www.gnu.org/licenses/>>.

6.1 Functions

zufallszahlen(*anzahl*, *maxwert*)

Zufallszahl ermitteln und als Wuerfelerggebnis nehmen return random valve

Parameters

anzahl: Gibt die Anzahl der Ausgabewerte an

(*type=int*)

maxwert: Gibt den höchsten Zahlenwert an

(*type=int*)

Return Value

Gibt Zufallszahlen zurueck. >>> zufallszahlen(16, 15) Traceback (most recent call last): ValueError: sample larger than population >>> zufallszahlen(16, -15) Traceback (most recent call last): ValueError: sample larger than population >>> zufallszahlen(-16, 15) Traceback (most recent call last): ValueError: sample larger than population >>> zufallszahlen(1, 1) [1] >>> zufallszahlen(1, 1.7) Traceback (most recent call last): TypeError: integer argument expected, got float >>> sorted(zufallszahlen(3, 3)) [1, 2, 3]

6.2 Variables

Name	Description
<code>__package__</code>	Value: 'lotto'

Index

- lotto (*package*), 3
 - lotto.dialog (*package*), 4
 - lotto.dialog.show_drawing (*module*), 5–8
 - lotto.lotto_gui1 (*module*), 9–13
 - lotto.lotto_gui1.gui (*function*), 9
 - lotto.lotto_gui1.MeinDialog (*class*), 9–13
 - lotto.lottokugeln_rc (*module*), 14
 - lotto.lottokugeln_rc.qCleanupResources (*function*), 14
 - lotto.lottokugeln_rc.qInitResources (*function*), 14
 - lotto.zufallszahl (*module*), 15–16
 - lotto.zufallszahl.zufallszahlen (*function*), 15