

API Documentation

API Documentation

March 9, 2013

Contents

Contents	1
1 Package lotto	3
1.1 Modules	3
1.2 Variables	3
2 Module lotto.auswertung	4
2.1 Variables	4
2.2 Class ui_lotto_auswertung	4
2.2.1 Methods	5
2.2.2 Properties	7
2.2.3 Class Variables	7
3 Module lotto.datahandler	8
3.1 Variables	8
3.2 Class Datahandler	8
3.2.1 Methods	8
3.2.2 Properties	10
4 Package lotto.gui	11
4.1 Modules	11
4.2 Variables	11
5 Module lotto.gui.auswertung	12
5.1 Variables	12
5.2 Class Ui_Dialog	12
5.2.1 Methods	12
5.2.2 Properties	12
6 Module lotto.gui.lotto_dateneing	13
6.1 Variables	13
6.2 Class Ui_MainWindow	13
6.2.1 Methods	13
6.2.2 Properties	13
7 Module lotto.gui.lotto_dialog	14
7.1 Variables	14
7.2 Class Ui_Dialog	14

7.2.1	Methods	14
7.2.2	Properties	14
8	Module lotto.lotto_gui_dateneing	15
8.1	Functions	15
8.2	Variables	15
8.3	Class ui_lotto_Dialog	16
8.3.1	Methods	16
8.3.2	Properties	19
8.3.3	Class Variables	19
8.4	Class MeinDialog	20
8.4.1	Methods	20
8.4.2	Properties	25
8.4.3	Class Variables	25
9	Module lotto.webzugriff	26
9.1	Functions	26
9.2	Variables	26
10	Module lotto.zufallszahl	27
10.1	Functions	28
10.2	Variables	28
	Index	29

1 Package lotto

1.1 Modules

- **auswertung**: pyLottoverwaltung
(Section 2, p. 4)
- **datahandler**: the data handler for insert, get and delete data in the database
(Section 3, p. 8)
- **gui** (Section 4, p. 11)
 - **auswertung** (Section 5, p. 12)
 - **lotto_dateneing** (Section 6, p. 13)
 - **lotto_dialog** (Section 7, p. 14)
- **lotto_gui_dateneing**: pyLottoverwaltung
(Section 8, p. 15)
- **webzugriff**: pyLottoverwaltung
(Section 9, p. 26)
- **zufallszahl**: Erzeugen einer Zufallszahl, mit Modultest beim direkten Aufruf
(Section 10, p. 27)

1.2 Variables

Name	Description
__package__	Value: None

2 Module `lotto.auswertung`

`pyLottoverwaltung`

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of `pyLottoverwaltung`.

`pyLottoverwaltung` is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.


`pyLottoverwaltung` is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with `pyLottoverwaltung`. If not, see <<http://www.gnu.org/licenses/>>.

2.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto'</code>

2.2 Class `ui_lotto_auswertung`



2.2.1 Methods

<code>__init__</code> (<i>self</i> , <i>rowid</i> , <i>data_handler</i>)
open analyze dialog Datenauswerte Dialog oeffnen
Parameters
<i>data_handler</i> : (<i>type=datahandler</i>)
<i>rowid</i> : (<i>type=int</i>)
Return Value
give <code>close(0)</code> back
Overrides: <code>object.__init__</code>

Inherited from `PyQt4.QtGui.QDialog`

`accept()`, `accepted()`, `closeEvent()`, `contextMenuEvent()`, `done()`, `eventFilter()`, `exec_()`, `extension()`, `finished()`, `isSizeGripEnabled()`, `keyPressEvent()`, `minimumSizeHint()`, `open()`, `orientation()`, `reject()`, `rejected()`, `resizeEvent()`, `result()`, `setExtension()`, `setModal()`, `setOrientation()`, `setResult()`, `setSizeGripEnabled()`, `setVisible()`, `showEvent()`, `showExtension()`, `sizeHint()`

Inherited from `PyQt4.QtGui.QWidget`

`acceptDrops()`, `accessibleDescription()`, `accessibleName()`, `actionEvent()`, `actions()`, `activateWindow()`, `addAction()`, `addActions()`, `adjustSize()`, `autoFillBackground()`, `backgroundRole()`, `baseSize()`, `changeEvent()`, `childAt()`, `childrenRect()`, `childrenRegion()`, `clearFocus()`, `clearMask()`, `close()`, `contentsMargins()`, `contentsRect()`, `contextMenuPolicy()`, `create()`, `cursor()`, `customContextMenuRequested()`, `destroy()`, `devType()`, `dragEnterEvent()`, `dragLeaveEvent()`, `dragMoveEvent()`, `dropEvent()`, `effectiveWinId()`, `enabledChange()`, `ensurePolished()`, `enterEvent()`, `event()`, `find()`, `focusInEvent()`, `focusNextChild()`, `focusNextPrevChild()`, `focusOutEvent()`, `focusPolicy()`, `focusPreviousChild()`, `focusProxy()`, `focusWidget()`, `font()`, `fontChange()`, `fontInfo()`, `fontMetrics()`, `foregroundRole()`, `frameGeometry()`, `frameSize()`, `geometry()`, `getContentsMargins()`, `grabGesture()`, `grabKeyboard()`, `grabMouse()`, `grabShortcut()`, `graphicsEffect()`, `graphicsProxyWidget()`, `handle()`, `hasFocus()`, `hasMouseTracking()`, `height()`, `heightForWidth()`, `hide()`, `hideEvent()`, `inputContext()`, `inputMethodEvent()`, `inputMethodHints()`, `inputMethodQuery()`, `insertAction()`, `insertActions()`, `isActiveWindow()`, `isAncestorOf()`, `isEnabled()`, `isEnabledTo()`, `isEnabledToTLW()`, `isFullScreen()`, `isHidden()`, `isLeftToRight()`, `isMaximized()`, `isMinimized()`, `isModal()`, `isRightToLeft()`, `isTopLevel()`, `isVisible()`, `isVisibleTo()`, `isWindow()`, `isWindowModified()`, `keyReleaseEvent()`, `keyboardGrabber()`, `languageChange()`, `layout()`, `layoutDirection()`, `leaveEvent()`, `locale()`, `lower()`, `mapFrom()`, `mapFromGlobal()`, `mapFromParent()`, `mapTo()`, `mapToGlobal()`, `mapToParent()`, `mask()`, `maximumHeight()`, `maximumSize()`, `maximumWidth()`, `metric()`, `minimumHeight()`, `minimumSize()`, `minimumWidth()`, `mouseDoubleClickEvent()`, `mouseGrabber()`, `mouseMoveEvent()`, `mousePressEvent()`, `mouseReleaseEvent()`, `move()`, `moveEvent()`, `nativeParentWidget()`, `nextInFocusChain()`, `normalGeometry()`, `overrideWindowFlags()`,

`overrideWindowState()`, `paintEngine()`, `paintEvent()`, `palette()`, `paletteChange()`,
`parentWidget()`, `pos()`, `previousInFocusChain()`, `raise_()`, `rect()`, `releaseKeyboard()`,
`releaseMouse()`, `releaseShortcut()`, `removeAction()`, `render()`, `repaint()`, `resetInput-`
`Context()`, `resize()`, `restoreGeometry()`, `saveGeometry()`, `scroll()`, `setAcceptDrops()`,
`setAccessibleDescription()`, `setAccessibleName()`, `setAttribute()`, `setAutoFillBack-`
`ground()`, `setBackgroundRole()`, `setBaseSize()`, `setContentsMargins()`, `setContextMenuPol-`
`icy()`, `setCursor()`, `setDisabled()`, `setEnabled()`, `setFixedHeight()`, `setFixedSize()`,
`setFixedWidth()`, `setFocus()`, `setFocusPolicy()`, `setFocusProxy()`, `setFont()`, `set-`
`ForegroundRole()`, `setGeometry()`, `setGraphicsEffect()`, `setHidden()`, `setInputCon-`
`text()`, `setInputMethodHints()`, `setLayout()`, `setLayoutDirection()`, `setLocale()`, `set-`
`Mask()`, `setMaximumHeight()`, `setMaximumSize()`, `setMaximumWidth()`, `setMin-`
`imumHeight()`, `setMinimumSize()`, `setMinimumWidth()`, `setMouseTracking()`, `set-`
`Palette()`, `setParent()`, `setShortcutAutoRepeat()`, `setShortcutEnabled()`, `setShown()`,
`setSizeIncrement()`, `setSizePolicy()`, `setStatusTip()`, `setStyle()`, `setStyleSheet()`, `set-`
`TabOrder()`, `setToolTip()`, `setUpdatesEnabled()`, `setWhatsThis()`, `setWindowFilePath()`,
`setWindowFlags()`, `setWindowIcon()`, `setWindowIconText()`, `setWindowModality()`,
`setWindowModified()`, `setWindowOpacity()`, `setWindowRole()`, `setWindowState()`,
`setWindowTitle()`, `show()`, `showFullScreen()`, `showMaximized()`, `showMinimized()`,
`showNormal()`, `size()`, `sizeIncrement()`, `sizePolicy()`, `stackUnder()`, `statusTip()`, `style()`,
`styleSheet()`, `tabletEvent()`, `testAttribute()`, `toolTip()`, `topLevelWidget()`, `under-`
`Mouse()`, `ungrabGesture()`, `unsetCursor()`, `unsetLayoutDirection()`, `unsetLocale()`,
`update()`, `updateGeometry()`, `updateMicroFocus()`, `updatesEnabled()`, `visibleRe-`
`gion()`, `whatsThis()`, `wheelEvent()`, `width()`, `winId()`, `window()`, `windowActivation-`
`Change()`, `windowFilePath()`, `windowFlags()`, `windowIcon()`, `windowIconText()`,
`windowModality()`, `windowOpacity()`, `windowRole()`, `windowState()`, `windowTi-`
`tle()`, `windowType()`, `x()`, `x11Info()`, `x11PictureHandle()`, `y()`

Inherited from `PyQt4.QtCore.QObject`

`__getattr__()`, `blockSignals()`, `childEvent()`, `children()`, `connect()`, `connectNo-`
`tify()`, `customEvent()`, `deleteLater()`, `destroyed()`, `disconnect()`, `disconnectNotify()`,
`dumpObjectInfo()`, `dumpObjectTree()`, `dynamicPropertyNames()`, `emit()`, `findChild()`,
`findChildren()`, `inherits()`, `installEventFilter()`, `isWidgetType()`, `killTimer()`, `metaOb-`
`ject()`, `moveToThread()`, `objectName()`, `parent()`, `property()`, `pyqtConfigure()`, `re-`
`ceivers()`, `removeEventFilter()`, `sender()`, `senderSignalIndex()`, `setObjectName()`,
`setProperty()`, `signalsBlocked()`, `startTimer()`, `thread()`, `timerEvent()`, `tr()`, `trUtf8()`

Inherited from `PyQt4.QtGui.QPaintDevice`

`colorCount()`, `depth()`, `heightMM()`, `logicalDpiX()`, `logicalDpiY()`, `numColors()`,
`paintingActive()`, `physicalDpiX()`, `physicalDpiY()`, `widthMM()`

Inherited from `sip.simplewrapper`

`__new__()`

Inherited from `lotto.gui.auswertung.Ui_Dialog`(Section 5.2)

`retranslateUi()`, `setupUi()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__reduce__()`,
`__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

2.2.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

2.2.3 Class Variables

Name	Description
<i>Inherited from PyQt4.QtGui.QDialog</i> Accepted, Rejected	
<i>Inherited from PyQt4.QtGui.QWidget</i> DrawChildren, DrawWindowBackground, IgnoreMask	
<i>Inherited from PyQt4.QtCore.QObject</i> staticMetaObject	
<i>Inherited from PyQt4.QtGui.QPaintDevice</i> PdmDepth, PdmDpiX, PdmDpiY, PdmHeight, PdmHeightMM, PdmNumColors, PdmPhysicalDpiX, PdmPhysicalDpiY, PdmWidth, PdmWidthMM	

3 Module `lotto.datahandler`

the data handler for insert, get and delete data in the database

pyLottoverwaltung

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of pyLottoverwaltung.

pyLottoverwaltung is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

pyLottoverwaltung is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with pyLottoverwaltung. If not, see <<http://www.gnu.org/licenses/>>.

3.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto'</code>

3.2 Class Datahandler

object └─ `lotto.datahandler.Datahandler`

3.2.1 Methods

<code>__init__(self, path)</code> <code>x.__init__(...)</code> initializes <code>x</code> ; see <code>help(type(x))</code> for signature Overrides: <code>object.__init__</code> <code>exitit</code> (inherited documentation)
<code>create_tables(self)</code> Tabellen erstellen

add_columns(*self*)

Add columns

insert_ziehung(*self*, *day*, *zahl_1*, *zahl_2*, *zahl_3*, *zahl_4*, *zahl_5*, *zahl_6*, *zahl_zusatz*, *zahl_super*, *zahl_spiel77*, *zahl_spielsuper6*)

Daten der Ziehung der Lottozahlen in der Datenbank speichern

insert_schein(*self*, *day*, *zahl_1*, *zahl_2*, *zahl_3*, *zahl_4*, *zahl_5*, *zahl_6*, *laufzeit*, *laufzeit_tag*, *scheinnr*)

Daten des Lottoscheines in der Datenbank speichern

update_ziehung(*self*, *row_id*, *day*, *zahl_1*, *zahl_2*, *zahl_3*, *zahl_4*, *zahl_5*, *zahl_6*, *zahl_zusatz*, *zahl_super*, *zahl_spiel77*, *zahl_spielsuper6*)

Daten der Ziehung der Lottozahlen in der Datenbank speichern

update_schein(*self*, *row_id*, *day*, *zahl_1*, *zahl_2*, *zahl_3*, *zahl_4*, *zahl_5*, *zahl_6*, *laufzeit*, *laufzeit_tag*, *scheinnr*)

Daten des Lottoscheines in der Datenbank speichern

get_ziehung(*self*, *rowid*=None, *date*=None)

Daten der Ziehung der Lottozahlen auslesen

get_numbers_from_ziehung(*self*, *rowid_lottoschein*)

Get numbers from ziehung Finde von Nummer in den Ziehungsdaten

Parameters

rowid_lottoschein: (*type*=int)

Return Value

ToDo

get_schein(*self*, *rowid*=None)

Get data from Lottoscheines Daten des Lottoscheines auslesen

Parameters

rowid: (*type*=int)

Return Value

data

delete__ziehung (<i>self</i> , <i>rowid</i>)
Daten der Ziehung der Lottozahlen löschen
Parameters
<i>rowid</i> : (<i>type=int</i>)

delete__schein (<i>self</i> , <i>rowid</i>)
Daten eines Lottoscheines löschen
Parameters
<i>rowid</i> : (<i>type=int</i>)

close (<i>self</i>)
close connection of database

Inherited from object

__delattr__(), __format__(), __getattr__(), __hash__(), __new__(),
__reduce__(), __reduce_ex__(), __repr__(), __setattr__(), __sizeof__(),
__str__(), __subclasshook__()

3.2.2 Properties

Name	Description
<i>Inherited from object</i>	
__class__	

4 Package lotto.gui

4.1 Modules

- **auswertung** (*Section 5, p. 12*)
- **lotto_dateneing** (*Section 6, p. 13*)
- **lotto_dialog** (*Section 7, p. 14*)

4.2 Variables

Name	Description
__package__	Value: None

5 Module *lotto.gui.auswertung*

5.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto.gui'</code>

5.2 Class *Ui_Dialog*

object └─ `lotto.gui.auswertung.Ui_Dialog`

Known Subclasses: `lotto.auswertung.ui_lotto_auswertung`

5.2.1 Methods

<code>setupUi(self, Dialog)</code>

<code>retranslateUi(self, Dialog)</code>
--

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

5.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

6 Module *lotto.gui.lotto_dateneing*

6.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto.gui'</code>

6.2 Class *Ui_MainWindow*

object └─ ***lotto.gui.lotto_dateneing.Ui_MainWindow***

Known Subclasses: *lotto.lotto_gui_dateneing.MeinDialog*

6.2.1 Methods

<i>setupUi(self, MainWindow)</i>

<i>retranslateUi(self, MainWindow)</i>

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

6.2.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

7 Module *lotto.gui.lotto_dialog*

7.1 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto.gui'</code>

7.2 Class *Ui_Dialog*

object └─ `lotto.gui.lotto_dialog.Ui_Dialog`

Known Subclasses: `lotto.lotto_gui_dateneing.ui_lotto_Dialog`

7.2.1 Methods

<code>setupUi(self, Dialog)</code>

<code>retranslateUi(self, Dialog)</code>
--

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__init__()`,
`__new__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`,
`__sizeof__()`, `__str__()`, `__subclasshook__()`

7.2.2 Properties

Name	Description
<i>Inherited from object</i>	
<code>__class__</code>	

8 Module `lotto.lotto_gui_dateneing`

pyLottoverwaltung

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of pyLottoverwaltung.

pyLottoverwaltung is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

pyLottoverwaltung is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with pyLottoverwaltung. If not, see <<http://www.gnu.org/licenses/>>.


8.1 Functions

gui()

8.2 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto'</code>

8.3 Class `ui_lotto_Dialog`



8.3.1 Methods

<code>__init__</code> (<i>self</i> , <i>typ</i> , <i>rowid</i>)
open analyze dialog Datenauswerte Dialog oeffnen
Parameters
typ : 0 == Gewinnzahlen, 1 == Lottoschein (<i>type=int</i>)
rowid : is the rowid number of the database (<i>type=int</i>)
Return Value
give close(0) or accept(1) back
Overrides: <code>object.__init__</code>

<code>onbtn_save_index(self, typ, rowid, date_of)</code>
--

drawing numbers move in database

Inherited from `PyQt4.QtGui.QDialog`

`accept()`, `accepted()`, `closeEvent()`, `contextMenuEvent()`, `done()`, `eventFilter()`, `exec_()`, `extension()`, `finished()`, `isSizeGripEnabled()`, `keyPressEvent()`, `minimumSizeHint()`, `open()`, `orientation()`, `reject()`, `rejected()`, `resizeEvent()`, `result()`, `setExtension()`, `setModal()`, `setOrientation()`, `setResult()`, `setSizeGripEnabled()`, `setVisible()`, `showEvent()`, `showExtension()`, `sizeHint()`

Inherited from `PyQt4.QtGui.QWidget`

`acceptDrops()`, `accessibleDescription()`, `accessibleName()`, `actionEvent()`, `actions()`, `activateWindow()`, `addAction()`, `addActions()`, `adjustSize()`, `autoFillBackground()`, `backgroundRole()`, `baseSize()`, `changeEvent()`, `childAt()`, `childrenRect()`, `childrenRegion()`, `clearFocus()`, `clearMask()`, `close()`, `contentsMargins()`, `contentsRect()`, `contextMenuPolicy()`, `create()`, `cursor()`, `customContextMenuRequested()`, `destroy()`, `devType()`, `dragEnterEvent()`, `dragLeaveEvent()`, `dragMoveEvent()`, `dropEvent()`, `effectiveWinId()`, `enabledChange()`, `ensurePolished()`, `enterEvent()`, `event()`, `find()`, `focusInEvent()`, `focusNextChild()`, `focusNextPrevChild()`, `focusOutEvent()`, `focusPolicy()`, `focusPreviousChild()`, `focusProxy()`, `focusWidget()`, `font()`, `fontChange()`, `fontInfo()`, `fontMetrics()`, `foregroundRole()`, `frameGeometry()`, `frameSize()`, `geometry()`, `getContentsMargins()`, `grabGesture()`, `grabKeyboard()`, `grabMouse()`, `grabShortcut()`, `graphicsEffect()`, `graphicsProxyWidget()`, `handle()`, `hasFocus()`, `hasMouseTracking()`, `height()`, `heightForWidth()`, `hide()`, `hideEvent()`, `inputContext()`, `inputMethodEvent()`, `inputMethodHints()`, `inputMethodQuery()`, `insertAction()`, `insertActions()`, `isActiveWindow()`, `isAncestorOf()`, `isEnabled()`, `isEnabledTo()`, `isEnabledToTLW()`, `isFullScreen()`, `isHidden()`, `isLeftToRight()`, `isMaximized()`, `isMinimized()`, `isModal()`, `isRightToLeft()`, `isTopLevel()`, `isVisible()`, `isVisibleTo()`, `isWindow()`, `isWindowModified()`, `keyReleaseEvent()`, `keyboardGrabber()`, `languageChange()`, `layout()`, `layoutDirection()`, `leaveEvent()`, `locale()`, `lower()`, `mapFrom()`, `mapFromGlobal()`, `mapFromParent()`, `mapTo()`, `mapToGlobal()`, `mapToParent()`, `mask()`, `maximumHeight()`, `maximumSize()`, `maximumWidth()`, `metric()`, `minimumHeight()`, `minimumSize()`, `minimumWidth()`, `mouseDoubleClickEvent()`, `mouseGrabber()`, `mouseMoveEvent()`, `mousePressEvent()`, `mouseReleaseEvent()`, `move()`, `moveEvent()`, `nativeParentWidget()`, `nextInFocusChain()`, `normalGeometry()`, `overrideWindowFlags()`, `overrideWindowState()`, `paintEngine()`, `paintEvent()`, `palette()`, `paletteChange()`, `parentWidget()`, `pos()`, `previousInFocusChain()`, `raise_()`, `rect()`, `releaseKeyboard()`, `releaseMouse()`, `releaseShortcut()`, `removeAction()`, `render()`, `repaint()`, `resetInputContext()`, `resize()`, `restoreGeometry()`, `saveGeometry()`, `scroll()`, `setAcceptDrops()`, `setAccessibleDescription()`, `setAccessibleName()`, `setAttribute()`, `setAutoFillBackground()`, `setBackgroundRole()`, `setBaseSize()`, `setContentsMargins()`, `setContextMenuPolicy()`, `setCursor()`, `setDisabled()`, `setEnabled()`, `setFixedHeight()`, `setFixedSize()`, `setFixedWidth()`, `setFocus()`, `setFocusPolicy()`, `setFocusProxy()`, `setFont()`, `set-`

`ForegroundRole()`, `setGeometry()`, `setGraphicsEffect()`, `setHidden()`, `setInputContext()`, `setInputMethodHints()`, `setLayout()`, `setLayoutDirection()`, `setLocale()`, `setMask()`, `setMaximumHeight()`, `setMaximumSize()`, `setMaximumWidth()`, `setMinimumHeight()`, `setMinimumSize()`, `setMinimumWidth()`, `setMouseTracking()`, `setPalette()`, `setParent()`, `setShortcutAutoRepeat()`, `setShortcutEnabled()`, `setShown()`, `setSizeIncrement()`, `setSizePolicy()`, `setStatusTip()`, `setStyle()`, `setStyleSheet()`, `setTabOrder()`, `setToolTip()`, `setUpdatesEnabled()`, `setWhatsThis()`, `setWindowFilePath()`, `setWindowFlags()`, `setWindowIcon()`, `setWindowIconText()`, `setWindowModality()`, `setWindowModified()`, `setWindowOpacity()`, `setWindowRole()`, `setWindowState()`, `setWindowTitle()`, `show()`, `showFullScreen()`, `showMaximized()`, `showMinimized()`, `showNormal()`, `size()`, `sizeIncrement()`, `sizePolicy()`, `stackUnder()`, `statusTip()`, `style()`, `stylesheet()`, `tabletEvent()`, `testAttribute()`, `toolTip()`, `topLevelWidget()`, `underMouse()`, `ungrabGesture()`, `unsetCursor()`, `unsetLayoutDirection()`, `unsetLocale()`, `update()`, `updateGeometry()`, `updateMicroFocus()`, `updatesEnabled()`, `visibleRegion()`, `whatsThis()`, `wheelEvent()`, `width()`, `winId()`, `window()`, `windowActivationChange()`, `windowFilePath()`, `windowFlags()`, `windowIcon()`, `windowIconText()`, `windowModality()`, `windowOpacity()`, `windowRole()`, `windowState()`, `windowTitle()`, `windowType()`, `x()`, `x11Info()`, `x11PictureHandle()`, `y()`

Inherited from `PyQt4.QtCore.QObject`

`__getattr__()`, `blockSignals()`, `childEvent()`, `children()`, `connect()`, `connectNotify()`, `customEvent()`, `deleteLater()`, `destroyed()`, `disconnect()`, `disconnectNotify()`, `dumpObjectInfo()`, `dumpObjectTree()`, `dynamicPropertyNames()`, `emit()`, `findChild()`, `findChildren()`, `inherits()`, `installEventFilter()`, `isWidgetType()`, `killTimer()`, `metaObject()`, `moveToThread()`, `objectName()`, `parent()`, `property()`, `pyqtConfigure()`, `receivers()`, `removeEventFilter()`, `sender()`, `senderSignalIndex()`, `setObjectName()`, `setProperty()`, `signalsBlocked()`, `startTimer()`, `thread()`, `timerEvent()`, `tr()`, `trUtf8()`

Inherited from `PyQt4.QtGui.QPaintDevice`

`colorCount()`, `depth()`, `heightMM()`, `logicalDpiX()`, `logicalDpiY()`, `numColors()`, `paintingActive()`, `physicalDpiX()`, `physicalDpiY()`, `widthMM()`

Inherited from `sip.simplewrapper`

`__new__()`

Inherited from `lotto.gui.lotto_dialog.Ui_Dialog`(Section 7.2)

`retranslateUi()`, `setupUi()`

Inherited from `object`

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__reduce__()`, `__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`


8.3.2 Properties

Name	Description
<i>Inherited from object</i> __class__	

8.3.3 Class Variables

Name	Description
<i>Inherited from PyQt4.QtGui.QDialog</i> Accepted, Rejected	
<i>Inherited from PyQt4.QtGui.QWidget</i> DrawChildren, DrawWindowBackground, IgnoreMask	
<i>Inherited from PyQt4.QtCore.QObject</i> staticMetaObject	
<i>Inherited from PyQt4.QtGui.QPaintDevice</i> PdmDepth, PdmDpiX, PdmDpiY, PdmHeight, PdmHeightMM, PdmNumColors, PdmPhysicalDpiX, PdmPhysicalDpiY, PdmWidth, PdmWidthMM	

8.4 Class *MeinDialog*



8.4.1 Methods

`__init__(self)`

initial the main window 1 to 49 button, 7 spinbox, calender, datafield

Overrides: *object.__init__*

`ondaten_gewinnz(self)`

Anzeigen der Gewinnzahlen an den Auswahlfeld Auslesen der Zeilennummer
Den Text der Zeile in der Beschriftung ausgeben

`ondaten_lottoschein(self)`

Anzeigen der Daten des Lottoscheins an den Auswahlfeld Auslesen der
Zeilennummer Den Text der Zeile in der Beschriftung ausgeben

onInfo(*self*)

Programm Info

closeEvent(*self*, *event*)

the program exit

Overrides: PyQt4.QtGui.QWidget.closeEvent

onData__lottode(*self*)

Load the actual draw from lotto.de

onData__lottozahlenonlinede(*self*, *first_year*, *last_year*)

Load the draw from lottozahlenonline.de

spinBox__1to7__clear(*self*, *number*)

Die SpinBoxen 1 bis 6 und Zusatzzahl löschen

onEingabefeld__1to49(*self*, *zahl*)

Ein Zahlenfelder 1 bis 49 wurde angeklickt

focusSpinBox__1to7(*self*, *number*)

Ein Auswahlfelder der 7 Gewinnzahlen oder Lottoscheins hat sich geändert

onBtn__hinzu(*self*)

drawing numbers move in database

onBtn__gz__aendern(*self*)

Gewinnzahlen anzeigen und ändern

onBtn__ls__aendern(*self*)

Lottoschein anzeigen und ändern

onBtn__ls__auswerten(*self*)

den Lottoschein auswerten

onBtn__gz__anzeigen(*self*)

show drawing numbers Gewinnzahlen im großen Feld anzeigen

onBtn_ls_anzeigen(*self*)

show tip numbers Lottoschein im großen Feld anzeigen,

onBtn_gz_loeschen(*self*)

delete drawing numbers from the database Gewinnzahlen einer Ziehung aus der Datenbank loeschen

onBtn_ls_loeschen(*self*)

delete tip numbers from the database Lottoschein aus der Datenbank loeschen

onBtn_ls_laden(*self*)

Read the Lottoschein from the Database loading into the QPlainTextEdit

onBtn_gz_laden(*self*)

Read the Gewinnzahlen from the Database loading into the QPlainTextEdit

onCBox_gz_kompl_ausgeben(*self*)

CheckBox: Show the complete database in TextEdit

onBtn_Zufall(*self*)

Die Zufallszahlen generieren

onBtn_set_calender_today(*self*)

set calender today

onmodus(*self*)

Wenn der Eingabe-Modus wechselt werden Schaltflächen an oder ab geschaltet

geaendert(*self*)

Überprüfen der SpinBoxen damit nicht zwei den gleichen Wert haben

geaendert_btn(*self*)

in den SpinBoxen die Nummern der Zahlen 1 bis 49 anzeigen wenn die Zahl abgewählt wird, wird auch der Wert der entsprechende Spinbox gelöscht

draw_numbers(<i>self</i>)

this numbers are in the draw

Inherited from PyQt4.QtGui.QMainWindow

addDockWidget(), addToolBar(), addToolBarBreak(), centralWidget(), contextMenuEvent(), corner(), createPopupMenu(), dockOptions(), dockWidgetArea(), documentMode(), event(), iconSize(), iconSizeChanged(), insertToolBar(), insertToolBarBreak(), isAnimated(), isDockNestingEnabled(), isSeparator(), menuBar(), menuWidget(), removeDockWidget(), removeToolBar(), removeToolBarBreak(), restoreDockWidget(), restoreState(), saveState(), setAnimated(), setCentralWidget(), setCorner(), setDockNestingEnabled(), setDockOptions(), setDocumentMode(), setIconSize(), setMenuBar(), setMenuWidget(), setStatusBar(), setTabPosition(), setTabShape(), setToolButtonStyle(), setUnifiedTitleAndToolBarOnMac(), splitDockWidget(), statusBar(), tabPosition(), tabShape(), tabifiedDockWidgets(), tabifyDockWidget(), toolBarArea(), toolBarBreak(), toolButtonStyle(), toolButtonStyleChanged(), unifiedTitleAndToolBarOnMac()

Inherited from PyQt4.QtGui.QWidget

acceptDrops(), accessibleDescription(), accessibleName(), actionEvent(), actions(), activateWindow(), addAction(), addActions(), adjustSize(), autoFillBackground(), backgroundRole(), baseSize(), changeEvent(), childAt(), childrenRect(), childrenRegion(), clearFocus(), clearMask(), close(), contentsMargins(), contentsRect(), contextMenuPolicy(), create(), cursor(), customContextMenuRequested(), destroy(), devType(), dragEnterEvent(), dragLeaveEvent(), dragMoveEvent(), dropEvent(), effectiveWinId(), enabledChange(), ensurePolished(), enterEvent(), find(), focusInEvent(), focusNextChild(), focusNextPrevChild(), focusOutEvent(), focusPolicy(), focusPreviousChild(), focusProxy(), focusWidget(), font(), fontChange(), fontInfo(), fontMetrics(), foregroundRole(), frameGeometry(), frameSize(), geometry(), getContentsMargins(), grabGesture(), grabKeyboard(), grabMouse(), grabShortcut(), graphicsEffect(), graphicsProxyWidget(), handle(), hasFocus(), hasMouseTracking(), height(), heightForWidth(), hide(), hideEvent(), inputContext(), inputMethodEvent(), inputMethodHints(), inputMethodQuery(), insertAction(), insertActions(), isActiveWindow(), isAncestorOf(), isEnabled(), isEnabledTo(), isEnabledToTLW(), isFullScreen(), isHidden(), isLeftToRight(), isMaximized(), isMinimized(), isModal(), isRightToLeft(), isTopLevel(), isVisible(), isVisibleTo(), isWindow(), isWindowModified(), keyPressEvent(), keyReleaseEvent(), keyboardGrabber(), languageChange(), layout(), layoutDirection(), leaveEvent(), locale(), lower(), mapFrom(), mapFromGlobal(), mapFromParent(), mapTo(), mapToGlobal(), mapToParent(), mask(), maximumHeight(), maximumSize(), maximumWidth(), metric(), minimumHeight(), minimumSize(), minimumSizeHint(), minimumWidth(), mouseDoubleClickEvent(), mouseGrabber(), mouseMoveEvent(), mousePressEvent(), mouseReleaseEvent(), move(), moveEvent(), nativeParentWidget(), nextInFocusChain(), normalGeometry(), overrideWindowFlags(), overrideWindowState(), paintEngine(),

`paintEvent()`, `palette()`, `paletteChange()`, `parentWidget()`, `pos()`, `previousInFocusChain()`, `raise_()`, `rect()`, `releaseKeyboard()`, `releaseMouse()`, `releaseShortcut()`, `removeAction()`, `render()`, `repaint()`, `resetInputContext()`, `resize()`, `resizeEvent()`, `restoreGeometry()`, `saveGeometry()`, `scroll()`, `setAcceptDrops()`, `setAccessibleDescription()`, `setAccessibleName()`, `setAttribute()`, `setAutoFillBackground()`, `setBackgroundRole()`, `setBaseSize()`, `setContentsMargins()`, `setContextMenuPolicy()`, `setCursor()`, `setDisabled()`, `setEnabled()`, `setFixedHeight()`, `setFixedSize()`, `setFixedWidth()`, `setFocus()`, `setFocusPolicy()`, `setFocusProxy()`, `setFont()`, `setForegroundRole()`, `setGeometry()`, `setGraphicsEffect()`, `setHidden()`, `setInputContext()`, `setInputMethodHints()`, `setLayout()`, `setLayoutDirection()`, `setLocale()`, `setMask()`, `setMaximumHeight()`, `setMaximumSize()`, `setMaximumWidth()`, `setMinimumHeight()`, `setMinimumSize()`, `setMinimumWidth()`, `setMouseTracking()`, `setPalette()`, `setParent()`, `setShortcutAutoRepeat()`, `setShortcutEnabled()`, `setShown()`, `setSizeIncrement()`, `setSizePolicy()`, `setStatusTip()`, `setStyle()`, `setStyleSheet()`, `setTabOrder()`, `setToolTip()`, `setUpdatesEnabled()`, `setVisible()`, `setWhatsThis()`, `setWindowFilePath()`, `setWindowFlags()`, `setWindowIcon()`, `setWindowIconText()`, `setWindowModality()`, `setWindowModified()`, `setWindowOpacity()`, `setWindowRole()`, `setWindowState()`, `setWindowTitle()`, `show()`, `showEvent()`, `showFullScreen()`, `showMaximized()`, `showMinimized()`, `showNormal()`, `size()`, `sizeHint()`, `sizeIncrement()`, `sizePolicy()`, `stackUnder()`, `statusTip()`, `style()`, `styleSheet()`, `tabletEvent()`, `testAttribute()`, `toolTip()`, `topLevelWidget()`, `underMouse()`, `ungrabGesture()`, `unsetCursor()`, `unsetLayoutDirection()`, `unsetLocale()`, `update()`, `updateGeometry()`, `updateMicroFocus()`, `updatesEnabled()`, `visibleRegion()`, `whatsThis()`, `wheelEvent()`, `width()`, `winId()`, `window()`, `windowActivationChange()`, `windowFilePath()`, `windowFlags()`, `windowIcon()`, `windowIconText()`, `windowModality()`, `windowOpacity()`, `windowRole()`, `windowState()`, `windowTitle()`, `windowType()`, `x()`, `x11Info()`, `x11PictureHandle()`, `y()`

Inherited from `PyQt4.QtCore.QObject`

`__getattr__()`, `blockSignals()`, `childEvent()`, `children()`, `connect()`, `connectNotify()`, `customEvent()`, `deleteLater()`, `destroyed()`, `disconnect()`, `disconnectNotify()`, `dumpObjectInfo()`, `dumpObjectTree()`, `dynamicPropertyNames()`, `emit()`, `eventFilter()`, `findChild()`, `findChildren()`, `inherits()`, `installEventFilter()`, `isWidgetType()`, `killTimer()`, `metaObject()`, `moveToThread()`, `objectName()`, `parent()`, `property()`, `pyqtConfigure()`, `receivers()`, `removeEventFilter()`, `sender()`, `senderSignalIndex()`, `setObjectName()`, `setProperty()`, `signalsBlocked()`, `startTimer()`, `thread()`, `timerEvent()`, `tr()`, `trUtf8()`

Inherited from `PyQt4.QtGui.QPaintDevice`

`colorCount()`, `depth()`, `heightMM()`, `logicalDpiX()`, `logicalDpiY()`, `numColors()`, `paintingActive()`, `physicalDpiX()`, `physicalDpiY()`, `widthMM()`

Inherited from `sip.simplewrapper`

`__new__()`

Inherited from `lotto.gui.lotto_dateneing.Ui_MainWindow`(Section 6.2)

`retranslateUi()`, `setupUi()`

Inherited from object

`__delattr__()`, `__format__()`, `__getattr__()`, `__hash__()`, `__reduce__()`,
`__reduce_ex__()`, `__repr__()`, `__setattr__()`, `__sizeof__()`, `__str__()`, `__subclasshook__()`

8.4.2 Properties

Name	Description
<i>Inherited from object</i> <code>__class__</code>	

8.4.3 Class Variables

Name	Description
<i>Inherited from <code>PyQt4.QtGui.QMainWindow</code></i> AllowNestedDocks, AllowTabbedDocks, AnimatedDocks, ForceTabbedDocks, VerticalTabs	
<i>Inherited from <code>PyQt4.QtGui.QWidget</code></i> DrawChildren, DrawWindowBackground, IgnoreMask	
<i>Inherited from <code>PyQt4.QtCore.QObject</code></i> staticMetaObject	
<i>Inherited from <code>PyQt4.QtGui.QPaintDevice</code></i> PdmDepth, PdmDpiX, PdmDpiY, PdmHeight, PdmHeightMM, PdmNumColors, PdmPhysicalDpiX, PdmPhysicalDpiY, PdmWidth, PdmWidthMM	

9 Module `lotto.webzugriff`

`pyLottoverwaltung`

Copyright (C) <2012-2013> Markus Hackspacher

This file is part of `pyLottoverwaltung`.

`pyLottoverwaltung` is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

`pyLottoverwaltung` is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with `pyLottoverwaltung`. If not, see <<http://www.gnu.org/licenses/>>.

9.1 Functions

<code>data_from_webpage()</code>

Data from <code>lotto.de</code>

Return Value

datum, list of numbers (draw 1-6, Zusatzzahl, Superzahl, Spiel77, Super6)

<code>data_from_achiv(<i>data_handler</i>, <i>quote_url</i>=None)</code>

Data from <code>www.lottozahlenonline.de</code>

<code>test_data_from_webpage()</code>
--

9.2 Variables

Name	Description
<code>__package__</code>	Value: <code>'lotto'</code>

10 Module *lotto.zufallszahl*

Erzeugen einer Zufallszahl, mit Modultest beim direkten Aufruf

pyLottoverwaltung

Copyright (C) <2012> Markus Hackspacher

This file is part of pyLottoverwaltung.

pyLottoverwaltung is free software: you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation, either version 3 of the License, or (at your option) any later version.

pyLottoverwaltung is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU Lesser General Public License for more details.

You should have received a copy of the GNU General Public License along with pyLottoverwaltung. If not, see <<http://www.gnu.org/licenses/>>.

10.1 Functions

zufallszahlen(*anzahl*, *maxwert*)

Zufallszahl ermitteln und als Wurfelergebnis nehmen return random value

Parameters

anzahl: Gibt die Anzahl der Ausgabewerte an.

(*type=int*)

maxwert: Gibt den höchsten Zahlenwert an

(*type=int*)

Return Value

Gibt Zufallszahlen zurueck.

```
>>> zufallszahlen(16, 15)
```

```
Traceback (most recent call last):
```

```
ValueError: sample larger than population
```

```
>>> zufallszahlen(16, -15)
```

```
Traceback (most recent call last):
```

```
ValueError: sample larger than population
```

```
>>> zufallszahlen(-16, 15)
```

```
Traceback (most recent call last):
```

```
ValueError: sample larger than population
```

```
>>> zufallszahlen(1, 1)
```

```
[1]
```

```
>>> zufallszahlen(1, 1.7)
```

```
Traceback (most recent call last):
```

```
TypeError: integer argument expected, got float
```

```
>>> sorted(zufallszahlen(3, 3))
```

```
[1, 2, 3]
```

10.2 Variables

Name	Description
<code>__package__</code>	Value: 'lotto'

Index

- lotto (*package*), 3
 - lotto.auswertung (*module*), 4–7
 - lotto.auswertung.ui_lotto_auswertung (*class*), 4–7
 - lotto.datahandler (*module*), 8–10
 - lotto.datahandler.Datahandler (*class*), 8–10
 - lotto.gui (*package*), 11
 - lotto.gui.auswertung (*module*), 12
 - lotto.gui.lotto_dateneing (*module*), 13
 - lotto.gui.lotto_dialog (*module*), 14
 - lotto.lotto_gui_dateneing (*module*), 15–25
 - lotto.lotto_gui_dateneing.gui (*function*), 15
 - lotto.lotto_gui_dateneing.MeinDialog (*class*), 19–25
 - lotto.lotto_gui_dateneing.ui_lotto_Dialog (*class*), 15–19
 - lotto.webzugriff (*module*), 26
 - lotto.webzugriff.data_from_achiv (*function*), 26
 - lotto.webzugriff.data_from_webpage (*function*), 26
 - lotto.webzugriff.test_data_from_webpage (*function*), 26
 - lotto.zufallszahl (*module*), 27–28
 - lotto.zufallszahl.zufallszahlen (*function*), 28