

Mathematical and Computational Modelling



Chunkit Lau

Beijing University of Posts and Telecommunications

Text

Welcome

Equations

Example

Code

Example



Text



This BUPT-themed template is derived from the OxPav template made by Clara Eleonore Pavillet ☺ for Oxford University.

1. Simple
2. Clean
3. BUPT University Colours

Enjoy! ☺



Equations



Let $p(x) = \mathcal{N}(\mu_1, \sigma^2_1)$ and $q(x) = \mathcal{N}(\mu_2, \sigma^2_2)$:

$$\mathcal{N} = \frac{1}{\sigma \sqrt{2\pi}} e^{-\frac{(x-\mu)^2}{2\sigma^2}} \quad (1)$$



Kullback-Leibler divergence for continuous probabilities:

$$\begin{aligned} D(p, q) &= \int p(x) \log \frac{p(x)}{q(x)} dx \\ &= \int p(x) \ln p(x) dx - \int p(x) \ln q(x) dx \\ &= \frac{1}{2} \ln (2 \pi \sigma_2^2) + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2 \sigma_2^2} - \frac{1}{2} (1 + \ln 2 \pi \sigma_1^2) \\ &= \ln \frac{\sigma_2}{\sigma_1} + \frac{\sigma_1^2 + (\mu_1 - \mu_2)^2}{2 \sigma_2^2} - \frac{1}{2} \end{aligned}$$



Code



Greatest Common Divisor

```
1 def greatest_c_remainder(a,b):
2     '''Greatest common divisor of a and b'''
3     r = a % b
4     if r == 0:
5         return b
6     else:
7         m = b
8         n = r
9     return greatest_c_remainder(m,n)
```

