

# Testkit-Lite User Guide

## Contents

1. Introduction
2. **Overview**
3. **Prerequisites**
4. **Installing Testkit-Lite**
5. **Testkit-Lite Options**
6. **Running Testkit-Lite**
7. **Checking Test Reports**

## 1. Introduction

This document gives an overview of Testkit-Lite and guides how to run test cases for Core and WebAPI components on Testkit-Lite.

## 2. Overview

Testkit-Lite is a test runner with command-line interface. It has the following functions:

- Accepts .xml test case descriptor files as input
- Drives automatic test execution
- Provides multiple options to meet various test requirements

## 3. Prerequisites

Before using Testkit-Lite, ensure that:

- Three packages have been installed: **python**, **python-lxml**, and **man**.

You can run the following command to install the packages:

```
$ sudo zypper -n install python
$ sudo zypper -n install python-lxml
$ sudo zypper -n install man
```

Note: **python** should be version 2.7 or later.

- An .xml test case descriptor file is ready.

Testkit-Lite recognizes and drives test cases through an .xml test case descriptor file, which describes test script, program, or HTML web test page. For details on how to create a valid .xml test case descriptor file, see the *Testkit-Lite Quick Start*.

## 4. Installing Testkit-Lite

To install Testkit-Lite from source code, perform the following steps:

- 1) Check out the latest source code:

```
$ git clone git@github.com:testkit/testkit-lite.git
```

- 2) Navigate to the work directory **testkit-lite**:

```
$ python ./setup.py build && python ./setup.py install
```

## 5. Testkit-Lite Options

- Mandatory options

Option	Description
-f <test_descriptor_file>.xml	Specify one or more test case descriptor files.
-e <Web Runtime Environment>	Specify Web Runtime Environment to run WebAPI testing, for example, <i>WRTLauncher</i>

*<test\_widget\_name>.*

Note: Only required for WebAPI testing.

Table 5-1 Mandatory options

- Optional options

Option	Description
<b>-A</b>	Testkit-Lite runs only auto test cases.
<b>-M</b>	Testkit-Lite runs only manual test cases.
<b>-O &lt;test_result_file&gt;</b>	Specify the name of result file. Testkit-Lite locates the result file under <b>/opt/testkit-lite/latest/</b> by default.
<b>-E</b>	Specific test engine.
<b>-D</b>	Dry-run the selected test cases.
<b>--fullscreen</b>	Testkit-Lite runs WebAPI test cases in full screen mode.

Table 5-2 Optional options

## 6. Running Testkit-Lite

- Show the help information:

```
$ testkit-lite --help
```

- Obtain statistics information from a test case descriptor file without testing:

```
$ testkit-lite -f /PATH/TO/<test_descript_file>.xml -D
```

- Run non-WebAPI test cases:

```
$ testkit-lite -f /PATH/TO/<test_descriptor_file>.xml
```

- Run WebAPI test cases:

```
$ testkit-lite -e "WRTLauncher <widget_name>" -f /PATH/TO/<test_descriptor_file>.xml
```

- Run both non-WebAPI and WebAPI test cases:

```
$ testkit-lite -e "WRTLauncher <widget_name>" -f  
/PATH/TO/<test_descriptor_file_for_webapi>.xml  
/PATH/TO/<test_descriptor_file_for_non_webapi>.xml
```

- Run test cases with multiple test case descriptor files:

Testkit-Lite can accept as many test case descriptor files at one time as you want. You can type all test case descriptor files sequentially after the ‘**-f**’ option:

```
$ testkit-lite -f /PATH/TO/<test_descript_file>.xml, ..., /PATH/TO/<test_descript_file_more>.xml
```

- Run a subset of test cases in test case descriptor file with filters

You can select and run a subset of test cases from the test case descriptor file by using filters.

Filter	Description
<b>--type</b>	Filter test cases by test case type: <ul style="list-style-type: none"><li>• functional_positive</li><li>• functional_negative</li><li>• security</li><li>• performance</li><li>• reliability</li><li>• portability</li><li>• maintainability</li><li>• compliance</li><li>• user_experience</li></ul>
<b>--priority</b>	Filter test cases by test case priority: <ul style="list-style-type: none"><li>• P0</li><li>• P1</li><li>• P2</li></ul>
<b>--category</b>	Filter test cases by test case category <ul style="list-style-type: none"><li>• IVI</li><li>• Netbook</li><li>• TV</li><li>• Mobile</li></ul>
<b>--status</b>	Filter test case by test case status: <ul style="list-style-type: none"><li>• ready</li><li>• approved</li><li>• designed</li></ul>
<b>--suite</b>	Filter test case by test suite
<b>--set</b>	Filter test case by test set
<b>--id</b>	Filter test case by test case id
<b>--component</b>	Filter test case by test case component

Table 5-3 Filtering test cases

You can assign multiple values to each filter. For example, to select test cases of both P0 and P1 priority, run the following command:

```
testkit-lite --priority P0 P1 -f <test_descriptor_file>.xml
```

You can use a group of filters at one time, because Testkit-Lite performs the AND logic when selecting test cases. For example, to select test cases by both **priority** and **component** filters, run the following command:

```
testkit-lite --priority P0 P1 --component comp1 comp2 -f <test_descriptor_file>.xml
```

You can freely combine all those usages in one command to meet your test requirement. For example, to select and run test cases from two test case descriptor files by filters of **priority**, **component** and **status**, run the following command:

```
testkit-lite --priority P0 P1 --component comp1 comp2 --status ready -f
<test_descriptor_file_1>.xml <test_descriptor_file_2>.xml
```

## 7. Checking Test Reports

After Testkit-Lite completes executing all test cases successfully, you can obtain an .xml test report from `/opt/testkit-lite/latest`.

### .xml Test Report

```
<?xml version="1.0" encoding="UTF-8"?>
<?xml-stylesheet type="text/xsl" href="testresult.xsl"?>
<test_definition><environment device_id="Empty device_id" device_model="Empty
device_model" device_name="Empty device_name" firmware_version="Empty firmwa
re_version" host="Empty host" os_version="Empty os_version" resolution="Empty
resolution" screen_size="Empty screen_size"><other>Here is a String for testin
g</other></environment>
<summary test_plan_name="Empty test_plan_name"><start_at>2000-02-29_17_25_06<
/start_at><end_at>2000-02-29_17_32_43</end_at></summary>
  <suite name="webapi-w3c-perf-tests">
    <set name="WebWorker">
      <testcase component="WebAPI/W3C_Perf/WebWorker" execution_type="manual"
id="SharedWorker_in_iframe" priority="P3" purpose="check if shared worker i
n iframe Tests" result="PASS" status="approved" type="compliance">
        <description>
          <pre_condition />
          <post_condition />
          <steps>
            <step order="1">
              <step_desc>to check if shared worker in iframe Tests</step_desc
c>
              <expected>shared worker in iframe Tests</expected>
            </step>
          </steps>
          <test_script_entry test_script_expected_result="0" timeout="90">/op
t/webapi-w3c-perf-tests/WebWorker/SharedWorker_in_iframe.html</test_script_en
try>
        </description>
        <specs>
          <spec>
            <spec_assertion category="Tizen W3C API Specifications" interface
="SharedWorker" section="Performance" specification="Web Workers (Partial)" u
sage="true" />
            <spec_url>http://www.w3.org/TR/workers/</spec_url>
          </spec>
        </specs>
        <result_info><actual_result>PASS</actual_result><start /><end /><stdout
/></result_info></testcase>
      </set>
    </suite>
  </test_definition>
```

Figure 5-1 .xml test report