
Index

Note: Page numbers representing figures are in **bold**; tables are in *italics*.

- A-7A Corsair II, 139, 155, 163, 402, 403
 - velocity frequency response, 163, 164
- Accelerated flight, 210
- Acceleration:
 - inertial, 66
 - initial pitch, 262
 - normal, 262
 - perturbations, derivatives, 346–350
 - and rotary motion, 68
 - tangential, 68
- Ackeret theory, 330
- Adjustment:
 - elevator tab, 49
 - trim tab, 49
- Adverse roll, 179
- Adverse yaw, 181
- Aerobatic aircraft, 69–70
- Aerodynamic:
 - centre, aerofoil, 28
 - coefficients, dimensionless, 82
 - control derivatives, 371–377
 - control terms, 76
 - drag, 322
 - force, and moment components, 339
 - modelling, 320–336
 - limitations of, 335
 - operating conditions, 57
 - spring, 186
 - stability derivatives, 76
 - longitudinal, 337–350
 - terms, 75–76
- Aerofoil:
 - aerodynamic centre, 29
 - cambered, 28
 - centre of pressure, 28
- Aerotrim, 61–64
- Agility, 212
- Aileron, displacements, 27
- Aircraft:
 - classification, 252
 - dynamics, and manoeuvring, 222–223
- Aircraft behaviour:
 - like amplifier, 162
 - like attenuator, 162
- Aircraft body fixed axes, 13–18
- Aircraft geometry, 5
- Aircraft trim condition, 57–59
 - calculation
 - Aerotrim, 61–64
 - controls fixed static stability, 60–61
 - elevator to trim, 59–60
- Airframes:
 - configuration, trimmed equilibrium, 32
 - flexibility, 39
- Algorithms:
 - Fadeeva, 118
 - Generalised Eigenvalue Problem, 118
- American Military Specification
 - MIL-F-8785C, 250–251
- American Military Standard
 - MIL-STD-1797A, 251
- Angle of attack, 28–29
- Angular:
 - perturbation, 75
 - relationships, symmetric flight,
 - 16–17, **16**
 - velocities, 22–24
- Apparent inertia, 347
- Apparent mass, 347
- Approximations:
 - dutch roll mode, 192–193
 - roll mode, 189–190
 - short period mode, 147–150
 - spiral mode, 190–192
- Aspect ratio, 25
- Atmospheric disturbances, 4, 5
- Attitude, 13, 18
 - angles, 18
 - constant steady state pitch, 110
 - perturbation, 74
 - rate, 22
- Augmentation system, design, 280–283, **281**
- Augmented state equation, 132–133
- Automatic flight control system (**AFCS**) 2
- Autopilot, stability augmentation system,
 - 275

- Axes:
 - aerodynamic, 14
 - body, 13
 - choice of, 17–18
 - generalised body, 13
 - moving, 13, **14**
 - principal inertia, 72
 - stability, 14
 - transformations, 18–24
 - wind, 14, 17
- Axial force:
 - due to elevator, 372
 - due to normal velocity, 341
 - due to pitch rate, 344
 - due to rate of change of normal velocity, 348
 - due to velocity, 322
- Axial velocity:
 - normal force due to, 340
 - and pitching moment, 342
- Balance, 75, 212
- Bandwidth, 159
 - frequency, 162
 - speed of response, 163
- Banked turn, **23**
- Bode diagram, 159–165, **161**, 195
 - break frequency, 160
 - gain plot, 160
 - interpretation, 161–165
- Body axis system, 13–14
- Body rates, angular, **22**
- Boeing B-747, 200–201, **238**, 236
- British Civil Airworthiness Requirements, 249
- British Defence Standard
 - DEF-STAN 00-970, 213–214, 250, 251
- Busemann theory, 330
- Centre of gravity:
 - location, 26, **24**
 - trimmed equilibrium, 32
- Centre of pressure, 28
 - wings, 28
- Characteristic equation, 102, 144, 182–183, 227
 - augmented, 282, 284
 - Douglas DC-8, 193
 - lateral–directional, 191, 231
 - order of, 189
 - reduced order, 149, 188
 - solution of, 182–183, 227
- Chord:
 - geometric, 25
 - mean aerodynamic, 25
 - standard mean, 25
- Civil Aviation Authority, 249
- Civil transport aeroplane:
 - stability and control characteristics, 392–396
- Closed loop, 166
 - control law, 284
 - equations of motion, 284
 - system analysis, 283–287, **283**
- Cockpit design, 4
- Coefficient *E*, 233–234
- Command and stability augmentation system (CSAS), 279
- Command path control, 281
- Compressibility, 327–335
- Computers, 8–10
 - analytical, 8
 - flight control, 8–9
 - software, 9–10
- Concise lateral state equation, 91
- Control:
 - augmentation, 6
 - derivatives, 7
 - Lockheed F-104 Starfighter, 106
 - error signal, **281**, 282
 - force, to trim, 32, 49
 - gains, 275
 - law, 275
 - closed loop, 274
 - stability augmentation system (SAS), 275, 277, 314
 - and response, 5
 - and stability, 6
 - system, closed loop, 274
 - terms, aerodynamic, 76
- Control Anticipation Parameter (CAP), 258, 260–263
 - definition, 261
- Controllability, 226, 240
- Controlled motion, 241–242
- Controlled system:
 - multi-input, 312
 - single input, 312
- Controls, 27–28
 - aerodynamic, 27
 - engine, 27–28
 - fixed
 - dynamic stability, 170
 - manoeuvre margin, 150, 217

- manoeuvre point, 150, 217
- neutral point, 29, 44, **46**, 150
- stability, 44–47, 216–218
- stability margin, 52, 150
- free
 - dynamic stability, 170
 - neutral point, 48, 51, **52**
 - stability, 47–51, 218–221
- notation, 27–28
- in pitch, 27
- in roll, 27
- in yaw, 27
- Convair CV-880, 393
- Conversions, 425
- Convolution integral, 120
- Cooper–Harper rating, 255–256, **257** (table)
- Coordinate transformation, 448–449
 - body to wind axes, 448
 - wind to body axes, 448–449
- Coupling:
 - aerodynamic, 81, 186, 192
 - dynamic, 167, 178, 202
 - mode, 167
- Coursework studies, 390–404
- Cramer's rule, 99–101, 103, 105
- Critical damping, 236
- Damped harmonic motion, 429
- Damped natural frequency, 429
- Damping, 33, 139, 144
 - angle, 235
 - ratio, 107, 110–111, 266
 - requirements, dutch roll mode, 268
- Datum-path, earth axes, 13
- Decoupled equations of motion, 79–82
- Definitions:
 - Control Anticipation Parameter (CAP), 261
 - Mach cone, 328
 - Mach number, 328
 - pitch, 15
 - roll, 15
 - shock stall, 328
 - shock wave, 328
 - stability, 224
 - subsonic flight, 328
 - supersonic flight, 328
 - yaw, 15
- Degrees of freedom, 66, 72, 85, 186
- Demonstration of compliance, 250
 - test flights, 250
- Department of Defense, 249
- Derivatives:
 - acceleration perturbations, 346–350
 - aerodynamic, 7, 76, 321
 - control, 371–377
 - lateral–directional stability, 350–371
 - longitudinal stability, 337–350
 - aero-normalised, 83
 - axial force due to velocity, 322–323
 - calculation, 324
 - concise, 187, 397–398
 - control
 - lateral, 414, 418
 - longitudinal, 413, 446
 - dimensional, 419–420, 420–421
 - dimensionless, 83, 84, 88, 90, 233, 234
 - due to elevator, 371–373
 - estimation, 323–327
 - force, 339–342
 - force–acceleration, 443
 - force–rotary, 441–442
 - force–velocity, 439–440
 - high-performance aeroplanes, 347
 - lateral, McDonnell F-4C Phantom, 90
 - magnitudes, 126
 - measurement
 - flight test, 325–327
 - wind tunnel, 324–325
 - moment–acceleration, 443–444
 - moment–rotary, 442–443
 - moment–velocity, 440–441
 - pitch velocity perturbation, 343–346
 - quasi-static, 321–323
 - rate of roll, 360–365, **361**, **362**
 - semi-empirical, 324
 - due to sideslip, 351–360
 - stability
 - lateral, 414, 417
 - longitudinal, 413, 415
 - yaw rate, 365–371
- Design modification, 6
- Dihedral effect, **53**, 185, 264, 352
- Dimensionless:
 - equations of motion, 82–85
 - inertias, 85
- Direct lift control (DLC), 212
- Direction cosine matrix, 19, 20
- Directional:
 - static stability, 54–57
 - weathercock effect, 234
- Disturbance forces, and moments, 72–73

- Douglas DC-8, 176–182, 195
 - characteristic equation, 227
 - frequency response, 195–200
 - sideslip angle frequency, **198**
 - source data, 147–153
- Downwash, 347–348
 - field, 42, **348**
- Drag:
 - coefficient, 330
 - lateral, 351
 - due to lift, 331
 - and pitching moment
 - subsonic lift, 329–330
 - supersonic lift, 330–332
 - variation with Mach number, **334**
 - properties, and Mach number, 333
 - skin friction, 331
 - wave, 331
- Drag–velocity plot, **322**
- Dutch roll mode, 186–188, 198–199,
 - 201, 202, 204, 232,
 - 264–265, 310
 - approximations, 192–193
 - damping ratio, 195
 - damping requirements, 268
 - flight recording, **205**
 - frequency, 197
 - limiting frequency, 268
 - McDonnell F-4 Phantom, 269
 - oscillatory, 178, **187**
- Dynamic coupling, 167
- Dynamic models, short term, 241–249
- Dynamics:
 - lateral–directional, 174
 - longitudinal, 138
 - short term, 201, 241
- Early aviation, 1
- Earth axes, 12–13, **13**
 - datum-path, 13
- Effective aspect ratio, 331
- Eigenvalues:
 - and eigenvectors, 120–121
 - matrix, 121
- Eigenvectors:
 - and eigenvalues, 120–121
 - magnitude, 126
 - matrix, 181
- Elevator:
 - angle
 - to trim, 43
 - trimmed equilibrium, 32
 - and axial force, 72
 - deflection, 82
 - displacements, 27, 218
 - hinge moment, 47, 218
 - longitudinal response to, 138
 - and normal force, 372
 - and pitching moment, 373
 - pulse duration, 167
 - tab
 - adjustment, 49
 - angle to trim, 43, 49
 - transfer function, Lockheed F-104 Starfighter, 285–287
- Engine:
 - control, 27–28
 - dynamics, 131–132
- Equations:
 - aero-normalised, 83
 - characteristic, 102, 144, 182–183, 227
 - error method, 326
 - generalised force, 70–71
 - generalised moment, 71–72
 - height, 128–129
 - lateral–directional state, 189
 - longitudinal characteristic, 144, 147
 - longitudinal state, 129, 132
 - modal, 121, 122
 - of motion, 5, 7
 - in American normalised form, 91–95
 - closed loop, 284
 - decoupled, 79–82
 - dimensional decoupled, 82
 - dimensionless, 82–85
 - lateral asymmetric, 82
 - lateral–directional, 81–82, 174–175
 - linearised, 73–79
 - longitudinal, 79–81, 83
 - McDonnell Douglas DC-8 *see* Douglas DC-8
 - McDonnell Douglas F-4C Phantom, 88–90, 90–91, 312
 - open loop, 284
 - small perturbations, 77–79
 - solving, 98
 - Laplace transform, 98–99
 - state space form, 85–91
 - pitching moment, 40–43, 214–216
 - reduced order, 148
 - steady state, 78
- Equilibrium, trimmed, 15, 32–40
- Euler angles, 18, 18
- Experiments, dynamic, 325

- Failure transient, 276
- Federal Aviation Administration, 249, 250
- Feed forward path, 281
- Feedback path, 280–281
- Fin:
 - disturbance, 55
 - effect, 185
 - effectiveness, 56
 - moment arm, 26, **27**
 - volume ratio, 26, **27**, 359
- Final value theorem, 111, 181, 243, 262
- Fixed axes, aircraft body, 13–18
- Fixed neutral point:
 - locating, 334–335
 - and Mach number, 334–335
- Flat earth, 12, 13
- Flexibility, airframes, 39
- Flight control system (FCS), 274–276, 275
 - design, 279
 - electronic (EFCS), 274
 - mechanical elements, 278
- Flight critical stability augmentation *see* Flight control system
- Flight envelopes, 6, 7, 253–255, 254, **255**, **256**
 - extended, 240
 - large, 37
 - McDonnell-Douglas A-4D Skyhawk, 254–255, **255**, **256**
 - normal load factor, 255
 - operational, 253, 254
 - permissible, 253
 - service, 253
- Flight path angle, 13
- Flight phase, 252
 - categories, 252
- Flight test measurement, 325–337, **326**
- Flow effects, **38**
- Fly-by-wire:
 - aeroplane, 251
 - civil transport aeroplanes, 9
 - controls, 4, **4**
 - system, 278–280, **279**
 - reliability, 279
 - unstable airframes, 295
- Flying, and handling, 3–4, 165–167, 200–202, 240
- Flying qualities:
 - lateral-directional, 263–266
 - Level of, 252–253
 - longitudinal, 256–260
 - McDonnell F-4C Phantom, 269–271
 - requirements, 249–251
 - on s-plane, 266–269, **267**
 - specification, 247
- Force balance, 32, 34
- Frequency:
 - phugoid, 107, 146, 162, 259, 260
 - response, 158–165, 195–200
- Full state feedback, 312, **314**
- Functional visibility, 5, 241, 280
- Functions:
 - Dirac delta, 123
 - unit impulse, 123
- Gain:
 - logarithmic, 160
 - margin, 162
 - and phase, calculation, 160
 - plot, Bode diagram, 160
- Generalised:
 - force equations, 70–71
 - moment equations, 71–72
- Gradients, stable, 257–258, **258**
- Gravitational:
 - force components, 74–75
 - terms, 74–75
- Gyration, longitudinal radius of, 263
- Handley Page Jetstream, 167, **168**, 202, 203
 - elevator angle to trim, **46**
 - flight test, 45, 50–51, 167
 - phugoid response, 169
 - roll subsidence mode, 202, **203**
 - with tailplane, 40
 - wind tunnel experiments, 39, **40**
 - without tailplane, 40
- Handling, 200–202
 - and flying, 165–167, 240
 - long term, 241
 - pilot's perception, 241
 - qualities, 3–4, **3**, **4**
 - criteria, 247
 - short term, 241
- Harmonisation, of control power, 240
- Height response, 128
- High pass filter, 276
- Hinge moment to trim, 50, **51**
- Horizontal fuselage datum, 14, 59
- Incidence angle feedback to elevator, 298–299, **298**
- Incidence lag, 243, 247–249, **249**
 - on pitch response, **249**, 248

- Inertia:
 - dimensionless, 84, 85
 - moments and products, 71
 - transformation
 - body to wind, 445
 - wind to body, 446
- Inertial acceleration, 68
 - components, 66–70
- Initial value theorem, 111, 112
- Inner control loop, 278
- Instability, conditional, 232–233
- Integrated actuation, 278
- Jet engine, exhaust, 38, **38**
- Joint Aviation Requirements, 249
- Kalman filtering, 326
- Lanchester phugoid model, 151–152, 157
- Laplace transforms, 397
- Lateral:
 - dihedral effect, 234
 - directional equations of motion, 81–82
 - perturbation, sideslip angle, 130
 - relative density, 84
 - response transfer functions, 105–108
- Lateral–directional:
 - augmentation, 300–311
 - control, steady, 263
 - derivative coefficients, 382–384
 - equations of motion, 81–82
 - modes, 267–269, **268**
 - stability, 33, 263–265, 350–371
- Level:
 - of flying qualities, 252–253
- Lift coefficient, **39**, 50, 83
- Lift to drag ratio, 155
- Lifting properties, and Mach number, 333, **334**
- Limiting frequency, dutch roll mode, 268, 265
- Linear second order system, 427–430
- Linear system modelling, 197
- Linear time invariant (LTI) system, 85
- Ling-Temco-Vought A-7A Corsair II, 139–143
- Lockheed F-104 Starfighter, 106–108, 132–134, 291–293
 - control derivatives, 106
 - elevator transfer function, 285–287
 - lateral–directional handling qualities, 396–401
 - longitudinal equations of motion, 125–128
 - phugoid stability, 287
 - pitch attitude response, 106
 - pitch response, 106–108
 - root locus plot, 287–291
 - stability, dimensional, 106
- Locus departure angle, **455**
- Logarithmic gain, 160
- Longitudinal:
 - characteristic equation, 144
 - derivative coefficients, 378–382
 - equations of motion, 79–81
 - manoeuvrability, 216, 222–223, 260, **261**
 - modes, 266–267
 - damping ratios, 266, 267
 - motion, 232
 - reduced order, 242–244
 - reference geometry, **24**
 - relative density, 83, 214
 - response to elevator, 138
 - short period, thumb print criterion, 247, **248**
 - stability, 165
 - state equation, 87, 129, 132, 155
 - decoupled, 129
 - static stability, test for, 43
- Low pass system, 159
- LTV A7-A Corsair aircraft, 401–404
- McDonnell-Douglas A-4D Skyhawk, 294–300
 - flight envelopes, 254, **255**
 - stability mode characteristics, 295
- McDonnell F-4C Phantom, 80–81, 88–90, 312–316
 - aerodynamic variables, 90
 - control characteristics, 269–271
 - dutch roll mode characteristics, 271
 - equations of motion, 312
 - flying qualities, 269–271
 - lateral derivatives, 90–91
 - longitudinal equations of motion, 90
 - longitudinal stability modes, 313, 315
 - stability, 269–271
- Mach cone, definition, 328
- Mach number, 82
 - critical, definition, 328
 - definition, 328
 - and drag properties, 333, **334**
 - and fixed neutral point, 291–292
 - flow, 329
 - and lifting properties, 333, **334**
 - and pitching moment, 334, **334**

- Manoeuvrability:
 - controls free, 260
 - lateral-directional, 265–266
 - sideslip excursions, 227
 - longitudinal, 260, **261**
- Manoeuvre stability, 211, 211–212
 - analysis, 212
 - longitudinal
 - controls fixed, 216–218
 - controls free, 218–221
- Manoeuvring:
 - and aircraft dynamics, 222–223
 - classical theory, 211
 - controls fixed, 216–218
 - controls free, 218–221
 - longitudinal stability, 216–221
 - normal, 210
 - steady pull-up, 212–214
 - steady symmetric, 212
 - symmetric pull-up, **213**
 - tailplane incidence, 215
 - transcient upset, 211
- Mathcad*, software, 10, 61–62
- Mathematical models, 5–6
 - approximate, 6
 - high fidelity, 5
- MATLAB*, 109
 - software, 9
- Matrix, 85
 - direct, 86
 - eigenvalue, 120
 - eigenvector, 121
 - exponential, 119, 122
 - identity, 86
 - input, 85
 - mass, 87
 - modal, 121
 - output, 86
 - polynomial, 115
 - state, 85
 - state transition, 119
 - transfer function, 114–118
 - longitudinal, 115–116
 - lateral-directional, 116–118
 - zero, 86
- Maximum likelihood method, 326
- Measurement:
 - flight test, 325–327, **326**
 - wind tunnel, 324–325
- Minimum drag speed, 34, 143
- Minimum phase, 162
- Ministry of Defence, 249
- Modal:
 - equations, 122
 - matrix, 121
- Modelling, pitching behaviour, 41
- Modes:
 - coupling, 167, 183
 - dynamic stability, 144–147
 - excitation, 167–170, 202–206
 - faster, 237
 - slow, 237
- Moment components, and aerodynamic force, 339
- Moments, and disturbance forces, 72–73
- Morane Saulnier MS-760 Paris, 255, **256**
- Motion:
 - cues, 241–242
 - variables, **15**
- Multi-input, controlled system, 312
- Natural frequency, 110, 145, 146, 155, 222
- Navigation, trans-globe, 12
- Navion Aircraft Corporation, Navion/H, 244–247, **245**
- Negative feedback, 274, 302
- Newton:
 - second law, 66, 70
 - rotational form, 71
- Nichols chart, 159
- Non-linear system, 225
- Non-minimum phase, 113, 162, 164, 179
- Normal:
 - acceleration
 - equations, 112
 - feedback to elevator, 299–300, **299**
 - response at cg, **114**
 - force
 - axial velocity, 340
 - due to elevator, 372
 - due to normal velocity, 342
 - due to pitch rate, 345
 - due to rate of change of normal velocity, 349
 - load factor, 69–70, 213, 243
 - flight envelopes, 253–254
 - velocity
 - and axial force, 341, 348
 - and normal force, 342, 349
 - and pitching moment, 343, 350
- North American derivative coefficient
 - notation, 377–385

- North American X-15 hypersonic research
 - aeroplane:
 - stability augmentation, 391–392
- Northrop T-38 Talon, transfer function data, 301
- Nyquist diagram, 159
- Open loop, equations of motion, 284
- Optical signal transmission, 280
- Oscillations:
 - phugoid, 146–147, **151**, 168, 151–158
 - pilot induced, 162
 - short period pitching, 107, 110, 126, 127, 141, 144–145, **145**, 148, 167, **168**, 258–259, **259**
- Outer control loop, 274, 275
- Output response variable, 158
- Parameter identification, 325–327, **326**
 - disadvantages, 327
 - equation error method, 326
 - maximum likelihood method, 326
 - statistical regression method, 326
- PC MATLAB*, 125, 127, 141, 160, 181, 272, 390
 - root locus plot, 272, 288
 - software, 9
- Peak roll, to peak yaw ratio, 187–188
- Perturbations:
 - angular, 75
 - attitude, 74
 - height, 21
 - small, 7–8
 - about trim, 37, 73, 201
 - variables, 14–16, **15**, **15**, **16**
 - velocity, 339
- Phase margin, 162
- Phugoid, 107, 146–147
 - damping, 290, 296
 - frequency, 162, 296
 - Lanchester model, 151–152
 - mode, 167, 168
 - oscillation, 127, **151**
 - reduced order model, 152–155
 - stability, 140
 - Lockheed F-104 Starfighter, 285
- Pilot opinion, 240
 - rating, 255–256
- Pilot workload, 226, 253
- Pitch, 19
 - attitude, and elevator, 106, 110, 161, 295
 - damper, 292
 - definition, 15
 - motion cue, 249
 - rate, 22
 - and axial force, 344–345
 - feedback, **291**
 - to elevator, 295–297, **296**
 - and normal force, 345
 - and pitching moment, 346
 - response, Lockheed F-104 Starfighter, 106–108
 - stiffness, 300, 343
 - velocity perturbation, 343–346
- Pitching:
 - Behaviour, modelling, 41
 - moment, 29, 34, **35**, **37**, 38, **38**
 - due to axial velocity, 342–343
 - due to elevator, 373
 - equation, 40–43, **41**, 214–216
 - simple development, 41–43
 - due to normal velocity, 343
 - due to pitch rate, 346
 - due to rate of change of normal velocity, 350
- Pole placement method, 311–316
 - application, 311
- Power effects:
 - indirect, 37
 - stability, 37–39
- Power terms, 77
- Prandtl–Glauert rule, 329–330, 333
- Pressure drag, 331
- Program CC*, 89, 109, 163
 - root locus plot, 272
 - software, 10
- Q-feel system, 278
- Rapid incidence adjustment, 148
- Rate command, 246
- Rate of roll, derivatives, 360–365, **361**, **362**
- Reduced order:
 - longitudinal response, **157**
 - models, 147–158, 152–155, 188–195
 - lateral–directional, 189–190
 - longitudinal, 242–247
 - phugoid dynamics, 154, 156
- Redundancy, 277, 279
- Reference centres, 28–30, **29**
- Reference geometry, **23**, **25** 24–27, **24**, **27**
- Resolvent, 119
- Resonant frequencies, 159
- Response, 98–106 119–128
 - to aileron, 175, 177, **179**
 - and control, 5

- to controls, 108–112, 138–144, 174–183
- to elevator, 138, 139, 141, **142**
- homogeneous, 120
- impulse, 120, 123
- pitch rate, 156, **245**, 246, **293**
- to rudder, 179, **180**
- second-order-like, 244–247, **245**
- shapes, 124
- shaping, 281, 282
- steady state, 143
- step, 102–103 120, 123–124
- transfer functions, 99, 101–108, 138–139, 159, 188
 - acceleration, 112–114
 - elevator, 102, 159, 269
 - flight path angle, 131
 - height, 128–129
 - improper, 101, 113
 - incidence, 129–130
 - lateral, 105–106
 - lateral–directional, 105–106, 421–422, 423
 - Ling-Temco-Vought A-7A Corsair II, 139–143
 - longitudinal, 102–105, 175, 419–420, 422–423
 - pitch rate, 104
 - sideslip, 129–130
 - thrust, 105
 - unforced, 122–123
- Restoring moment, 36, 145, 184
- Retrimming, 45, 48
- Reynolds number, 82
- Ride quality, 166
- Roll, 19
 - attitude
 - feedback to aileron, 304–305, **305**
 - feedback to rudder, 309–310, **310**
 - definition, 15
 - mode, approximation, 183–184
 - rate, 22
 - and aileron, 102, 105, 108
 - feedback to aileron, 302, **303**
 - feedback to rudder, 307–308, **308**
 - and rolling moment, 317–319, 362–365
 - and side force, 360, 361
 - and yawing moment, 364–365
 - response
 - to aileron, 189, **194**
 - subsidence mode, 118, 178, 182, 183–184, 201, 202, 206, 263–264, **264**
 - flight recording, 202, **203**
 - Handley Page Jetstream, 172, **172**, 202, **203**
 - maximum value, 264
- Rolling moment:
 - coefficient, 54
 - equation, 189
 - negative, 54
 - due to roll rate, 362–365
 - due to sideslip, 352–359
 - due to yaw rate, 367–368, **368**
- Root locus plot, 287–291, **289**, 451–455
 - angle condition, 452
 - applications, 288
 - background, 451–452
 - constructing, 452–455
 - incidence angle feedback to elevator, 298–299, **298**
 - interpretation, 288
 - magnitude condition, 452
 - normal acceleration feedback to elevator, 299–300, **299**
 - pitch attitude feedback to elevator, 295, **296**
 - pitch rate feedback to elevator, 295–297, **296**
 - roll attitude feedback to aileron, 304–305, **305**
 - roll attitude feedback to rudder, 309–310, **310**
 - roll rate feedback to aileron, 302, **303**
 - roll rate feedback to rudder, 307–308, **308**
 - sideslip angle feedback to aileron, 301–302, **302**
 - sideslip angle feedback to rudder, 306–307, **307**
 - single variable feedback, 293
 - velocity feedback to elevator, 297–298, **297**
 - yaw attitude feedback to aileron, 305–306, **306**
 - yaw attitude feedback to rudder, 310, **311**
 - yaw rate feedback to aileron, 303–304, **304**
 - yaw rate feedback to rudder, 308–309, **309**
- Rotary motion:
 - and acceleration, **68**
 - and velocity, **67**
- Routh array, 228
- Routh–Hurwitz criterion:
 - application, 227–229
 - stability, 227–228

- Routh's discriminant, 232
- Rudder surface, displacements, 27
- s*-plane:
 - complex roots on, **235**
 - flying qualities on, 266–269
 - lateral-directional modes on, 267–269, **268**
 - longitudinal modes on, 266–267, **267**
 - root mapping on, 234–236
- Safety, 276–277
- Setting angle, tailplane, 40
- Shock expansion, 330
- Shock stall, definition, 328
- Shock wave, definition, 328
- Short period mode approximation, 147–150
- Short term, dynamic models:
 - controlled motion and motion cues, 241–242
 - longitudinal reduced order model, 242–247
 - thumb print criterion, 247
 - incidence log, 247–249
- Sideforce:
 - due to roll rate, 360
 - due to sideslip, 351
 - due to yaw rate, 365
- Side-stick controller, 279
- Sideslip, 62
 - angle, 20
 - angle feedback to aileron, 301–302, **302**
 - angle feedback to rudder, 306–307, **307**
 - disturbance, 54, **55**, 351
 - fin lift, **358**
 - lateral cross flow, 358
 - and rolling moment, 352–359
 - and sideforce, 351
 - swept wing in, 355
 - and yawing moment, 359–360
- Similarity transform, 121
- Single input, controlled system, 312
- Single variable feedback, root locus plot, 293
- Small perturbations, 7–8
 - equations of motion, 77–79
- Software:
 - 20-Sim*, 10
 - Mathcad*, 10
 - MATLAB*, 9
 - Program CC*, 10
 - Simulink*, 9–10
- Specification, flying qualities, 250
- Spherical coordinates, 12
- Spiral mode, 118, 178, 184–186, **185**, 201, 203, **204**, 264, **264**, **265**
 - approximations, 190–192
 - boundary, 268
 - stable, 188, 191
 - time constant, 191
 - unstable, 186, 203, 301
- Stability, 178, 240–241
 - aerodynamic, 7
 - augmentation, 6, 251, 290–291
 - control law, 292
 - longitudinal, 293–300, **294**
 - system, 240, 275, 277–280, **277**, **279**
 - autopilot, 275
 - control law, 276
 - role of, 278
- conditions for, 33–35, **34**
- and control, 6
- controls, 225–226
 - fixed, 43, 44–47, 216–218
 - margin, 44
 - static, 218–221
- fixed dynamic, 170, 205
- free, 41, 43, 47–50, 218–221
 - meaning, 47
- free dynamic, 170, 205
- free margin, 48
- definition, 224
- degree of, 35–36, **36**
- directional static, 54–57, 185
- dynamic modes, 144–147, 183–188
- estimating, 321
- graphical interpretation, 234–236, **235**
- lateral static, 53–54, 185, 352
- lateral-directional, 33, 202, 350–371
 - augmentation, 300–311, **301**
 - dynamic, 263–265
 - short period, 201
- longitudinal, 266–267
 - dynamic, 258–260
 - manoeuvring, 216–221
 - margins, **52**
 - modes, 167, 168
 - static, 44–53, 256–258
- manoeuvre, 211
- margin, 36, 44
- modes, 178, 237, **238**
- non-linear systems, 225
- phugoid, 146–147, 259, 287, 295
- power effects, 37–39, **38**

- quartic, 231–234
 - definition, 231
- relative sensitivity, 290
- reversal, **39**
- Routh–Hurwitz criterion, 227–228
- short period mode, 259
- static
 - and dynamic, 225
 - longitudinal, 43, 44–53
 - margins, 258
 - subsonic, 36–37
 - supersonic, 37
 - variable, 247
 - variation in, 36–40
- Stable system, *430*
- State space method, 114–128
 - Laplace transform, 119
- State space model augmentation, 128–134
- State transition matrix, 119
- Static stability, longitudinal, 43, 44–53
- Statistical regression, 326
- Stick displacement, 218
- Stick force per g, 221
 - measuring, 221
- Subsonic flight, definition, 328
- Subsonic lift, drag and pitching moment, 329–330
- Supersonic flight, definition, 328
- Supersonic lift, drag and pitching moment, 330–332
- Symmetric flight, angular relationships, 16–17, **16**
- Symmetry, of airframe, 32
- System analysis, closed loop, 283–287, **283**
- System realization, 132
- Tailplane:
 - lift coefficient, 42, 215, 371
 - moment arm, 26
 - setting angle, 42
 - volume ratio, 26, 345
 - weathercock tendency, 145
- Test flights:
 - demonstration of compliance, 250
 - variable stability, 247
- Throttle lever angle, 77, 132
- Thrust, 77
 - line, **37**
 - trimmed equilibrium, 33
 - variation, 82
- Thumb print criterion, 247
- longitudinal short period, 247, **248**
- Time response, 98, 110, **111**
- Transfer function, 197, 282
 - angular pitch acceleration, 262
 - matrix, 94–95, 114–115
 - lateral–directional, 116
 - Lockheed C-5A, 116–118
 - longitudinal, 115–116
 - open loop, 295
- Transformation:
 - angular rates, 230
 - angular velocities, 22–24
 - coordinate, 448–449
 - body to wind axes, 438, 444, 448
 - wind to body axes, 448–449
 - force and moment, 438
 - inertia, 449
 - linear, 19–21
- Transonic flight, 258, 328
- Trim:
 - change of, 257
 - function, electrical, 279
 - hands-off, 47, 48, 49
 - state, 5, 32
 - tabs, 32
 - adjustment, 49
 - elevator, 32
- Trimmability, 32
- Trimmed aircraft, 57, 167, 202
- Trimmed equilibrium, 15, 32–40
 - airframe configuration, 32
 - centre of gravity, 32
 - elevator angle, 33
 - flight path angle, 32, 33
 - lateral–directional, 33
 - longitudinal, 33
 - stable, 34
 - thrust, 33
 - weight, 32
- Units, 425
- Variable stability, 36–39
 - test flights, 247
- Velocity:
 - eigenfunctions, 124, 126
 - feedback to elevator, 291–293, **292**
 - linear disturbance, 73
 - perturbations, moment derivatives, 342–343
 - resolution, **20**
 - and rotary motion, **67**
 - tangential, 67

- Virtual inertia, 347
- Virtual mass, 347
- Wake, 38
- Washout filter, 276, 400
- Weathercock, 54, **56**, 145
- Weight, trimmed equilibrium, 32
- Wind axes, perturbed, **338**
- Wind tunnel:
 - experiments, Handley Page Jetstream, **40**
 - measurement, 324–325
 - accuracy, 325
- Wing:
 - area, 24
 - aspect ratio, 25
 - centre of pressure, 28
 - mean aerodynamic chord (mac), 25
 - standard mean chord (smc), 25
 - sweep back, 39
- Yaw, 19
 - adverse, 181
 - angle, 18, 22
 - attitude
 - feedback to aileron, 305–306, **306**
 - feedback to rudder, 310, **311**
 - definition, 15
 - rate, 22
 - derivatives, 365–371
 - feedback to aileron, 303–304, **304**
 - feedback to rudder, 303–309, **309**
 - fin incidence, **366**
 - and rolling moment, 366–369,
367, 368
 - and sideforce, 365
 - and yawing moment, 369–371
- Yawing moment:
 - due to aileron, 375
 - about cg, 369
 - coefficient, 52, **53**, 54
 - due to roll rate, 364–365
 - due to rudder, 377
 - due to sideslip, 359–360
 - due to yaw rate, 369–371