

Insightly

# Web API - Documentation

*Version 1.0 Preliminary documentation.*

## Introduction

The **Insightly Web API** enables developers to access some of the core primitives of **Insightly** including Tasks, Contacts, Organizations, Opportunities, Projects, Emails, Events and other settings.

The resources are accessible via the following URL: [https://api.insight.ly/v1/{resource\\_name}](https://api.insight.ly/v1/{resource_name})

The supported format of returned data is JSON and XML.

The **Insightly Web API** supports limited OData queries. The current support of query string parameters is \$top and \$skip.

## Authentication

The **Insightly Web API** requires HTTP Basic Authentication to access Insightly resources.

The user API key should be encrypted with base64, as per the HTTP specification.

## Limits

If a request is to return over 10,000 records, only the parent objects will be returned in the JSON result and not any child objects (eg: addresses, phone numbers, links etc). This is mostly applicable to large contact lists, organization lists, or task lists. To retrieve the child objects, request each individual record from the server.

## Quick Reference of all API Paths

/Contacts?\$top=50&\$skip=500

/Contacts/:id

/Contacts/:id/image

/Contacts/:id/Notes - Get Only

/Contacts/:id/Emails - Get Only

/Countries - List of Country Names for Addresses

/Currencies - List of Supported Currencies by Insightly

/Tasks

/Tasks/:id

/TaskCategories

/TaskLinks

/Tags/Contacts

/Tags/Organisations

/Tags/Opportunities

/Tags/Projects

/Tags/Emails

/Organisations

/Organisations/:id

/Organisations/:id/image

/Organisations/:id/Notes - Get Only

/Organisations/:id/Emails - Get Only

/Opportunities

/Opportunities/:id

/Opportunities/:id/image

/Opportunities/:id/Notes - Get Only

/Opportunities/:id/Emails - Get Only

/OpportunityCategories

/OpportunityStateChange/:id - PUT only with new State Reason in body.

/OpportunityStateReasons (GET only - list of all reasons)

/Projects

/Projects/:id

/Projects/:id/image

/Projects/:id/Notes -Get Only

/Projects/:id/Emails -Get Only

/ProjectCategories

/Emails  
/Emails?Brief=True -- Does not get body extract or file attachments or note links  
/Emails/:id -- Get and Delete Only  
/Emails/:id/comments  
/EmailLinks

/Events  
/Events/:id

/Notes -- Gets Only first 100 characters of each Note Body  
/Notes?Brief=True -- Does not get body or file attachments or note links  
/Notes/:id -- Full body  
/Notes/:id/comments  
/NoteLinks

/Comments/:id -

/FileAttachments/:id  
/FileCategories

/Teams  
/Teams/:id

/TeamMembers  
/TeamMembers/:id

/Pipelines  
/Pipelines/:id

/Users (Read Only)  
/Users/:id

/Relationships (Read Only)

/PipelineStages  
/PipelineStages/:id

/CustomFields  
/CustomFields/:id

## Resources

Resource	Description
<a href="#">GET /tasks</a>	Return list of tasks.
<a href="#">GET /tasks/:id</a>	Return a single task, specified by an id parameter.
<a href="#">POST /tasks</a>	Add a new task.
<a href="#">PUT /tasks/</a>	Update a selected task.
<a href="#">DELETE /tasks/:id</a>	Delete a task by specifying an id parameter.
<a href="#">GET /tasks/:id/comments</a>	Return list of comments for a task, specified by a task id parameter.
<a href="#">POST /tasks/:id/comments</a>	Post a new comment for a task, specified by an id parameter. <b>Note:</b> we are supporting only XML content-type for posting new comment. See Comment section for more information. Uploading file attachment is not supported yet.

## Task properties

Property	Type	Description / Remarks
TASK_ID	Long	This ID will be generated when you add a new task.
TITLE	String	Required.
CATEGORY_ID	Long	Link to a task category.
DUE_DATE	Date	
COMPLETED	Boolean	
PROJECT_ID	Long	Link to a project.
DETAILS	String	
STATUS	String	Values: "NOT STARTED", "IN PROGRESS", "WAITING", "COMPLETED", "DEFERRED".
PRIORITY	Short	
PERCENT_COMPLETE	Short	
START_DATE	Date	
ASSIGNED_BY_USER_ID	Integer	
PARENT_TASK_ID	Long	
RECURRENCE	String	Values: "EVERYDAY", "EVERY WEEKDAY", "EVERY WEEK", "EVERY 2 WEEKS", "EVERY MONTH", "EVERY 2 MONTHS", "EVERY 3 MONTHS", "EVERY 6 MONTHS", "EVERY YEAR"
RESPONSIBLE_USER_ID	Integer	Required.
OWNER_USER_ID	Integer	Required.
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set

### Sample 1 - GET (Content-Type: JSON)

```
{
  "TASK_ID":54321,
  "TITLE":"Task JSON",
  "CATEGORY_ID":null,
  "DUE_DATE":"2014-07-25 12:00:00",
  "COMPLETED_DATE_UTC":"2011-10-14 07:42:00",
  "PUBLICLY_VISIBLE":true,
  "COMPLETED":true,
  "PROJECT_ID":null,
  "DETAILS":null,
  "STATUS":"COMPLETED",
  "PRIORITY":2,
  "PERCENT_COMPLETE":100,
  "START_DATE":"2011-10-14 12:00:00",
  "ASSIGNED_BY_USER_ID":null,
  "PARENT_TASK_ID":null,
  "RECURRENCE":null,
  "RESPONSIBLE_USER_ID":12345,
  "OWNER_USER_ID":12345,
  "DATE_CREATED_UTC":"2011-04-23 12:40:00",
  "DATE_UPDATED_UTC":"2011-10-14 07:41:32"
}
```

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Task xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TASK_ID>54321</TASK_ID>
  <TITLE>Task XML</TITLE>
  <CATEGORY_ID xsi:nil="true"/>
  <DUE_DATE>2014-07-25T00:00:00</DUE_DATE>
  <COMPLETED_DATE_UTC>2011-10-14T07:42:00</COMPLETED_DATE_UTC>
  <PUBLICLY_VISIBLE>true</PUBLICLY_VISIBLE>
  <COMPLETED>true</COMPLETED>
  <PROJECT_ID xsi:nil="true"/>
  <STATUS>COMPLETED</STATUS>
  <PRIORITY>2</PRIORITY>
  <PERCENT_COMPLETE>100</PERCENT_COMPLETE>
  <START_DATE>2011-10-14T00:00:00</START_DATE>
  <ASSIGNED_BY_USER_ID xsi:nil="true"/>
  <PARENT_TASK_ID xsi:nil="true"/>
  <RESPONSIBLE_USER_ID>12345</RESPONSIBLE_USER_ID>
  <OWNER_USER_ID>1345</OWNER_USER_ID>
  <DATE_CREATED_UTC>2011-04-23T12:40:00</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-10-14T07:41:32.277</DATE_UPDATED_UTC>
</Task>
```

---

## Contacts

### Resources

Resource	Description
GET /contacts	Return list of contacts.
GET /contacts/:id	Return a single contact, specified by an id parameter.
GET /contacts/:id/image	Return contact image
POST /contacts	Add a new contact.
POST /contacts/:id/image/:filename	Change contact image. A file name with its extension is required in order to upload a new image.
PUT /contacts	Update a selected contact.
PUT /contacts/:id/image/:filename	Change contact image. A file name with its extension is required in order to upload a new image.
DELETE /contacts/:id	Delete a contact by specifying an id parameter.
DELETE /contact/:id/image	Delete contact image

### Contact properties

Property	Type	Description / Remarks
CONTACT_ID	Long	This ID will be generated when you add a new contact.
SALUTATION	String	
FIRST_NAME	String	
LAST_NAME	String	
BACKGROUND	String	
CONTACT_FIELD_1	Object	Field link to Custom Field. Up to 10 fields.
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
ADDRESSES	List of Address	
CONTACT_INFO	List of Contact Info	
VISIBLE_TO	String	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS". Required.
VISIBLE_TEAM_ID	Long	

### Address properties

Property	Type	Description / Remarks
ADDRESS_ID	Long	This ID will be generated when you add a new contact address.
ADDRESS_TYPE	String	Values: "Work", "Home", "Other". Required.
STREET	String	
CITY	String	
STATE	String	
POSTCODE	String	
COUNTRY	String	

## Contact Info properties

Property	Type	Description / Remarks
CONTACT_INFO_ID	Long	This ID will be generated when you add a new contact info.
TYPE	String	Values: "EMAIL", "PHONE", "WEBSITE". Required.
SUBTYPE	String	
LABEL	String	Required.
DETAIL	String	Required.

### Sample 1 - GET (Content-Type: JSON)

```
{
  "CONTACT_ID":1234567,
  "SALUTATION":null,
  "FIRST_NAME":"John",
  "LAST_NAME":"Doe",
  "BACKGROUND":null,
  "CONTACT_FIELD_1":null,
  "CONTACT_FIELD_2":null,
  "CONTACT_FIELD_3":null,
  "CONTACT_FIELD_4":null,
  "CONTACT_FIELD_5":null,
  "CONTACT_FIELD_6":null,
  "CONTACT_FIELD_7":null,
  "CONTACT_FIELD_8":null,
  "CONTACT_FIELD_9":null,
  "CONTACT_FIELD_10":null,
  "DATE_CREATED_UTC":"2012-03-13 05:19:10",
  "DATE_UPDATED_UTC":"2012-03-13 05:19:10",
  "ADDRESSES":[
  ],
  "CONTACTINFOS":[
    {
      "CONTACT_INFO_ID":7894561,
      "TYPE":"EMAIL",
      "SUBTYPE":null,
      "LABEL":"Home",
      "DETAIL":"johndoe@insight.ly"
    }
  ],
  "VISIBLE_TO":"EVERYONE",
  "VISIBLE_TEAM_ID":null
}
```



## Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Contact xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <INSTANCE_ID>54321</INSTANCE_ID>
  <CONTACT_ID>1234567</CONTACT_ID>
  <FIRST_NAME>John</FIRST_NAME>
  <LAST_NAME>Doe</LAST_NAME>
  <DATE_CREATED_UTC>2011-03-31T13:44:00</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-03-31T14:12:00</DATE_UPDATED_UTC>
  <ContactInfos>


---


    <CONTACT_INFO>    <CONTACT_INFO_ID>7894561</CONTACT_INFO_ID>
      <TYPE>EMAIL</TYPE>
      <LABEL>Work</LABEL>
      <DETAIL>johndoe@insight.ly</DETAIL>
    </CONTACT_INFO>


---


  </ContactInfos> <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
</Contact>
```

---

## Organizations

### Resources

Resource	Description
<a href="#">GET /organisations</a>	Return list of organizations.
<a href="#">GET /organisations/:id</a>	Return a single organization, specified by an id parameter.
<a href="#">GET /organisations/:id/image</a>	Return organization image
<a href="#">POST /organisations</a>	Add a new organization.
<a href="#">POST /organisations/:id/image/:filename</a>	Change organization image. A file name with its extension is required in order to upload a new image.
<a href="#">PUT /organisations</a>	Update a selected organization.
<a href="#">PUT /organisations/:id/image/:filename</a>	Change organization image. A file name with its extension is required in order to upload a new image.
<a href="#">DELETE /organisations/:id</a>	Delete an organization by specifying an id parameter.
<a href="#">DELETE /organisations/:id/image</a>	Delete organization image

### Organization properties

Property	Type	Description / Remarks
ORGANISATION_ID	Long	This ID will be generated when you add a new organization.
ORGANISATION_NAME	String	Required.
BACKGROUND	String	
ORGANISATION_FIELD_1	Object	Field link to Custom Field. Up to 10 fields.
OWNER_USER_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
ADDRESSES	List of Address	
CONTACTINFOS	List of Contact Info	
VISIBLE_TO	String	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS". Required.
VISIBLE_TEAM_ID	Long	

### Address properties

Property	Type	Description / Remarks
ADDRESS_ID	Long	This ID will be generated when you add new organization address.
ADDRESS_TYPE	String	Values: "Work", "Home", "Other". Required.
STREET	String	
CITY	String	
STATE	String	
POSTCODE	String	
COUNTRY	String	

## Contact Info properties

Property	Type	Description / Remarks
CONTACT_INFO_ID	Long	This ID will be generated when you add new organization contact info.
TYPE	String	Values: "EMAIL", "PHONE", "WEBSITE". Required.
SUBTYPE	String	
LABEL	String	Required.
DETAIL	String	Required.

### Sample 1 - GET (Content-Type: JSON)

```
{
  "ORGANISATION_ID":4567891,
  "ORGANISATION_NAME":"OrganizationTest.com",
  "BACKGROUND":"Organization Description"
  "ORGANISATION_FIELD_1":"Organisation Field No 1",
  "ORGANISATION_FIELD_2":"2011-10-28 12:00:00",
  "ORGANISATION_FIELD_3":"f3frfrewq",
  "ORGANISATION_FIELD_4":null,
  "ORGANISATION_FIELD_5":null,
  "ORGANISATION_FIELD_6":null,
  "ORGANISATION_FIELD_7":null,
  "ORGANISATION_FIELD_8":null,
  "ORGANISATION_FIELD_9":null,
  "ORGANISATION_FIELD_10":null,
  "OWNER_USER_ID":12345,
  "DATE_CREATED_UTC":"2011-07-15 02:20:00",
  "DATE_UPDATED_UTC":"2011-10-10 08:51:19",
  "VISIBLE_TO":"EVERYONE",
  "VISIBLE_TEAM_ID":null
}
```

### Sample 2 – GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Organisation xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <ORGANISATION_ID>7894561</ORGANISATION_ID>
  <ORGANISATION_NAME>OrganizationTest.com</ORGANISATION_NAME>
  <BACKGROUND>Organization Description</BACKGROUND>
  <ORGANISATION_FIELD_1 xsi:type="xsd:string">Organization Field No 1</ORGANISATION_FIELD_1>
  <ORGANISATION_FIELD_2 xsi:type="xsd:dateTime">2011-10-28T00:00:00</ORGANISATION_FIELD_2>
  <ORGANISATION_FIELD_3 xsi:type="xsd:string">f3frfrewq</ORGANISATION_FIELD_3>
  <OWNER_USER_ID>12345</OWNER_USER_ID>
  <DATE_CREATED_UTC>2011-07-15T02:20:00</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-10-10T08:51:19.527</DATE_UPDATED_UTC>
  <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
</Organisation>
```

## Resources

Resource	Description
<a href="#">GET /opportunities</a>	Return list of opportunities.
<a href="#">GET /opportunities/:id</a>	Return a single opportunity, specified by an id parameter.
<a href="#">GET /opportunities/:id/image</a>	Return opportunity image
<a href="#">POST /opportunities/:id/image/:filename</a>	Change opportunity image. A file name with its extension is required in order to upload a new image.
<a href="#">PUT /opportunities/:id/image/:filename</a>	Change opportunity image. A file name with its extension is required in order to upload a new image.
<a href="#">POST /opportunities</a>	Add a new opportunity.
<a href="#">PUT /opportunities</a>	Update a selected opportunity.
<a href="#">DELETE /opportunities/:id</a>	Delete an opportunity by specifying an id parameter.
<a href="#">DELETE /opportunities/:id/image</a>	Delete opportunity image

## Opportunity properties

Property	Type	Description / Remarks
OPPORTUNITY_ID	Long	This ID will be generated when you add a new opportunity.
OPPORTUNITY_NAME	String	Required.
OPPORTUNITY_DETAILS	String	
PROBABILITY	Short	
BID_CURRENCY	String	Value fromCurrencies list
BID_AMOUNT	Long	
BID_TYPE	String	Values: "Fixed Bid", "Per Year", "Per Month", "Per Week", "Per Day", "Per Hour"
BID_DURATION	Integer	
FORECAST_CLOSE_DATE	Date	
ACTUAL_CLOSE_DATE	Date	
CATEGORY_ID	Long	Link to an opportunity category.
PIPELINE_ID	Long	Link to a pipeline.
STAGE_ID	Long	Link to a pipeline stage.
OPPORTUNITY_STATE	String	Values: "Open", "Abandoned", "Suspended", "Lost", "Won". Required.
OPPORTUNITY_FIELD_1	Object	Field link to Custom Field. Up to 10 fields.
RESPONSIBLE_USER_ID	Integer	
OWNER_USER_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
VISIBLE_TO	String	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS". Required.
VISIBLE_TEAM_ID	Long	

### Sample 1 - GET (Content-Type: JSON)

```
{
  "OPPORTUNITY_ID":13245,
  "OPPORTUNITY_NAME":"2",
  "OPPORTUNITY_DETAILS":null,
  "PROBABILITY":50,
  "BID_CURRENCY":"MYR",
  "BID_AMOUNT":56000,
  "BID_TYPE":"Fixed Bid",
  "BID_DURATION":null,
  "FORECAST_CLOSE_DATE":"2011-08-01 12:00:00",
  "ACTUAL_CLOSE_DATE":null,
  "CATEGORY_ID":45612,
  "PIPELINE_ID":null,
  "STAGE_ID":null,
  "OPPORTUNITY_STATE":"WON",
  "OPPORTUNITY_FIELD_1":"11-015",
  "OPPORTUNITY_FIELD_2":null,
  "OPPORTUNITY_FIELD_3":null,
  "OPPORTUNITY_FIELD_4":null,
  "OPPORTUNITY_FIELD_5":null,
  "OPPORTUNITY_FIELD_6":null,
  "OPPORTUNITY_FIELD_7":null,
  "OPPORTUNITY_FIELD_8":null,
  "OPPORTUNITY_FIELD_9":null,
  "OPPORTUNITY_FIELD_10":null,
  "RESPONSIBLE_USER_ID":45612,
  "OWNER_USER_ID":45612,
  "DATE_CREATED_UTC":"2011-11-04 02:41:35",
  "DATE_UPDATED_UTC":"2011-11-04 02:41:35",
  "VISIBLE_TO":"EVERYONE",
  "VISIBLE_TEAM_ID":null
}
```

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Opportunity xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <OPPORTUNITY_ID>12345</OPPORTUNITY_ID>
  <OPPORTUNITY_NAME>2</OPPORTUNITY_NAME>
  <PROBABILITY>50</PROBABILITY>
  <BID_CURRENCY>MYR</BID_CURRENCY>
  <BID_AMOUNT>56000</BID_AMOUNT>
  <BID_TYPE>Fixed Bid</BID_TYPE>
  <BID_DURATION xsi:nil="true"/>
  <FORECAST_CLOSE_DATE>2011-08-01T00:00:00</FORECAST_CLOSE_DATE>
  <ACTUAL_CLOSE_DATE xsi:nil="true"/>
  <CATEGORY_ID>12345</CATEGORY_ID>
  <PIPELINE_ID xsi:nil="true"/>
  <STAGE_ID xsi:nil="true"/>
  <OPPORTUNITY_STATE>WON</OPPORTUNITY_STATE>
  <OPPORTUNITY_FIELD_1 xsi:type="xsd:string">11-015</OPPORTUNITY_FIELD_1>
  <RESPONSIBLE_USER_ID>45612</RESPONSIBLE_USER_ID>
  <OWNER_USER_ID>45612</OWNER_USER_ID>
  <DATE_CREATED_UTC>2011-11-04T14:41:35.353</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-11-04T14:41:35.353</DATE_UPDATED_UTC>
  <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
</Opportunity>
```

## Resources

Resource	Description
GET /projects	Return list of projects.
GET /projects/:id	Return a single project, specified by an id parameter.
GET /projects/:id/image	Return project image
POST /projects	Add a new project.
POST /projects/:id/image/:filename	Change project image. A file name with its extension is required in order to upload a new image.
PUT /projects	Update a selected project.
PUT /projects/:id/image/:filename	Change project image. A file name with its extension is required in order to upload a new image.
DELETE /projects/:id	Delete a project by specifying an id parameter.
DELETE /projects/:id/image	Delete project image

## Project properties

Property	Type	Description / Remarks
PROJECT_ID	Long	This ID will be generated when you add a new project.
PROJECT_NAME	String	Required.
STATUS	String	Required.
PROJECT_DETAILS	Short	
OPPORTUNITY_ID	String	Link to an opportunity.
STARTED_DATE	Long	
COMPLETED_DATE	String	
PROJECT_FIELD_1	Integer	Field link to Custom Field. Up to 10 fields.
RESPONSIBLE_USER_ID	String	
OWNER_USER_ID	Short	
DATE_CREATED_UTC	Long	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Long	This UTC DateTime is automatically generated and cannot be set
CATEGORY_ID	Long	Link to a project category.
PIPELINE_ID	String	Link to a pipeline.
STAGE_ID	Object	Link to a pipeline stage.
VISIBLE_TO	Integer	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS". Required.
VISIBLE_TEAM_ID	Integer	

### Sample 1 - GET (Content-Type: JSON)

```
{
  "PROJECT_ID":12345,
  "PROJECT_NAME":"Test Project",
  "STATUS":"NOT STARTED",
  "PROJECT_DETAILS":null,
  "OPPORTUNITY_ID":null,
  "STARTED_DATE":null,
  "COMPLETED_DATE":null,
  "PROJECT_FIELD_1":null,
  "PROJECT_FIELD_2":null,
  "PROJECT_FIELD_3":null,
  "PROJECT_FIELD_4":null,
  "PROJECT_FIELD_5":null,
  "PROJECT_FIELD_6":null,
  "PROJECT_FIELD_7":null,
  "PROJECT_FIELD_8":null,
  "PROJECT_FIELD_9":null,
  "PROJECT_FIELD_10":null,
  "RESPONSIBLE_USER_ID":45612,
  "OWNER_USER_ID":21354,
  "DATE_CREATED_UTC":"2011-10-13 04:11:39",
  "DATE_UPDATED_UTC":"2012-03-06 02:10:01",
  "CATEGORY_ID":null,
  "PIPELINE_ID":null,
  "STAGE_ID":null,
  "VISIBLE_TO":"EVERYONE",
  "VISIBLE_TEAM_ID":null
}
```

---

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Project xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <PROJECT_ID>45612</PROJECT_ID>
  <PROJECT_NAME>Test Project</PROJECT_NAME>
  <STATUS>NOT STARTED</STATUS>
  <OPPORTUNITY_ID xsi:nil="true"/>
  <STARTED_DATE xsi:nil="true"/>
  <COMPLETED_DATE xsi:nil="true"/>
  <RESPONSIBLE_USER_ID>12345</RESPONSIBLE_USER_ID>
  <OWNER_USER_ID>12365</OWNER_USER_ID>
  <DATE_CREATED_UTC>2011-10-13T04:11:39.243</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2012-03-06T02:10:01.343</DATE_UPDATED_UTC>
  <CATEGORY_ID xsi:nil="true"/>
  <PIPELINE_ID xsi:nil="true"/>
  <STAGE_ID xsi:nil="true"/>
  <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
</Project>
```

---

## Emails

### Resources

Resource	Description
<a href="#">GET /emails</a>	Return list of active emails. The body displayed is a preview of the mail body.
<a href="#">GET /emails/:id</a>	Return a single email, specified by an id parameter.
<a href="#">DELETE /emails/:id</a>	Delete an email by specifying an id parameter.
<a href="#">GET /emails/:id/comments</a>	Return list of comments for an email, specified by an id parameter.
<a href="#">POST /emails/:id/comments</a>	Post a new comment for an email, specified by an id parameter. <b>Note:</b> we are supporting only XML content-type for posting new comment. See Comment section for more information. Uploading file attachment is not supported yet.

### Email properties

Property	Type	Description / Remarks
EMAIL_ID	Long	
EMAIL_MESSAGE_ID	String	Link to a Gmail message id.
EMAIL_IN_REPLY_TO	String	
EMAIL_DATE_UC	Date	This UTC DateTime is automatically generated and cannot be set
EMAIL_FROM	String	
SUBJECT	String	
BODY	String	
FORMAT	String	
SIZE	Long	
OWNER_USER_ID	Integer	
VISIBLE_TO	String	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS".
VISIBLE_TEAM_ID	Long	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
FILE_ATTACHMENTS	List of File Attachment	



### Sample 1 - GET (Content-Type: JSON)

```
{
  "EMAIL_ID":456123,
  "GMAIL_MESSAGE_ID":"13448a1da66326aa96",
  "EMAIL_IN_REPLY_TO":null,
  "EMAIL_DATE_UTC":"2011-09-05 08:08:44",
  "EMAIL_FROM":"no-reply@insight.ly",
  "SUBJECT":"Insightly presentation",
  "BODY":" Insightly Body.",
  "FORMAT":"HTML",
  "SIZE":1726744,
  "VISIBLE_TO":"EVERYONE",
  "OWNER_USER_ID":12345,
  "VISIBLE_TEAM_ID":null,
  "DATE_CREATED_UTC":"2011-09-06 02:15:00",
  "FILE_ATTACHMENTS":[
    {
      "FILE_ID":4561232,
      "FILE_NAME":"Insightly_Presentation.ppt",
      "CONTENT_TYPE":"application/vnd.ms-powerpoint",
      "FILE_SIZE":1260032,
      "FILE_CATEGORY_ID":null,
      "OWNER_USER_ID":12457,
      "DATE_CREATED_UTC":"2011-09-06 02:15:00",
      "DATE_UPDATED_UTC":"2011-09-06 02:15:00",
      "URL":"/api/fileattachments/4561232"
    }
  ]
}
```

---

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Email xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <EMAIL_ID>456123</EMAIL_ID>
  <GMAIL_MESSAGE_ID>13448a1da66326aa96</GMAIL_MESSAGE_ID>
  <EMAIL_DATE_UTC>2011-09-05T08:08:44</EMAIL_DATE_UTC>
  <EMAIL_FROM>no-reply@insight.ly</EMAIL_FROM>
  <SUBJECT>Insightly presentation</SUBJECT>
  <BODY>Insightly Body.<BODY>
  <FORMAT>HTML</FORMAT>
  <SIZE>1726744</SIZE>
  <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <OWNER_USER_ID>12345</OWNER_USER_ID>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
  <DATE_CREATED_UTC>2011-09-06T02:15:00</DATE_CREATED_UTC>
  <FILE_ATTACHMENTS>
    <FileAttachment>
      <FILE_ID>4561232</FILE_ID>
      <FILE_NAME>Insightly_Presentation.ppt</FILE_NAME>
      <CONTENT_TYPE>application/vnd.ms-powerpoint</CONTENT_TYPE>
      <FILE_SIZE>1260032</FILE_SIZE>
      <FILE_CATEGORY_ID xsi:nil="true"/>
      <OWNER_USER_ID>12345</OWNER_USER_ID>
      <DATE_CREATED_UTC>2011-09-06T02:15:00</DATE_CREATED_UTC>
      <DATE_UPDATED_UTC>2011-09-06T02:15:00</DATE_UPDATED_UTC>
      <URL>/api/fileattachments/4561232</URL>
    </FileAttachment>
  </FILE_ATTACHMENTS>
</Email>
```

---

## Events

### Resources

Resource	Description
<a href="#">GET /events</a>	Return list of events.
<a href="#">GET /events/:id</a>	Return a single event, specified by an id parameter.
<a href="#">POST /events</a>	Add a new event.
<a href="#">PUT /events</a>	Update a selected event.
<a href="#">DELETE /events/:id</a>	Delete an event by specifying an id parameter.

### Event properties

Property	Type	Description / Remarks
EVENT_ID	Long	This ID will be generated when you add a new event.
TITLE	String	
LOCATION	String	
DETAILS	String	
START_DATE_UTC	Date	Required.
END_DATE_UTC	Date	Required.
ALL_DAY	Boolean	Required.
PUBLICLY_VISIBLE	Boolean	
REMINDER_SETTING	String	
REMINDER_DATE_UTC	Date	
REMINDER_SENT	Boolean	Required.
OWNER_USER_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set

### Sample 1 - GET (Content-Type: JSON)

```
{
  "EVENT_ID":41242,
  "TITLE":"Event test",
  "LOCATION":"Test",
  "DETAILS":"Details of Event Here",
  "START_DATE_UTC":"2011-12-04 10:00:00",
  "END_DATE_UTC":"2011-12-04 11:00:00",
  "ALL_DAY":false,
  "PUBLICLY_VISIBLE":true,
  "REMINDER_SETTING":null,
  "REMINDER_DATE_UTC":null,
  "REMINDER_SENT":false,
  "OWNER_USER_ID":12345,
  "DATE_CREATED_UTC":"2011-12-04 09:17:21",
  "DATE_UPDATED_UTC":"2011-12-04 09:17:21"
}
```

## Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<CalendarEvent xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <EVENT_ID>41242</EVENT_ID>
  <TITLE>Event test</TITLE>
  <LOCATION>Test</LOCATION>
  <DETAILS>Details of Event Here</DETAILS>
  <START_DATE_UTC>2011-12-04T10:00:00</START_DATE_UTC>
  <END_DATE_UTC>2011-12-04T11:00:00</END_DATE_UTC>
  <ALL_DAY>false</ALL_DAY>
  <PUBLICLY_VISIBLE>true</PUBLICLY_VISIBLE>
  <REMINDER_DATE_UTC xsi:nil="true"/>
  <REMINDER_SENT>false</REMINDER_SENT>
  <OWNER_USER_ID>12345</OWNER_USER_ID>
  <DATE_CREATED_UTC>2011-12-04T09:17:21.14</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-12-04T09:17:21.14</DATE_UPDATED_UTC>
</CalendarEvent>
```

---

## Resources

Resource	Description
<a href="#">GET /notes</a>	Return list of notes.
<a href="#">GET /notes/:id</a>	Return a single note, specified by an id parameter.
<a href="#">POST /notes</a>	Add a new note. Uploading file attachment is not supported yet.
<a href="#">PUT /notes</a>	Update a selected note.
<a href="#">DELETE /notes/:id</a>	Delete a note by specifying an id parameter.
<a href="#">GET /notes/:id/comments</a>	Return list of comments for a note, specified by an id parameter.
<a href="#">POST /notes/:id/comments</a>	Post a new comment for a note, specified by an id parameter. <b>Note:</b> we are supporting only XML content-type for posting new comment. See Comment section for more information

## Note properties

Property	Type	Description / Remarks
NOTE_ID	Long	This ID will be generated when you add a new note.
TITLE	String	Required.
BODY	String	
LINK_SUBJECT_ID	Short	Link to a subject.
LINK_SUBJECT_TYPE	String	Link to a subject type.
OWNER_USER_ID	Long	
VISIBLE_TO	String	Values: "EVERYONE", "OWNER", "TEAM", "INDIVIDUALS". Required.
VISIBLE_TEAM_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
FILE_ATTACHMENTS		

### Sample 1 - GET (Content-Type: JSON)

```
{
  "NOTE_ID":123456,
  "TITLE":"test note",
  "BODY":"body test note",
  "LINK_SUBJECT_ID":124562,
  "LINK_SUBJECT_TYPE":"ORGANISATION",
  "VISIBLE_TO":"EVERYONE",
  "OWNER_USER_ID":12345,
  "VISIBLE_TEAM_ID":null,
  "DATE_CREATED_UTC":"2012-03-12 09:09:15",
  "DATE_UPDATED_UTC":"2012-03-12 09:09:15",
  "FILE_ATTACHMENTS":[
    {
      "FILE_ID":456512,
      "FILE_NAME":"notes.txt",
      "CONTENT_TYPE":"text/plain",
      "FILE_SIZE":200,
      "FILE_CATEGORY_ID":null,
      "OWNER_USER_ID":12345,
      "DATE_CREATED_UTC":"2012-03-12 09:09:16",
      "DATE_UPDATED_UTC":"2012-03-12 09:09:16",
      "URL":"/api/fileattachments/456512"
    }
  ]
}
```

---

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Note xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <NOTE_ID>123456</NOTE_ID>
  <TITLE>test note</TITLE>
  <BODY>body test note</BODY>
  <LINK_SUBJECT_ID>124562</LINK_SUBJECT_ID>
  <LINK_SUBJECT_TYPE>ORGANISATION</LINK_SUBJECT_TYPE>
  <VISIBLE_TO>EVERYONE</VISIBLE_TO>
  <OWNER_USER_ID>12345</OWNER_USER_ID>
  <VISIBLE_TEAM_ID xsi:nil="true"/>
  <DATE_CREATED_UTC>2012-03-12T21:09:15.503</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2012-03-12T21:09:15.503</DATE_UPDATED_UTC>
  <FILE_ATTACHMENTS>
    <FileAttachment>
      <FILE_ID>456512</FILE_ID>
      <FILE_NAME>notes.txt</FILE_NAME>
      <CONTENT_TYPE>text/plain</CONTENT_TYPE>
      <FILE_SIZE>200</FILE_SIZE>
      <FILE_CATEGORY_ID xsi:nil="true"/>
      <OWNER_USER_ID>12345</OWNER_USER_ID>
      <DATE_CREATED_UTC>2012-03-12T21:09:16.027</DATE_CREATED_UTC>
      <DATE_UPDATED_UTC>2012-03-12T21:09:16.027</DATE_UPDATED_UTC>
      <URL>/api/fileattachments/456512</URL>
    </FileAttachment>
  </FILE_ATTACHMENTS>
</Note>
```

---

## Comments

### Post a comment

Posting a comment is accessible directly via the following resources: Tasks, Emails and Notes. See related section for more information.

### Resources

Resource	Description
<a href="#">GET /comments/:id</a>	Return a single comment, specified by an id parameter.
<a href="#">PUT /comments</a>	Update a selected comment.
<a href="#">DELETE /comments/:id</a>	Delete a comment by specifying an id parameter.

### Comment properties

Property	Type	Description / Remarks
COMMENT_ID	Long	This ID will be generated when you add a new comment.
BODY	String	
OWNER_USER_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
FILE_ATTACHMENTS	List of File Attachment	

### Sample 1 - GET (Content-Type: JSON)

```
{
  "COMMENT_ID":132456,
  "BODY":"test comment",
  "OWNER_USER_ID":12345,
  "DATE_CREATED_UTC":"2012-03-09 11:59:19",
  "DATE_UPDATED_UTC":"2012-03-09 11:59:19",
  "FILE_ATTACHMENTS":[
    {
      "FILE_ID":4567899,
      "FILE_NAME":"test.docx",
      "CONTENT_TYPE":"application/vnd.openxmlformats-officedocument.wordprocessingml.document",
      "FILE_SIZE":12489,
      "FILE_CATEGORY_ID":null,
      "OWNER_USER_ID":12345,
      "DATE_CREATED_UTC":"2012-03-09 11:59:20",
      "DATE_UPDATED_UTC":"2012-03-09 11:59:20",
      "URL":"/api/fileattachments/4567899"
    }
  ]
}
```

## Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Comment xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <COMMENT_ID>132456</COMMENT_ID>
  <BODY>test comment</BODY>
  <OWNER_USER_ID>12345</OWNER_USER_ID>
  <DATE_CREATED_UTC>2012-03-09T23:59:19.503</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2012-03-09T23:59:19.503</DATE_UPDATED_UTC>
  <FILE_ATTACHMENTS>
    <FileAttachment>
      <FILE_ID>4567899</FILE_ID>
      <FILE_NAME>test.docx</FILE_NAME>
      <CONTENT_TYPE>application/vnd.openxmlformats-officedocument.wordprocessingml.document</CONTENT_TYPE>
      <FILE_SIZE>12489</FILE_SIZE>
      <FILE_CATEGORY_ID xsi:nil="true"/>
      <OWNER_USER_ID>12345</OWNER_USER_ID>
      <DATE_CREATED_UTC>2012-03-09T23:59:20.093</DATE_CREATED_UTC>
      <DATE_UPDATED_UTC>2012-03-09T23:59:20.093</DATE_UPDATED_UTC>
      <URL>/api/fileattachments/4567899</URL>
    </FileAttachment>
  </FILE_ATTACHMENTS>
</Comment>
```

---

## File Attachments

### Resources

Resource	Description
<a href="#">GET /fileattachments/:id</a>	Download a file attachment, specified by an id parameter.

### Custom Field properties

Property	Type	Description / Remarks
FILE_ID	Long	
FILE_NAME	String	
CONTENT_TYPE	String	
FILE_SIZE	Long	
FILE_CATEGORY_ID	Long	Link to a file category
OWNER_USER_ID	Integer	
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
URL	String	



## Categories

### Types

Name	URL
Task	<a href="/task_categories">/task_categories</a>
Project	<a href="/project_categories">/project_categories</a>
Opportunity	<a href="/opportunity_categories">/opportunity_categories</a>
File	<a href="/file_categories">/file_categories</a>

### Resources

Resource	Description
<a href="#">GET /{type_categories}</a>	Return list of active categories.
<a href="#">GET /{type_categories} /:id</a>	Return a single category, specified by an id parameter.
<a href="#">POST /{type_categories}</a>	Add a new category. Only accessible for administrator users.
<a href="#">PUT /{type_categories}</a>	Update a selected category. Only accessible for administrator users.
<a href="#">DELETE {type_categories}/:id</a>	Delete a category by specifying an id parameter. Only accessible for administrator users.

### Category properties

Property	Type	Description / Remarks
CATEGORY_ID	Long	This ID will be generated when you add a new category.
CATEGORY_NAME	String	Required.
ACTIVE	Boolean	
BACKGROUND_COLOR	String	Hexadecimal format. (Without #). Required.

#### Sample 1 - GET (Content-Type: JSON)

```
{
  "CATEGORY_ID":125699,
  "CATEGORY_NAME":"Meeting",
  "ACTIVE":true,
  "BACKGROUND_COLOR":"9f4681"
}
```

#### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Category xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <CATEGORY_ID>125699</CATEGORY_ID>
  <CATEGORY_NAME>Meeting</CATEGORY_NAME>
  <ACTIVE>true</ACTIVE>
  <BACKGROUND_COLOR>9f4681</BACKGROUND_COLOR>
</Category>
```

## Resources

Resource	Description
<a href="#">GET /teams</a>	Return list of teams.
<a href="#">GET /teams/:id</a>	Return a single opportunity, specified by an id parameter.
<a href="#">POST /teams</a>	Add a new opportunity. Only accessible for administrator users.
<a href="#">PUT /teams/</a>	Update a selected opportunity. Only accessible for administrator users.
<a href="#">DELETE /teams/:id</a>	Delete an opportunity by specifying an id parameter. Only accessible for administrator users.

## Team properties

Property	Type	Description / Remarks
TEAM_ID	Long	This ID will be generated when you add a new team.
TEAM_NAME	String	
ANONYMOUS_TEAM	Boolean	Used internally when specifying individuals that have permission to a record
DATE_CREATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set
DATE_UPDATED_UTC	Date	This UTC DateTime is automatically generated and cannot be set

### Sample 1 - GET (Content-Type: JSON)

```
{
  "TEAM_ID":99132,
  "TEAM_NAME":null,
  "ANONYMOUS_TEAM":true,
  "DATE_CREATED_UTC":"2011-05-09 04:46:00",
  "DATE_UPDATED_UTC":"2011-05-09 04:46:00"
}
```

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Team xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <TEAM_ID>99132</TEAM_ID>
  <ANONYMOUS_TEAM>true</ANONYMOUS_TEAM>
  <DATE_CREATED_UTC>2011-05-09T04:46:00</DATE_CREATED_UTC>
  <DATE_UPDATED_UTC>2011-05-09T04:46:00</DATE_UPDATED_UTC>
</Team>
```

## Team Members

### Resources

Resource	Description
GET /team_members	Return list of team members.
GET /team_members/:id	Return a single team member, specified by an id parameter.
POST /team_members	Add a new member to a team. Only accessible for administrator users.
PUT /team_members	Update a selected team member. Only accessible for administrator users.
DELETE /team_members/:id	Remove a member from a team by specifying an id parameter. Only accessible for administrator users.

### Team properties

Property	Type	Description / Remarks
PERMISSION_ID	Long	This ID will be generated when you add a new team member.
TEAM_ID	Long	Required.
MEMBER_USER_ID	Integer	Required.
MEMBER_TEAM_ID	Integer	

### Sample 1 - GET (Content-Type: JSON)

```
{  
  "PERMISSION_ID":199123,  
  "TEAM_ID":9999,  
  "MEMBER_USER_ID":13245,  
  "MEMBER_TEAM_ID":null  
}
```

---

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>  
<Team_Member xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://  
www.w3.org/2001/XMLSchema">  
  <PERMISSION_ID>199123</PERMISSION_ID>  
  <TEAM_ID>9999</TEAM_ID>  
  <MEMBER_USER_ID>13245</MEMBER_USER_ID>  
  <MEMBER_TEAM_ID xsi:nil="true"/>  
</Team_Member>
```

---

## Pipelines

### Resources

Resource	Description
GET /pipelines	Return list of pipelines.
GET /pipelines/:id	Return a single pipeline, specified by an id parameter.

### Pipeline properties

Property	Type	Description / Remarks
PIPELINE_ID	Long	This ID will be generated when you add a new pipeline.
PIPELINE_NAME	String	Required.
FOR_OPPORTUNITIES	Boolean	Required.
FOR_PROJECTS	Boolean	Required.
OWNER_USER_ID	Integer	

### Sample 1 - GET (Content-Type: JSON)

```
{
  "PIPELINE_ID":1234,
  "PIPELINE_NAME":"Presentation",
  "FOR_OPPORTUNITIES":true,
  "FOR_PROJECTS":true,
  "OWNER_USER_ID":13423
}
```

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Pipeline xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <PIPELINE_ID>1234</PIPELINE_ID>
  <PIPELINE_NAME>Presentation</PIPELINE_NAME>
  <FOR_OPPORTUNITIES>true</FOR_OPPORTUNITIES>
  <FOR_PROJECTS>true</FOR_PROJECTS>
  <OWNER_USER_ID>13423</OWNER_USER_ID>
</Pipeline>
```

## Pipeline Stages

### Resources

Resource	Description
<a href="#">GET /pipeline_stages</a>	Return list of pipeline stages.
<a href="#">GET /pipeline_stages/:id</a>	Return a single pipeline stage, specified by an id parameter.

### Pipeline properties

Property	Type	Description / Remarks
STAGE_ID	Long	This ID will be generated when you add a new stage.
PIPELINE_ID	Long	
STAGE_NAME	String	Required.
STAGE_ORDER	Integer	
OWNER_USER_ID	Integer	

### Sample 1 - GET (Content-Type: JSON)

```
{
  "PIPELINE_ID":1234,
  "STAGE_ID":13245,
  "STAGE_NAME":"Outline slides",
  "STAGE_ORDER":1,
  "OWNER_USER_ID":78945
}
```

### Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<Pipeline_Stage xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <PIPELINE_ID>1234</PIPELINE_ID>
  <STAGE_ID>13245</STAGE_ID>
  <STAGE_NAME>Outline slides</STAGE_NAME>
  <STAGE_ORDER>1</STAGE_ORDER>
  <OWNER_USER_ID>78945</OWNER_USER_ID>
</Pipeline_Stage>
```

## Custom Fields

### Resources

Resource	Description
<a href="#">GET /customfields</a>	Return list of custom fields.
<a href="#">GET /customfields/:id</a>	Return a single custom field, specified by an id parameter.

### Custom Field properties

Property	Type	Description / Remarks
CUSTOM_FIELD_ID	String	Required.
ORDER_ID	Long	Required.
FIELD_FOR	String	Required.
FIELD_NAME	String	Required.
FIELD_TYPE	String	Required.
FIELD_HELP_TEXT	String	
CUSTOM_FIELD_OPTIONS	List of Custom Field Option	

### Custom Field Option properties

Property	Type	Description / Remarks
OPTION_ID	Integer	
OPTION_VALUE	String	Required.
OPTION_DEFAULT	Boolean	Required.

### Sample 1 - GET (Content-Type: JSON)

```
{
  "CUSTOM_FIELD_ID": "CONTACT_FIELD_1",
  "ORDER_ID": 37,
  "FIELD_FOR": "CONTACT",
  "FIELD_NAME": "User Field 1",
  "FIELD_TYPE": "TEXT",
  "FIELD_HELP_TEXT": null,
  "CUSTOM_FIELD_OPTIONS": []
}
```

## Sample 2 - GET (Content-Type: XML)

```
<?xml version="1.0" encoding="utf-8"?>
<CustomField xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://
www.w3.org/2001/XMLSchema">
  <CUSTOM_FIELD_ID>CONTACT_FIELD_1</CUSTOM_FIELD_ID>
  <ORDER_ID>37</ORDER_ID>
  <FIELD_FOR>CONTACT</FIELD_FOR>
  <FIELD_NAME>User Field 1</FIELD_NAME>
  <FIELD_TYPE>TEXT</FIELD_TYPE>
  <CUSTOM_FIELD_OPTIONS/>
</CustomField>
```

---