

1 Unix utilities and shell builtins

1.1 File system

- **cat** concatenates and prints files:
 - A shows all nonprinting characters,
 - b numbers nonempty output lines,
 - n numbers all output lines,
 - s suppresses repeated empty output lines.
- **tac** does the same in reverse.
- ★ **rev** reverses lines characterwise.
- **nl** numbers lines of files:
 - s adds „string” after line number,
 - w uses „number” columns for line numbers.
- **chgrp** changes group ownership.
- **chmod** changes permissions of a file:
 - ugo permissions of the owner, group, other/all users,
 - + = adds, removes or sets selected file mode bits,
 - rwX selects file mode bits: read/write/execute (4/2/1).
- **chown** changes owner of a file.
- ★ **umask** sets file mode creation mask.
- **touch** changes file timestamps:
 - a only the access time,
 - m only the modification time,
 - t uses custom stamp instead of current time,
 - c does not create files.
- **shasum** prints or checks SHA message digests:
 - a algorithm: 1, 224, 256, 384, 512, 512224 or 512256,
 - b reads in binary mode,
 - c checks SHA sums read from the „files”.
- See also **cksum** (CRC checksums) and **md5sum**.
- **wc** prints newline, word and byte counts (1wc):
 - m prints the character counts,
 - L prints the maximum display width.
- **dd** converts and copies a file:
 - if = reads from a file instead of standard input,
 - of = writes to a file instead of standard output,
 - bs = up to „bytes” bytes at a time,
 - count = copies only „n” input blocks.
- **cp** copies files and directories:
 - b makes a backup of each existing destination file,
 - f removes an existing destination file if needed,
 - i prompts before overwrite,
 - n does not overwrite existing files,
 - L always follows symlinks in „source”,
 - P never follows symlinks in „source”,
 - r copies directories recursively,
 - s makes symbolic links instead,
 - L hard links files instead,
 - t copies all „source” arguments into „directory”,
 - T treats „destination” as a normal file,
 - u copies only newer source files,
 - v explains what is being done.
- **mv** moves (renames) files:
 - b makes a backup of each existing destination file,
 - i prompts before overwriting,
 - f does not prompt before overwriting,
 - n does not overwrite existing destination files.
 - t moves all „source” arguments into „directory”,
 - T treats „destination” as a normal file,
 - u moves only newer source files,
 - v explains what is being done.
- **rm** removes files or directories:
 - f never prompts,
 - i always prompts,
 - r removes directories and their contents.
- See also **rmdir** (directories removal).
- **mkdir** makes directories (mkdir -p: with parents as needed, no error if existing).
- **df** reports file system disk space usage:
 - h prints size in powers of 1024,
 - i list inode information instead of block usage,
 - t limits listing to file systems of given type,
 - x limits listing to file systems not of given type,
 - T prints file systems types.
- **du** estimates file space usage:
 - a writes counts for all files, not just directories,
 - c produces a grand total,
 - d the depth at which summing should occur,
 - h prints sizes in human readable format,
 - s displays only a total,
 - X excludes files that match pattern.
- ★ **file** determines file type.
- ★ **fsck** checks and repairs a Linux filesystem:
 - a automatically repairs (without any question!),
 - t specifies the type(s) of filesystem to be checked,
 - A tries to check all filesystems in one run,
 - M skips mounted filesystems,
 - R skips the root filesystem.
- **ln** makes hard links between files (not directories; only in the same file system):
 - s makes symbolic links instead.
- **ls** lists directory contents:
 - a does not ignore entries starting with dot,
 - F appends indicator to entries,
 - h prints human readable sizes,
 - i prints the index number of each file,
 - l prints permissions, number of hard links, owner, group, size, last-modified date as well,
 - r reverses order while sorting,
 - R lists subdirectories recursively,
 - S sorts by file size (largest first),
 - t sorts by modification time (newest first),
- ★ **tree** folds lower case to upper case characters.
- ★ **mount** mounts a filesystem.
- **pwd** prints name of current directory.
- ★ **tar** stores and extracts files from a disk archive:
 - c creates a new archive,
 - x extracts files,
 - t lists the contents of an archive,
 - v verbosely lists files processed,
 - j bzip2 compression,
 - z uses zip/gzip (gz compression),
 - f uses archive file or device (???),
 - k does not replace existing files when extracting.
- **tee** duplicates pipe content:
 - a appends to the given files, does not overwrite,
 - i ignores interrupts.
- ★ Missing: **cmp**, **fuser**, **pax**, **type**.

1.2 Processes

- ★ **chroot** changes the root directory for the current running process and their children.
- ★ **at** schedules commands to be executed once, at a particular time in the future: it accepts times of the form HH:MM, midnight, noon or teatime; MMDD [CC] YY, MM/DD / [CC] YY, DD .MM . [CC] YY or [CC] YY-MM-DD (the specification of a date must follow the specification of the time of day). You can also give times like now + 3 hours.
- ★ **bg** resumes suspended jobs in the background.
- ★ **fg** resumes suspended jobs in the foreground.
- ★ **jobs** lists the active jobs.
- ★ **command &** runs command in the background.
- ★ **cron**: a daemon executing scheduled commands.
- ★ **crontab** maintain individual users' crontab files.
- ★ **kill** sends a TERM signal to a process.
- ★ **killall** kills processes by name.
- ★ **ps** reports a snapshot of the current processes:
 - e selects all processes,
 - f does full-format listing,
 - C selects processes by command name,
 - p selects processes by PID,
 - u selects processes by EUID or name.
- ★ **pstree** displays a tree of processes.

- ★ **nice** changes process priority.
- ★ **pgrep**, **pgkill** looks up or signals processes based on name and other attributes.
- ★ **time** runs programs and summarizes system resource usage.
- ★ **top** displays linux processes.

1.3 User environment

- ★ **clear** clears the terminal screen.
- ★ **env** runs a program in a modified environment.
- ★ **exit** terminates the calling process.
- ★ **finger** looks up user information.
- ★ **history** displays the history list.
- ★ **mesg** displays messages from other users.
- ★ **passwd** changes user password:
 - d deletes an account's password (makes it empty),
 - e expires an account's password,
 - n sets minimum days to change password,
 - w sets warning days before password expire,
 - x sets the maximum number of days a password remains valid.
- ★ **su** changes user ID or becomes superuser.
- ★ **sudo** executes a command as another user.
- ★ **uname** prints system information:
 - a all information, in the following order:
 - s the kernel name,
 - n the network node hostname,
 - r the kernel release,
 - v the kernel version,
 - m the machine hardware name,
 - p the processor type,
 - i the hardware platform,
 - o the operating system.
- ★ **uptime**: how long has the system been running?
- ★ **wall** writes a message to all users,
- ★ **write** sends a message to another user.
- ★ **who** shows who is logged on,
- ★ **w** does the same and shows what they are doing,
- ★ **whoami** prints effective userid.

1.4 Text processing

- ★ **awk** is a pattern scanning / processing language, a pseudo-C interpreter. Sample code:

```
1 BEGIN {print "- Start -"}
2 /word/ {print NR " " $1, $2}
3 END {print "- End -"}
```

Examples of conditions:

- (a) /word[0+9]+/: regular expressions
- (b) !/word[0+9]+/: regexes inverted
- (c) ~ and !~: matches / does not match.
- (d) length(\$0) > 18.

Important variables:

- (a) FS: field separator (tab),
- (b) OFS: output field separator,
- (c) RS: record separator (new line),
- (d) NR: number of the current record,
- (e) NF: number of fields in the current record.

- ★ **grep** prints lines matching a pattern:
 - c prints a count of matching lines instead,
 - e uses a „regexp” pattern,
 - f obtains patterns from a file,
 - i ignores case distinctions,
 - v inverts the sense of matching,
 - w selects only lines containing matches that form whole words,
 - n prints line numbers as well,
 - A prints „num” lines of trailing content,
 - B prints „num” lines of leading content,
 - C prints „num” lines of both contents,
 - R ???,
- ★ **sed**: a stream editor filtering/transforming text.

- **comm** compares two sorted files line by line.
- **shuf** generates random permutations:
 - e treats each „arg” as an input line,
 - i treats each number .. through .. as an input line,
 - n outputs at most „count” lines,
 - r output lines can be repeated (with -n).
- **sort** sorts lines of text files:
 - c checks for sorted input,
 - f folds lower case to upper case characters,
 - g compares general numerical values,
 - h compares human readable numbers,
 - k sorts via a key,
 - n compares string numerical values,
 - r reverses the results,
 - s stabilizes the sort.
- **tsort** performs topological sort.
- **uniq** omits repeated lines:
 - c prefixes lines by the number of occurrences,
 - d only prints duplicate lines, one for each group,
 - f avoids comparing first fields,
 - i ignores differences in case,
 - s avoids comparing first characters,
 - w compares no more than *n* characters.
- **cut** prints selected parts of lines:
 - complement complements the selection,
 - c selects only these characters,
 - d uses „delim” instead of Tab for field delimiter,
 - f selects only these fields,
 - s does not print lines not containing delimiters.
- **join** joins lines of two files on a common field.
- **paste** merges lines of files.
 - d reuses characters from „list” instead of tabs,
 - s pastes one file at a time, not in parallel.
- **tr** translates or deletes characters:
 - c uses the complement of „set1”,
 - d deletes characters, does not translate,
 - s replaces each sequence of a repeated character that is listed in the last specified „set” with a single occurrence of that character.
- ★ **diff** compares files line by line:
 - y outputs in two columns,
 - i ignores case differences,
 - w ignores all white space.
- ★ **fmt** is a simple optimal text formatter,
- ★ **fold** wraps each line to fit in specified width.
- **head** outputs the first (last) part of files:
 - c the first „num” bytes,
 - n the first „num” lines,
- **tail** the last „num” bytes:
 - c the last „num” bytes,
 - n the last „num” lines,

- f outputs appended data as the file grows,
- s sleeps for „n” seconds between iterations.
- **split** splits a file into pieces:
 - a generates suffixes of length „n” (default 2),
 - b puts „size” bytes per output file,
 - d uses numeric (not alphabetic) suffixes,
 - l puts „number” lines/records per output file,
 - n generates „chunks” output files.
- See also: **csplit**.
- ★ **less** is opposite of **more**.
- ★ **more** is a file perusal filter for crt viewing.
- ★ **xargs** builds and executes command lines from standard input.
- ★ **yes** outputs a string repeatedly until killed.

1.5 Shell builtins

- ★ **alias** allows a string to be substituted for a word.
- ★ **cd** changes the shell working directory:
 - to the previous directory.
- ★ **echo*** displays a line of text:
 - e enables interpretation of backslash escapes,
 - n does not output the trailing newline.
- ★ **test** checks file types and compares values.
- ★ **unset** unsets a shell variable, removing it from memory and the shell's exported environment.
- ★ **wait** waits for process to change state.

1.6 Networking

- ★ **curl** transfers a URL.
- ★ **dig** is a DNS lookup utility (domain information groper).
 - x simplified reverse lookups.
- ★ **host** is a DNS lookup utility.
- ★ **ifconfig** configures a network interface.
- ★ **inetd** is a super-server daemon that provides Internet services.
- ★ **netcat**: arbitrary TCP and UDP connections and listens.
- ★ **netstat** prints network connections, routing tables, interface statistics, masquerade connections, and multicast memberships.
- ★ **nslookup** queries Internet name servers interactively.
- ★ **ping** tests the reachability of a host on an IP network by sending ICMP ECHO_REQUEST:
 - c stops after sending „count” packets,
 - n numeric output only, avoids to lookup symbolic names for host addresses.
- ★ **rdate** sets the system's date from a remote host.
- ★ **rlogin** is an OpenSSH SSH client (remote login program)

- ★ **route** shows and manipulates the IP routing table.
- ★ **ssh** is an OpenSSH SSH client (remote login program).
 - D (bind address)
 - p (port)
 - X (X11 forwarding)
- ★ **traceroute** is a computer network diagnostic tool for displaying the route (path) and measuring transit delays of
- ★ **wget** is a non-interactive network downloader.
 - A, R specifies lists of file suffixes or patterns (when wildcard characters appear) to accept or reject,
 - b goes to background immediately after startup,
 - c continues getting a partially-downloaded file,
 - m turns on options suitable for mirroring: infinite recursion and time-stamping,
 - np does not ever ascend to the parent directory when retrieving recursively,
 - U identifies as „agent-string” to the HTTP server.
 - w waits the specified number of seconds between the retrievals (see also -random-wait).

1.7 Searching

- ★ **find** searches for files in a directory hierarchy.
- ★ **locate** finds files by names.
- ★ **whatis** displays one-line manual page description.
- ★ **whereis** locates the binary, source, and manual page files for a command.

1.8 Miscellaneous

- ★ **bc** is an arbitrary precision calculator language.
 1. **echo 'obase=16;255' | bc** prints FF,
 2. **echo 'ibase=2;obase=A;10' | bc** prints 2,
 3. **scale=10 (after bc -l)** sets working precision.
- ★ **dc** is a reverse-polish desk calculator. One of the oldest Unix utilities, predating even the invention of the C programming language.
- ★ **cal**, **ncal** displays a calendar.
 - e displays date of Easter,
 - j displays Julian days,
 - m displays the specified month,
 - w prints the numbers of the weeks,
 - y displays a calendar for the specified year,
 - 3 displays the previous, current and next month.
- ★ **date** prints or set the system date and time.
- ★ **lp** prints files.
- ★ **od** dumps files in octal.
- ★ **sleep** delays for a specified amount of time.
- ★ **true**, **false** does nothing, (un)successfully.