PAGE 159 | PIN R


PIN RECEPTACLES

FOR .015" - .020" DIAMETER PINS (#11 CONTACT) AND .015" - .022" DIAMETER PINS (#21 CONTACT) (SEE SPECIFIC CONTACT RANGE ON PAGE 251)

8467

8467-0-15-XX-21-XX-04-0


Hex press-fit in .036 plated through-hole



6192

6192-0-15-XX-21-XX-04-0


Square press-fit in .032 plated through-hole



9553

9553-0-15-XX-X1-XX-04-0


Hex press-fit in .041 plated through-hole



5531

5531-0-15-XX-21-XX-10-0


Hex press-fit in .041 plated through-hole



7553

7553-0-15-XX-11-XX-10-0


Hex press-fit in .041 plated through-hole



9407

9407-0-15-XX-11-XX-10-0


Solder mount in .040 min. mounting hole



9462

9462-0-15-XX-21-XX-04-0


Hex press-fit in .043 plated through-hole



1147

1147-0-18-XX-21-XX-10-0


Press-fit in .043 min. mounting hole Accepts wire sizes up to .014" dia.



3061

3061-0-19-XX-21-XX-10-0


Wire Crimp Termination. Accepts wire sizes 28 AWG Max. / 32 AWG Min.



0579

0579-0-15-XX-X1-XX-10-0


Press-fit in .040 mounting hole



8874

8874-0-15-XX-11-XX-10-0


Bottom entry surface mount See page 152 for application details



0613

0613-0-15-XX-21-XX-10-0

Press-fit in .047 mounting hole



SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Inches

Tolerances On: Lengths: $\pm .005$

Diameters: $\pm .002$ Angles: $\pm 2^{\circ}$



ORDER CODE: <u>XXXX - X</u> - 1X - <u>XX</u> - <u>XX</u> - <u>XX</u> - XX - XX - 0

01 200 μ'' TIN/LEAD OVER NICKEL

- ◆ **80** 200 μ" TIN OVER NICKEL (RoHS)
- ◆ **15** 10 μ" GOLD OVER NICKEL (RoHS)

$\frac{XX}{\uparrow} - \frac{XX}{\uparrow} - XX - 0$

SPECIFY CONTACT FINISH:

02 100 μ " TIN/LEAD OVER NICKEL

- ◆ 84 100 µ" TIN OVER NICKEL (RoHS)
- ◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#11 or #21 CONTACT (DATA ON PAGE 251)

(For alternate contact choices, see group A on page 248)



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mill-Max:

9553-0-15-01-21-02-04-0 9553-0-15-01-11-02-04-0 9553-0-15-01-11-27-04-0 9462-0-15-01-21-27-04-0 3061-0-1901-21-02-10-0 3061-0-19-01-21-27-10-0 1147-0-18-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-02-10-0 0579-0-15-01-21-27-10-0 0579-0-15-15-21-27-10-0 0579-0-15-15-21-27-10-0 0579-0-15-15-21-27-10-0 0579-0-15-15-21-27-10-0 0579-0-15-15-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-27-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-10-0 0579-0-15-01-21-14-04-0 0579-