

Validation

The validation is an essential functionality of any existing web application. To automatically validate incoming requests, we leverage **class-validator** package which built-in **ValidationPipe** makes use of underneath. The **ValidationPipe** provides a convenient method to validate incoming client payloads with a variety of powerful validation rules.

Overview

In **Pipes** chapter, we went through the process of building a simplified validation pipe. To better understand what we're doing under the hood, we heavily recommend to read this article. Here, we'll mainly focus on the real use-cases instead.

Auto-validation

For the sake of this tutorial, we'll bind ValidationPipe to the whole application, thus, all endpoints will be automatically protected from the incorrect data.

```
async function bootstrap() {
  const app = await NestFactory.create(ApplicationModule);
  app.useGlobalPipes(new ValidationPipe());
  await app.listen(3000);
}
bootstrap();
```

To test our pipe, let's create a basic endpoint.

```
@Post()
create(@Body() createUserDto: CreateUserDto) {
  return 'This action adds a new user';
}
```

Then, add a few validation rules in our CreateUserDto.

```
import { IsEmail, IsNotEmpty } from 'class-validator';

export class CreateUserDto {
   @IsEmail()
   email: string;
```

```
@IsNotEmpty()
password: string;
}
```

Now, when someone requests our endpoint with an invalid email, the application would respond with a 400 Bad Request code and the following response body.

Obviously, the response body is not a sole use-case for the ValidationPipe. Imagine, that we would like to accept :id in the endpoint path. Only numbers shall be valid though. This is pretty simple as well.

```
@Get(':id')
findOne(@Param() params: FindOneParams) {
   return 'This action returns a user';
}
```

And FindOneParams looks like below.

```
import { IsNumberString } from 'class-validator';

export class FindOneParams {
    @IsNumberString()
    id: number;
}
```

Disable detailed errors

Error messages help a lot in order to comprehend what was wrong with the data sent through the network. However, in some production environments, you might want to disable detailed errors.

```
app.useGlobalPipes(
  new ValidationPipe({
    disableErrorMessages: true,
    }),
);
```

Now, error messages won't be populated to the end user.

Stripping properties

Quite frequently, we would like only predefined (whitelisted) properties to be passed on. For instance, if we expect email and password properties, when someone sends age, this property should be stripped and not available in the DTO. To enable such behavior, set whitelist to true.

```
app.useGlobalPipes(
  new ValidationPipe({
    whitelist: true,
    }),
);
```

This setting will enable auto-stripping of non-whitelisted (without any decorator on top of them) properties. However, if you want to stop the request processing entirely, and return an error response to the user, use forbidNonWhitelisted instead.

Auto payload transforming

The ValidationPipe doesn't automatically transform your payloads to the corresponding DTO classes. If you take a look at either createUserDto or findOneParams in your controller methods, you will notice that they're not actual instances of these classes. To enable auto-transformation, set transform to true.

```
app.useGlobalPipes(
  new ValidationPipe({
    transform: true,
  }),
```

Websockets & Microservices

All these guidelines cornern both WebSockets as well as microservices, regardless of transport method that is being used.

Learn more

In order to read more about custom validators, error messages, and available decorators, visit this page.

Support us

Nest is an MIT-licensed open source project. It can grow thanks to the support by these awesome people. If you'd like to join them, please read more here.

Principal Sponsor



Sponsors / Partners





Copyright © 2017-2019 MIT by Kamil Myśliwiec Designed by Jakub Staroń, hosted by Netlify