SINGLE-ENGINE PISTONS NORMALLLY ASPIRATED

Manufacturer			Cirrus Design	Textron Aviation	Cirrus Design	Textron Aviation
Model			SR20 G7+ SR20	Cessna Skylane CE-182T	SR22 G7+ SR22	Beechcraft Bonanza G36 G36
BCA Equipped Price			$694,900	$772,000	$937,900	$1,404,000
Characteristics		Seating	1+3/4	1+3/3	1+3/4	1+5/5
		Wing Loading	21.7	17.8	23.5	20.2
		Power Loading	14.65	13.48	11.61	12.68
		Noise (dBA)	83.4	77.7	83.7	76.7
External Dimensions (ft.)		Length	26.0	29.0	26.0	27.5
		Height	8.9	9.3	8.9	8.6
		Span	38.3	36.0	38.3	33.5
Internal Dimensions (ft.)		Length	8.0	7.2	8.0	12.6
		Height	4.1	4.0	4.1	4.2
		Width	4.1	3.5	4.1	3.5
Power		Engine	Lyc IO-390-C3B6	Lyc IO-540-AB1A5	Cont IO-550-N	Cont IO-550-B
		Output (hp)	215	230	310	300
		Inspection Interval	2,000t	2,000t	2,000t	1,900t
Weights (lb.)		Max Ramp	3,160	3,110	3,610	3,860
		Max Takeoff	3,150	3,100	3,600	3,805
		Max Landing	3,150	2,950	3,600	3,805
		Zero Fuel	3,043b	2,986b	3,400c	3,665b
		EOW	2,147	2,000	2,252	2,605
		Max Payload	896	986	1,148	1,060
		Useful Load	1,013	1,110	1,358	1,255
		Max Baggage	130	200	130	670
		Max Fuel	336	522	552	444
		Available Payload w/Max Fuel	677	588	806	811
		Available Fuel w/Max Payload	117	124	210	195
Limits		V_{NE}	201	175	205	203
		V_{NO}	164	140	176	165
		V_A	133	110	140	139
Airport Performance		TO (SL elev./ISA temp.)	2,530	1,514	1,756	1,913
		TO (5,000-ft. elev.@25C)	4,305	2,708	3,016	TBD
		V_{SO}	62	49	64	59
		V_X	81	65	88	84
		V_Y	88	80	108	100
Climb		Time to Climb (min.)/Altitude	20/FL 100	15/FL 100	11/FL 100	TBD/FL 100
		Initial Gradient (ft./nm)	540	694	775	TBD
Ceiling (ft.)		Service	17,500	18,100	17,500	18,500
Cruise	Long Range	TAS	135	125	160	160
		Fuel Flow	53	61	68	71
		Altitude	FL 080	FL 100	FL 080	FL 080
		Specific Range	2.547	2.049	2.353	2.254
	Recommended	TAS	145	135	171	167
		Fuel Flow	61	69	92	86
		Altitude	FL 080	FL 100	FL 080	FL 080
		Specific Range	2.377	1.957	1.859	1.942
	High Speed	TAS	152	144	180	174
		Fuel Flow	71	76	107	93
		Altitude	FL 080	FL 060	FL 080	FL 080
		Specific Range	2.141	1.895	1.682	1.865
Ranges	Seats Full	Nautical Miles	672	723	1,118	217
		Average Speed	135	130	162	153
		Fuel Used	275	379	492	115
		Specific Range/Altitude	2.444/FL 080	1.908/FL 120	2.272/FL 080	1.887/FL 040
	Tanks Full	Nautical Miles	672	912	1,118	860
		Average Speed	135	131	162	159
		Fuel Used	275	471	492	403
		Specific Range/Altitude	2.444/FL 080	1.936/FL 120	2.272/FL 080	2.134/FL 080
Missions (4 occupants)	200 nm	Runway	1,685	1,249	1,303	1,665
		Block Time	1+26	1+37	1+09	1+11
		Fuel Used	112	123	127	130
		Specific Range/Altitude	1.786/FL 080	1.626/FL 120	1.575/FL 080	1.538/FL 060
	500 nm	Runway	1,685	1,402	1,519	1,858
		Block Time	3+30	3+52	2+49	2+54
		Fuel Used	245	269	305	304
		Specific Range/Altitude	2.041/FL 080	1.859/FL 120	1.639/FL 080	1.645/FL 060
		Suggested Base Price	$694,900	NA	$937,900	NA
Remarks		Certification Basis	FAR 23, 2000 Includes Garmin Perspective Touch+ and Safe Return; Emergency Autoland standard.	FAR 23 A23-6, 1996/2001 Garmin G1000 NXi with GFC 700 autopilot.	FAR 23, 2000 Includes Garmin Perspective Touch+ and Safe Return; Emergency Autoland standard.	CAR 3, 1956/69/83/2005 A/C system standard; Garmin G1000 NXi.

SINGLE-ENGINE PISTONS TURBOCHARGED

Manufacturer			Textron Aviation	Cirrus Design	Textron Aviation
Model			Turbo Skylane CE-T182T	SR22T G7+ SR22T	Turbo Stationair HD CE-T206H
BCA Equipped Price			$871,000	$1,069,900	$1,069,000
Characteristics		Seating	1+3/3	1+3/4	1+5/5
		Wing Loading	17.8	23.5	21.8
		Power Loading	13.19	11.43	12.22
		Noise (dBA)	75.4	80.3	82.6
External Dimensions (ft.)		Length	29.0	26.0	28.3
		Height	9.3	8.9	9.3
		Span	36.0	38.3	36.0
Internal Dimensions (ft.)		Length	7.2	8.0	9.3
		Height	4.0	4.1	4.1
		Width	3.5	4.1	3.7
Power		Engine	Lyc TIO-540-AK1A	Cont TSIO-550-K	Lyc TIO-540-AJ1A
		Output (hp)	235	315	310
		Inspection Interval	2,000t	2,000t	2,000t
Weights (lb.)		Max Ramp	3,112	3,610	3,806
		Max Takeoff	3,100	3,600	3,789
		Max Landing	2,950	3,600	3,600
		Zero Fuel	2,953b	3,400c	3,615b
		EOW	2,114	2,362	2,365
		Max Payload	839	1,038	1,250
		Useful Load	998	1,248	1,441
		Max Baggage	200	130	180
		Max Fuel	522	552	522
		Available Payload w/Max Fuel	476	696	919
		Available Fuel w/Max Payload	159	210	191
Limits		V_{NE}	175	205	182
		V_{NO}	140	176	149
		V_A	110	140	125
Airport Performance		TO (SL elev./ISA Temp.)	1,385	1,517	1,970
		TO (5,000-ft. elev.@25C)	1,928	2,268	2,845
		V_{SO}	50	64	59
		V_X	64	88	70
		V_Y	84	103	88
Climb		Time to Climb (min.)/Altitude	10/FL 100	7/FL 100	12/FL 100
		Initial Gradient (ft./nm)	743	782	724
Ceilings (ft.)		Certificated	20,000	25,000	26,000
		Service	20,000	25,000	26,000
Cruise	Long Range	TAS	132	171	137
		Fuel Flow	62	76	85
		Altitude	FL 200	FL 250	FL 240
		Specific Range	2.129	2.250	1.612
	Recommended	TAS	152	201	155
		Fuel Flow	77	98	99
		Altitude	FL 200	FL 250	FL 240
		Specific Range	1.974	2.051	1.574
	High Speed	TAS	165	213	164
		Fuel Flow	98	110	116
		Altitude	FL 200	FL 250	FL 200
		Specific Range	1.684	1.936	1.410
Ranges	Seats Full	Nautical Miles	520	1,021	465
		Average Speed	134	171	137
		Fuel Used	291	486	358
		Specific Range/Altitude	1.787/FL 200	2.101/FL 250	1.299/FL 200
	Tanks Full	Nautical Miles	915	1,021	608
		Average Speed	134	171	138
		Fuel Used	476	486	430
		Specific Range/Altitude	1.922/FL 200	2.101/FL 250	1.414/FL 240
Missions (4 occupants)	200 nm	Runway	1,385	1,405	1,420
		Block Time	1+24	1+08	1+23
		Fuel Used	144	197	163
		Specific Range/Altitude	1.389/FL 120	1.015/FL 100	1.227/FL 150
	500 nm	Runway	1,385	1,699	1,626
		Block Time	3+14	2+28	3+22
		Fuel Used	319	360	386
		Specific Range/Altitude	1.567/FL 200	1.389/FL 180	1.295/FL 240
		Suggested Base Price	NA	$1,069,900	NA
Remarks		Certification Basis	FAR 23, 2006 Garmin G1000 NXi with GFC 700 autopilot standard.	FAR 23, 2010 Garmin Perspective Touch+ and Safe Return; Emergency Autoland std.	FAR 23, 1998 Garmin G1000 NXi with GFC 700 autopilot standard.

SINGLE-ENGINE PISTONS PRESSURIZED

Manufacturer			Piper Aircraft
Model			M350 PA-46-350P
BCA Equipped Price			$2,060,000
Characteristics		Seating	1+4/5
		Wing Loading	24.8
		Power Loading	12.40
		Noise (dBA)	81.0
External Dimensions (ft.)		Length	28.9
		Height	11.3
		Span	43.0
Internal Dimensions (ft.)		Length	12.3
		Height	3.9
		Width	4.2
Power		Engine	Lyc TIO-540-AE2A
		Output (hp)	350
		Inspection Interval	2,000t
Weights (lb.)		Max Ramp	4,358
		Max Takeoff	4,340
		Max Landing	4,123
		Zero Fuel	4,123c
		EOW	3,134
		Max Payload	989
		Useful Load	1,224
		Max Baggage	200
		Max Fuel	720
		Available Payload w/Max Fuel	504
		Available Fuel w/Max Payload	235
Limits		V_{NE}	198
		V_{NO}	168
		V_A	133
		PSI	5.6
Airport Performance		TO (SL elev./ISA temp.)	2,690
		TO (5,000-ft. elev.@25C)	3,877
		V_{SO}	58
		V_X	81
		V_Y	110
Climb		Time to Climb (min.)/Altitude	8/FL 100
		Initial Gradient (ft./nm)	703
Ceilings (ft.)		Certificated	25,000
		Service	25,000
		Sea-Level Cabin	12,300
Cruise	Long Range	TAS	156
		Fuel Flow	66
		Altitude	FL 250
		Specific Range	2.364
	Recommended	TAS	203
		Fuel Flow	108
		Altitude	FL 250
		Specific Range	1.880
	High Speed	TAS	213
		Fuel Flow	120
		Altitude	FL 250
		Specific Range	1.775
Ranges	Seats Full	Nautical Miles	535
		Average Speed	138
		Fuel Used	312
		Specific Range/Altitude	1.715/FL 120
	Tanks Full	Nautical Miles	1,343
		Average Speed	159
		Fuel Used	670
		Specific Range/Altitude	2.004/FL 250
Missions (4 occupants)	200 nm	Runway	2,690
		Block Time	1+06
		Fuel Used	167
		Specific Range/Altitude	1.198/FL 200
	500 nm	Runway	2,690
		Block Time	2+31
		Fuel Used	350
		Specific Range/Altitude	1.429/FL 250
		Suggested Base Price	$1,867,441
Remarks		Certification Basis	FAR 23, 1983/88 Garmin G1000 NXi, GFC 700 and GDL 60 with PlaneSync; pressurized and A/C.

MULTIENGINE PISTONS NORMALLY ASPIRATED

Manufacturer			Vulcanair SpA	Textron Aviation
Model			P.68C	Beechcraft Baron G58
BCA Equipped Price			$2,054,000*	$2,155,000
Characteristics		Seating	1+5/6	1+5/5
		Wing Loading	22.9	27.6
		Power Loading	11.49	9.17
		Noise (dBA)	74.7	77.6
External Dimensions (ft.)		Length	31.3	29.8
		Height	11.2	9.8
		Span	39.4	37.8
Internal Dimensions (ft.)		Length	10.6	12.6
		Height	3.9	4.2
		Width	3.8	3.5
Power		Engines	2 Lyc IO-360-A1B6	2 Cont IO-550-C
		Output (hp each)	200	300
		Inspection Interval	2,000t	1,900t
Weights (lb.)		Max Ramp	4,630	5,524
		Max Takeoff	4,594	5,500
		Max Landing	4,365	5,400
		Zero Fuel	4,167c	5,210b
		EOW	3,153	3,965
		Max Payload	1,014	1,245
		Useful Load	1,477	1,559
		Max Fuel	1,063	1,164
		Available Payload w/Max Fuel	415	395
		Available Fuel w/Max Payload	463	314
Limits		VNE	194	223
		VNO	154	195
		VA	132	156
Airport Performance		TO (SL elev./ISA Temp.)	1,312	2,345
		TO (5,000-ft. elev.@25C)	4,000	4,144
		A/S (SL elev./ISA)	2,150	3,009
		A/S (5,000-ft. elev.@25C)	2,950	4,335
		VMCA	60	84
		VDEC	70	85
		VXSE	82	100
		VYSE	88	101
Climb		Time to Climb (min.)/Altitude	12/FL 100	10/FL 100
		Initial Engine-Out Rate (fpm)	217	390
		Initial All-Engine Gradient (ft./nm)	1,100	988
		Initial Engine-Out Gradient (ft./nm)	147	232
Ceilings (ft.)		Certificated	—	—
		All-Engine Service	18,000	20,688
		Engine-Out Service	5,000	7,284
Cruise	Long Range	TAS	144	185
		Fuel Flow	94	144
		Altitude	FL 080	FL 080
		Specific Range	1.532	1.285
	Recommended	TAS	155	192
		Fuel Flow	108	174
		Altitude	FL 080	FL 080
		Specific Range	1.435	1.103
	High Speed	TAS	162	200
		Fuel Flow	116	193
		Altitude	FL 080	FL 080
		Specific Range	1.397	1.035
Ranges	Max Payload	Nautical Miles	300	250
		Average Speed	140	174
		Trip Fuel	315	231
		Specific Range/Altitude	0.952/FL 080	1.082/FL 040
	Ferry	Nautical Miles	1,000	1,480
		Average Speed	145	180
		Trip Fuel	975	1,081
		Specific Range/Altitude	1.026/FL 080	1.369/FL 120
Missions (4 occupants)	200 nm	Runway	1,450	2,861
		Block Time	1+28	1+02
		Fuel Used	140	226
		Specific Range/Altitude	1.429/FL 080	0.885/FL 060
	500 nm	Runway	1,500	2,940
		Block Time	3+25	2+31
		Fuel Used	375	531
		Specific Range/Altitude	1.333/FL 080	0.942/FL 060
		Suggested Base Price	$2,054,000	NA
Remarks		Certification Basis	FAR 23, 1976/80 Garmin G1000 NXi with GFC 700 autopilot. **BCA* estimated price.	CAR 3, 1957/69/83/2005 A/C system standard; Garmin G1000 NXi; max payload mission flown with six occupants.

MULTIENGINE PISTONS TURBOCHARGED

Manufacturer			Vulcanair SpA
Model			P.68C TC
BCA Equipped Price			$2,154,000*
Characteristics		Seating	1+5/5
		Wing Loading	20.7
		Power Loading	10.94
		Noise (dBA)	74.7
External Dimensions (ft.)		Length	31.3
		Height	11.2
		Span	39.4
Internal Dimensions (ft.)		Length	10.6
		Height	3.9
		Width	3.8
Power		Engines	2 Lyc TIO-360-C1A6D
		Output (hp each)	210
		Inspection Interval	2,000t
Weights (lb.)		Max Ramp	4,630
		Max Takeoff	4,594
		Max Landing	4,365
		Zero Fuel	4,140b
		EOW	3,197
		Max Payload	943
		Useful Load	1,433
		Max Fuel	1,062
		Available Payload w/Max Fuel	371
		Available Fuel w/Max Payload	490
Limits		VNE	194
		VNO	154
		VA	132
Airport Performance		TO (SL elev./ISA temp.)	1,260
		TO (5,000-ft. elev.@25C)	2,200
		A/S (SL elev./ISA)	1,800
		A/S (5,000-ft. elev.@25C)	2,400
		VMCA	66
		VDEC	NA
		VXSE	78
		VYSE	88
Climb		Time to Climb (min.)/Altitude	10/FL 100
		Initial Engine-Out Rate (fpm)	240
		Initial All-Engine Gradient (ft./nm)	1,400
		Initial Engine-Out Gradient (ft./nm)	NA
Ceilings (ft.)		Certificated	20,000
		All-Engine Service	20,000
		Engine-Out Service	10,000
Cruise	Long Range	TAS	144
		Fuel Flow	104
		Altitude	FL 080
		Specific Range	1.385
	Recommended	TAS	155
		Fuel Flow	125
		Altitude	FL 080
		Specific Range	1.240
	High Speed	TAS	162
		Fuel Flow	150
		Altitude	FL 080
		Specific Range	1.080
Range	Ferry	Nautical Miles	1,100
		Average Speed	145
		Trip Fuel	960
		Specific Range/Altitude	1.146/FL 080
Missions (4 occupants)	200 nm	Runway	NA
		Block Time	1+28
		Fuel Used	260
		Specific Range/Altitude	0.769/FL 080
	500 nm	Runway	NA
		Block Time	3+25
		Fuel Used	485
		Specific Range/Altitude	1.031/FL 080
		Suggested Base Price	$2,154,000
Remarks		Certification Basis	FAR 23, 1982 *BCA* estimated data. Garmin G1000 NXi. **BCA* estimated price.

SINGLE-ENGINE TURBOPROPS

Manufacturer			Textron Aviation	Textron Aviation	Piper Aircraft	Daher	Piper Aircraft	Daher
Model			Cessna Caravan CE-208	Grand Caravan EX CE-208B	M500 PA-46-500TP	Kodiak 100 Kodiak 100 Series III	M600 PA-46-600TP	Kodiak 200 Kodiak 900
BCA Equipped Price			$2,808,000	$3,132,000	$3,500,000	$3,761,606	$4,200,000	$4,344,346
Characteristics		Seating	1+9/13*	1+9/13*	1+4/5	1+6/9	1+4/5	1+6/9
		Wing Loading	28.6	31.5	27.8	30.2	28.7	33.3
		Power Loading	11.85	10.16	10.18	9.67	10.00	8.89
		Noise (dBA)	79.0	84.1	76.8	77.0	76.8	79.5
External Dimensions (ft.)		Length	37.6	41.6	29.5	33.8	29.6	37.7
		Height	14.9	15.5	11.3	14.7	11.5	16.1
		Span	52.1	52.1	43.0	45.0	43.1	45.0
Internal Dimensions (ft.)		Length	12.7	16.7	12.3	15.8	12.3	18.1
		Height	4.5	4.5	3.9	4.8	3.9	4.8
		Width	5.3	5.3	4.1	4.5	4.1	4.5
Power		Engine	P&WC PT6A-114A	P&WC PT6A-140	P&WC PT6A-42A	P&WC PT6A-34	P&WC PT6A-42A	P&WC PT6A-140A
		Output (shp)/Flat Rating	675/ISA+31C	867/ISA+24C	500/ISA+60C	750/ISA+7C	600/ISA+45C	900/ISA+22C
		Inspection Interval	3,600t	4,000t	3,600t	4,000t	3,600t	4,000t
Weights (lb.)		Max Ramp	8,035	8,842	5,134	7,305	6,050	8,100
		Max Takeoff	8,000	8,807	5,092	7,255	6,000	8,000
		Max Landing	7,800	8,500	4,850	7,255	5,800	7,800
		Zero Fuel	7,432b	8,152b	4,850c	7,071c	4,850c	7,410c
		BOW	4,930	5,510	3,634	4,417	3,850	4,840
		Max Payload	2,502	2,642	1,216	2,654	1,000	2,570
		Useful Load	3,105	3,332	1,500	2,888	2,200	3,260
		Max Fuel	2,224	2,246	1,160	2,144	1,742	2,144
		Available Payload w/Max Fuel	881	1,086	340	744	458	1,116
		Available Fuel w/Max Payload	604	691	284	234	1,200	690
Limits		V_{MO}	175	175	188	180	251	190
		V_A	150	148	127	143	153	155
		PSI	—	—	5.6	—	5.6	—
Airport Performance		TO (SL elev./ISA temp.)	2,055	2,160	2,438	1,468	2,635	1,504
		TO (5,000-ft. elev.@25C)	2,973	3,661	3,691	2,396	3,998	2,515
		V_{SO}	61	61	69	60	62	65
		V_X	90	86	95	73	95	79
		V_Y	107	108	125	101	122	111
Climb		Time to Climb (min.)/Altitude	9/FL 100	9/FL 100	19/FL 250	10/FL 100	21/FL 250	7/FL 100
		Initial Gradient (ft./nm)	771	816	753	778	785	932
Ceilings (ft.)		Certificated	25,000	25,000	30,000	25,000	30,000	25,000
		Service	25,000	25,000	30,000	25,000	30,000	25,000
		Sea-Level Cabin	—	—	12,600	—	12,600	—
Cruise	Long Range	TAS	157	156	179	164	184	185
		Fuel Flow	281	328	135	251	155	324
		Altitude	FL 100	FL 100	FL 280	FL 120	FL 280	FL 120
		Specific Range	0.559	0.476	1.326	0.653	1.187	0.571
	High Speed	TAS	186	185	258	175	274	210
		Fuel Flow	379	437	242	335	324	409
		Altitude	FL 100	FL 100	FL 280	FL 120	FL 280	FL 120
		Specific Range	0.491	0.423	1.066	0.522	0.846	0.513
NBAA IFR Ranges (100-nm alternate)	Full Fuel (w/available payload)	Nautical Miles	965	807	834	1,005	1,406	925
		Average Speed	156	156	171	175	179	210
		Trip Fuel	1,799	1,761	748	1,941	1,324	1,903
		Specific Range/Altitude	0.536/FL 100	0.458/FL 100	1.115/FL 280	0.518/FL 120	1.062/FL 280	0.486/FL 120
	Ferry	Nautical Miles	970	816	834	1,299	1,406	1,345
		Average Speed	156	156	171	141	179	177
		Trip Fuel	1,800	1,772	748	1,941	1,324	1,903
		Specific Range/Altitude	0.539/FL 100	0.460/FL 100	1.115/FL 280	0.669/FL 200	1.062/FL 280	0.707/FL 200
Missions (4 passengers)	300 nm	Runway	1,468	1,428	1,550	1,468	1,593	1,504
		Flight Time	1+40	1+41	1+22	1+50	1+21	1+30
		Fuel Used	648	750	379	591	429	651
		Specific Range/Altitude	0.463/FL 100	0.400/FL 100	0.792/FL 280	0.508/FL 120	0.699/FL 280	0.461/FL 120
	600 nm	Runway	1,675	1,792	1,625	1,468	1,687	1,504
		Flight Time	3+17	3+19	2+32	3+32	2+31	2+55
		Fuel Used	1,260	1,462	660	1,165	735	1,235
		Specific Range/Altitude	0.476/FL 100	0.410/FL 100	0.909/FL 280	0.515/FL 120	0.816/FL 280	0.486/FL 120
	1,000 nm	Runway	NP	NP	1,700	1,467	1,812	1,504
		Flight Time	NP	NP	4+18	5+50	4+06	4+50
		Fuel Used	NP	NP	985	1,931	1,142	2,014
		Specific Range/Altitude	NP/NP	NP/NP	1.015/FL 280	0.518/FL 120	0.876/FL 280	0.497/FL 120
		Suggested Base Price	NA	NA	$3,313,028	$3,339,926	$3,999,000	$4,064,616
Remarks		Certification Basis	FAR 23, 1984/98 Garmin G1000 NXi with GFC 700 autopilot. *Export only.	FAR 23, 1986/2012 Includes cargo pod; Garmin G1000 NXi and GFC700 autopilot. *Export only.	FAR 23 A52 Garmin G1000 NXi with SVS; GFC 700 autopilot; enhanced AFCS. 1,000 nm, three occupants.	FAR 23, 2007 Normal category Includes Garmin G1000 NXi and GFC 700 autopilot with coupled GA; Summit interior.	FAR 23 A62, 2016 Garmin G3000 with SVS and Enhanced AFCS; Garmin GDL 60 with PlaneSync; HALO emergency autoland.	FAR 23, 2007/22 Normal category includes Garmin G1000 NXi and GFC 700 autopilot with coupled GA; Summit+ interior.

SINGLE-ENGINE TURBOPROPS

Manufacturer			Piper Aircraft	Epic Aircraft	Daher	Daher	Pilatus	*Textron Aviation*
Model			M700 PA-46-701TP	E1000 AX E1000	TBM 960 TBM 700 N	TBM 980 TBM 700 N	PC-12 PRO PC-12/47 G	*Beechcraft Denali* *BE-220*
BCA Equipped Price			$4,500,000	$5,100,000	$5,620,630	$5,793,630	$6,475,000	***$7,950,000***
Characteristics		Seating	1+4/5	1+5/6	1+5/6	1+5/6	1+8/11	*1+7/9*
		Wing Loading	28.7	38.6	39.4	39.4	37.6	*NA*
		Power Loading	8.57	6.67	8.96	8.96	8.7	*NA*
		Noise (dBA)	73.2	76.9	77.1	77.1	77.0	*NA*
External Dimensions (ft.)		Length	29.6	35.8	35.2	35.2	47.3	*48.8*
		Height	11.5	12.5	14.3	14.3	14.0	*15.2*
		Span	43.1	43.0	42.1	42.1	53.3	*54.3*
Internal Dimensions (ft.)		Length	12.3	13.1	15.0	15.0	16.9	*16.8*
		Height	3.9	4.5	4.1	4.1	4.8	*4.8*
		Width	4.1	4.5	4.0	4.0	5.0	*5.3*
Power		Engine	P&WC PT6A-52	P&WC PT6A-67A	P&WC PT6E-66XT	P&WC PT6E-66XT	P&WC PT6E-67XP	*GE Aerospace* *Catalyst*
		Output (shp)/Flat Rating	700/ISA+45C	1,200/ISA+35C	850/ISA+37C	850/ISA+37C	1,200/ISA+35C	*1,300/NA*
		Inspection Interval	3,600t	3,500t	5,000t	5,000t	5,000t	*OC*
Weights (lb.)		Max Ramp	6,050	8,050	7,650	7,650	10,495	*NA*
		Max Takeoff	6,000	8,000	7,615	7,615	10,450	*NA*
		Max Landing	5,800	7,600	7,110	7,110	9,921	*NA*
		Zero Fuel	5,050c	7,600b	6,252c	6,252c	9,039c	*NA*
		BOW	3,850	5,290	4,982	4,982	6,697	*NA*
		Max Payload	1,000	2,310	1,270	1,270	2,342	*NA*
		Useful Load	2,320	2,956	2,668	2,668	3,798	*NA*
		Max Fuel	1,742	1,770	1,955	1,955	2,704	*NA*
		Available Payload w/Max Fuel	578	1,175	713	713	988	*1,100*
		Available Fuel w/Max Payload	1,320	646	1,398	1,398	1,456	*NA*
Limits		V_{MO}	251	270	266	266	240	*NA*
		V_A	153	170	160	160	166	*NA*
		PSI	5.6	6.6	6.2	6.2	5.8	*7.6*
Airport Performance		TO (SL elev./ISA temp.)	1,994	2,254	2,535	2,535	2,485	*NA*
		TO (5,000-ft. elev.@25C)	3,025	3,193	3,680	3,680	4,080	*NA*
		V_{SO}	62	68	65	65	67	*NA*
		V_X	95	116	100	100	120	*NA*
		V_Y	122	150	124	124	130	*NA*
Climb		Time to Climb (min.)/Altitude	14/FL 250	11/FL 250	13/FL 250	13/FL 250	19/FL 250	*NA/NA*
		Initial Gradient (ft./nm)	1,039	1,400	1,000	1,000	877	*NA*
Ceilings (ft.)		Certificated	30,000	34,000	31,000	31,000	30,000	*31,000*
		Service	30,000	34,000	31,000	31,000	30,000	*31,000*
		Sea-Level Cabin	12,600	15,000	14,390	14,390	13,100	*18,700*
Cruise	**Long Range**	TAS	206	240	252	252	225	*NA*
		Fuel Flow	167	233	241	241	269	*NA*
		Altitude	FL 300	FL 340	FL 310	FL 310	FL 300	*NA*
		Specific Range	1.234	1.030	1.046	1.046	0.84	*NA*
	High Speed	TAS	301	322	330	330	290	*285*
		Fuel Flow	365	334	412	412	463	*NA*
		Altitude	FL 250	FL 340	FL 280	FL 280	FL 240	*NA*
		Specific Range	0.825	0.964	0.801	0.801	0.626	*NA*
NBAA IFR Ranges (100-nm alternate)	**Full Fuel** (w/available payload)	Nautical Miles	1,424	1,232	1,514	1,514	1,548	*1,600*
		Average Speed	206	310	252	252	270	*NA*
		Trip Fuel	1,322	1,374	1,599	1,599	2,235	*NA*
		Specific Range/Altitude	1.077/FL 300	0.897/FL 340	0.947/FL 310	0.947/FL 310	0.693/FL 300	*NA/NA*
	Ferry	Nautical Miles	1,836	1,243	1,594	1,594	1,607	*NA*
		Average Speed	206	312	252	252	280	*NA*
		Trip Fuel	1,617	1,374	1,598	1,598	2,281	*NA*
		Specific Range/Altitude	1.135/FL 300	0.905/FL 340	0.997/FL 310	0.997/FL 310	0.705/FL 300	*NA/NA*
Missions (4 passengers)	**300 nm**	Runway	1,069	1,197	1,765	1,765	1,651	*NA*
		Flight Time	1+09	0+59	1+00	1+00	1+08	*NA*
		Fuel Used	443	453	440	440	534.0	*NA*
		Specific Range/Altitude	0.677/FL 250	0.662/FL 340	0.682/FL 280	0.682/FL 280	0.562/FL 240	*NA/NA*
	600 nm	Runway	1,213	1,440	2,005	2,005	1,824	*NA*
		Flight Time	2+08	1+54	1+55	1+55	2+12	*NA*
		Fuel Used	769	790	830	830	977	*NA*
		Specific Range/Altitude	0.780/FL 250	0.759/FL 340	0.723/FL 280	0.723/FL 280	0.614/FL 260	*NA/NA*
	1,000 nm	Runway	1,261	1,527	2,380	2,380	2,100	*NA*
		Flight Time	3+36	3+09	3+10	3+10	3+40	*NA*
		Fuel Used	1,115	1,207	1,320	1,320	1,525	*NA*
		Specific Range/Altitude	0.897/FL 300	0.829/FL 340	0.758/FL 290	0.758/FL 290	0.656/FL 280	*NA/NA*
		Suggested Base Price	$4,419,833	NA	$5,383,106	$5,556,106	$5,800,000	*NA*
Remarks		Certification Basis	FAR 23 A62, 2016 Garmin G3000 with SVS and Enhanced AFCS; Garmin GDL 60 with PlaneSync; HALO emergency autoland.	FAR 23 2019/21 Garmin G1000 NXi; all performance at MTOW.	FAR 23, 1990/ 2006/07/14/22 Pilot door standard; five-blade propeller; HomeSafe; E-throttle (PT6E-66XT EPECS); Garmin G3000; Prestige cabin; five-year system warranty.	FAR 23, 1990/ 2006/07/14/22/26 Pilot door standard; five-blade propeller; HomeSafe; E-throttle (PT6E-66XT EPECS); Garmin G3000 Prime; Prestige cabin; five-year system warranty.	FAR 23, 1996/2005/08/19 Typically equipped with executive interior; customized Garmin 3000 Prime with autothrottle and Safety Autoland feature,	*FAR/EASA 23 pending Garmin G3000; typically equipped with executive interior, autothrottle. All data preliminary.*

MULTIENGINE TURBOPROPS ≤12,500-LB. MTOW

Manufacturer			Textron Aviation	De Havilland Canada	Baykar Piaggio Aerospace sPa
Model			Beechcraft King Air 260 B200GT	Twin Otter Classic 300-G DHC-6-400	Avanti Evo P.180 Avanti II
BCA Equipped Price			$8,150,000	$8,400,000*	$10,790,000
Characteristics		Seating	1+8/10	1+19/19	1+7/9
		Wing Loading	40.3	29.8	70.3
		Power Loading	7.35	10.08	7.12
		Noise (dBA)	81.2	85.6	74.0
External Dimensions (ft.)		Length	43.8	51.8	47.3
		Height	14.8	19.8	13.0
		Span	57.9	65.0	47.1
Internal Dimensions (ft.)		**Length:** OA/Net	16.7/16.7	18.4/24.5	17.5/17.5
		Height	4.8	4.9	5.8
		Width: Max/Floor	4.5/4.1	5.8/4.4	6.1/3.5
Power		Engines	2 P&WC PT6A-52	2 P&WC PT6A-27	2 P&WC PT6A-66B
		Output (shp each)/Flat Rating	850/ISA+37C	620/ISA+18C	850/ISA+28C
		Inspection Interval	3,600t	3,600t	3,600t
Weights (lb.)		Max Ramp	12,590	12,600	12,150
		Max Takeoff	12,500	12,500	12,100
		Max Landing	12,500	12,300	11,500
		Zero Fuel	11,000c	12,300c	10,200c
		BOW	8,830	7,523	8,350
		Max Payload	2,170	4,777	1,850
		Useful Load	3,760	5,077	3,800
		Max Fuel	3,645	3,176	2,802
		Available Payload w/Max Fuel	115	1,901	998
		Available Fuel w/Max Payload	1,590	300	1,950
Limits		V_{MO}	259	170	260
		V_A	181	136	202
		PSI	6.5	—	9.0
Airport Performance		TO (SL elev./ISA temp.)	2,111	1,490	3,196
		TO (5,000-ft. elev.@25C)	3,099	2,260	4,700
		A/S (SL elev./ISA temp.)	3,687	2,220	5,750
		A/S (5,000-ft. elev.@25C)	4,859	2,810	7,400
		V_{MCA}	86	64	100
		V_{DEC}	94	NA	106
		V_{XSE}	115	NA	132
		V_{YSE}	121	80	140
Climb		Time to Climb (min.)/Altitude	13/FL 250	7/FL 100	10/FL 250
		Initial Engine-Out Rate (fpm)	682	340	670
		Initial All-Engine Gradient (ft./nm)	1,170	1,063	1,067
		Initial Engine-Out Gradient (ft./nm)	364	633	287
Ceilings (ft.)		Certificated	35,000	25,000	41,000
		All-Engine Service	35,000	26,700	41,000
		Engine-Out Service	26,000	11,600	22,500
		Sea-Level Cabin	15,000	—	24,000
Cruise	**Long Range**	TAS	256	137	304
		Fuel Flow	430	372	438
		Altitude	FL 350	FL 100	FL 390
		Specific Range	0.595	0.368	0.694
	High Speed	TAS	310	185	378
		Fuel Flow	750	619	783
		Altitude	FL 260	FL 100	FL 310
		Specific Range	0.413	0.299	0.483
NBAA IFR Ranges (100-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	321	260	774
		Average Speed	267	145	297
		Trip Fuel	870	858	1,315
		Specific Range/Altitude	0.369/FL 330	0.303/FL 100	0.589/FL 390
	Max Fuel (w/available payload)	Nautical Miles	1,403	957	1,366
		Average Speed	291	142	300
		Trip Fuel	2,941	2,837	2,165
		Specific Range/Altitude	0.477/FL 330	0.337/FL 100	0.631/FL 390
	Full Fuel (w/4 passengers)	Nautical Miles	1,038	990	1,376
		Average Speed	288	139	300
		Trip Fuel	2,225	2,842	2,165
		Specific Range/Altitude	0.467/FL 330	0.348/FL 100	0.636/FL 390
	Ferry	Nautical Miles	1,420	1,012	1,389
		Average Speed	293	137	304
		Trip Fuel	2,942	2,842	2,165
		Specific Range/Altitude	0.483/FL 330	0.356/FL 100	0.642/FL 390
Missions (4 passengers)	**300 nm**	Runway	3,504	880	2,350
		Flight Time	1+03	1+42	0+53
		Fuel Used	869	1,068	725
		Specific Range/Altitude	0.345/FL 250	0.281/FL 100	0.414/FL 310
	600 nm	Runway	3,587	930	2,550
		Flight Time	2+03	3+19	1+45
		Fuel Used	1,494	2,086	1,220
		Specific Range/Altitude	0.402/FL 290	0.288/FL 100	0.492/FL 350
	1,000 nm	Runway	3,677	NP	2,700
		Flight Time	3+28	NP	3+05
		Fuel Used	2,147	NP	1,672
		Specific Range/Altitude	0.466/FL 330	NP/NP	0.598/FL 390
		Suggested Base Price	NA	NA	NA
Remarks		Certification Basis	FAR 23, 1973/80/2008/11 Collins Pro Line Fusion standard; Wi-Fi optional; STC SA02131SE; autothrottles standard.	EASA/FAR 23 A57, 2010 Garmin G1000 NXi; PT6A-34 optional; air conditioning optional. **BCA* estimated price.	EASA 23, 2014; FAR 23, 2015 Collins Pro Line 21 including TCAS I, Class B TAWS, SBAS LPV, RVSM, Cat. II and steep approach, weather radar; enlarged door; VIP interior; optional 390-lb. additional fuel tank, EVS.

MULTIENGINE TURBOPROPS >12,500-LB. MTOW

Manufacturer			Textron Aviation	Textron Aviation	Textron Aviation	Textron Aviation
Model			Beechcraft King Air 360 B300	SkyCourier (Freighter) CE-408	Beechcraft King Air 360ER B300ER	SkyCourier (Passenger) CE-408
BCA Equipped Price			$9,255,000	$9,293,100	$9,760,000	$10,108,200
Characteristics		Seating	1+9/11	1+1/1	1+9/11	2+19/19
		Wing Loading	48.4	43.0	53.2	43.0
		Power Loading	7.14	8.56	7.86	8.56
		Noise (dBA)	72.9	84.6	81.5	84.6
External Dimensions (ft.)		Length	46.7	55.1	46.7	55.1
		Height	14.3	20.7	14.3	20.7
		Span	57.9	72.3	57.9	72.3
Internal Dimensions (ft.)		**Length:** OA/Net	19.5/19.5	23.3/23.3	19.5/19.5	23.3/19.5
		Height	4.8	5.9	4.8	5.9
		Width: Max/Floor	4.5/4.1	6.4/5.8	4.5/4.1	6.2/5.8
Power		Engines	2 P&WC PT6A-60A	2 P&WC PT6A-65SC	2 P&WC PT6A-60A	2 P&WC PT6A-65SC
		Output (shp each)/Flat Rating	1,050/ISA+10C	1,110/ISA+35C	1,050/ISA+10C	1,110/ISA+35C
		Inspection Interval	3,600t	6,000t	3,600t	6,000t
Weights (lb.)		Max Ramp	15,100	19,070	16,600	19,070
		Max Takeoff	15,000	19,000	16,500	19,000
		Max Landing	15,000	18,600	15,675	18,600
		Zero Fuel	12,500c	17,200c	13,000c	17,725c
		BOW	9,955	11,200	10,215	12,725
		Max Payload	2,545	6,000	2,785	5,000
		Useful Load	5,145	7,870	6,385	6,345
		Max Fuel	3,611	4,826	5,192	4,826
		Available Payload w/Max Fuel	1,534	3,044	1,193	1,519
		Available Fuel w/Max Payload	2,600	1,870	3,600	1,345
Limits		MMO	0.58	0.40	0.58	0.40
		Trans. Alt. FL/VMO	210/263	120/210	240/245	120/210
		VA	184	153	182	153
		PSI	6.8	—	6.8	—
Airport Performance		TO (SL elev./ISA temp.)	3,300	2,700*	4,057	3,580*
		TOFL (5,000-ft. elev.@25C)	5,376	3,650*	7,675	4,740*
		Mission Weight	14,196	19,000	16,100	19,000
		NBAA IFR Range	1,549	797	2,257	792
		V2	109	98	111	98
		VREF	100	96	104	96
		Landing Distance	2,390	2,014	2,728	2,096
Climb		Time to Climb (min.)/Altitude	15/FL 250	32/FL 250	18/FL 250	32/FL 250
		*FAR 25 Initial Engine-Out Rate (fpm)	622	233	337	233
		FAR 25 Initial Engine-Out Gradient (ft./nm)	304	143	182	143
Ceilings (ft.)		Certificated	35,000	25,000	35,000	25,000
		All-Engine Service	35,000	25,000	35,000	25,000
		Engine-Out Service	21,500	13,900	17,100	13,900
		Sea-Level Cabin	16,500	—	16,500	—
Cruise	**Long Range**	TAS	235	166	238	166
		Fuel Flow	362	640	402	640
		Altitude	FL 330	FL 120	FL 330	FL 120
		Specific Range	0.649	0.259	0.592	0.259
	High Speed	TAS	312	214	303	214
		Fuel Flow	773	1,009	764	1,009
		Altitude	FL 240	FL 120	FL 240	FL 120
		Specific Range	0.404	0.212	0.397	0.212
NBAA IFR Ranges (100-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	896	100	1,316	85
		Average Speed	273	189	261	182
		Trip Fuel	1,891	609	2,880	533
		Specific Range/Altitude	0.474/FL 350	0.164/FL 120	0.457/FL 350	0.159/FL 120
	Max Fuel (w/available payload)	Nautical Miles	1,485	783	2,223	783
		Average Speed	280	205	269	205
		Trip Fuel	2,944	3,915	4,528	3,915
		Specific Range/Altitude	0.504/FL 350	0.200/FL 120	0.491/FL 350	0.200/FL 120
	Full Fuel (w/4 passengers)	Nautical Miles	1,533	792	2,271	787
		Average Speed	285	208	271	206
		Trip Fuel	2,951	3,946	4,533	3,925
		Specific Range/Altitude	0.519/FL 350	0.201/FL 120	0.501/FL 350	0.201/FL 120
	Ferry	Nautical Miles	1,560	795	2,338	790
		Average Speed	289	207	276	207
		Trip Fuel	2,958	3,956	4,543	3,936
		Specific Range/Altitude	0.527/FL 350	0.201/FL 120	0.515/FL 350	0.201/FL 120
Missions (4 passengers)	**300 nm**	Runway	2,586	1,698	2,795	2,737
		Flight Time	1+02	1+28	1+05	1+29
		Fuel Used	881	1,545	919	1,538
		Specific Range/Altitude	0.341/FL 250	0.194/FL 120	0.326/FL 250	0.195/FL 120
	600 nm	Runway	2,702	1,984	2,927	3,141
		Flight Time	2+02	2+54	2+07	2+55
		Fuel Used	1,470	3,007	1,529	3,005
		Specific Range/Altitude	0.408/FL 290	0.200/FL 120	0.392/FL 290	0.200/FL 120
	1,000 nm	Runway	2,827	NP	3,048	NP
		Flight Time	3+27	NP	3+35	NP
		Fuel Used	2,102	NP	2,195	NP
		Specific Range/Altitude	0.476/FL 330	NP/NP	0.456/FL 330	NP/NP
		Suggested Base Price	NA	$7,750,000	NA	$8,350,000
Remarks		Certification Basis	FAR 23, 1989 Commuter category Collins Pro Line Fusion MultiScan radar and iTAWS; Wi-Fi optional; RVSM app'd.; also available as 350HW with 16,500-lb. MTOW, 15,675-lb. MLW; autothrottles standard.	FAR 23 A64, 2022 Normal category (Level 1) Garmin G1000 NXi; 800-lb. payload for *BCA* missions. *AE TOD 50-ft. obstacle.	FAR 23, 1989/2007 Commuter category Collins Pro Line Fusion Multi-Scan radar and iTAWS; Wi-Fi optional; RVSM approved; autothrottles standard.	FAR 23 A64, 2022 Normal category (Level 4) Garmin G1000 NXi. *OEI TOFL 35-ft. obstacle.

JETS <10,000-LB. MTOW

Manufacturer			Cirrus Design
Model			Vision Jet G3 SF-50
BCA Equipped Price			$3,460,000
Characteristics		Seating	1+5/7
		Wing Loading	30.7
		Power Loading	3.25
		Noise (EPNdB): Lateral/Flyover/Approach	79.6/70.9/80.3
External Dimensions (ft.)		Length	30.7
		Height	10.9
		Span	38.7
Internal Dimensions (ft.)		**Length:** OA/Net	11.5/9.8
		Height/Dropped Aisle Depth	4.1/NA
		Width: Max/Floor	5.1/3.1
Baggage		**Internal:** Cu. ft./lb.	24/NA
		External: Cu. ft./lb.	30/NA
Power		Engine(s)	1 Wms Intl FJ33-5A
		Output (lb. each)/Flat Rating	1,846/ISA+10C
		Inspection Interval/Manu. Service Plan Interval	4,000t/—
Weights (lb.)		Max Ramp	6,040
		Max Takeoff	6,000
		Max Landing	5,550
		Zero Fuel	4,900c
		BOW	3,860
		Max Payload	1,040
		Useful Load	2,180
		Max Fuel	2,000
		Available Payload w/Max Fuel	180
		Available Fuel w/Max Payload	1,140
Limits		MMO	0.540
		Trans. Alt. FL/VMO	FL 183/250
		PSI	7.1
Airport Performance		TOFL (SL elev./ISA temp.)	1,920
		TOFL (5,000-ft. elev.@25C)	3,045
		Mission Weight	6,000
		NBAA IFR Range	1,098
		V_2	91
		V_{REF}	87
		Landing Distance	1,628
Climb		Time to Climb/Altitude	23/FL 310
		FAR 25 Engine-Out Rate (fpm)	NA
		FAR 25 Engine-Out Gradient (ft./nm)	NA
Ceilings (ft.)		Certificated	31,000
		All-Engine Service	31,000
		Engine-Out Service	—
		Sea-Level Cabin	NA
Cruise	Long Range	TAS	259
		Fuel Flow	300
		Altitude	FL 310
		Specific Range	0.863
	High Speed	TAS	305
		Fuel Flow	384
		Altitude	FL 310
		Specific Range	0.794
NBAA IFR Ranges (100-nm alternate)	Max Payload (w/available fuel)	Nautical Miles	461
		Average Speed	233
		Trip Fuel	745
		Specific Range/Altitude	0.619/FL 310
	Max Fuel (w/available payload)	Nautical Miles	1,171
		Average Speed	233
		Trip Fuel	1,611
		Specific Range/Altitude	0.727/FL 310
	Four Passengers (w/available fuel)	Nautical Miles	622
		Average Speed	233
		Trip Fuel	941
		Specific Range/Altitude	0.661/FL 310
	Ferry	Nautical Miles	1,220
		Average Speed	233
		Trip Fuel	1,760
		Specific Range/Altitude	0.693/FL 310
Missions (4 passengers)	300 nm	Runway	1,867
		Flight Time	1+12
		Fuel Used	548
		Specific Range/Altitude	0.547/FL 310
	600 nm	Runway	2,036
		Flight Time	2+36
		Fuel Used	914
		Specific Range/Altitude	0.656/FL 310
	1,000 nm	Runway	2,437
		Flight Time	4+18
		Fuel Used	1,401
		Specific Range/Altitude	0.714/FL 310
Remarks		Certification Basis	FAR 23, 2016/18 Garmin Perspective Touch+; RVSM standard; Safe Return emergency autoland; Cirrus IQ standard.

JETS <20,000-LB. MTOW

Manufacturer			Nextant Aerospace	Embraer
Model			Nextant 400 XTi BE 400A	Phenom 100 EX EMB-500
BCA Equipped Price			$4,650,000	$5,795,000
Characteristics		Seating	2+7/9/9	1+7/7/7
		Wing Loading/Power Loading	67.6/2.67	53.1/3.09
		Noise (EPNdB): Lateral/Flyover/Approach	76.9/91.5/88.8	81.6/70.8/86.1
External Dimensions (ft.)		Length	48.4	42.1
		Height	13.9	14.3
		Span	43.5	40.4
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	15.5/15.5/—	11.0/11.0/11.0
		Height/Dropped Aisle Depth	4.8/flat floor	4.9/0.3
		Width: Max/Floor	4.9/4.0	5.1/3.6
Baggage		**Internal:** Cu. ft./lb.	27/410	4/26
		External: Cu. ft./lb.	26/450	60/419
Power		Engines	2 Wms Intl FJ44-3AP	2 P&WC PW 617F1-E
		Output (lb. each)/Flat Rating	3,052/ISA+7C	1,730/ISA+8C
		Inspection Interval/Manu. Service Plan Interval	5,000t/—	3,500t/—
Weights (lb.)		Max Ramp	16,500	10,748
		Max Takeoff	16,300	10,703
		Max Landing	15,700	9,998
		Zero Fuel	13,000c	9,072c
		BOW	10,950	7,297
		Max Payload	2,050	1,775
		Useful Load	5,550	3,451
		Max Fuel	4,912	2,804
		Available Payload w/Max Fuel	638	647
		Available Fuel w/Max Payload	3,500	1,676
Limits		MMO	0.780	0.700
		Trans. Alt. FL/VMO	FL 290/320	FL 280/275
		PSI/Sea-Level Cabin	9.1/24,000	8.3/21,280
Airport Performance		TOFL (SL elev./ISA temp.)	3,821	3,190
		TOFL (5,000-ft. elev.@25C)	5,088	5,663
		Mission Weight	14,500p	10,703
		NBAA IFR Range	1,197	1,113
		V_2	116	99
		V_{REF}	105	95
		Landing Distance	2,960	2,473
Climb		Time to Climb/Altitude	16/FL 370	19/FL 370
		FAR 25 Engine-Out Rate (fpm)	305	747
		FAR 25 Engine-Out Gradient (ft./nm)	158	453
Ceilings (ft.)		Certificated	45,000	41,000
		All-Engine Service	45,000	41,000
		Engine-Out Service	27,500	24,045
Cruise	Long Range	TAS/Fuel Flow (lb./hr.)	406/740	340/543
		Altitude/Specific Range	FL 450/0.549	FL 410/0.626
	High Speed	TAS/Fuel Flow (lb./hr.)	447/968	406/955
		Altitude/Specific Range	FL 430/0.462	FL 330/0.425
NBAA IFR Ranges (FAR Part 23, 100-nm alternate; FAR Part 25, 200-nm alternate)	Max Payload (w/available fuel)	Nautical Miles	1,024	466
		Average Speed	367	325
		Trip Fuel	2,411	1,036
		Specific Range/Altitude	0.425/FL 450	0.450/FL 410
	Max Fuel (w/available payload)	Nautical Miles	1,895	1,194
		Average Speed	384	333
		Trip Fuel	3,953	2,196
		Specific Range/Altitude	0.479/FL 450	0.544/FL 410
	Four Passengers (w/available fuel)	Nautical Miles	1,801	1,092
		Average Speed	383	333
		Trip Fuel	3,706	2,038
		Specific Range/Altitude	0.486/FL 450	0.536/FL 410
	Ferry	Nautical Miles	1,981	1,254
		Average Speed	381	329
		Trip Fuel	3,986	2,220
		Specific Range/Altitude	0.497/FL 450	0.565/FL 410
Missions (4 passengers)	300 nm	Runway	3,015	2,909
		Flight Time	0+48	0+53
		Fuel Used	786	753
		Specific Range/Altitude	0.382/FL 390	0.398/FL 390
	600 nm	Runway	3,044	3,121
		Flight Time	1+30	1+45
		Fuel Used	1,323	1,236
		Specific Range/Altitude	0.454/FL 430	0.485/FL 390
	1,000 nm	Runway	3,101	3,179
		Flight Time	2+28	2+54
		Fuel Used	2,145	1,919
		Specific Range/Altitude	0.466/FL 450	0.521/FL 410
Remarks		Certification Basis	FAR 25, 1981/85 STC 02371LA STC 10959SC STC 03960AT	FAR 23, 2008

JETS <20,000-LB. MTOW

Manufacturer			Textron Aviation	Honda Aircraft Co.	Textron Aviation	Textron Aviation	Embraer	Pilatus Aircraft
Model			Citation M2 Gen2 CE-525	HondaJet Elite II HA-420	Citation CJ3 Gen2 CE-525B	Citation CJ4 Gen2 CE-525C	Phenom 300E EMB-505	PC-24
BCA Equipped Price			$6,995,000	$7,600,000	$11,745,000	$12,800,000	$13,395,000	$14,295,000
Characteristics		Seating	1+7/7/7	1+5/7/7	1+8/9/9	1+9/10/10	1+7/10/10	1+8/11/11
		Wing Loading/Power Loading	44.6/2.72	62.9/2.71	47.2/2.46	51.8/2.36	60.5/2.67	56.0/2.74
		Noise (EPNdB): Lateral/Flyover/Approach	85.9/73.2/88.5	85.5/73.1/87.4	88.7/74.0/88.6	92.8/75.6/89.5	89.2/70.6/88.9	90.3/79.2/92.1
External Dimensions (ft.)		Length	42.6	42.6	51.2	53.3	51.2	55.2
		Height	13.9	14.9	15.2	15.4	16.7	17.3
		Span	47.3	39.8	53.3	50.8	52.2	55.8
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	8.8/11.0/11.0	12.1/12.1/NA	12.3/15.7/15.7	12.9/17.3/17.3	14.8/17.2/17.2	17.0/17.0/23.1
		Height/Dropped Aisle Depth	4.8/0.4	4.8/NA	4.8/0.4	4.8/0.4	4.9/0.3	5.1/Flat Floor
		Width: Max/Floor	4.8/3.1	5.0/NA	4.8/3.1	4.8/3.3	5.1/3.6	5.6/3.8
Baggage		**Internal:** Cu. ft./lb.	—/—	NA/NA	—/—	7/40	10/77	90/530
		External: Cu. ft./lb.	46/725	62/750	65/1,000	71/1,000	74/573	NA/NA
Power		Engines	2 Wms Intl FJ44-1AP-21	2 GE Honda HF-120-H1A	2 Wms Intl FJ44-3A	2 Wms Intl FJ44-4A	2 P&WC PW 535E1	2 Wms Intl FJ44-4A-QPM
		Output (lb. each)/Flat Rating	1,965/ISA+7C	2,050/ISA+10C	2,820/ISA+11C	3,621/ISA+11C	3,478/ISA+15C	3,420/ISA+23C
		Inspection Interval/Manu. Service Plan Interval	3,500t/5,000	5,000t*/—	4,000t/5,000	5,000t/5,000	5,000t/—	5,000t/5,000
Weights (lb.)		Max Ramp	10,800	11,180	14,070	17,230	18,618	18,840
		Max Takeoff	10,700	11,100	13,870	17,110	18,552	18,740
		Max Landing	9,900	10,360	12,750	15,660	17,273	17,340
		Zero Fuel	8,500c	9,300c	10,675c	12,500c	14,264c	14,660c
		BOW	6,990	7,422	8,540	10,280	11,628	11,618
		Max Payload	1,510	1,878	2,135	2,220	2,636	3,042
		Useful Load	3,810	3,758	5,530	6,950	6,990	7,222
		Max Fuel	3,296	3,138	4,710	5,828	5,404	5,965
		Available Payload w/Max Fuel	514	620	820	1,122	1,586	1,257
		Available Fuel w/Max Payload	2,300	1,880	3,395	4,730	4,354	4,180
Limits		MMO	0.710	0.720	0.737	0.770	0.800	0.740
		Trans. Alt. FL/VMO	FL 305/263	FL 302/270	FL 293/278	FL 279/305	FL 276/320	FL 280/290
		PSI/Sea-Level Cabin	8.5/22,027	8.8/23,060	8.9/23,586	9.0/24,005	9.4/25,560	9.3/25,100
Airport Performance		TOFL (SL elev./ISA temp.)	3,210	3,699	3,180	3,410	3,209	3,090
		TOFL (5,000-ft. elev.@25C)	5,580	5,637	4,750	5,180	5,374	5,600
		Mission Weight	10,700	11,100	13,870	16,788	18,552	18,326
		NBAA IFR Range	1,204	1,380	1,918	2,109	2,033	2,125
		V2	111	117	114	117	111	108
		VREF	101	108	98	98	103	90
		Landing Distance	2,340	2,912	2,394	2,450	2,212	2,120
Climb		Time to Climb/Altitude	18/FL 370	16/FL 370	15/FL 370	14/FL 370	14/FL 370	14/FL 370
		FAR 25 Engine-Out Rate (fpm)	618	634	808	839	872	665
		FAR 25 Engine-Out Gradient (ft./nm)	334	284	425	430	471	379
Ceilings (ft.)		Certificated	41,000	43,000	45,000	45,000	45,000	45,000
		All-Engine Service	41,000	43,000	45,000	45,000	45,000	45,000
		Engine-Out Service	26,800	26,400	26,250	28,200	30,137	29,100
Cruise	**Long Range**	TAS/Fuel Flow (lb./hr.)	323/516	360/543	352/624	377/812	385/783	371/862
		Altitude/Specific Range	FL 410/0.626	FL 430/0.663	FL 450/0.564	FL 450/0.464	FL 450/0.492	FL 450/0.430
	High Speed	TAS/Fuel Flow (lb./hr.)	401/920	419/999	415/1,197	442/1,470	464/1,549	436/1,571
		Altitude/Specific Range	FL 350/0.436	FL 330/0.419	FL 350/0.347	FL 370/0.301	FL 350/0.300	FL 330/0.278
NBAA IFR Ranges (FAR Part 23, 100-nm alternate; FAR Part 25, 200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	759	612	945	1,425	1,381	1,169
		Average Speed	358	332	366	407	397	393
		Trip Fuel	1,600	1,255	2,381	3,753	3,369	3,116
		Specific Range/Altitude	0.474/FL 410	0.488/FL 430	0.397/FL 450	0.380/FL 450	0.410/FL 450	0.375/FL 450
	Max Fuel (w/available payload)	Nautical Miles	1,357	1,523	1,814	1,913	1,932	1,946
		Average Speed	372	347	377	413	393	387
		Trip Fuel	2,675	2,601	3,846	4,904	4,450	4,978
		Specific Range/Altitude	0.507/FL 410	0.586/FL 430	0.472/FL 450	0.390/FL 450	0.434/FL 450	0.391/FL 450
	Four Passengers (w/available fuel)	Nautical Miles	1,183	1,358	1,825	1,927	2,010	1,994
		Average Speed	370	346	376	416	387	393
		Trip Fuel	2,352	2,366	3,767	4,920	4,471	5,078
		Specific Range/Altitude	0.503/FL 410	0.574/FL 430	0.484/FL 450	0.392/FL 450	0.450/FL 450	0.393/FL 450
	Ferry	Nautical Miles	1,550	1,605	2,040	2,165	2,094	2,027
		Average Speed	378	344	383	420	380	411
		Trip Fuel	2,705	2,622	3,872	4,955	4,498	5,105
		Specific Range/Altitude	0.573/FL 410	0.612/FL 430	0.527/FL 450	0.437/FL 450	0.466/FL 450	0.397/FL 450
Missions (4 passengers)	**300 nm**	Runway	2,625	3,372	2,608	2,669	2,899	2,314
		Flight Time	0+51	0+53	0+49	0+46	0+49	0+47
		Fuel Used	804	715	969	1,087	998	1,379
		Specific Range/Altitude	0.373/FL 370	0.420/FL 390	0.310/FL 370	0.276/FL 390	0.301/FL 390	0.218/FL 280
	600 nm	Runway	2,692	3,413	2,609	2,715	2,868	2,326
		Flight Time	1+38	1+40	1+35	1+27	1+29	1+35
		Fuel Used	1,362	1,185	1,571	1,865	1,653	1,678
		Specific Range/Altitude	0.441/FL 390	0.506/FL 430	0.382/FL 410	0.322/FL 410	0.363/FL 410	0.358/FL 450
	1,000 nm	Runway	3,009	3,473	2,720	2,770	2,831	2,391
		Flight Time	2+41	2+43	2+36	2+23	2+24	2+33
		Fuel Used	2,018	1,872	2,315	2,747	2,533	2,646
		Specific Range/Altitude	0.496/FL 410	0.534/FL 430	0.432/FL 430	0.364/FL 430	0.395/FL 450	0.378/FL 450
Remarks		Certification Basis	FAR 23, 2013	FAR 23, 2015/19 *Mature TBO.	FAR 23, 2004/14 Commuter category Garmin G3000.	FAR 23, 2010 Commuter category Collins Pro Line 21.	FAR 23, 2009/20 Commuter category	EASA CS 23, 2017/23; FAR 23, 2018/23 SN 501 and above approved for unpaved runway operations.

JETS ≥20,000-LB. MTOW

Manufacturer			Textron Aviation	Embraer	Textron Aviation	Gulfstream Aerospace	Embraer
Model			Citation Ascend CE-560XL	Praetor 500 EMB-545	Citation Latitude CE-680A	G280	Praetor 600 EMB-550
BCA Equipped Price			$18,175,000	$21,645,000	$21,995,000	$25,000,000	$25,795,000
Characteristics		Seating	2+9/12/12	2+7/9/9	2+9/9/9	2+9/10/19	2+8/12/12
		Wing Loading/Power Loading	55.5/2.43	77.7/2.87	56.8/2.61	80.0/2.60	88.7/2.85
		Noise (EPNdB): Lateral/Flyover/Approach	85.6/71.0/91.9	84.1/73.5/89.9	87.7/73.5/87.7	89.5/75.2/90.5	86.9/75.1/90.3
External Dimensions (ft.)		Length	52.7	64.6	62.3	66.8	68.1
		Height	17.2	21.1	20.9	21.3	21.2
		Span	55.7	70.5	72.3	63.0	70.5
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	14.3/18.5/18.5	17.4/20.6/24.0	15.9/21.8/21.8	17.7/25.8/32.3	21.3/24.1/27.5
		Height/Dropped Aisle Depth	5.0*/flat floor**	6.0/flat floor	6.0/flat floor	6.1/4.5	6.0/flat floor
		Width: Max/Floor	5.5/3.9	6.8/4.7	6.4/4.1	6.9/5.4	6.8/4.7
Baggage		**Internal:** Cu. ft./lb.	NA/NA	40/418	27/245	154/1,980	45/418
		External: Cu. ft./lb.	80/700	110/880	100/1,000	—/—	110/880
Power		Engines	2 P&WC PW545D	2 Hon HTF7500E	2 P&WC PW306D1	2 Hon HTF7250G	2 Hon HTF7500E
		Output (lb. each)/Flat Rating	4,218/ISA+10C	6,540/ISA+18C	5,907/ISA+15C	7,624/ISA+17C	7,528/ISA+18C
		Inspection Interval/Manu. Service Plan Interval	6,000t/—	OC/—	6,000t/—	OC/—	OC/—
Weights (lb.)		Max Ramp	20,700	37,699	31,050	39,750	42,990
		Max Takeoff	20,500	37,567	30,800	39,600	42,857
		Max Landing	18,700	34,172	27,575	32,700	37,478
		Zero Fuel	15,800	25,959c	21,430c	28,200c	28,660
		BOW	13,060	23,038	18,656	24,200	24,658
		Max Payload	2,740	2,921	2,774	4,000	4,002
		Useful Load	7,640	14,661	12,394	15,550	18,332
		Max Fuel	6,740	13,051	11,394	14,600	16,138
		Available Payload w/Max Fuel	900	1,610	1,000	950	2,194
		Available Fuel w/Max Payload	4,900	11,740	9,620	11,550	14,330
Limits		M_{MO}	0.750	0.830	0.800	0.850	0.830
		Trans. Alt. FL/V_{MO}	FL 265/305	FL 295/320	FL 298/305	FL 280/340	FL 295/320
		PSI/Sea-Level Cabin	9.3/25,230	9.7/27,140	9.7/26,800	9.2/25,000	9.7/27,140
Airport Performance		TOFL (SL elev./ISA temp.)	3,800	4,222	3,580	4,750	4,717
		TOFL (5,000-ft. elev.@25C)	3,180	5,692	5,070	7,320	6,431
		Mission Weight	20,600	37,567	30,675	39,600	42,857
		NBAA IFR Range	1,940	3,412	2,700	3,700	4,040
		V_2	120	119	115	137	128
		V_{REF}	107	101	95	115	104
		Landing Distance	2,780	2,086	2,085	2,365	2,165
Climb		Time to Climb/Altitude	16/FL 370	14/FL 370	16/FL 370	14/FL 370	13/FL 370
		FAR 25 Engine-Out Rate (fpm)	800	743	652	680	777
		FAR 25 Engine-Out Gradient (ft./nm)	400	375	340	298	364
Ceilings (ft.)		Certificated	45,000	45,000	45,000	45,000	45,000
		All-Engine Service	43,000	43,000	43,000	44,100	43,000
		Engine-Out Service	28,600	27,513	27,620	28,000	28,189
Cruise	**Long Range**	TAS/Fuel Flow (lb./hr.)	385/941	426/1,352	368/1,114	459/1,522	433/1,449
		Altitude/Specific Range	FL 430/0.409	FL 450/0.315	FL 430/0.330	FL 450/0.302	FL 450/0.299
	High Speed	TAS/Fuel Flow (lb./hr.)	430/1,248	469/2,018	432/1,765	482/1,877	466/1,826
		Altitude/Specific Range	FL 410/0.345	FL 390/0.232	FL 390/0.245	FL 410/0.257	FL 430/0.255
NBAA IFR Ranges (FAR Part 23, 100-nm alternate; FAR Part 25, 200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	1,135	2,819	2,135	2,628	3,277
		Average Speed	389	423	394	447	426
		Trip Fuel	3,491	9,963	7,901	9,667	12,600
		Specific Range/Altitude	0.325/FL 430	0.283/FL 450	0.270/FL 450	0.272/FL 450	0.260/FL 450
	Max Fuel (w/available payload)	Nautical Miles	1,800	3,282	2,645	3,688	3,878
		Average Speed	400	419	401	451	425
		Trip Fuel	5,257	11,322	9,586	12,837	14,357
		Specific Range/Altitude	0.342/FL 450	0.290/FL 450	0.276/FL 450	0.287/FL 450	0.270/FL 450
	Four Passengers (w/available fuel)	Nautical Miles	1,830	3,340	2,678	3,703	4,018
		Average Speed	401	417	401	451	423
		Trip Fuel	5,328	11,342	9,594	12,843	14,404
		Specific Range/Altitude	0.343/FL 450	0.294/FL 450	0.279/FL 450	0.288/FL 450	0.279/FL 450
	Ferry	Nautical Miles	2,010	3,416	2,731	3,787	4,102
		Average Speed	383	417	405	451	421
		Trip Fuel	5,331	11,357	9,628	12,872	14,436
		Specific Range/Altitude	0.377/FL 450	0.301/FL 450	0.284/FL 450	0.294/FL 450	0.284/FL 450
Missions (4 passengers)	**300 nm**	Runway	2,904	2,673	2,760	2,860	2,745
		Flight Time	0+47	0+48	0+46	0+47	0+46
		Fuel Used	1,215	1,564	1,610	1,405	1,558
		Specific Range/Altitude	0.247/FL 390	0.192/FL 430	0.186/FL 390	0.214/FL 450	0.193/FL 450
	600 nm	Runway	2,968	2,690	2,845	2,885	2,746
		Flight Time	1+29	1+28	1+29	1+26	1+26
		Fuel Used	2,067	2,494	2,573	2,309	2,580
		Specific Range/Altitude	0.290/FL 410	0.241/FL 450	0.233/FL 430	0.260/FL 450	0.233/FL 450
	1,000 nm	Runway	3,164	2,858	2,951	3,020	2,810
		Flight Time	2+27	2+21	2+25	2+18	2+18
		Fuel Used	3,114	3,802	3,989	3,539	3,969
		Specific Range/Altitude	0.321/FL 430	0.263/FL 450	0.251/FL 430	0.283/FL 450	0.252/FL 450
Remarks		Certification Basis	FAR 25, 2025 Garmin G5000 *5.7 ft. optional. **0.7 ft. optional.	RBAC/FAR 25, 2015/19; EASA CS 25, 2015/19 Mod: DCA 0550-000-00100-2018.	FAR 25, 2015 Garmin G5000.	FAR 25, 2012; EASA CS 25, 2013	ANAC, 2019; RBAC/FAR/EASA CS 25, 2014/19 Mod: DCA 0550-000-00026-2016.

JETS ≥20,000-LB. MTOW

Manufacturer			Bombardier	Textron Aviation	Bombardier	Dassault	*Gulfstream Aerospace*
Model			Challenger 3500 BD-100-1A10	Citation Longitude CE-700	Challenger 650 CL-600-2B16	Falcon 2000LXS Falcon 2000EX	*G400* *GVII-G400*
BCA Equipped Price			$29,500,000	$29,995,000	$35,500,000	$38,300,000	*$44,950,000*
Characteristics		Seating	2+9/11/19	2+8/12/12	2+12/13/19	2+8/10/19	*2+11/19/19*
		Wing Loading/Power Loading	77.6/2.77	73.5/2.58	98.6/2.61	81.2/3.06	*73.5/2.59*
		Noise (EPNdB): Lateral/Flyover/Approach	87.6/75.3/89.6	88.4/72.9/89.9	86.2/81.2/90.3	91.7/76.4/90.5	*NA/NA/NA*
External Dimensions (ft.)		Length	68.7	73.2	68.4	66.3	*86.2*
		Height	20.0	19.4	20.7	23.3	*25.3*
		Span	69.0	68.9	64.3	70.2	*86.3*
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	16.6/25.2/28.6	16.5/25.2/28.1	15.4/25.6/28.3	17.1/26.2/31.0	*20.4/36.3/42.4*
		Height/Dropped Aisle Depth	6.0/flat floor	6.0/flat floor	6.0/flat floor	6.2/flat floor	*6.2/flat floor*
		Width: Max/Floor	7.2/5.1	6.4/4.1	7.9/6.9	7.7/6.3	*7.6/6.1*
Baggage		**Internal:** Cu. ft./lb.	106/750	112/1,115	112/900	131/1,600	*175/2,250*
		External: Cu. ft./lb.	—/—	NA/NA	—/—	8/92	*—/—*
Power		Engines	2 Hon HTF 7350	2 Hon HTF7700L	2 GE CF34-3B	2 P&WC PW308C	*2 P&WC* *PW812GA*
		Output (lb. each)/Flat Rating	7,323/ISA+15C	7,665/ISA+19C	9,220*/ISA+15C	7,000/ISA+15C	*13,486/NA*
		Inspection Interval/Manu. Service Plan Interval	OC/—	OC/—	OC/—	7,000c/—	*OC/—*
Weights (lb.)		Max Ramp	40,750	39,700	48,300	43,000	*70,250*
		Max Takeoff	40,600	39,500	48,200	42,800	*69,850*
		Max Landing	34,150	33,500	38,000	39,300	*60,000*
		Zero Fuel	28,200c	26,800c	32,000c	29,700c	*47,150c*
		BOW	24,800	23,600	27,150	24,750	*43,100*
		Max Payload	3,400	3,200	4,850	4,950	*4,050*
		Useful Load	15,950	16,100	21,150	18,250	*27,150*
		Max Fuel	14,045	14,500	19,852	16,660	*25,350*
		Available Payload w/Max Fuel	1,905	1,600	1,298	1,590	*1,800*
		Available Fuel w/Max Payload	12,550	12,900	16,300	13,300	*23,100*
Limits		M_{MO}	0.830	0.840	0.850	0.862	*0.900*
		Trans. Alt. FL/V_{MO}	FL 295/320	FL 293/325	FL 222/348	FL 250/370	*NA/NA*
		PSI/Sea-Level Cabin	9.7/26,900	9.7/26,800	8.8/23,100	9.3/25,300	*10.7/31,900*
Airport Performance		TOFL (SL elev./ISA temp.)	4,835	4,810	5,640	4,675	*5,000*
		TOFL (5,000-ft. elev.@25C)	6,809	6,810	9,025	6,840	*6,900*
		Mission Weight	40,600	38,725	48,200	42,010	*69,850*
		NBAA IFR Range	3,400	3,500	4,044	4,100	*4,270*
		V_2	133	136	147	127	*NA*
		V_{REF}	111	110	117	106	*NA*
		Landing Distance	2,303	2,595	2,368	2,295	*NA*
Climb		Time to Climb/Altitude	14/FL 370	13/FL 370	21/FL 370	17/FL 370	*NA/NA*
		FAR 25 Engine-Out Rate (fpm)	NA	1,330	NA	463	*NA*
		FAR 25 Engine-Out Gradient (ft./nm)	NA	456	NA	221	*NA*
Ceilings (ft.)		Certificated	45,000	45,000	41,000	47,000	*51,000*
		All-Engine Service	44,000	43,000	37,200	42,315	*NA*
		Engine-Out Service	27,500	28,420	20,000	21,010	*NA*
Cruise	**Long Range**	TAS/Fuel Flow (lb./hr.)	442/1,473	449/1,478	424/1,828	437/1,485	*NA/NA*
		Altitude/Specific Range	FL 450/0.300	FL 450/0.304	FL 410/0.232	FL 450/0.294	*NA/NA*
	High Speed	TAS/Fuel Flow (lb./hr.)	470/1,656	478/1,937	470/2,089	483/2,325	*NA/NA*
		Altitude/Specific Range	FL 450/0.284	FL 430/0.247	FL 410/0.225	FL 390/0.208	*NA/NA*
NBAA IFR Ranges (FAR Part 23, 100-nm alternate; FAR Part 25, 200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	2,814	3,074	3,015	2,915	*NA*
		Average Speed	432	452	416	427	*NA*
		Trip Fuel	10,628	11,600	14,255	11,438	*NA*
		Specific Range/Altitude	0.265/FL 450	0.265/FL 450	0.212/FL 410	0.255/FL 450	*NA/NA*
	Max Fuel (w/available payload)	Nautical Miles	3,297	3,422	3,979	3,990	*NA*
		Average Speed	434	453	418	430	*NA*
		Trip Fuel	12,164	12,763	17,940	14,798	*NA*
		Specific Range/Altitude	0.271/FL 450	0.268/FL 450	0.222/FL 410	0.270/FL 470	*NA/NA*
	Four Passengers (w/available fuel)	Nautical Miles	3,377	3,500	4,025	4,065	*NA*
		Average Speed	434	454	419	430	*NA*
		Trip Fuel	12,193	12,763	17,959	14,798	*NA*
		Specific Range/Altitude	0.277/FL 450	0.274/FL 450	0.224/FL 410	0.275/FL 470	*NA/NA*
	Ferry	Nautical Miles	3,435	3,500	4,100	4,155	*NA*
		Average Speed	434	454	418	431	*NA*
		Trip Fuel	12,214	12,787	17,988	14,798	*NA*
		Specific Range/Altitude	0.281/FL 450	0.274/FL 450	0.228/FL 410	0.281/FL 470	*NA/NA*
Missions (4 passengers)	**300 nm**	Runway	3,612	2,744	3,387	2,795	*NA*
		Flight Time	0+48	0+44	0+48	0+47	*NA*
		Fuel Used	1,573	1,516	1,573	1,525	*NA*
		Specific Range/Altitude	0.191/FL 450	0.198/FL 450	0.191/FL 410	0.197/FL 470	*NA/NA*
	600 nm	Runway	3,655	2,880	3,415	2,855	*NA*
		Flight Time	1+29	1+23	1+28	1+27	*NA*
		Fuel Used	2,527	2,457	2,810	2,465	*NA*
		Specific Range/Altitude	0.237/FL 450	0.244/FL 450	0.214/FL 410	0.243/FL 470	*NA/NA*
	1,000 nm	Runway	3,714	3,025	3,444	2,920	*NA*
		Flight Time	2+23	2+16	2+20	2+20	*NA*
		Fuel Used	3,822	3,746	4,502	3,755	*NA*
		Specific Range/Altitude	0.262/FL 450	0.267/FL 450	0.222/FL 410	0.266/FL 470	*NA/NA*
Remarks		Certification Basis	FAR 25 A98; JAR 25 Chg. 15 Collins Pro Line 21 Advanced.	FAR 25, 2019 Garmin G5000.	FAR 25, 1980/83/87/95/2006/15 Collins Pro Line 21 Advanced. *9,220-lb. max takeoff; 8,729-lb. normal takeoff.	FAR/EASA CS 25, 2013 EASy II flight deck; 2026 delivery price; FalconEye available.	*FAR 25 pending; EASA CS 25 pending Note: First flight, Aug, 15, 2024.*

JETS ≥20,000-LB. MTOW

Manufacturer			Bombardier	Gulfstream Aerospace	Dassault	Airbus	Airbus
Model			Global 5500 BD-700-1A11	G500 GVII-G500	Falcon 6X	ACJTwoTwenty BD500-1A10	ACJ320neo A320-271N*
BCA Equipped Price			$50,000,000	$54,250,000	$59,400,000	$82,500,000*	$117,000,000**
Characteristics		Seating	3+13/16/19	2+13/19/19	3+12/16/19	5+8/19/135**	4+19/NA/195***
		Wing Loading/Power Loading	90.6/3.06	83.8/2.63	99.4/2.87	116.2/2.88	132.1/3.25
	Noise (EPNdB):	Lateral/Flyover/Approach	88.9/79.7/89.4	87.7/75.3/91.0	91.1/80.8/89.8	87.9/79.6/91.3	86.4/81.7/92.4
External Dimensions (ft.)		Length	96.8	91.2	84.3	114.8	123.3
		Height	25.5	25.5	24.5	38.7	38.6
		Span	94.0	86.3	85.1	115.1	117.4
Internal Dimensions (ft.)	**Length:**	Main Seating/Net/Gross	27.2/40.7/45.7	26.3/41.5/47.6	27.5/40.3/46.0	51.6/78.1/78.1	91.0/91.0/91.0
		Height/Dropped Aisle Depth	6.2/flat floor	6.2/flat floor	6.5/flat floor	6.9/flat floor	7.4/flat floor
	Width:	Max/Floor	7.9/6.5	7.6/6.1	8.5/7.2	10.8/10.1	12.1/11.7
Baggage	**Internal:**	Cu. ft./lb.	195/1,000	175/2,250	155/2,210	150***/NA	NA/NA
	External:	Cu. ft./lb.	—/—	—/—	8/92	177/2,300	650/NA
Power		Engines	2 RR BR700-710D5-21*	2 P&WC PW814GA	2 P&WC PW812D	2 P&W PW1524G****	2 P&W PW1127G
		Output (lb. each)/Flat Rating	15,125/ISA+15C	15,144/ISA+15C	13,500/ISA+20C	24,400/ISA+15C	26,800/ISA+15C
		Inspection Interval/Manu. Service Plan Interval	OC/—	OC/—	OC/—	OC/—	OC/—
Weights (lb.)		Max Ramp	92,750	80,000	77,900	141,000	175,045
		Max Takeoff	92,500	79,600	77,500	140,500	174,165
		Max Landing	78,600	64,350	66,200	112,500	148,592
		Zero Fuel	58,000c	52,100c	45,900c	108,000c	141,757c
		BOW	50,861	46,850	42,250	87,675***	110,000****
		Max Payload	7,139	5,250	3,650	20,325	31,757
		Useful Load	41,889	33,150	35,650	53,325	65,045
		Max Fuel	38,967	30,250	33,800	50,578	60,812
		Available Payload w/Max Fuel	2,922	2,900	1,850	2,747	4,233
		Available Fuel w/Max Payload	34,750	27,900	32,000	33,000	33,288
Limits		M_{MO}	0.900	0.925	0.900	0.820	0.820
		Trans. Alt. FL/V_{MO}	FL 308/340	FL 290/340	FL 295/350	FL 275/330	FL 250/350
		PSI/Sea-Level Cabin	10.3/30,125	10.7/31,900	10.4/31,000	9.3/NA	9.2/NA
Airport Performance		TOFL (SL elev./ISA temp.)	5,340	5,300	5,115	5,478	6,333
		TOFL (5,000-ft. elev.@25C)	7,284	7,300	6,635	8,706	8,189
		Mission Weight	92,500	79,600	76,690	140,500	174,165
		NBAA IFR Range	6,310	5,400	5,705	5,686	6,000
		V_2	133	148	138	NA	NA
		V_{REF}	108	117	110	110	115
		Landing Distance	2,195	2,645	2,440	2,300	2,565
Climb		Time to Climb/Altitude	18/FL 370	16/FL 370	22/FL 370	23/FL 370	19/FL 350
		FAR 25 Engine-Out Rate (fpm)	NA	916	420	NA	NA
		FAR 25 Engine-Out Gradient (ft./nm)	NA	370	98	NA	NA
Ceilings (ft.)		Certificated	51,000	51,000	51,000	41,000	41,000
		All-Engine Service	41,000	45,200	41,500	41,000	41,000
		Engine-Out Service	25,100	26,100	19,500	24,000	23,000
Cruise	**Long Range**	TAS/Fuel Flow (lb./hr.)	488/2,815	488/2,417	459/2,440	432/3,507***	447/4,046****
		Altitude/Specific Range	FL 450/0.173	FL 470/0.202	FL 450/0.188	FL 410/0.123	FL 410/0.110
	High Speed	TAS/Fuel Flow (lb./hr.)	505/3,016	516/3,048	499/3,285	465/3,937***	465/4,681****
		Altitude/Specific Range	FL 410/0.167	FL 430/0.169	FL 410/0.152	FL 410/0.118	FL 410/0.099
NBAA IFR Ranges (FAR Part 23, 100-nm alternate; FAR Part 25, 200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	5,037	4,670	5,135	3,105	2,500
		Average Speed	477	480	453	422	447
		Trip Fuel	31,785	24,987	29,110	28,150	27,152
		Specific Range/Altitude	0.158/FL 470	0.187/FL 490	0.176/FL 480	0.110/FL 390	0.092/FL 370
	Max Fuel (w/available payload)	Nautical Miles	5,893	5,238	5,545	5,684	6,000
		Average Speed	479	481	453	427	NA
		Trip Fuel	36,124	27,406	30,910	46,528***	55,832
		Specific Range/Altitude	0.163/FL 470	0.191/FL 490	0.179/FL 480	0.122/FL 410	0.107/FL 410
	Four Passengers (w/available fuel)	Nautical Miles	6,038	5,408	5,670	5,724	6,060
		Average Speed	479	481	453	427	NA
		Trip Fuel	36,186	27,468	31,150	46,550	55,368
		Specific Range/Altitude	0.167/FL 490	0.197/FL 510	0.182/FL 480	0.123/FL 410	0.109/FL 410
	Ferry	Nautical Miles	6,095	5,476	5,740	5,763	6,100
		Average Speed	479	481	454	427	NA
		Trip Fuel	36,209	27,491	31,150	46,571	55,394
		Specific Range/Altitude	0.168/FL 490	0.199/FL 510	0.184/FL 480	0.124/FL 410	0.110/FL 410
Missions (4 passengers)	**300 nm**	Runway	2,540	3,595	2,845	3,201	3,235
		Flight Time	0+47	0+45	0+47	0+53	0+53
		Fuel Used	2,542	2,405	2,250	3,264	3,489
		Specific Range/Altitude	0.118/FL 430	0.125/FL 470	0.133/FL 470	0.092/FL 390	0.086/FL 370
	600 nm	Runway	2,557	3,615	2,855	3,268	3,297
		Flight Time	1+25	1+22	1+26	1+36	1+34
		Fuel Used	4,008	3,659	3,555	5,330	5,790
		Specific Range/Altitude	0.150/FL 490	0.164/FL 510	0.169/FL 480	0.113/FL 410	0.104/FL 410
	1,000 nm	Runway	2,583	3,640	2,875	3,327	3,402
		Flight Time	2+14	2+11	2+18	2+34	2+27
		Fuel Used	6,033	5,351	5,345	8,136	8,780
		Specific Range/Altitude	0.166/FL 490	0.187/FL 510	0.187/FL 480	0.123/FL 410	0.114/FL 410
Remarks		Certification Basis	FAR 25, 1998/2004/19; EASA 25, 2004 Global Vision flight deck; ModSums: 700T901902 700T03185 700T63572 *Marketed as Pearl 15.	FAR 25, 2018; EASA CS 25, 2019	FAR/EASA CS 25, 2023 EASy IV flight deck; DFCS; 2026 delivery price; FalconEye; Dual HUD with FalconEye available.	FAR 25, 2015 *BCA estimate. **Airliner configuration. ***ACJ estimate. ****Also available with PW1521G rated at 21,000 lbf; includes five additional center tanks and VIP cabin.	FAR 25, 1999/2016 *Also available as -251N with CFM LEAP1A-26 engines rated at 26,600 lbf; includes four additional center tanks and VIP cabin. **BCA estimate. ***Airliner configuration. ****ACJ estimate.

ULTRA-LONG-RANGE JETS

Manufacturer			Bombardier	Gulfstream Aerospace	Dassault	Gulfstream Aerospace	Gulfstream Aerospace
Model			Global 6500 BD-700-1A10	G600 GVII-G600	Falcon 8X Falcon 7X	G800 GVIII-G800	G700 GVIII-G700
BCA Equipped Price			$61,000,000	$63,500,000	$69,700,000	$80,400,000	$84,900,000
Characteristics		Seating	4+13/17/19	4+16/19/19	3+12/14/19	4+16/19/19	4+16/19/19
		Wing Loading/Power Loading	97.5/3.29	81.5/3.02	95.9/3.62	82.2/2.89	83.8/2.95
		Noise (EPNdB): Lateral/Flyover/Approach	88.7/82.2/89.4	88.3/78.3/91.3	88.7/80.1/90.6	88.4/75.2/88.2	88.3/75.6/88.1
External Dimensions (ft.)		Length	99.4	96.1	80.2	99.8	109.9
		Height	25.5	25.3	26.1	25.5	25.4
		Span	94.0	94.1	86.3	103.0	103.0
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	27.3/43.3/48.3	32.0/45.2/51.3	29.8/42.7/50.1	32.7/46.8/53.6	40.8/56.9/63.7
		Height/Dropped Aisle Depth	6.2/flat floor	6.2/flat floor	6.2/flat floor	6.3/flat floor	6.3/flat floor
		Width: Max/Floor	7.9/6.5	7.6/6.1	7.7/6.3	8.2/6.7	8.2/6.7
Baggage		**Internal:** Cu. ft./lb.	195/1,000	175/2,500	140/2,004	195/2,500	195/2,500
		External: Cu. ft./lb.	—/—	—/—	—/—	—/—	—/—
Power		Engines	2 RR BR700-710D5-21*	2 P&WC PW815GA	3 P&WC PW307D	2 RR BR700-730B2-14*	2 RR BR700-730B2-14*
		Output (lb. each)/Flat Rating	15,125/ISA+15C	15,680/ISA+15C	6,722/ISA+17C	18,250/ISA+15C	18,250/ISA+15C
		Inspection Interval/Manu. Service Plan Interval	0C/—	0C/—	7,200c/—	0C/—	0C/—
Weights (lb.)		Max Ramp	99,750	95,000	73,200	106,000	108,000
		Max Takeoff	99,500	94,600	73,000	105,600	107,600
		Max Landing	78,600	76,800	62,400	83,500	83,500
		Zero Fuel	58,000c	57,440c	41,000c	60,500c	62,750c
		BOW	52,230	50,900	36,800	54,300	56,765
		Max Payload	5,770	6,540	4,200	6,200	5,985
		Useful Load	47,520	44,100	36,400	51,700	51,235
		Max Fuel	44,715	41,500	35,141	49,400	49,400
		Available Payload w/Max Fuel	2,805	2,600	1,259	2,300	1,835
		Available Fuel w/Max Payload	41,750	37,560	32,200	45,500	45,250
Limits		MMO	0.900	0.925	0.900	0.935	0.935
		Trans. Alt. FL/VMO	FL 308/340	FL 290/340	FL 270/370	FL 290/340	FL 290/340
		PSI/Sea-Level Cabin	10.3/30,125	10.7/31,900	10.2/30,300	10.7/31,900	10.7/31,900
Airport Performance		TOFL (SL elev./ISA temp.)	6,145	5,700	5,880	5,812	5,995
		TOFL (5,000-ft. elev.@25C)	8,509	8,493	8,540	9,475	9,751
		Mission Weight	99,500	94,600	72,591	105,600	107,600
		NBAA IFR Range	6,990	6,630	6,415	8,220	7,765
		V2	138	142	138	153	154
		VREF	109	109	107	115	118
		Landing Distance	2,231	2,365	2,245	2,455	2,552
Climb		Time to Climb/Altitude	21/FL 370	18/FL 370	20/FL 370	16/FL 370	17/FL 370
		FAR 25 Engine-Out Rate (fpm)	NA	644	774	902	876
		FAR 25 Engine-Out Gradient (ft./nm)	NA	270	339	351	339
Ceiling (ft.)		Certificated	51,000	51,000	51,000	51,000	51,000
		All-Engine Service	41,000	43,800	40,075	44,100	43,400
		Engine-Out Service	22,000	25,000	26,645	26,500	26,000
Cruise	**Long Range**	TAS	488	488	459	488	488
		Fuel Flow	2,986	2,809	2,254	2,750	2,904
		Altitude	FL 430	FL 450	FL 430	FL 450	FL 450
		Specific Range	0.163	0.174	0.204	0.177	0.168
	High Speed	TAS	505	516	497	516	516
		Fuel Flow	3,094	3,590	3,172	3,350	3,598
		Altitude	FL 410	FL 410	FL 390	FL 430	FL 430
		Specific Range	0.163	0.144	0.157	0.154	0.143
NBAA IFR Ranges (200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	5,954	5,665	5,555	7,245	6,835
		Average Speed	478	481	452	488	482
		Trip Fuel	38,783	34,478	29,507	42,627	42,070
		Specific Range/Altitude	0.154/FL 470	0.164/FL 470	0.188/FL 470	0.170/FL 490	0.162/FL 470
	Max Fuel (w/available payload)	Nautical Miles	6,547	6,544	6,325	8,150	7,745
		Average Speed	479	482	453	488	483
		Trip Fuel	41,835	38,518	32,558	46,628	46,334
		Specific Range/Altitude	0.156/FL 470	0.170/FL 490	0.194/FL 470	0.175/FL 510	0.167/FL 490
	Eight Passengers (w/available fuel)	Nautical Miles	6,636	6,630	6,235	8,220	7,765
		Average Speed	480	481	453	488	483
		Trip Fuel	41,870	38,543	32,204	46,645	46,340
		Specific Range/Altitude	0.158/FL 470	0.172/FL 490	0.194/FL 470	0.176/FL 510	0.168/FL 490
	Ferry	Nautical Miles	6,754	6,767	6,475	8,380	7,920
		Average Speed	480	483	454	488	483
		Trip Fuel	41,916	38,584	32,653	46,685	46,384
		Specific Range/Altitude	0.161/FL 490	0.175/FL 490	0.198/FL 470	0.180/FL 510	0.171/FL 490
Missions (8 passengers)	**1,000 nm**	Runway	2,718	3,655	2,715	3,150	2,960
		Flight Time	2+14	2+10	2+12	2+10	2+10
		Fuel Used	6,219	5,872	5,440	5,565	5,852
		Specific Range/Altitude	0.161/FL 490	0.170/FL 510	0.184/FL 450	0.180/FL 510	0.171/FL 490
	3,000 nm	Runway	3,487	3,870	3,730	3,270	3,320
		Flight Time	6+21	6+17	6+19	6+16	6+17
		Fuel Used	17,490	16,102	15,945	15,196	16,050
		Specific Range/Altitude	0.172/FL 490	0.186/FL 490	0.188/FL 450	0.197/FL 510	0.187/FL 490
	6,000 nm	Runway	5,482	5,115	5,785	4,354	4,690
		Flight Time	12+32	12+26	12+45	12+26	12+27
		Fuel Used	37,302	34,243	32,200	32,062	34,049
		Specific Range/Altitude	0.161/FL 490	0.175/FL 490	0.186/FL 470	0.187/FL 510	0.176/FL 490
Remarks		Certification Basis	FAR 25, 1998/2003/19; EASA CS 25, 1998/2019 BEVS and Global Vision flight deck standard. ModSums: 700T901901, 700T03185, 700T63572. *Marketed as Pearl 15.	FAR 25, 2019; EASA CS 25, 2020	FAR/EASA CS25, 2016 EASy IV flight deck; DFCS; 2026 delivery price; FalconEye; Dual HUD with FalconEye available.	FAR 25, 2025; EASA CS 25, 2025 *Marketed as Pearl 700.	FAR 25, 2024; EASA CS 25, 2024 *Marketed as Pearl 700.

ULTRA-LONG-RANGE JETS

Manufacturer			Bombardier	Boeing	Airbus	Boeing	Boeing
Model			Global 8000 BD-700-2A12	BBJ MAX 7 737-7	ACJ319neo A319-153N*	BBJ MAX 8 737-8	BBJ MAX 9 737-9
BCA Equipped Price			$85,000,000	$97,500,000.00*	$107,500,000**	$115,000,000.00*	$124,000,000.00*
Characteristics		Seating	4+17/19/19	4+19/NA/172	4+19/NA/160	4+19/NA/189	4+19/NA/220
		Wing Loading/Power Loading	91.6/3.04	132.0/3.35	130.8/3.22	135.1/3.25	145.2/3.49
		Noise (EPNdB): Lateral/Flyover/Approach	91.6/80.3/88.8	NA/NA/NA	86.1/80.7/91.8	88.5/82.6/94.2	NA/NA/NA
External Dimensions (ft.)		Length	111.0	116.7	111.0	129.7	138.2
		Height	27.0	40.3	38.6	40.3	40.3
		Span	104.0	117.8	117.4	117.8	117.8
Internal Dimensions (ft.)		**Length:** Main Seating/Net/Gross	36.0/54.4/60.6	85.7/85.7/85.7	79.0/79.0/79.0	98.5/98.5/98.5	107.2/107.2/107.2
		Height/Dropped Aisle Depth	6.2/flat floor	7.1/flat floor	7.4/flat floor	7.1/flat floor	7.1/flat floor
		Width: Max/Floor	8.0/6.8	11.6/10.7	12.1/11.7	11.6/10.7	11.6/10.7
Baggage		**Internal:** Cu. ft./lb.	195/2,500	NA/NA	NA/NA	NA/NA	NA/NA
		External: Cu. ft./lb.	—/—	274/NA	128/NA	593/NA	775/NA
Power		Engines	2 GE Passport 20-19BB1B	2 CFMI LEAP-1B27	2 P&W PW1127G	2 CFMI LEAP-1B28	2 CFMI LEAP-1B28
		Output (lb. each)/Flat Rating	18,920/ISA+15C	26,400/ISA+15C	26,800/ISA+15C	27,900/ISA+15C	27,900/ISA+15C
		Inspection Interval/Manu. Service Plan Interval	OC/—	OC/—	OC/—	OC/—	OC/
Weights (lb.)		Max Ramp	115,100	177,500	173,283	181,700	195,200
		Max Takeoff	114,850	177,000	172,401	181,200	194,700
		Max Landing	87,600	145,600	140,875	152,800	163,900
		Zero Fuel	67,500c	138,700c	116,845c	145,400c	156,500c
		BOW	60,900	101,550	104,000***	105,200	111,750
		Max Payload	6,600	37,150	12,845	40,200	44,750
		Useful Load	54,200	75,950	69,283	76,500	83,450
		Max Fuel	51,952	67,690	66,209	69,553	73,097
		Available Payload w/Max Fuel	2,248	8,260	3,074	6,947	10,353
		Available Fuel w/Max Payload	47,600	38,800	56,438	36,300	38,700
Limits		MMO	0.950	0.820	0.820	0.820	0.820
		Trans. Alt. FL/VMO	FL 350/320	FL 260/340	FL 250/350	FL 260/340	FL 260/340
		PSI/Sea-Level Cabin	10.7/32,000	9.0/24,000	9.2/NA	9.0/24,000	9.0/24,000
Airport Performance		TOFL (SL elev./ISA temp.)	5,760	6,820	6,217	6,600	8,380
		TOFL (5,000-ft. elev.@25C)	8,679	NA	8,189	NA	NA
		Mission Weight	114,850	NA	172,401	NA	NA
		NBAA IFR Range	8,070	6,810	6,750	6,680	6,600
		V2	137	NA	NA	NA	NA
		VREF	108	118	119	120	122
		Landing Distance	2,216	2,360	2,740	2,335	2,520
Climb		Time to Climb/Altitude	20/FL 370	23/FL 360	19/FL 350	25/FL 360	25/FL 340
		FAR 25 Engine-Out Rate (fpm)	NA	NA	NA	NA	NA
		FAR 25 Engine-Out Gradient (ft./nm)	NA	NA	NA	NA	NA
Ceiling (ft.)		Certificated	51,000	41,000	41,000	41,000	41,000
		All-Engine Service	43,000	41,000	41,000	41,000	41,000
		Engine-Out Service	26,600	NA	24,000	NA	NA
Cruise	**Long Range**	TAS	488	456	447	456	456
		Fuel Flow	2,924	4,903	4,004***	5,182	5,630
		Altitude	FL 450	FL 410	FL 410	FL 410	FL 410
		Specific Range	0.167	0.093	0.112	0.088	0.081
	High Speed	TAS	516	471	465	471	471
		Fuel Flow	3,099	4,529	4,637***	4,710	5,120
		Altitude	FL 470	FL 410	FL 410	FL 410	FL 410
		Specific Range	0.167	0.104	0.100	0.100	0.092
NBAA IFR Ranges (200-nm alternate)	**Max Payload** (w/available fuel)	Nautical Miles	7,053	3,060	5,250	2,655	2,615
		Average Speed	481	439	447	439	439
		Trip Fuel	44,487	33,177	51,295	30,419	32,397
		Specific Range/Altitude	0.159/FL 510	0.092/FL 370	0.102/FL 410	0.087/FL 370	0.081/FL 350
	Max Fuel (w/available payload)	Nautical Miles	7,980	6,525	6,750	6,465	6,255
		Average Speed	482	448	442	450	450
		Trip Fuel	49,009	63,026	61,436	64,874	68,030
		Specific Range/Altitude	0.163/FL 510	0.104/FL 410	0.110/FL 410	0.100/FL 410	0.092/FL 410
	Eight Passengers (w/available fuel)	Nautical Miles	8,042	6,810	6,750	6,680	6,600
		Average Speed	482	448	442	450	450
		Trip Fuel	49,027	63,214	61,436	64,981	68,195
		Specific Range/Altitude	0.164/FL 510	0.108/FL 410	0.110/FL 410	0.103/FL 410	0.097/FL 410
	Ferry	Nautical Miles	8,180	6,885	6,870	6,755	6,660
		Average Speed	482	448	NA	450	450
		Trip Fuel	49,071	63,250	60,994	65,022	68,212
		Specific Range/Altitude	0.167/FL 510	0.109/FL 410	0.113/FL 410	0.104/FL 410	0.098/FL 410
Missions (8 passengers)	**1,000 nm**	Runway	3,363	3,640	3,543	3,345	3,630
		Flight Time	2+11	2+26	2+26	2+25	2+25
		Fuel Used	6,004	8,909	8,591	9,255	9,793
		Specific Range/Altitude	0.167/FL 510	0.112/FL 410	0.116/FL 410	0.108/FL 410	0.102/FL 410
	3,000 nm	Runway	3,493	3,940	4,114	4,055	4,505
		Flight Time	6+18	6+51	6+54	6+49	6+48
		Fuel Used	16,500	25,596	25,148	26,782	28,430
		Specific Range/Altitude	0.182/FL 510	0.117/FL 410	0.119/FL 410	0.112/FL 410	0.106/FL 410
	6,000 nm	Runway	4,417	5,480	5,308	5,720	6,545
		Flight Time	12+28	13+26	13+38	13+23	13+23
		Fuel Used	34,737	54,502	53,086	57,265	61,004
		Specific Range/Altitude	0.173/FL 510	0.110/FL 410	0.113/FL 410	0.105/FL 410	0.098/FL 410
Remarks		Certification Basis	FAR 25, 2018; EASA CS 25, 2019	FAR 25 A137, A141, 2026 VIP cabin; includes seven auxiliary fuel tanks. *BCA* estimate.	FAR 25, 1999/2018 *Also available as -271N with CFM LEAP1A-26 engines with 26,600 lbf; includes five additional center tanks and VIP cabin. **BCA* estimate. ***ACJ estimate.	FAR 25 A137, A141, 2017 VIP cabin; includes seven auxiliary fuel tanks. *BCA* estimate.	FAR 25 A137, A141, 2018 VIP cabin; includes eight auxiliary fuel tanks. *BCA* estimate.