
decisionengine

Release 1.1.1

Fermi Research Alliance, LLC.

May 14, 2020

CONTENTS

1	Release Notes	3
2	Developer Documentation	7
3	Source code	11
4	Indices and tables	29
	Python Module Index	31
	Index	33

The Decision Engine is a critical component of the HEP Cloud Facility. It provides the functionality of resource scheduling for disparate resource providers, including those which may have a cost or a restricted allocation of cycles

RELEASE NOTES

1.1 Release 1.1.0

In this release:

- Fixed. https://github.com/HEPCloud/decisionengine_modules/issues/108 “Supply Postgres script to delete fields in main database before a certain date”
- significant code cleanup and pep8 compliance
- unit test work
- CI (GitHub actions and Travis) is introduced

commits

f894b1d : Skip unittest (#77)

632e64b : Add ipython

f681a79 : Make python 2.7 tests run on 1.1 branch

d6a32c0 : implementation of data reaper (#75)

2ad8614 : Use sparse checkout for first checkout to get .github/actions (#65)

812f032 : Cat output of pytest log Exit pylint entripoint with the line count of pep8 and pylint logs Deal with (detach from ...) Only tar up (S)RPMS dirs for rpm build.

6b05ec7 : Fix errors reported by run_pylint (#62)

d9f5b66 : Setup pep8speaks

c3b8ac2 : Run github actions as non-root uid. Install packages in virtualenv and remove system rpms.

ae01f9e : Support Python 3 for Boost Python

579761c : Support Python 3 for Boost Python

044b979 : Remove unnecessary using declarations.

00f6d00 : Add extra header dependency due to Boost Python ommission.

24e0795 : Apply clang-format

17c17f9 : Remove JSON dependency.

faa0b22 : Massive cleanup.

07b555f : Updates to Github Actions to allow building with python3.6

fef6c11 : Fix errors when running pylint.sh multiple times

da6f077 : Autopep8 -i fixes

39fe5b3 : TaskManager: fix calling log_exception with correct number of arguments and minor format changes to reduce PEP8 warnings

17396da : logicengine: get rid of compiler warnings

01dc3d1 : Only track what we need

b609d73 : Configure coveralls (and some minor cleanup)

bd9ed5e : Many C++ cleanups

2a61876 : Add Badges

c864f27 : Do not call pytest fixtures directly.

307db5f : white space fix

882b58f : fix unit tests

1da687c : Replace Boost facilities with C++ STL ones.

5a6e6b1 : Run tests on push

8404245 : Add missing Boost regex library dependency.

ceb5fe7 : Apply clang-format to files that were missed earlier.

3de9940 : Apply clang-format to C++ code.

8a8f560 : Cache venv directory instead

ad017ce : Build private boost for testing

928c64a : Test pip cache

358939a : Adjust CMakeLists.txt files to use correct Python versions

9f0ddb3 : Add pylint github action.

5e6ce4a : Remove more unused C++ files.

63717fe : Setup travis to use new cmake var

74fab2a : Use cmake argument -DPYVER=3.6 to build python3 library <https://fermicloud140.fnal.gov/reviews/r/31/>

843f30c : Minor cleanups per travis-lint

a538cac : Remove unused C++ files.

4c9d125 : Update repo where action is taken from

87fb2d9 : Update rpms installed in docker image. Update entrypoint.sh to use cmake3.

199ee87 : Find python3 libraries using cmake3 from epel rpm Also need to install python3-devel

4c79d2c : Remove unused GNUmakefiles.

94342ee : Add unit test as a Github Action

1a0e102 : more advanced travis.yml

0be413f : Add helper file for pip

7794327 : Make recursive import happy

7005c78 : Add simple target

de8b0fa : python3 compliance: replace string.join() where appropriate, handle UserDict

2662e6c : note required packages
3b87119 : Add missing header includes.
3e79b84 : Remove defunct code and its tests
b1dbe1a : Ensure attribs are defined at **init**
c4ad78a : Correct logger arguments do avoid duplicate string parse
a8dcc67 : Remove unused imports (per pylint)
d3502b5 : Remove obsolete CVS directories.
d744111 : add six module to the list of required modules
0a9b1e8 : Fix class declaration
b83157e : Handle metaclasses
549f33b : Add config for Travis CI
ee71044 : Drop trailing white space
3f82af6 : Python3 forward compatible syntax
28bf291 : Add safe (for python 2.7) python3 compatible syntax
1d1d76f : prepare for python3

DEVELOPER DOCUMENTATION

First command `cd` is just to make sure that you end up in a directory that will contain two subdirectory `decisionengine` and `decisionengine_modules`. Of course this can be done in any directory, not necessarily home directory.

2.1 Decisionengine framework

2.1.1 Prerequisites:

```
yum install -y https://dl.fedoraproject.org/pub/epel/epel-release-latest-7.noarch.rpm
yum install -y https://download.postgresql.org/pub/repos/yum/repos/EL-7-x86_64/
↳ pgdg-redhat-repo-latest.noarch.rpm
yum install -y python3 python3-pip cmake3 boost-devel python36-devel boost-python36-
↳ devel postgresql11 postgresql11-server
pip3 install pandas DBUtils psycpg2-binary tabulate mock pytest
```

2.1.2 Build & test

```
cd
git clone https://github.com/HEPCloud/decisionengine

export PYTHONPATH=`pwd`

mkdir decisionengine/framework/logicengine/cxx/build
cd decisionengine/framework/logicengine/cxx/build
cmake3 .. -DPYVER=3.6
make -j <number> # say number of CPUs on your box
cd ../../
ln -s cxx/build/ErrorHandler/RE.so
ln -s cxx/build/ErrorHandler/libLogicEngine.so
export LD_LIBRARY_PATH=`pwd`
cd ../../
#pytest -v --tb=native
python3 -m pytest

===== test session starts
↳ =====
platform linux -- Python 3.6.8, pytest-5.3.5, py-1.8.1, pluggy-0.13.1
rootdir: /root/junjk/decisionengine
collected 26 items
```

(continues on next page)

(continued from previous page)

```

framework/dataspace/tests/test_Reaper.py .....
↳ [ 26%]
framework/logicengine/tests/test_cascaded_rules.py ..
↳ [ 34%]
framework/logicengine/tests/test_construction.py .....
↳ [ 53%]
framework/logicengine/tests/test_facts.py .....
↳ [ 73%]
framework/logicengine/tests/test_pandas_fact.py ..
↳ [ 80%]
framework/logicengine/tests/test_rule_with_negated_fact.py ..
↳ [ 88%]
framework/logicengine/tests/test_simple_configuration.py ..
↳ [ 96%]
framework/util/tests/test_tsort.py .
↳ [100%]

```

```

===== 26 passed in 23.86s_
↳=====

```

2.2 Decisionengine_modules

2.2.1 Prerequisites:

In Addition to above installed packages

```

yum install condor
pip3 install htcondor boto boto3 google_auth google-api-python-client gcs-oauth2-boto-
↳plugin

```

2.2.2 Test

```

cd

git clone https://github.com/HEPCloud/decisionengine_modules
python3 -m pytest decisionengine_modules

```

Current status:

```

[root@fermicloud371 tmp]# python3 -m pytest decisionengine_modules
===== test session starts_
↳=====
platform linux -- Python 3.6.8, pytest-5.3.5, py-1.8.1, pluggy-0.13.1
rootdir: /root/junk
collected 85 items

decisionengine_modules/AWS/tests/test_AWSInstancePerformance.py ..
↳ [ 2%]
decisionengine_modules/AWS/tests/test_AWSJobLimits.py ..
↳ [ 4%]
decisionengine_modules/AWS/tests/test_AWSOccupancyWithSourceProxy.py ..
↳ [ 7%]

```

(continues on next page)

(continued from previous page)

```

decisionengine_modules/AWS/tests/test_AWSSpotPriceWithSourceProxy.py ..
↳ [ 9%]
decisionengine_modules/AWS/tests/test_AWS_figure_of_merit_publisher.py ..
↳ [ 11%]
decisionengine_modules/AWS/tests/test_AWS_price_performance_publisher.py ..
↳ [ 14%]
decisionengine_modules/AWS/tests/test_FigureOfMerit.py ...
↳ [ 17%]
decisionengine_modules/tests/test_AwsBurnRate.py ..
↳ [ 20%]
decisionengine_modules/tests/test_GCEBillingInfo.py ..
↳ [ 22%]
decisionengine_modules/tests/test_GCEFigureOfMerit_publisher.py ..
↳ [ 24%]
decisionengine_modules/tests/test_GCEInstancePerformanceInfo.py ..
↳ [ 27%]
decisionengine_modules/tests/test_GCEPricePerformance_publisher.py ..
↳ [ 29%]
decisionengine_modules/tests/test_GCEResourceLimits.py ..
↳ [ 31%]
decisionengine_modules/tests/test_GceBurnRate.py ..
↳ [ 34%]
decisionengine_modules/tests/test_GceFigureOfMerit.py ..
↳ [ 36%]
decisionengine_modules/tests/test_GceOccupancy.py ..
↳ [ 38%]
decisionengine_modules/tests/test_NerscAllocationInfo.py ..
↳ [ 41%]
decisionengine_modules/tests/test_NerscFigureOfMerit.py ..
↳ [ 43%]
decisionengine_modules/tests/test_NerscFigureOfMerit_publisher.py ..
↳ [ 45%]
decisionengine_modules/tests/test_NerscInstancePerformance.py ..
↳ [ 48%]
decisionengine_modules/tests/test_NerscJobInfo.py ..
↳ [ 50%]
decisionengine_modules/tests/test_factory_client.py ....
↳ [ 55%]
decisionengine_modules/tests/test_factory_entries.py ....
↳ [ 60%]
decisionengine_modules/tests/test_factory_global.py ....
↳ [ 64%]
decisionengine_modules/tests/test_fomorderplugin.py ....
↳ [ 69%]
decisionengine_modules/tests/test_grid_figure_of_merit.py .
↳ [ 70%]
decisionengine_modules/tests/test_htcondor_query.py ....
↳ [ 75%]
decisionengine_modules/tests/test_job_clustering.py .....
↳ [ 81%]
decisionengine_modules/tests/test_job_clustering_publisher.py ..
↳ [ 83%]
decisionengine_modules/tests/test_job_q.py ...
↳ [ 87%]
decisionengine_modules/tests/test_slots.py ..
↳ [ 89%]
decisionengine_modules/tests/glideinwms/publishers/test_decisionenginemonitor.py ...
↳ [ 92%]

```

(continues on next page)

(continued from previous page)

```
decisionengine_modules/tests/glideinwms/publishers/test_fe_group_classads.py ...
↳ [ 96%]
decisionengine_modules/tests/glideinwms/publishers/test_glideclientglobal.py ...
↳ [100%]

===== warnings summary =====
↳ =====
/usr/local/lib/python3.6/site-packages/boto/plugin.py:40
  /usr/local/lib/python3.6/site-packages/boto/plugin.py:40: DeprecationWarning: the
↳ imp module is deprecated in favour of importlib; see the module's documentation for
↳ alternative uses
    import imp

-- Docs: https://docs.pytest.org/en/latest/warnings.html
===== 85 passed, 1 warning in 9.73s =====
↳ =====
```

SOURCE CODE

3.1 Welcome to decisionengine's documentation!

3.1.1 decisionengine package

Subpackages

decisionengine.framework package

Subpackages

decisionengine.framework.configmanager package

Submodules

decisionengine.framework.configmanager.ConfigManager module

```
class decisionengine.framework.configmanager.ConfigManager.ConfigManager
    Bases: object
    check_keys (channel_conf_dict)
        check that channel config has mandatory keys :type data: dict
    static create (module_name, class_name, parameters)
    get_channels ()
    get_global_config ()
    get_produces (channel_config)
    is_updated ()
    load ()
    reload ()
    validate_channel (channel)
        Validate channels :type channel: dict
```

Module contents

decisionengine.framework.dataspace package

Subpackages

decisionengine.framework.dataspace.datasources package

Submodules

decisionengine.framework.dataspace.datasources.postgresql module

```
class decisionengine.framework.dataspace.datasources.postgresql.Postgresql (config_dict)
    Bases: decisionengine.framework.dataspace.datasource.DataSource
    Implementation of postgresql data source
    _Postgresql__query (query_string, values=None, cursor_factory=None)
    _abc_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache_version = 185
    _abc_registry = <_weakrefset.WeakSet object>
    _delete (sql_query, values=None)
    _insert (table_name_or_sql_query, record=None)
    _insert_returning_result (table_name_or_sql_query, record=None)
    _remove (sql_query, values=None)
    _select (query_string, values=None, cursor_factory=None)
    _select_dictresult (sql_query, values=None)
    _select_getresult (sql_query, values=None)
    _select_tuple (sql_query, values)
    _update (query_string, values=None)
    _update_returning_result (query_string, values=None)
    close ()
        Close all connections to the database
    connect ()
        Create a pool of database connections
    create_tables ()
        Create database tables
    delete_data_older_than (days)
        Delete data older than days interval :type days: int :arg days: remove data older than days interval
    duplicate_datablock (taskmanager_id, generation_id, new_generation_id)
        For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id
        for the datablock copy
```


Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **new_generation_id** (int) – generation_id of the new datablock created

get_connection ()

get_datablock (taskmanager_id, generation_id)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data

get_dataproduct (taskmanager_id, generation_id, key)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_header (taskmanager_id, generation_id, key)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_last_generation_id (taskmanager_name, taskmanager_id=None)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **name** (string) – task manager name
- **taskmanager_id** (string) – task manager id

get_metadata (taskmanager_id, generation_id, key)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

get_schema (table=None)

Given the table name return it's schema

Parameters **table** (string) – Name of the table

get_taskmanager (taskmanager_name, taskmanager_id=None)

Retrieve TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve

insert (*taskmanager_id, generation_id, key, value, header, metadata*)

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*string*) – taskmanager_id for generation to be retrieved
- **generation_id** (*int*) – generation_id of the data
- **key** (*string*) – key for the value
- **value** (*object*) – Value can be an object or dict
- **header** (*Header*) – Header for the value
- **header** – Metadata for the value

store_taskmanager (*name, taskmanager_id*)

Store TaskManager :type taskmanager_name: *string* :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: *string* :arg taskmanager_id: id of taskmanager to retrieve

tables = {'dataprodukt': ['taskmanager_id TEXT', 'generation_id INT', 'key TEXT', 'va

update (*taskmanager_id, generation_id, key, value, header, metadata*)

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*string*) – taskmanager_id for generation to be retrieved
- **generation_id** (*int*) – generation_id of the data
- **key** (*string*) – key for the value
- **value** (*object*) – Value can be an object or dict
- **header** (*Header*) – Header for the value
- **header** – Metadata for the value

decisionengine.framework.dataspace.datasources.postgresql.**generate_insert_query** (*table_name, keys*)

Generate insert query given table name and list of fields

Parameters

- **table_name** (*str*) – Name of the table to insert into
- **keys** – List of column names

Keys *list*

Return type *str* - insert query

Module contents

Submodules

decisionengine.framework.dataspace.datablock module

```
class decisionengine.framework.dataspace.datablock.DataBlock (dataspace,
                                                    name, taskman-
                                                    ager_id=None,
                                                    genera-
                                                    tion_id=None, se-
                                                    quence_id=None)
```

Bases: object

_insert (*key, value, header, metadata*)
 Insert a new product into database with header and metadata

_setitem (*key, value, header, metadata=None*)
 put a product in the database with header and metadata

_update (*key, value, header, metadata*)
 Update an existing product in the database with header and metadata

duplicate ()
 Duplicate the datablock and return this new DataBlock. The intent is that at the point the duplication occurs there is only information from the sources in the DataBlock. This also increments the generation_id of this DataBlock.

TODO: Also update the header and the metadata information TODO: Make this threadsafe

Return type *DataBlock*

get (*key, default=None*)
 Return the value associated with the key in the database

Return type dict

get_header (*key*)
 Return the Header associated with the key in the database

Return type *Header*

get_metadata (*key*)
 Return the metadata associated with the key in the database

Return type *Metadata*

get_taskmanager (*taskmanager_name, taskmanager_id=None*)
 Retrieve TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve :rtype: :obj: dict

The dictionary returned looks like : {'timestamp': datetime.datetime(2017, 12, 20, 17, 37, 17, 503210, tzinfo=psycopg2.tz.FixedOffsetTimezone(offset=-360, name=None)),
 'sequence_id': 135L, 'name': 'AWS_Calculations', 'taskmanager_id': '77B16EB5-C79E-45B0-B1B1-37E846692E1D'}

is_expired (*key=None*)
 Check if the dataproduct for a given key or any key is expired

```
keys ()

mark_expired (expiration_time)
    Set the expiration_time for the current generation of the dataproduct and mark it as expired if expiration_time <= current time

put (key, value, header, metadata=None)
    Put data into the DataBlock

store_taskmanager (taskmanager_name, taskmanager_id)
    Persist TaskManager, returns sequence number :type taskmanager_name: string :type taskmanager_id:
    :obj: string :rtype: int

exception decisionengine.framework.dataspace.datablock.ExpiredDataError
    Bases: Exception
    Errors due to invalid Metadata

class decisionengine.framework.dataspace.datablock.Header (taskmanager_id, create_time=None, expiration_time=None, scheduled_create_time=None, creator='module', schema_id=None)

    Bases: collections.UserDict

    _abc_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache_version = 185
    _abc_registry = <_weakrefset.WeakSet object>
    default_data_lifetime = 1800

    is_valid ()
        Check if the Header has minimum required information

    required_keys = {'create_time', 'creator', 'expiration_time', 'scheduled_create_time',

exception decisionengine.framework.dataspace.datablock.InvalidHeaderError
    Bases: Exception
    Errors due to invalid Metadata

exception decisionengine.framework.dataspace.datablock.InvalidMetadataError
    Bases: Exception
    Errors due to invalid Metadata

exception decisionengine.framework.dataspace.datablock.KeyNotFoundError
    Bases: Exception
    Errors due to invalid Metadata

class decisionengine.framework.dataspace.datablock.Metadata (taskmanager_id, state='NEW', generation_id=None, generation_time=None, missed_update_count=0)

    Bases: collections.UserDict
```

```

    _abc_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache_version = 185
    _abc_registry = <_weakrefset.WeakSet object>
    required_keys = {'generation_id', 'generation_time', 'missed_update_count', 'state', '...'
    set_state (state)
        Set the state for the Metadata

    valid_states = {'END_CYCLE', 'METADATA_UPDATE', 'NEW', 'START_BACKUP'}
decisionengine.framework.dataspace.datablock.compress (obj)
    Compress python object :param obj: python object :return: compressed object
decisionengine.framework.dataspace.datablock.decompress (zbytes)
    Decompress zipped byte stream, convert to string. :param zbytes: byte stream :return: uncompressed string
decisionengine.framework.dataspace.datablock.zdumps (obj)
    Pickle and compress :param obj: a python object :return: compressed string
decisionengine.framework.dataspace.datablock.zloads (zbytes)
    Decompress and unpickle If input is not compressed attempts to just unpickle it

    Parameters zbytes – compressed bytes
    Returns returns python object

```

decisionengine.framework.dataspace.datasource module

```

class decisionengine.framework.dataspace.datasource.DataSource (config)
    Bases: object

    _abc_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache = <_weakrefset.WeakSet object>
    _abc_negative_cache_version = 185
    _abc_registry = <_weakrefset.WeakSet object>

    abstract close ()
        Close all connections to the database

    abstract connect ()
        Create a pool of database connections

    abstract create_tables ()
        Create database tables

    dataproduct_table = 'dataproduct'
        Name of the dataproduct table

    abstract delete_data_older_than (days)
        Delete data older that interval :type days: long :arg days: remove data older than interval

    abstract duplicate_datablock (taskmanager_id, generation_id, new_generation_id)
        For the given taskmanager_id, make a copy of the datablock with given generation_id, set the generation_id
        for the datablock copy

```

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **new_generation_id** (int) – generation_id of the new datablock created

abstract get_datablock (*taskmanager_id, generation_id*)

Return the entire datablock from the dataproduct table for the given taskmanager_id, generation_id

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data

abstract get_dataproduct (*taskmanager_id, generation_id, key*)

Return the data from the dataproduct table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_header (*taskmanager_id, generation_id, key*)

Return the header from the header table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_last_generation_id (*name, taskmanager_id=None*)

Return last generation id for current task manager or taskmanager w/ task_manager_id.

Parameters

- **name** (string) – task manager name
- **taskmanager_id** (string) – task manager id

abstract get_metadata (*taskmanager_id, generation_id, key*)

Return the metadata from the metadata table for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (string) – taskmanager_id for generation to be retrieved
- **generation_id** (int) – generation_id of the data
- **key** (string) – key for the value

abstract get_schema (*table=None*)

Given the table name return it's schema

Parameters **table** (string) – Name of the table

abstract get_taskmanager (*taskmanager_name, taskmanager_id*)

Retrieve TaskManager :type taskmanager_name: string :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: string :arg taskmanager_id: id of taskmanager to retrieve

```
header_table = 'header'
```

Name of the header table

```
abstract insert (taskmanager_id, generation_id, key, value, header, metadata)
```

Insert data into respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*string*) – taskmanager_id for generation to be retrieved
- **generation_id** (*int*) – generation_id of the data
- **key** (*string*) – key for the value
- **value** (*object*) – Value can be an object or dict
- **header** (*Header*) – Header for the value
- **header** – Metadata for the value

```
metadata_table = 'metadata'
```

Name of the metadata table

```
abstract store_taskmanager (taskmanager_name, taskmanager_id)
```

Store TaskManager :type taskmanager_name: *string* :arg taskmanager_name: name of taskmanager to retrieve :type taskmanager_id: *string* :arg taskmanager_id: id of taskmanager to retrieve

```
taskmanager_table = 'taskmanager'
```

Name of the taskmanager table

```
abstract update (taskmanager_id, generation_id, key, value, header, metadata)
```

Update the data in respective tables for the given taskmanager_id, generation_id, key

Parameters

- **taskmanager_id** (*string*) – taskmanager_id for generation to be retrieved
- **generation_id** (*int*) – generation_id of the data
- **key** (*string*) – key for the value
- **value** (*object*) – Value can be an object or dict
- **header** (*Header*) – Header for the value
- **header** – Metadata for the value

decisionengine.framework.dataspace.dataspace module

```
class decisionengine.framework.dataspace.dataspace.DataSourceLoader
```

Bases: object

```
_ds = None
```

```
static create_datasource (module_name, class_name, config)
```

```
class decisionengine.framework.dataspace.dataspace.DataSpace (config)
```

Bases: object

DataSpace class is collection of datablocks and provides interface to the database used to store the actual data

```
_tables_created = False
```

Description of tables and their columns

```
close ()
```

```
delete (taskmanager_id, all_generations=False)
duplicate_datablock (taskmanager_id, generation_id, new_generation_id)
get_dataproduct (taskmanager_id, generation_id, key)
get_header (taskmanager_id, generation_id, key)
get_last_generation_id (taskmanager_name, taskmanager_id=None)
get_metadata (taskmanager_id, generation_id, key)
get_taskmanager (taskmanager_name, taskmanager_id=None)
insert (taskmanager_id, generation_id, key, value, header, metadata)
mark_demented (taskmanager_id, keys, generation_id=None)
mark_expired (taskmanager_id, generation_id, key, expiry_time)
store_taskmanager (name, id)
update (taskmanager_id, generation_id, key, value, header, metadata)

exception decisionengine.framework.dataspace.dataspace.DataSpaceConfigurationError
    Bases: Exception
    Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceConnectionError
    Bases: Exception
    Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceError
    Bases: Exception
    Errors related to database access

exception decisionengine.framework.dataspace.dataspace.DataSpaceExistsError
    Bases: Exception
    Errors related to database access

class decisionengine.framework.dataspace.dataspace.Reaper (config)
    Bases: object
    Reaper provides functionality of periodic deletion of data older than retention_interval in days
    _reaper_loop (delay)
    _set_state (value)
    get_retention_interval ()
    get_state ()
    reap ()
    set_retention_interval (interval)
    start (delay=0)
        Start thread with an optional delay to start the thread in X seconds
    stop ()
```



```

class decisionengine.framework.dataspace.dataspace.Singleton
    Bases: type

    Singleton pattern using Metaclass http://stackoverflow.com/questions/6760685/creating-a-singleton-in-python

    _instances = {}

class decisionengine.framework.dataspace.dataspace.State
    Bases: enum.Enum

    An enumeration.

    ERROR = 7

    IDLE = 1

    RUNNING = 3

    SLEEPING = 4

    STARTING = 2

    STOPPED = 6

    STOPPING = 5

```

Module contents

decisionengine.framework.engine package

Submodules

decisionengine.framework.engine.DecisionEngine module

Main loop for Decision Engine. The following environment variable points to decision engine configuration file: `DECISION_ENGINE_CONFIG_FILE` if this environment variable is not defined the `DE-Config.py` file from the `../tests/etc/` directory will be used.

```

class decisionengine.framework.engine.DecisionEngine.DecisionEngine(cfg,
                                                                    server_address,
                                                                    Re-
                                                                    questHandler-
                                                                    Class)

Bases: socketserver.ThreadingMixIn, xmlrpc.server.SimpleXMLRPCServer

_dispatch (method, params)
    Dispatches the XML-RPC method.

    XML-RPC calls are forwarded to a registered function that matches the called XML-RPC method name.
    If no such function exists then the call is forwarded to the registered instance, if available.

    If the registered instance has a _dispatch method then that method will be called with the name of the
    XML-RPC method and its parameters as a tuple e.g. instance._dispatch('add',(2,3))

    If the registered instance does not have a _dispatch method then the instance will be searched to find a
    matching method and, if found, will be called.

    Methods beginning with an '_' are considered private and will not be called.

get_logger ()

handle_sighup (signum, frame)

```

```
reaper_start (delay)
reaper_status ()
reaper_stop ()
reload_config ()
rpc_print_product (product, columns=None, query=None)
rpc_print_products ()
rpc_reaper_start (delay=0)
    Start the reaper process after 'delay' seconds. Default 0 seconds delay. :type delay: int
rpc_reaper_status ()
rpc_reaper_stop ()
rpc_reload_config ()
rpc_show_config (channel=None)

rpc_start_channel (channel)
rpc_start_channels ()
rpc_status ()
rpc_stop ()
rpc_stop_channel (channel)
rpc_stop_channels ()
start_channel (channel)
start_channels ()
stop_channel (channel)
stop_channels ()

class decisionengine.framework.engine.DecisionEngine.RequestHandler (request,
                                                                    client_address,
                                                                    server)
    Bases: xmlrpc.server.SimpleXMLRPCRequestHandler
    rpc_paths = ('/RPC2',)

class decisionengine.framework.engine.DecisionEngine.RpcServer (server_address,
                                                                Re-
                                                                questHandler-
                                                                Class)
    Bases: socketserver.ThreadingMixIn, xmlrpc.server.SimpleXMLRPCServer

class decisionengine.framework.engine.DecisionEngine.Worker (task_manager, con-
                                                            fig)
    Bases: multiprocessing.context.Process
    run ()
        Method to be run in sub-process; can be overridden in sub-class
```

decisionengine.framework.engine.de_client module

Module contents

decisionengine.framework.modules package

Submodules

decisionengine.framework.modules.LogicEngine module

```
class decisionengine.framework.modules.LogicEngine.LogicEngine (set_of_parameters)  
    Bases: decisionengine.framework.modules.Module.Module  
    evaluate (data_block)
```

decisionengine.framework.modules.Module module

```
class decisionengine.framework.modules.Module.Module (set_of_parameters)  
    Bases: object  
    get_data_block ()  
    get_paramaters ()  
    set_data_block (data_block)
```

decisionengine.framework.modules.Publisher module

```
class decisionengine.framework.modules.Publisher.Publisher (set_of_parameters)  
    Bases: decisionengine.framework.modules.Module.Module  
    consumes (name_list)  
    publish (data_block=None)
```

decisionengine.framework.modules.Source module

```
class decisionengine.framework.modules.Source.Source (set_of_parameters)  
    Bases: decisionengine.framework.modules.Module.Module  
    acquire ()  
    produces (name_schema_id_list)
```

decisionengine.framework.modules.SourceProxy module

Fill in data from another channel data block

```
class decisionengine.framework.modules.SourceProxy.SourceProxy(*args,
                                                                **kwargs)
    Bases: decisionengine.framework.modules.Source.Source

    Source Proxy Channel configuration using source proxy must have in parameters 'channel_name', defining
    foreign channel name and 'Dataproducts', defining foreign (and optionally local) data keys. See consumes()
    doc. Example of source proxy configuration:

    "AWSJobLimits": { "module": "modules.source_proxy", "name": "SourceProxy", "parameters":
    {"channel_name": "channel_aws_config_data",
        "Dataproducts": [("aws_instance_limits", "Job_Limits")], "retries": 3,
        "retry_timeout": 20,
    },
    "schedule": 360,
},
_get_data(data_block, key)
acquire()
    Overrides Source class method
consumes()
    Assumes that self.datakeys has the following structure: is a list of tuples or singletons: [
        (data_product_name, data_product_name_translation), .... ] or [ data_product_name, ....
    ]
must_have = ('channel_name', 'Dataproducts')
produces()
    Assumes that self.datakeys has the following structure or
decisionengine.framework.modules.SourceProxy.main()
    Call this a a test unit or use as CLI of this module
decisionengine.framework.modules.SourceProxy.module_config_info()
    print this module configuration information
decisionengine.framework.modules.SourceProxy.module_config_template()
    print a template for this module configuration data
```

decisionengine.framework.modules.Transform module

```
class decisionengine.framework.modules.Transform.Transform(set_of_parameters)
    Bases: decisionengine.framework.modules.Module.Module

    consumes(name_list)

    produces(name_schema_id_list)

    transform()
```

decisionengine.framework.modules.de_logger module

Looger to use in all modules

```
decisionengine.framework.modules.de_logger.get_logger()
```

get default logger - "decision_engine" :rtype: logging.Logger - rotating file logger

```
decisionengine.framework.modules.de_logger.set_logging(log_file_name='/tmp/decision_engine_logs/decision_
max_file_size=2000000000,
max_backup_count=6)
```

Parameters

- **log_file_name** (str) – log file name
- **max_file_size** (int) – maximal size of log file. If reached save and start new log.
- **max_backup_count** (int) – start rotaion after this number is reached

Return type logging.Logger - rotating file logger

```
decisionengine.framework.modules.de_logger.set_stream_logging(logger_name="")
```

This is for debugging. Set stream logging for logger.

Parameters **logger_name** (str) – logger name

Return type logging.Logger

Module contents

decisionengine.framework.taskmanager package

Submodules

decisionengine.framework.taskmanager.TaskManager module

Task Manager

```
class decisionengine.framework.taskmanager.TaskManager.Channel(channel_dict)
    Bases: object
```

Decision Channel. Instantiates workers according to channel configuration

```
class decisionengine.framework.taskmanager.TaskManager.TaskManager(name,
                                                                    task_manager_id,
                                                                    genera-
                                                                    tion_id,
                                                                    chan-
                                                                    nel_dict,
                                                                    global_config)
```

Bases: object

Task Manager

```
data_block_put (data, header, data_block)
    Put data into data block
```

Parameters

- **data** (dict) – key, value pairs

- **header** (*Header*) – data header
- **data_block** (*DataBlock*) – data block

decision_cycle ()

Decision cycle to be run periodically (by trigger)

do_backup ()

Duplicate current data block and return its copy

Return type *DataBlock*

get_state ()

offline_task_manager (*current_data_block*)

offline and stop task manager

run ()

Task Manager main loop

run_logic_engine (*data_block=None*)

Run Logic Engine.

Parameters **data_block** (*DataBlock*) – data block

run_publishers (*actions, facts, data_block=None*)

Run Publishers in main process.

Parameters **data_block** (*DataBlock*) – data block

run_source (*src*)

Get the data from source and put it into the data block

Parameters **src** (*Worker*) – source Worker

run_transform (*transform, data_block*)

Run a transform

Parameters

- **transform** (*Worker*) – source Worker
- **data_block** (*DataBlock*) – data block

run_transforms (*data_block=None*)

Run transforms. So far in main process.

Parameters **data_block** (*DataBlock*) – data block

set_state (*state*)

start_sources (*data_block=None*)

Start sources, each in a separate thread

Parameters **data_block** (*DataBlock*) – data block

stop_task_manager ()

signal task manager to stop

wait_for_all (*events_done*)

Wait for all sources or transforms to finish

Parameters **events_done** (*list*) – list of events to wait for

wait_for_any (*events_done*)

Wait for any sources to finish

Parameters `events_done` (list) – list of events to wait for

class `decisionengine.framework.taskmanager.TaskManager.Worker` (*conf_dict*)
 Bases: object

Provides interface to loadable modules and events to synchronise execution

DEFAULT_SCHEDULE = 300

`decisionengine.framework.taskmanager.TaskManager.log_exception` (*logger*,
header_message)

Module contents

decisionengine.framework.util package

Submodules

decisionengine.framework.util.tsort module

See:

https://en.wikipedia.org/wiki/Topological_sorting

Kahn's topological sorting algorithm

L Empty list that will contain the sorted elements S Set of all nodes with no incoming edge while S is non-empty do

 remove a node n from S add n to tail of L for each node m with an edge e from n to m do

 remove edge e from the graph if m has no other incoming edges then

 insert m into S

if graph has edges then return error (graph has at least one cycle)

else return L (a topologically sorted order)

`decisionengine.framework.util.tsort.tsort` (*graph*)

Function implementing Kahn's topological sorting algorithm returns two lists : sorted list and cyclic lost (if graph is acyclic second list is always None)

Return type list

Module contents

Module contents

Module contents

3.2 Indices and tables

- `genindex`
- `modindex`
- `search`

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

d

`decisionengine`, [27](#)
`decisionengine.framework`, [27](#)
`decisionengine.framework.configmanager`,
 [12](#)
`decisionengine.framework.configmanager.ConfigManager`,
 [11](#)
`decisionengine.framework.dataspace`, [21](#)
`decisionengine.framework.dataspace.datablock`,
 [15](#)
`decisionengine.framework.dataspace.datasources`,
 [17](#)
`decisionengine.framework.dataspace.datasources`,
 [14](#)
`decisionengine.framework.dataspace.datasources.postgresql`,
 [12](#)
`decisionengine.framework.dataspace.dataspace`,
 [19](#)
`decisionengine.framework.engine`, [23](#)
`decisionengine.framework.engine.de_client`,
 [23](#)
`decisionengine.framework.engine.DecisionEngine`,
 [21](#)
`decisionengine.framework.modules`, [25](#)
`decisionengine.framework.modules.de_logger`,
 [25](#)
`decisionengine.framework.modules.LogicEngine`,
 [23](#)
`decisionengine.framework.modules.Module`,
 [23](#)
`decisionengine.framework.modules.Publisher`,
 [23](#)
`decisionengine.framework.modules.Source`,
 [23](#)
`decisionengine.framework.modules.SourceProxy`,
 [24](#)
`decisionengine.framework.modules.Transform`,
 [24](#)
`decisionengine.framework.taskmanager`,
 [27](#)
`decisionengine.framework.taskmanager.TaskManager`,
 [25](#)
`decisionengine.framework.util`, [27](#)
`decisionengine.framework.util.tsort`, [27](#)

INDEX

Symbols

<code>_Postgresql__query()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12	<code>_abc_registry</code>	(decisionengine.framework.dataspace.datablock.Metadata attribute), 16
<code>_abc_cache</code>	(decisionengine.framework.dataspace.datablock.Header attribute), 16	<code>_abc_registry</code>	(decisionengine.framework.dataspace.datasource.DataSource attribute), 17
<code>_abc_cache</code>	(decisionengine.framework.dataspace.datablock.Metadata attribute), 16	<code>_abc_registry</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 12
<code>_abc_cache</code>	(decisionengine.framework.dataspace.datasource.DataSource attribute), 17	<code>_delete()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
<code>_abc_cache</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 12	<code>_dispatch()</code>	(decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 21
<code>_abc_negative_cache</code>	(decisionengine.framework.dataspace.datablock.Header attribute), 16	<code>_ds</code>	(decisionengine.framework.dataspace.datasource.Loader attribute), 19
<code>_abc_negative_cache</code>	(decisionengine.framework.dataspace.datablock.Metadata attribute), 17	<code>_get_data()</code>	(decisionengine.framework.modules.SourceProxy.SourceProxy method), 24
<code>_abc_negative_cache</code>	(decisionengine.framework.dataspace.datasource.DataSource attribute), 17	<code>_insert()</code>	(decisionengine.framework.dataspace.datablock.DataBlock method), 15
<code>_abc_negative_cache</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 12	<code>_insert()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
<code>_abc_negative_cache_version</code>	(decisionengine.framework.dataspace.datablock.Header attribute), 16	<code>_insert_returning_result()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
<code>_abc_negative_cache_version</code>	(decisionengine.framework.dataspace.datablock.Metadata attribute), 17	<code>_instances</code>	(decisionengine.framework.dataspace.datasource.Singleton attribute), 21
<code>_abc_negative_cache_version</code>	(decisionengine.framework.dataspace.datasource.DataSource attribute), 17	<code>_reaper_loop()</code>	(decisionengine.framework.dataspace.datasource.Reaper method), 20
<code>_abc_negative_cache_version</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 12	<code>_remove()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
<code>_abc_registry</code>	(decisionengine.framework.dataspace.datablock.Header attribute), 16	<code>_select()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
		<code>_select_dictresult()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
		<code>_select_getresult()</code>	(decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12

`method`), 12
`_select_tuple()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 24
`method`), 12
`_set_state()` (decisionengine.framework.modules.Transform.Transform method), 24
`method`), 20
`_setitem()` (decisionengine.framework.dataspace.datablock.DataBlock static method), 11
`method`), 15
`_tables_created` (decisionengine.framework.dataspace.dataspace.DataSource static method), 19
`attribute`), 19
`_update()` (decisionengine.framework.dataspace.datablock.DataBlock method), 17
`method`), 15
`_update()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
`method`), 12
`_update_returning_result()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
`method`), 12
`data_block_put()` (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 25
A
`acquire()` (decisionengine.framework.modules.Source.SourceDataBlock (class in decisionengine.framework.dataspace.datablock), method), 23
`acquire()` (decisionengine.framework.modules.SourceProxy.SourceProxy method), 24
C
`Channel` (class in decisionengine.framework.taskmanager.TaskManager), 25
`check_keys()` (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11
`close()` (decisionengine.framework.dataspace.datasource.DataSource (class in decisionengine.framework.dataspace.dataspace), method), 17
`close()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
`close()` (decisionengine.framework.dataspace.dataspace.DataSource DataSourceLoader (class in decisionengine.framework.dataspace.dataspace), method), 19
`close()` (decisionengine.framework.dataspace.dataspace.DataSource DataSourceConfigurationError, 20
`close()` (decisionengine.framework.dataspace.dataspace.DataSource DataSourceConnectionError, 20
`close()` (decisionengine.framework.dataspace.dataspace.DataSource DataSourceError, 20
`compress()` (in module decisionengine.framework.dataspace.datablock), 17
`decision_cycle()` (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26
`ConfigManager` (class in decisionengine.framework.configmanager.ConfigManager), 11
`connect()` (decisionengine.framework.dataspace.datasource.DataSource DecisionEngine (class in decisionengine.framework.engine.DecisionEngine), method), 17
`connect()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 12
`consumes()` (decisionengine.framework.modules.Publisher.Publisher method), 23
`consumes()` (decisionengine.framework.modules.SourceProxy.SourceProxy method), 24
`consumes()` (decisionengine.framework.modules.Transform.Transform method), 24
`create()` (decisionengine.framework.configmanager.ConfigManager.ConfigManager static method), 11
`create_datasource()` (decisionengine.framework.dataspace.dataspace.DataSourceLoader static method), 19
`create_tables()` (decisionengine.framework.dataspace.datasource.DataSource static method), 19
`create_tables()` (decisionengine.framework.dataspace.datablock.DataBlock static method), 11
`create_tables()` (decisionengine.framework.dataspace.datasources.postgresql.Postgresql static method), 12
`data_block_put()` (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 25
D
`DataBlock` (class in decisionengine.framework.dataspace.datablock), 23
`DataSource` (class in decisionengine.framework.dataspace.datasource), 17
`DataSourceLoader` (class in decisionengine.framework.dataspace.dataspace), 19
`DataSourceConfigurationError`, 20
`DataSourceConnectionError`, 20
`DataSourceError`, 20
`DataSourceExistsError`, 20
`decision_cycle()` (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26
`DecisionEngine` (class in decisionengine.framework.engine.DecisionEngine), 21
`decisionengine` module, 27
`decisionengine.framework` module, 27
`decisionengine.framework.configmanager` module, 12
`decisionengine.framework.configmanager.ConfigManager` module, 12

module, 11
 decisionengine.framework.dataspace
 module, 21
 decisionengine.framework.dataspace.datablock.delete_data_older_than() (decision-
 module, 15 engine.framework.dataspace.datasources.postgresql.Postgresql
 decisionengine.framework.dataspace.datasource method), 17
 module, 17 do_backup() (decision-
 decisionengine.framework.dataspace.datasources engine.framework.taskmanager.TaskManager.TaskManager
 module, 14 method), 26
 decisionengine.framework.dataspace.datasources.postgresql (decision-
 module, 12 engine.framework.dataspace.datablock.DataBlock
 decisionengine.framework.dataspace.dataspace method), 15
 module, 19 duplicate_datablock() (decision-
 decisionengine.framework.engine engine.framework.dataspace.datasource.DataSource
 module, 23 method), 17
 decisionengine.framework.engine.de_clientduplicate_datablock() (decision-
 module, 23 engine.framework.dataspace.datasources.postgresql.Postgresql
 decisionengine.framework.engine.DecisionEngine method), 12
 module, 21 duplicate_datablock() (decision-
 decisionengine.framework.modules engine.framework.dataspace.dataspace.DataSpace
 module, 25 method), 20
 decisionengine.framework.modules.de_logger
 module, 25
 decisionengine.framework.modules.LogicEngine (decisionengine.framework.dataspace.dataspace.State
 module, 23 attribute), 21
 decisionengine.framework.modules.Module evaluate() (decision-
 module, 23 engine.framework.modules.LogicEngine.LogicEngine
 decisionengine.framework.modules.Publisher method), 23
 module, 23 ExpiredDataError, 16
 decisionengine.framework.modules.Source
 module, 23
 decisionengine.framework.modules.SourceProxy
 module, 24 generate_insert_query() (in module decisio-
 decisionengine.framework.modules.Transform engine.framework.dataspace.datasources.postgresql),
 module, 24 14
 decisionengine.framework.taskmanager get() (decisionengine.framework.dataspace.datablock.DataBlock
 module, 27 method), 15
 decisionengine.framework.taskmanager.TaskManager get_channels() (decision-
 module, 25 engine.framework.configmanager.ConfigManager.ConfigManager
 decisionengine.framework.util method), 11
 module, 27 get_connection() (decision-
 decisionengine.framework.util.tsort engine.framework.dataspace.datasources.postgresql.Postgresql
 module, 27 method), 13
 decompress() (in module decisio- get_data_bock() (decision-
 engine.framework.dataspace.datablock), engine.framework.modules.Module.Module
 17 method), 23
 default_data_lifetime (decision- get_datablock() (decision-
 engine.framework.dataspace.datablock.Header engine.framework.dataspace.datasource.DataSource
 attribute), 16 method), 18
 DEFAULT_SCHEDULE (decision- get_datablock() (decision-
 engine.framework.taskmanager.TaskManager.Worker engine.framework.dataspace.datasources.postgresql.Postgresql
 attribute), 27 method), 13
 delete() (decisionengine.framework.dataspace.dataspace.DataSpace get_dataproduct() (decision-
 method), 19 engine.framework.dataspace.datasource.DataSource
 method), 18

get_dataproduct () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_dataproduct () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

get_global_config () (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

get_header () (decisionengine.framework.dataspace.datablock.DataBlock method), 15

get_header () (decisionengine.framework.dataspace.datasource.DataSource method), 18

get_header () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_header () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

get_header () (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

get_header () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_header () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

get_last_generation_id () (decisionengine.framework.datasource.DataSource method), 18

get_last_generation_id () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_last_generation_id () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

get_last_generation_id () (decisionengine.framework.dataspace.datasource.DataSource method), 20

get_logger () (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 21

get_logger () (in module decisionengine.framework.modules.de_logger), 25

get_metadata () (decisionengine.framework.dataspace.datablock.DataBlock method), 15

get_metadata () (decisionengine.framework.datasource.DataSource method), 18

get_metadata () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_metadata () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

get_paramaters () (decisionengine.framework.modules.Module.Module method), 23

get_produces () (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

get_retention_interval () (decisionengine.framework.dataspace.dataspace.Reaper method), 20

get_schema () (decisionengine.framework.dataspace.datasource.DataSource method), 18

get_schema () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_state () (decisionengine.framework.dataspace.dataspace.Reaper method), 20

get_state () (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

get_taskmanager () (decisionengine.framework.dataspace.datablock.DataBlock method), 15

get_taskmanager () (decisionengine.framework.dataspace.datasource.DataSource method), 18

get_taskmanager () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

get_taskmanager () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

handle_sighup () (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 21

Header (class in decisionengine.framework.dataspace.datablock), 16

header_table (decisionengine.framework.datasource.DataSource attribute), 18

idle (decisionengine.framework.dataspace.dataspace.State attribute), 21

insert () (decisionengine.framework.datasource.DataSource method), 19

insert () (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 13

insert () (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

InvalidHeaderError, 16

InvalidMetadataError, 16

is_expired () (decisionengine.framework.dataspace.datablock.DataBlock method), 15

is_updated() (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

is_valid() (decisionengine.framework.dataspace.datablock.Header method), 16

K

KeyNotFoundError, 16

keys() (decisionengine.framework.dataspace.datablock.DataBlock method), 15

L

load() (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

log_exception() (in module decisionengine.framework.taskmanager.TaskManager), 27

LogicEngine (class in decisionengine.framework.modules.LogicEngine), 23

M

main() (in module decisionengine.framework.modules.SourceProxy), 24

mark_demented() (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

mark_expired() (decisionengine.framework.dataspace.datablock.DataBlock method), 16

mark_expired() (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

Metadata (class in decisionengine.framework.dataspace.datablock), 16

metadata_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 19

module

- decisionengine, 27
- decisionengine.framework, 27
- decisionengine.framework.configmanager, 12
- decisionengine.framework.configmanager.ConfigManager, 11
- decisionengine.framework.dataspace, 21
- decisionengine.framework.dataspace.datablock, 15
- decisionengine.framework.dataspace.datasources, 17

O

offline_task_manager() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

P

Postgresql (class in decisionengine.framework.dataspace.datasources.postgresql), 12

produces() (decisionengine.framework.modules.Source.Source

method), 23

produces ((decisionengine.framework.modules.SourceProxy.SourceProxy method), 24

produces ((decisionengine.framework.modules.Transform.Transform method), 24

publish ((decisionengine.framework.modules.Publisher.Publisher method), 23

Publisher (class in decisionengine.framework.modules.Publisher), 23

put ((decisionengine.framework.dataspace.datablock.DataBlock method), 16

R

reap ((decisionengine.framework.dataspace.dataspace.Reaper method), 20

Reaper (class in decisionengine.framework.dataspace.dataspace), 20

reaper_start ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

reaper_status ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

reaper_stop ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

reload ((decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

reload_config ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

RequestHandler (class in decisionengine.framework.engine.DecisionEngine), 22

required_keys (decisionengine.framework.dataspace.datablock.Header attribute), 16

required_keys (decisionengine.framework.dataspace.datablock.Metadata attribute), 17

rpc_paths (decisionengine.framework.engine.DecisionEngine.RequestHandler attribute), 22

rpc_print_product ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_print_products ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_reaper_start ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_reaper_status ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_reaper_stop ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_show_config ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_start_channel ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_start_channels ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_status ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_stop ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_stop_channel ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

rpc_stop_channels ((decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

reload_config ((decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

RpcServer (class in decisionengine.framework.engine.DecisionEngine), 22

run ((decisionengine.framework.engine.DecisionEngine.Worker method), 22

run ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_logic_engine ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_publishers ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_request_handler ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_transform ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_transforms ((decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

run_engine ((decisionengine.framework.dataspace.dataspace.State

attribute), 21

S

set_data_bock() (decisionengine.framework.modules.Module.Module method), 23

set_logging() (in module decisionengine.framework.modules.de_logger), 25

set_retention_interval() (decisionengine.framework.dataspace.dataspace.Reaper method), 20

set_state() (decisionengine.framework.dataspace.datablock.Metadata method), 17

set_state() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

set_stream_logging() (in module decisionengine.framework.modules.de_logger), 25

Singleton (class in decisionengine.framework.dataspace.dataspace), 20

SLEEPING (decisionengine.framework.dataspace.dataspace.State attribute), 21

Source (class in decisionengine.framework.modules.Source), 23

SourceProxy (class in decisionengine.framework.modules.SourceProxy), 24

start() (decisionengine.framework.dataspace.dataspace.Reaper method), 20

start_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

start_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

start_sources() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

STARTING (decisionengine.framework.dataspace.dataspace.State attribute), 21

State (class in decisionengine.framework.dataspace.dataspace), 21

stop() (decisionengine.framework.dataspace.dataspace.Reaper method), 20

stop_channel() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

stop_channels() (decisionengine.framework.engine.DecisionEngine.DecisionEngine method), 22

stop_task_manager() (decisionengine.framework.taskmanager.TaskManager.TaskManager method), 26

STOPPED (decisionengine.framework.dataspace.dataspace.State attribute), 21

STOPPING (decisionengine.framework.dataspace.dataspace.State attribute), 21

store_taskmanager() (decisionengine.framework.dataspace.datablock.DataBlock method), 16

store_taskmanager() (decisionengine.framework.dataspace.datasource.DataSource method), 19

store_taskmanager() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 14

store_taskmanager() (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

T

tables (decisionengine.framework.dataspace.datasources.postgresql.Postgresql attribute), 14

TaskManager (class in decisionengine.framework.taskmanager.TaskManager), 25

taskmanager_table (decisionengine.framework.dataspace.datasource.DataSource attribute), 19

Transform (class in decisionengine.framework.modules.Transform), 24

transform() (decisionengine.framework.modules.Transform.Transform method), 24

tsort() (in module decisionengine.framework.util.tsort), 27

U

update() (decisionengine.framework.dataspace.datasource.DataSource method), 19

update() (decisionengine.framework.dataspace.datasources.postgresql.Postgresql method), 14

update() (decisionengine.framework.dataspace.dataspace.DataSpace method), 20

V

valid_states (decisionengine.framework.dataspace.datablock.Metadata attribute), 17

validate_channel() (decisionengine.framework.configmanager.ConfigManager.ConfigManager method), 11

W

`wait_for_all()` (*decisionengine.framework.taskmanager.TaskManager.TaskManager* method), [26](#)

`wait_for_any()` (*decisionengine.framework.taskmanager.TaskManager.TaskManager* method), [26](#)

`Worker` (*class* in *decisionengine.framework.engine.DecisionEngine*), [22](#)

`Worker` (*class* in *decisionengine.framework.taskmanager.TaskManager*), [27](#)

Z

`zdumps()` (*in module decisionengine.framework.dataspace.datablock*), [17](#)

`zloads()` (*in module decisionengine.framework.dataspace.datablock*), [17](#)