
decisionengine

Release 1.1.1

Fermi Research Alliance, LLC.

Mar 18, 2021

CONTENTS

1	Release Notes	3
2	Developer Documentation	11
3	Jenkins CI pipeline	13
4	Source code	19
5	Indices and tables	29
	Python Module Index	31
	Index	33

The `decisionengine_modules` package contains provider specific implementations of base classes provided by the decision engine framework.

RELEASE NOTES

1.1 Release 1.6.0

In this release:

- Adapt to decisionengine framework migration to setuptools.
- Drop cmake step before running unit tests.
- Enhanced logging.
- Bug fixes.

1.1.1 Issues fixed in this release

275 : (b639a74)

1.1.2 Full list of commits since version 1.5.0

f93831c : enhanced logging and error handling in util directory (#320)

798972f : replaced method_whitelist with allowed_methods (as former os deprecated) (#319)

b8af4b3 : Update Jenkins pipeline configuration (#318)

b639a74 : Handle KeyError exception (#317)

4c9e25e : Add about.py for useful names (#310)

48e725f : update unittest document

36b799e : Configure DE Modules to use DE Framework with setuptools (#316)

45fc425 : Move to raw flake8 test action (#315)

478b0a5 : Update gh-actions to best practices (#311)

6285f49 : Drop obsolete github action (#309)

911fef7 : Do a limited pin on dependencies (#308)

ab096a8 : Sync-up .gitignore (#304)

cd7e668 : Move to raw github actions (and codecov.io) (#298)

4a997d4 : Remove building of C++ Logic Engine from unit tests

1.2 Release 1.5.0

In this release:

- New AWS bill calculator
- Bug fixes

1.2.1 Issues fixed in this release

- 271 : Change configuration so the bill-calculator-hep-mapsacosta library doesn't write stuff to stdout (5410c46)
- 283 : Change DEAccountConstants.py to allow more variables through (7a65032)
- 293 : Unit test tests/test_job_q.py is failing (f5006fb)
- 263 : Python3 encodes hex strings differently, resulting in malformed htcondor classads (c16f0)
- 289 : Travis CI fails after decisionengine transitioned to pybind11 (2bec1da)
- 281 : New exception in NERSC newt get_usage (398dc42)

1.2.2 Full list of commits since version 1.4.2

5410c46 : new bill calculator package (#303)

7a65032 : Resolving issue 283 (#301)

1a2c3e4 : Fix syntax errors and pylint bits (#300)

976c4a4 : Minor linting of actions (#297)

c43f311 : Drop redundant action, pep8speaks is already doing this (#296)

10691e4 : Add support to use custom docker layer as base of the docker image (#295)

f5006fb : fix for unit test test_job_q issue 293 (#294)

0b588ef : Update workflow per changes at github (#292)

7841d19 : Updated Jenkins configuration documentation (#291)

c08ffce : edited release notes

c16f0ac : Another fix to malformed strings (#288)

2bec1da : Fix #289 where TravisCI is missing changes from <https://github.com/HEPcloud/decisionengine/commit/ea7ade57ca825afb0afbfa5ebd49820b16786d8b> (#290)

8647bb2 : Update to current python test matrix (#287)

234a78e : update release notes

398dc42 : decisionengine_modules/NERSC/util: Added more 5xx codes to retry (#285)

d2df861 : force docker pull when building the docker container to make sure to use an updated base layer (#280)

9a78d22 : added 1.4.0 release notes

5d3b7ec : Updating Dockerfile for unittest (#279)

e16531e : Provide default for util function. (#278)

02f1738 : set RPM version number to 1.5.0rc and drop py3 suffix (#277)

664b9fe : Add timeout support for unit test on Jenkins for DE modules repo (#274)

e392a3c : Added initial unit test for glide_frontend_element.py (#269)

2f0069f : Updated DE modules Jenkins documentation

1.3 Release 1.4.2

In this release:

- Bug fixes to 1.4.1 release

1.3.1 Issues fixed in this release

- 282 : Decision Engine classad encoding problems make multiple exceptions in the factory (c16f0ac)

1.3.2 Full list of commits since version 1.4.1

c16f0ac : Another fix to malformed strings (#288)

1.4 Release 1.4.1

In this release:

- Bug fixes to 1.4.0 release

1.4.1 Issues fixed in this release

- 281 : New exception in NERSC newt get_usage (4d1301e)

1.4.2 Full list of commits since version 1.4.0

4d1301e : decisionengine_modules/NERSC/util: Added more 5xx codes to retry (#285)

1.5 Release 1.4.0

In this release:

- Works with python3 glideinWMS package
- Uses new AWS bill calculator
- Improved Jenkins CI pipeline

1.5.1 Issues fixes in this release

- [59](#) : Replace AWS Billing and GCE Billing modules with revamped bill Calculator code ([71f25ea](#))
- [246](#) : Modify NERSCAllocation main() so that it can be run standalone ([11ce772](#))
- [263](#) : Python3 encodes hex strings differently, resulting in malformed htcondor classads ([13a24e4](#))
- [255](#) : Add option to config of condor/sources/job_q.py and slots.py ([6f65af4](#))

1.5.2 Full list of commits since version 1.3.0

[42f62d3](#) : remove py3 from package name

[6e56c4d](#) : bump version number

[6433dba](#) : Add support to test any branch in Jenkins for DE modules repo (#276)

[60db1b3](#) : Accommodate breaking changes to framework's configuration system. (#273)

[13a24e4](#) : Fix263 (#272)

[a866e47](#) : Correct 'file_cache is unavailable when using oauth2client >= 4.0.0' (#267)

[2c82064](#) : Fix requirements.txt for #266 (#268)

[6f65af4](#) : A more generic solution for the issue 255 (#265)

[df08cb4](#) : Speed up tests. (#264)

[057e578](#) : Update Jenkins pipeline to properly test closing PR (#262)

[a28f272](#) : Adding Jenkins pipeline documentation (#261)

[71f25ea](#) : T59 (#258)

[90b6580](#) : Updating Jenkins pipeline configuration (#260)

[b4bd759](#) : dealing with 2 columnsindividually (#257)

[11ce772](#) : decisionengine_modules/NERSC: Can run NerscAllocationInfo.py without (#256)

[4a70465](#) : doc: add release notes

1.6 Release 1.3.0

In this release:

- Introduced Jsonnet based configuration system
- Improved error handling

1.6.1 Full list of commits since version 1.2.0

e8c8e24 : Update to split a tuple key into two separate keys, this allows python config file to be JSON compliant config file (#254)

fb5d28 : add jsonnet dependency in build/scripts/utls.sh for unit tests (#252)

95a0a32 : decisionengine_modules/glideinwms: Added retry to factory queries (#250)

77f894a : Aws (#249)

3be5be1 : Set theme jekyll-theme-slate

a73e7f8 : Doc (#247)

f8aa96d : Adding editor config file, see <https://editorconfig.org/> (#248)

1ab1720 : Issue no. 237 (#245)

5edc8f9 : Issue 227 (#243)

e6047f2 : GCE channel goes OFFLINE on a timeout (#242)

63e3627 : Aws billing (#241)

c3626b9 : 1.1.3/fix (#239)

ae7c5a6 : Jenkins pipeline improvements (#236)

310befd : T198 (#235)

a65886d : Fix import as reported in : <https://github.com/HEPCloud/decisionengine...> (#232)

93711cc : Run coveralls even if tests fail (#229)

03d763a : Jenkins pipeline improvements (#230)

f48d30f : Fix/223 (#228)

c8aa262 : github ticket 199 (#222)

0323bda : Address : https://github.com/HEPCloud/decisionengine_modules/issues/224 (#226)

62e4df6 : Add support to run CI on Jenkins (#221)

5ab1541 : bump master version to 1.2.0 (for now) (#219)

bc19c65 : decisionengine_modules/NERSC: Added retry loop for NERSC API Calls (#220)

41a50de : Sync up pep8speaks and run_pylint.sh with decisionengine settings (#218)

db4634f : silence pylint error (#217)

1b95141 : Fix whitespace around operator error

746ea38 : ignore W503

8a8b5f4 : remove unused variable

a6668bf : fix PEP8 warnings

13773ee : address pep8 warnings

6bea4ca : silence pylint error

f589895 : Pass sort=True parameter to fix future warning (#215)

a1d0507 : fixing pep8 warning

a10bd17 : debugging one import error

ec501ad : make coveralls.io links work

deab1a7 : T201 (#204)

69f2645 : Add coverage

6d8a5f5 : decisionengine_modules/NERSC: Make Nersc API call backward-compatible with old config (#196)

a7e0af9 : Only run Github Actions for python3.6 (#24)

1.7 Release 1.2.0

In this release:

- Switched to python3
- NERSC newt interface adapted to changed NERSC RESTful API
- Improved unit tests
- Added Jenkins CI pipeline

1.8 Patches:

30d928b : clone version 1.2.0 of decisionengine

ae7c5a6 : Jenkins pipeline improvements (#236)

310befd : T198 (#235)

a65886d : Fix import as reported in : https://github.com/HEPCloud/decisionengine_modules/issues/232 (#232)

93711cc : Run coveralls even if tests fail (#229)

03d763a : Jenkins pipeline improvements (#230)

f48d30f : Fix/223 (#228)

c8aa262 : github ticket 199 (#222)

0323bda : Address : https://github.com/HEPCloud/decisionengine_modules/issues/224 (#226)

62e4df6 : Add support to run CI on Jenkins (#221)

5ab1541 : bump master version to 1.2.0 (for now) (#219)

bc19c65 : decisionengine_modules/NERSC: Added retry loop for NERSC API Calls (#220)

41a50de : Sync up pep8speaks and run_pylint.sh with decisionengine settings (#218)

db4634f : silence pylint error (#217)

1b95141 : Fix whitespace around operator error

746ea38 : ignore W503

8a8b5f4 : remove unused variable

a6668bf : fix PEP8 warnings

13773ee : address pep8 warnings

6bea4ca : silence pylint error

f589895 : Pass sort=True parameter to fix future warning (#215)

a1d0507 : fixing pep8 warning

a10bd17 : debugging one import error

ec501ad : make coveralls.io links work

deab1a7 : T201 (#204)

69f2645 : Add coverage

6d8a5f5 : decisionengine_modules/NERSC: Make Nersc API call backward-compatible with old config (#196)

a7e0af9 : Only run Github Actions for python3.6 (#24)

DEVELOPER DOCUMENTATION

2.1 Decisionengine_modules

2.1.1 Prerequisites:

```
yum install postgresql11 postgresql11-server  
sudo localedef -v -c -i en_US -f UTF-8 C.UTF-8 # (needed for tests)
```

2.1.2 Test

```
git clone https://github.com/HEPCloud/decisionengine_modules  
./decisionengine_modules/.github/actions/unittest-in-sl7-docker/entrypoint.sh
```


JENKINS CI PIPELINE

3.1 Decisionengine modules CI with Jenkins pipeline

Jenkins dashboard with Decisionengine modules CI results is available [here](#).

A CI build is triggered any time a PR is created/closed or a commit is made to an existing PR. There are also *nightly CI builds* to test a list of predefined branches.

The Jenkins pipeline runs *pep8*, *pylint* and *unit_tests* test suites alongside the *rpmbuild* stage. The Jenkins dashboard looks like this:

Jenkins > CI > decisionengine_modules_pipeline

Pipeline decisionengine_modules_pipeline

DE modules pipeline

Last Successful Artifacts

pep8_mail_results	1.31 KB	view
pep8_pep8_merge258.log	0 B	view
pep8_pylint_merge258.log	0 B	view
pep8_results_merge258.log	44 B	view
pylint_mail_results	1.31 KB	view
pylint_pep8_merge258.log	0 B	view
pylint_pylint_merge258.log	0 B	view
pylint_results_merge258.log	44 B	view
pytest.log	10.78 KB	view
rpmbuild.tar	210.00 KB	view

Recent Changes

Build History

Build	Time	Status
189#PR#258	Sep 2, 2020 4:14 PM	Success
188#PR#258	Sep 2, 2020 3:31 PM	Success
187#PR#258	Sep 2, 2020 3:05 PM	Success
186#master	Sep 2, 2020 2:31 AM	Success
185#PR#260	Sep 1, 2020 1:38 PM	Success
184	Sep 1, 2020 2:31 AM	Success
183	Aug 31, 2020 2:31 AM	Success
182	Aug 30, 2020 2:31 AM	Success
181	Aug 29, 2020 2:31 AM	Success
180	Aug 28, 2020 2:31 AM	Success
179	Aug 27, 2020 3:54 PM	Success
178	Aug 27, 2020 3:54 PM	Success
177	Aug 27, 2020 3:39 PM	Success
176	Aug 27, 2020 3:39 PM	Success

Stage View


Average stage times: (Average full run time: ~25min 17s)


	Declarative: Checkout SCM	DE modules tests	pep8	pylint	unit_tests	rpmbuild
189#PR#258	903ms	66ms	4min 28s	22min 26s	10min 36s	3min 16s
Sep 02 16:14	1s	72ms	14min 10s	34min 22s	22min 31s	14min 52s
188#PR#258	539ms	112ms	4min 53s	24min 50s	11min 13s	6min 3s
Sep 02 15:31	850ms	79ms	3min 35s	24min 7s	10min 50s failed	1min 19s
186#master	1s	58ms	3min 27s	21min 55s	9min 3s	22s
Sep 02 02:31	777ms	54ms	7s failed	25s failed	5s failed	4s failed
185#PR#260	494ms	36ms	2min 49s	22min 16s	8min 53s	21s
Sep 01 02:31	618ms	78ms	3min 36s	23min 3s	9min 2s	28s
Aug 31 02:31						


On the bottom left side there is the list of recent CI builds that are named after the PR or the branch tested.

On the bottom right side the dashboard shows for each CI build detailed status for each test suite.

Hovering the mouse over the *status box* for each CI build stage, a tool-tip with a button to access log details shows up.

Next to the build number the symbol  gives access to a menu with the list of artifacts stored for that build. Those artifacts include logs and the tarball with RPMs.

From the panel on the left side it is possible to access the PR on GitHub by clicking on the PR icon that looks like this  #258.

On occasion it could be useful to trigger a manual CI build to test a branch on the official DE GitHub repository or on the user fork. For this purpose, on the top left panel the user can click on the  **Build with Parameters** button, and this panel shows up

Pipeline decisionengine_modules_pipeline

This build requires parameters:

DOCKER_IMAGE	<input type="text" value="vitodb/decision-engine-modules-ci:jenkins"/> Docker image name to use. Default is: vitodb/decision-engine-modules-ci:jenkins
DE_MOD_REPO	<input type="text" value="https://github.com/HEPCloud/decisionengine_modules/"/> Decisionengine modules repo. Default is: https://github.com/HEPCloud/decisionengine_modules/
BRANCH	<input type="text" value="master"/> Branch to test. Default is: master
PYTEST_TIMEOUT	<input type="text" value="300"/> Timeout in seconds for unit_tests (it applies to individual unit test) Default is: 300

Build

the user can modify these parameters to customize what code to test with the CI build.

The *DE_MOD_REPO* parameter can point to the user fork or to the main repository.

The *BRANCH* parameter can point to the desired branch to test.

The *PYTEST_TIMEOUT* parameter is the timeout in seconds for *unit_tests*.

When ready, by clicking on the *Build* button, the CI build will start.

The [pipeline configuration](#) is part of the decisionengine_modules repo.

3.1.1 Nightly CI build configuration

The nightly CI build for Decisionengine framework uses this [Jenkins project](#) that triggers a CI build using the Jenkins pipeline described above to test a list of predefined branches.

The screenshot shows the Jenkins web interface for a project named 'decisionengine_ci'. The top navigation bar includes 'Jenkins', 'CI', and 'decisionengine_ci'. The left sidebar contains a list of actions: 'Back to Dashboard', 'Status' (selected), 'Changes', 'Workspace', 'Build Now', 'Configure', 'Delete Multi-configuration project', 'Rebuild Last', 'Job Config History', 'Rename', and 'Set Next Build Number'. The main content area displays the project name 'Project decisionengine_ci' with a description 'Decision Engine CI running inside dedicated docker container'. Below this, there are sections for 'Configurations' showing 'BRANCH=master' and 'BRANCH=1.4', 'Subprojects' under a 'Static' category listing 'decisionengine_modules_pipeline(non-blocking)' and 'decisionengine_pipeline(non-blocking)', and 'Permalinks' with a list of build links: 'Last build (#295), 7 hr 6 min ago', 'Last stable build (#295), 7 hr 6 min ago', 'Last successful build (#295), 7 hr 6 min ago', and 'Last completed build (#295), 7 hr 6 min ago'. At the bottom, the 'Build History' section shows a table of recent builds.

Build Number	Timestamp
#295	Nov 19, 2020 2:23 AM
#294	Nov 18, 2020 2:23 AM
#293	Nov 17, 2020 2:23 AM

Branches to test are defined using the project matrix as shown in the picture below. Each branch in the list (here *master* and *1.4*) spawns an independent CI build.

The screenshot shows the Jenkins Configuration Matrix configuration page. The 'Configuration Matrix' tab is selected. Under the 'User-defined Axis' section, the 'Name' field is set to 'BRANCH' and the 'Values' field is set to 'master 1.4'. There is a red 'X' icon in the top right corner of the axis configuration area and a blue question mark icon next to the values field.

In the *Build* section of the configuration it is set the list of Jenkins subprojects to be triggered, in this case we have *decisionengine_pipeline* and *decisionengine_modules_pipeline*.

The *Parameters* text box is used to override parameters of each Jenkins subproject with a custom value.

In total this Jenkins project triggers 4 CI builds, i.e. 2 branches X 2 Jenkins subprojects.

The screenshot shows the Jenkins Build configuration page. The 'Build' tab is selected. Under the 'Trigger/call builds on other projects' section, the 'Projects to build' field is set to 'decisionengine_pipeline,decisionengine_modules_pipeline'. The 'Block until the triggered projects finish their builds' checkbox is unchecked. Under the 'Predefined parameters' section, the 'Parameters' field is set to 'BRANCH=\${BRANCH}'. There are red 'X' icons in the top right corner of the 'Trigger/call builds on other projects' and 'Predefined parameters' sections, and blue question mark icons next to the 'Projects to build' and 'Parameters' fields.

Finally the *Build Triggers* section is used to setup the schedule for the periodic build, in this case it is scheduled to run at about 2 AM.

Jenkins will choose the actual time depending on the actual load on the system.

General

Advanced Project Options

Source Code Management

Build Triggers

Configuration Matrix

Build Environment

Build

Post-build Actions

Build Triggers

☐ Trigger builds remotely (e.g., from scripts)

☐ Build after other projects are built

☒ Build periodically

Schedule

H 2 * * *

Would last have run at Wednesday, November 4, 2020 2:23:53 AM CST;
would next run at Thursday, November 5, 2020 2:23:53 AM CST.

SOURCE CODE

4.1 Welcome to decisionengine_modules's documentation!

4.1.1 decisionengine_modules package

Subpackages

decisionengine_modules.AWS package

Subpackages

decisionengine_modules.AWS.publishers package

Submodules

decisionengine_modules.AWS.publishers.AWS_burn_rate module

decisionengine_modules.AWS.publishers.AWS_figure_of_merit module

decisionengine_modules.AWS.publishers.AWS_generic_publisher module

decisionengine_modules.AWS.publishers.AWS_price_performance module

Module contents

decisionengine_modules.AWS.sources package

Submodules

decisionengine_modules.AWS.sources.AWSBurnRateSourceProxy module

decisionengine_modules.AWS.sources.AWSInstancePerformance module

decisionengine_modules.AWS.sources.AWSJobLimits module

decisionengine_modules.AWS.sources.AWSOccupancy module

decisionengine_modules.AWS.sources.AWSOccupancyWithSourceProxy module

decisionengine_modules.AWS.sources.AWSSpotPrice module

decisionengine_modules.AWS.sources.AWSSpotPriceWithSourceProxy module

decisionengine_modules.AWS.sources.BillingInfo module

decisionengine_modules.AWS.sources.BillingInfoSourceProxy module

decisionengine_modules.AWS.sources.DEAccountConstants module

This data is taken from billing and arranged as dictionary of AccountConstants instead of separate class for each billing class. This way is more convenient to use in programmes.

```
class decisionengine_modules.AWS.sources.DEAccountConstants.AccountConstants (constants={})  
    Bases: object
```

```
    info ()
```

```
decisionengine_modules.AWS.sources.DEAccountConstants.load_constants (constants_file)  
    Load constants from file.
```

```
    Parameters constants_file (file) – configuration file as python dict
```

```
    Return type AccountConstants
```

decisionengine_modules.AWS.sources.FigureOfMeritSourceProxy module

decisionengine_modules.AWS.sources.FinancialParameters module

decisionengine_modules.AWS.sources.occupancy_config_sample module

decisionengine_modules.AWS.sources.spot_price_config_sample module

Module contents

decisionengine_modules.AWS.transforms package

Submodules

decisionengine_modules.AWS.transforms.AwsBurnRate module

decisionengine_modules.AWS.transforms.FigureOfMerit module

Module contents

Submodules

decisionengine_modules.AWS.AWSSpotPrice module

decisionengine_modules.AWS.CloudBudget module

decisionengine_modules.AWS.CloudRequests module

decisionengine_modules.AWS.HPCAllocation module

decisionengine_modules.AWS.HTCondorJobQ module

decisionengine_modules.AWS.LocalCapacity module

decisionengine_modules.AWS.ProvisionerResourceList module

decisionengine_modules.AWS.pandas_scratch_pad module

decisionengine_modules.AWS.pandas_scratch_pad.**load_data_frame** (*list_of_dicts*)

Module contents

decisionengine_modules.GCE package

Subpackages

decisionengine_modules.GCE.publishers package

Submodules

decisionengine_modules.GCE.publishers.GCEBurnRatePublisher module

decisionengine_modules.GCE.publishers.GCEFigureOfMerit_publisher module

decisionengine_modules.GCE.publishers.GCEPricePerformance_publisher module

Module contents

decisionengine_modules.GCE.sources package

Submodules

decisionengine_modules.GCE.sources.GCEBillingInfo module

decisionengine_modules.GCE.sources.GCEBillingInfoSourceProxy module

decisionengine_modules.GCE.sources.GCEInstancePerformance module

decisionengine_modules.GCE.sources.GCEResourceLimits module

decisionengine_modules.GCE.sources.GceBurnRateSourceProxy module

decisionengine_modules.GCE.sources.GceFigureOfMeritSourceProxy module

decisionengine_modules.GCE.sources.GceOccupancy module

Module contents

decisionengine_modules.GCE.transforms package

Submodules

decisionengine_modules.GCE.transforms.GceBurnRate module

decisionengine_modules.GCE.transforms.GceFigureOfMerit module

Module contents

Module contents

decisionengine_modules.NERSC package

Subpackages

decisionengine_modules.NERSC.publishers package

Submodules

decisionengine_modules.NERSC.publishers.NerscFigureOfMerit_publisher module

Module contents

decisionengine_modules.NERSC.sources package

Submodules

decisionengine_modules.NERSC.sources.NerscAllocationInfo module

decisionengine_modules.NERSC.sources.NerscAllocationInfoSourceProxy module

decisionengine_modules.NERSC.sources.NerscFigureOfMeritSourceProxy module

decisionengine_modules.NERSC.sources.NerscInstancePerformance module

decisionengine_modules.NERSC.sources.NerscJobInfo module

Module contents

decisionengine_modules.NERSC.transforms package

Submodules

decisionengine_modules.NERSC.transforms.CompareNerscFactoryJobs module

decisionengine_modules.NERSC.transforms.CompareNerscUserpoolSlots module

decisionengine_modules.NERSC.transforms.NerscFigureOfMerit module

Module contents

decisionengine_modules.NERSC.util package

Submodules

decisionengine_modules.NERSC.util.newt module

Newt API interface

```
class decisionengine_modules.NERSC.util.newt.Newt (password_file,  
                                                newt_base_url=None,  
                                                num_retries=0,  
                                                retry_backoff_factor=0)
```

Bases: object

_add_retries_to_session()

Adds retries to requests Session for requests to NEWT URLs :return: void

_login()

Establishes newt Session :return: void

get_queue(system, query=None)

Returns information about queues controlled by optional query name parameter ;param system: string system name (like 'cori', 'edison' ..) ;param query: string query (optional) :return: json containing queue information

get_status(system=None)

Returns system status for a given system (if provided) or all systems ;param system: string name of the system (optional) :return: json containing system status

get_usage(username)

Returns allocation and usage for the given user using NEWT IRIS API ;param username: string username :return: json containing allocation and usage information for a given user

Module contents

Module contents

decisionengine_modules.graphite package

Subpackages

decisionengine_modules.graphite.publishers package

Submodules

decisionengine_modules.graphite.publishers.generic_publisher module

Module contents

Module contents

decisionengine_modules.htcondor package

Subpackages

decisionengine_modules.htcondor.publishers package

Submodules

decisionengine_modules.htcondor.publishers.publisher module

Module contents

decisionengine_modules.htcondor.sources package

Submodules

decisionengine_modules.htcondor.sources.job_q module

decisionengine_modules.htcondor.sources.job_q_source_proxy module

decisionengine_modules.htcondor.sources.slots module

decisionengine_modules.htcondor.sources.slots_source_proxy module

decisionengine_modules.htcondor.sources.source module

Module contents

Submodules

decisionengine_modules.htcondor.htcondor_query module

```

class decisionengine_modules.htcondor.htcondor_query.CondorQ(schedd_name=None,
                                                             pool_name=None)
    Bases: decisionengine_modules.htcondor.htcondor_query.CondorQuery
    Class to implement condor_q
    _abc_impl = <_abc_data object>
    fetch (constraint=None, format_list=None, condor_config=None)
        Fetch job classads

class decisionengine_modules.htcondor.htcondor_query.CondorQuery(resource_str,
                                                                    group_attr,
                                                                    pool_name=None,
                                                                    env=None)
    Bases: decisionengine_modules.htcondor.htcondor_query.Query
    Fully implemented class for CondorQuery
    _abc_impl = <_abc_data object>

class decisionengine_modules.htcondor.htcondor_query.CondorStatus(subsystem_name=None,
                                                                    pool_name=None,
                                                                    group_attr=None)
    Bases: decisionengine_modules.htcondor.htcondor_query.CondorQuery
    Class to implement condor_status
    _abc_impl = <_abc_data object>
    fetch (constraint=None, format_list=None, condor_config=None)
        Fetch resource classads and return a list of evaluated classads

class decisionengine_modules.htcondor.htcondor_query.Query
    Bases: object
    Pure virtual class to have a minimum set of methods defined
    _abc_impl = <_abc_data object>
    abstract fetch (constraint=None, format_list=None, condor_config=None)
        Fetch the classad attributes specified in the format_list matching the constraint
    fetch_stored (constraint_func=None)
        Parameters constraint_func – A boolean function, with only one argument (data el). If
        None, return all the data.
        @rtype: dict @return: Same as fetch(), but limited to constraint_func(el)==True
    load (constraint=None, format_list=None, condor_config=None)
        Fetch the data and store it in self.stored_data

exception decisionengine_modules.htcondor.htcondor_query.QueryError(err_str)
    Bases: RuntimeError
    Thrown when there are exceptions using htcondor python bindings or commands

decisionengine_modules.htcondor.htcondor_query.apply_constraint (data,      con-
                                                                    straint_func)
    Return a subset of data that satisfies constraint_function If constraint_func is None, return back entire data

```

`decisionengine_modules.htcondor.htcondor_query.bindings_friendly_attrs` (*format_list*)
Convert the *format_list* into *attrs* that can be used with python bindings Python bindings should take care of the typing

`decisionengine_modules.htcondor.htcondor_query.bindings_friendly_constraint` (*constraint*)
Convert the *constraint* to format that can be used with python bindings

`decisionengine_modules.htcondor.htcondor_query.eval_classad_expr` (*classads*, *format_list=None*)
Convert the *classads* into list of classads Guarantees any attribute in *format_list* to be added with default value *None*

`decisionengine_modules.htcondor.htcondor_query.list2dict` (*list_data*, *attr_name*)
Convert a list to a dictionary and group the results based on attributes specified by *attr_name*

`decisionengine_modules.htcondor.htcondor_query.resource_str_to_py_adtype` (*resource_str*)
Given the resource string return equivalent classad type

`decisionengine_modules.htcondor.htcondor_query.split_collector_host` (*collector_host*)
Given the *collector_host* string extract primary *collector_host* which is the first collector host in the list and sort the secondary collectors. Return a tuple of primary collector and CSV secondary collector.

Module contents

decisionengine_modules.util package

Submodules

decisionengine_modules.util.figure_of_merit module

Calculate figure of merit

`decisionengine_modules.util.figure_of_merit.figure_of_merit` (*performance*,
running, *allowed*, *idle=None*,
max_idle=None)

decisionengine_modules.util.retry_function module

`decisionengine_modules.util.retry_function.retry_on_error` (*nretries=1*,
retry_interval=2,
backoff=True)

`decisionengine_modules.util.retry_function.retry_wrapper` (*f*, *nretries=1*,
retry_interval=2, *backoff=True*)

Retry on error with parameters of how many times (*nretries*) and interval in seconds (*retry_interval*). If the function to be decorated is an instance method and the values come from a configuration, then this decorator can retrieve these two parameters from instance attributes with the same name. Otherwise, use the default values or pass new values to the decorator.

decisionengine_modules.util.test_retry_function module

```

class decisionengine_modules.util.test_retry_function.Dummy (name='Dummy')
    Bases: object
        _func_failure (foo, input2=3)
        _func_success (foo, input2=3)
        func_failure (foo, input2=3)
        func_success (foo, input2=3)
decisionengine_modules.util.test_retry_function.test_all()

```

decisionengine_modules.util.testutils module

Utils to simplify testing

```

decisionengine_modules.util.testutils.compare_dfs (df1, df2)
    for some reason df.equals does not work here but if I compare cell by cell it works :type df1: pd.DataFrame
    :arg df1: data frame instance :type df2: pd.DataFrame :arg df2: data frame instance :rtype: bool - True if
    equal

decisionengine_modules.util.testutils.input_from_file (fname)
decisionengine_modules.util.testutils.raw_input_from_file (fname)

```

Module contents

Submodules

decisionengine_modules.about module

PEP-0396 provides instructions for providing module versions While we are at it, add a few other useful bits

decisionengine_modules.graphite_client module

```

class decisionengine_modules.graphite_client.Graphite (host='fifemondata.fnal.gov',
                                                    pickle_port=2004)
    Bases: object
        send_dict (namespace, data, debug_print=True, send_data=True)
            send data contained in dictionary as {k: v} to graphite dataset $namespace.k with current timestamp
decisionengine_modules.graphite_client.sanitize_key (key)

```

decisionengine_modules.load_config module

`decisionengine_modules.load_config.load(python_file, retries=0, timeout=0)`
Load constants from file.

Parameters `constants_file` (*file*) – configuration file as python dict

Return type `object`

Module contents

4.2 Indices and tables

- [genindex](#)
- [modindex](#)
- [search](#)

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

d

decisionengine_modules, 28

decisionengine_modules.about, 27

decisionengine_modules.AWS, 21

decisionengine_modules.AWS.pandas_scratch_pad, 21

decisionengine_modules.AWS.publishers, 19

decisionengine_modules.AWS.sources, 20

decisionengine_modules.AWS.sources.DEAccountContains, 20

decisionengine_modules.AWS.sources.occupancy_config_sample, 20

decisionengine_modules.AWS.sources.spot_price_config_sample, 20

decisionengine_modules.AWS.transforms, 20

decisionengine_modules.GCE, 22

decisionengine_modules.GCE.publishers, 21

decisionengine_modules.GCE.sources, 22

decisionengine_modules.GCE.transforms, 22

decisionengine_modules.graphite, 24

decisionengine_modules.graphite.publishers, 24

decisionengine_modules.graphite_client, 27

decisionengine_modules.htcondor, 26

decisionengine_modules.htcondor.htcondor_query, 25

decisionengine_modules.htcondor.publishers, 24

decisionengine_modules.htcondor.sources, 24

decisionengine_modules.load_config, 28

decisionengine_modules.NERSC, 24

decisionengine_modules.NERSC.publishers, 22

decisionengine_modules.NERSC.sources, 23

decisionengine_modules.NERSC.transforms, 23

decisionengine_modules.NERSC.util, 24

decisionengine_modules.NERSC.util.newt, 23

decisionengine_modules.util, 27

decisionengine_modules.util.figure_of_merit, 26

decisionengine_modules.util.retry_function, 26

decisionengine_modules.util.test_retry_function, 27

decisionengine_modules.util.testutils, 27

Symbols

`_abc_impl (decisionengine_modules.htcondor.htcondor_query.CondorQ`
`attribute), 25`
`_abc_impl (decisionengine_modules.htcondor.htcondor_query.CondorQuery`
`attribute), 25`
`_abc_impl (decisionengine_modules.htcondor.htcondor_query.CondorStatus`
`attribute), 25`
`_abc_impl (decisionengine_modules.htcondor.htcondor_query.Query`
`attribute), 25`
`_add_retries_to_session () (decision-`
`engine_modules.NERSC.util.newt.Newt`
`method), 23`
`_func_failure () (decision-`
`engine_modules.util.test_retry_function.Dummy`
`method), 27`
`_func_success () (decision-`
`engine_modules.util.test_retry_function.Dummy`
`method), 27`
`_login () (decisionengine_modules.NERSC.util.newt.Newt`
`method), 23`
A
`AccountConstants (class in decisio-`
`nengine_modules.AWS.sources.DEAccountConstants),`
`20`
`apply_constraint () (in module decisio-`
`nengine_modules.htcondor.htcondor_query),`
`25`
B
`bindings_friendly_attrs () (in module decisio-`
`nengine_modules.htcondor.htcondor_query),`
`26`
`bindings_friendly_constraint ()`
`(in module decisio-`
`nengine_modules.htcondor.htcondor_query),`
`26`
C
`compare_dfs () (in module decisio-`
`nengine_modules.util.testutils), 27`
`CondorQ (class in decisio-`
`nengine_modules.htcondor.htcondor_query),`
`25`
`CondorQuery (class in decisio-`
`nengine_modules.htcondor.htcondor_query),`
`25`
`CondorStatus (class in decisio-`
`nengine_modules.htcondor.htcondor_query),`
`25`
D
`decisionengine_modules`
`module, 28`
`decisionengine_modules.about`
`module, 27`
`decisionengine_modules.AWS`
`module, 21`
`decisionengine_modules.AWS.pandas_scratch_pad`
`module, 21`
`decisionengine_modules.AWS.publishers`
`module, 19`
`decisionengine_modules.AWS.sources`
`module, 20`
`decisionengine_modules.AWS.sources.DEAccountContants`
`module, 20`
`decisionengine_modules.AWS.sources.occupancy_config`
`module, 20`
`decisionengine_modules.AWS.sources.spot_price_config`
`module, 20`
`decisionengine_modules.AWS.transforms`
`module, 20`
`decisionengine_modules.GCE`
`module, 22`
`decisionengine_modules.GCE.publishers`
`module, 21`
`decisionengine_modules.GCE.sources`
`module, 22`
`decisionengine_modules.GCE.transforms`
`module, 22`
`decisionengine_modules.graphite`
`module, 24`
`decisionengine_modules.graphite.publishers`

module, 24
 decisionengine_modules.graphite_client
 module, 27
 decisionengine_modules.htcondor
 module, 26
 decisionengine_modules.htcondor.htcondor_queries
 module, 25
 decisionengine_modules.htcondor.publishers
 module, 24
 decisionengine_modules.htcondor.sources
 module, 24
 decisionengine_modules.load_config
 module, 28
 decisionengine_modules.NERSC
 module, 24
 decisionengine_modules.NERSC.publishers
 module, 22
 decisionengine_modules.NERSC.sources
 module, 23
 decisionengine_modules.NERSC.transforms
 module, 23
 decisionengine_modules.NERSC.util
 module, 24
 decisionengine_modules.NERSC.util.newt
 module, 23
 decisionengine_modules.util
 module, 27
 decisionengine_modules.util.figure_of_merit
 module, 26
 decisionengine_modules.util.retry_function
 module, 26
 decisionengine_modules.util.test_retry_function
 module, 27
 decisionengine_modules.util.testutils
 module, 27
 Dummy (class in decision-
 engine_modules.util.test_retry_function),
 27

E

eval_classad_expr() (in module decisio-
 nengine_modules.htcondor.htcondor_query),
 26

F

fetch() (decisionengine_modules.htcondor.htcondor_query.CondorQ
 method), 25
 fetch() (decisionengine_modules.htcondor.htcondor_query.CondorStatus
 method), 25
 fetch() (decisionengine_modules.htcondor.htcondor_query.Query
 method), 25
 fetch_stored() (decisio-
 nengine_modules.htcondor.htcondor_query.Query
 method), 25

figure_of_merit() (in module decisio-
 nengine_modules.util.figure_of_merit), 26
 func_failure() (decisio-
 nengine_modules.util.test_retry_function.Dummy
 method), 27
 func_success() (decisio-
 nengine_modules.util.test_retry_function.Dummy
 method), 27

G

get_queue() (decisio-
 nengine_modules.NERSC.util.newt.Newt
 method), 23
 get_status() (decisio-
 nengine_modules.NERSC.util.newt.Newt
 method), 23
 get_usage() (decisio-
 nengine_modules.NERSC.util.newt.Newt
 method), 23
 Graphite (class in decisio-
 nengine_modules.graphite_client), 27

I

info() (decisionengine_modules.AWS.sources.DEAccountContants.Account
 method), 20
 input_from_file() (in module decisio-
 nengine_modules.util.testutils), 27

L

list2dict() (in module decisio-
 nengine_modules.htcondor.htcondor_query),
 26
 load() (decisionengine_modules.htcondor.htcondor_query.Query
 method), 25
 load() (in module decisio-
 nengine_modules.load_config), 28
 load_constants() (in module decisio-
 nengine_modules.AWS.sources.DEAccountContants),
 20
 load_data_frame() (in module decisio-
 nengine_modules.AWS.pandas_scratch_pad),
 21

M

module
 decisionengine_modules, 28
 decisionengine_modules.about, 27
 decisionengine_modules.AWS, 21
 decisionengine_modules.AWS.pandas_scratch_pad,
 21
 decisionengine_modules.AWS.publishers,
 19
 decisionengine_modules.AWS.sources,
 20

decisionengine_modules.AWS.sources.DECAccountConstants,
 20 Query (class in decisio-
 decisionengine_modules.AWS.sources.occupancy_config_sample, *engine_modules.htcondor.htcondor_query*),
 20 25
 decisionengine_modules.AWS.sources.spot_price_config_sample,
 20 QueryError, 23
 decisionengine_modules.AWS.transforms
 20 raw_input_from_file() (in module decisio-
 decisionengine_modules.GCE, 22 *engine_modules.util.testutils*), 27
 decisionengine_modules.GCE.publishers, resource_str_to_py_adtype() (in module decisio-
 21 *engine_modules.htcondor.htcondor_query*),
 decisionengine_modules.GCE.sources, 26
 22
 decisionengine_modules.GCE.transforms, retry_on_error() (in module decisio-
 22 *engine_modules.util.retry_function*), 26
 decisionengine_modules.graphite, 24 retry_wrapper() (in module decisio-
 decisionengine_modules.graphite.publishers, *engine_modules.util.retry_function*), 26
 24
 decisionengine_modules.graphite_client, **S**
 27
 decisionengine_modules.htcondor, 26 sanitize_key() (in module decisio-
 decisionengine_modules.htcondor.htcondor_query, *engine_modules.graphite_client*), 27
 25 send_dict() (decisio-
 decisionengine_modules.htcondor.publishers, *engine_modules.graphite_client.Graphite*
 24 method), 27
 decisionengine_modules.htcondor.sources, split_collector_host() (in module decisio-
 24 *engine_modules.htcondor.htcondor_query*),
 26
 decisionengine_modules.load_config, 28
 28
 decisionengine_modules.NERSC, 24 **T**
 decisionengine_modules.NERSC.publishers, test_all() (in module decisio-
 22 *engine_modules.util.test_retry_function*),
 27
 decisionengine_modules.NERSC.sources, 23
 decisionengine_modules.NERSC.transforms, 23
 decisionengine_modules.NERSC.util, 24
 decisionengine_modules.NERSC.util.newt, 23
 decisionengine_modules.util, 27
 decisionengine_modules.util.figure_of_merit, 26
 decisionengine_modules.util.retry_function, 26
 decisionengine_modules.util.test_retry_function, 27
 decisionengine_modules.util.testutils, 27

N

Newt (class in decisio-
engine_modules.NERSC.util.newt), 23