

JCS - JSON Clear Text Signature

Although XML Signatures are extremely flexible they come at a price: limited interoperability and mobile platform support. The case for XML has also been considerably weakened by REST which more or less has replaced SOAP for web-based systems used by for example Google and Facebook. In REST-based systems response-data is usually in JSON format.

Converting to JSON

Due to the reasons above I felt a need converting the XML-based KeyGen2 system to JSON. However, there is currently no direct counterpart to XML DSig's enveloped signatures which forced me into developing such a system. It turned out that less than 3,000 lines of Java code were required to *Encode/Decode* and *Sign/Verify* JSON data:

<https://code.google.com/p/openkeystore/source/browse/#svn%2Flibrary%2Ftrunk%2Fsrc%2Forg%2Fwebpki%2Fjson>

I can now safely retire my 200,000+ lines Android port of Xerces ☺

Things that make JSON signatures simpler than XML DSig include:

- No confusing attribute versus element canonicalization rules
- No namespaces
- No defaults
- No XPath
- No SOAP envelopes
- No WS-Security framework

The JSON parser mentioned does a pretty good job for supporting conformance verification with intended messages though registered message types as well through strict type control and *checks for missing references*.

Together with additional tests performed at application-level the system should be comparable to XML schema although the declarative mode of course is sadly missing.

Obviously there are complex systems that live or die by the use of XML DSig and XML Schema but KeyGen2 is hopefully not one of them...

Sample Signature

```
{
  "@context": "http://example.com/signature",
  "Now": "2013-09-02T04:57:30+02:00",
  "RT":
  {
    "rt": "67",
    "YT":
    {
      "Value": -689,
      "String": "656756#",
      "Fantastic": false
    },
    "er": "33"
  },
  "Array": [],
  "Barray":
  [{
    "Value": -689,
    "String": "656756#",
    "Fantastic": true
  }],
}
```

```

{
  "Value": -689,
  "String": "656756#",
  "Fantastic": false
}],
"ID": "3RP31_WkjyYtUMbDxw",
"Strings": ["One", "Two", "Three"],
"EscapeMe": "A\\n\\",
"Int": 78,
"Signature":
{
  "Algorithm": "http://www.w3.org/2001/04/xmldsig-more#ecdsa-sha256",
  "KeyInfo":
  {
    "PublicKey":
    {
      "EC":
      {
        "NamedCurve": "http://xmlns.webpki.org/sks/algorithm#ec.p256",
        "X": "lNxnVAUEE8t7DSQBft93LVSXxKCiVjhbWWfyg023FCk=",
        "Y": "LmTlQxB3LgZrNLmhOfMaCnDizczC/RfQ6Kx8iNwFFA="
      }
    }
  },
  "SignatureValue":
  "MEYCIQC0czpCRdc7n9Z7l0uUaTMB7cOxxgbl05+Z+eHzJl6d3wIhAJpu2+0Jt3VVAwylmctq/zVF6eZ3ViJfEzeU5gk4wEt"
}
}

```

Signature Scope

The scope of a signature (=what is actually signed) comprises all properties and values including possible child objects of the JSON object holding the `Signature` property minus the `SignatureValue` name-value pair.

Canonicalization

Precondition: Valid JSON data as described on <http://www.json.org> has been received.

Restrictions: `\uhhhh` and `\/` *must not* be featured in quoted strings.

The canonicalization steps are as follows:

- Whitespace is removed which in practical terms means removal of all characters outside of quoted strings having a value \leq ASCII space
- Properties are sorted in lexical UNICODE order
- The JSON object of the signature scope is recreated using the actual textual data. Textual data means that if a sender puts 0.99999999999999999999 in a JSON message and the receiver would after reading the value interpret it as 1.0, the parser must still always keep the original representation internally in order to perform proper canonicalization

The sample signature has the following canonicalization data:

```

{"@context":"http://example.com/signature","Array":[],"Barray":[{"Fantastic":true,"String":"656756#","Value":-689},{"Fantastic":false,"String":"656756#","Value":-689}],"EscapeMe":"A\\n\\","ID":"3RP31_WkjyYtUMbDxw","Int":78,"Now":"2013-09-02T04:57:30+02:00","RT":{"YT":{"Fantastic":false,"String":"656756#","Value":-689},"er":"33","rt":"67"},"Signature":{"Algorithm":"http://www.w3.org/2001/04/xmldsig-more#ecdsa-sha256","KeyInfo":{"PublicKey":{"EC":{"NamedCurve":"http://xmlns.webpki.org/sks/algorithm#ec.p256","X":"lNxnVAUEE8t7DSQBft93LVSXxKCiVjhbWWfyg023FCk=","Y":"LmTlQxB3LgZrNLmhOfMaCnDizczC/RfQ6Kx8iNwFFA="}}}}},"Strings":["One","Two","Three"]}

```

Supported Signature Types

The JSON Signature scheme supports the following key types as indicated by the `KeyInfo` object:

- *RSA keys:*

```
{
  "PublicKey":
  {
    "RSA":
    {
      "Modulus": "tF3wS3naI4lhzUm2q ... Yhr+a1Jhh6VpgKY4R2FlJi9Ow==",
      "Exponent": "AQAB"
    }
  }
}
```

- *EC keys:*

```
{
  "PublicKey":
  {
    "EC":
    {
      "NamedCurve": "http://xmlns.webpki.org/sks/algorithm#ec.p256",
      "X": "TQL/LgkOykT65MeeYhHCPEHoowrYckIdfGnaNYPUnLA=",
      "Y": "CuiM80A5/bAkxqnEiYkat2V+0udAk1sfn7txOx4pNR4="
    }
  }
}
```

- *X.509 certificates*

```
{
  "SignatureCertificate":
  {
    "Issuer": "CN=Demo Sub CA,DC=webpki,DC=org",
    "SerialNumber": 1377713637130,
    "Subject": "CN=example.com,O=Example Organization,C=US"
  },
  "X509CertificatePath":
  [
    "MIIClzCCAX+gAwIBAgIGAUD ... a00ixD+q5P2OszRBYG3uk9W/uNIHdoyQn19w=="
  ]
}
```

} *Optional*

- *Symmetric keys*

```
{
  "KeyID": "hj65-9grt-076s1"
}
```

In addition to in-line keys, `KeyInfo` may also point to an external location holding a public key or an X.509 certificate path in PEM format:

```
{
  "URL": "http://example.com/my-key.pem"
}
```

Version Attribute

In similarity to CMS there a `Signature` object may also carry an *optional* `Version` property which by default has the value `"http://xmlns.webpki.org/jcs/v1"`.

Multiple Signatures

Since JSON properties are single-valued the described scheme does not automatically support multiple signings of the same object. It would be technically possible to rather use an array of signatures *but that would also greatly complicate canonicalization*.

However, there is a workaround which fits most real-world scenarios using multiple signatures and that is using wrapping signatures like the following:

```
{
  {
    "@context": "http://example.com/test-multiple-signatures",
    "Now": "2013-08-30T07:56:08+02:00",
    "ID": "1ADU_s0067Wlgo052-9L",
    "STRINGS": ["One", "Two", "Three"],
    "Signature":
      {
        ...
      }
  },
  "Signature":
  {
    ...
  }
}
```

That is, there is in this scheme no difference between multiple signatures and counter-signatures.

Other JSON Signature Solutions

The IETF JOSE WG has defined a JSON signature scheme called JWS. The primary reason why I haven't adopted JWS for KeyGen2 is because it is based on *in-line signatures using Base64-encoded payloads*.

Although certainly working Base64-encoded messages disrupts readability making the switch from XML to JSON unnecessary painful for schemes where the *message* is the core and a signature only is there to vouch for the message's authenticity. The following shows how a JWS-based conversion of the sample message could look like:

```
{
  "payload": "dTzJcZgb ... QWBBRaQnES",
  "signatures":
    [{
      Signature data
    }]
}
```

Yet another scheme which is quite similar to this specification is something known as "HTTP Keys":

<https://payswarm.com/specs/source/http-keys>

The authors of HTTP Keys also created their own signature scheme for multiple reasons, with clear-text messaging as one objective.

*Disclaimer: This document does not represent a standard of any kind.
It might at best be useful as input to a future standardization process*

Author: Anders Rundgren

anders.rundgren.net@gmail.com

2013-09-02