```
kali@kali: ~/Desktop
 File Actions Edit View Help
          RX errors 0 dropped 0 overruns 0 frame 0
          TX packets 24 bytes 3024 (2.9 KiB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
          inet 127.0.0.1 netmask 255.0.0.0
inet6 ::1 prefixlen 128 scopeid 0×10<host>
          loop txqueuelen 1000 (Local Loopback)
          RX packets 4 bytes 240 (240.0 B)
          RX errors 0 dropped 0 overruns 0 frame 0 TX packets 4 bytes 240 (240.0 B)
          TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
(kali@kali)-[~]

$ sudo nano /etc/network/interfaces
[sudo] password for kali:
  —(kali⊕kali)-[~]
s python w3e5.py
python: can't open file '/home/kali/w3e5.py': [Errno 2] No such file or directory
(kali@ kali)-[~]
$ cd desktop
cd: no such file or directory: desktop
(kali@ kali)-[~]
$ cd Desktop
(kali® kali)-[~/Desktop]
spython w3e5.py
ip target : ^CTraceback (most recent call last):
File "/home/kali/Desktop/w3e5.py", line 3, in <module>
SRV_ADRS=(input("ip target :"))
target ai quali vogliamo inviare i pacchetti
                                                                                     # riga 3 e 4 impostiamo l'ip e la porta
KeyboardInterrupt
(kali@ kali)-[~/Desktop]
spython w3e5.py
inserisci ip target :127.0.0.1
inserisci porta target:1234
quanti pacchetti vuoi inviare?25
  —(kali⊕kali)-[~/Desktop]
<u></u>$ []
```

