

CIT237

Chapter 20: Recursion

November 27, 2019

NOTICE to Students: Portions of these lecture slides are

Copyright 2018 Pearson Education, Inc.

We have a license to use this material *only* in the context of this course.

There is NO PERMISSION to share these lecture slides with anyone not taking the course.

There is NO PERMISSION to post these lecture slides on the Internet.

Reminders / Announcement

- Quiz 7 will be held at the start of class on
Wednesday, December 11.
The material covered on Quiz 7 will be announced as the date gets closer.
- Project 3:
EXTENDED due date is December 9.
- Our last day of class is Monday, December 16.
 - In addition to a lecture, we will be demonstrating Lab solutions during that class.

Introduction to Recursion

- A recursive function contains a call to itself:


```
void countDown(int num)
{
    if (num == 0)
        cout << "Blastoff!";
    else
    {
        cout << num << "... \n";
        countDown(num-1); // recursive
                           // call
    }
}
```

What Happens When Called? (1)

If a program contains a line like `countDown (2) ;`

1. `countDown (2)` generates the output `2 . . .`, then it calls `countDown (1)`
2. `countDown (1)` generates the output `1 . . .`, then it calls `countDown (0)`
3. `countDown (0)` generates the output `Blastoff!`, then returns to `countDown (1)`
4. `countDown (1)` returns to `countDown (2)`
5. `countDown (2)` returns to the original calling function


What Happens When Called? (2)



What Happens When Called? (3)

- Each time a recursive function is called, a new copy of the function runs, and new instances of the calling parameters and local variables are created.
- As each copy finishes executing, it returns to the copy of the function that called it.
- When the initial copy finishes executing, it returns to the part of the program that made the initial call to the function.

What Happens When Called? (4)



Recursive Functions - Purpose

- Recursive functions are used to reduce a complex problem to a simpler-to-solve problem.
- The simpler-to-solve problem is known as the base case
- Recursive calls stop when the base case is reached

Stopping the Recursion (1)

- A recursive function must always include a test to determine if another recursive call should be made, or if the recursion should stop with this call
- In the sample program, the test is:

```
if (num == 0)
```

Stopping the Recursion (2)

```
void countDown(int num)
{
    if (num == 0) // test
        cout << "Blastoff!";
    else
    {
        cout << num << "...\\n";
        countDown(num-1); // recursive
    } // call
}
```

Stopping the Recursion (3)

- Recursion uses a process of breaking a problem down into smaller problems until the problem can be solved
- In the `countDown` function, a different value is passed to the function each time it is called
- Eventually, the parameter reaches the value in the test, and the recursion stops

Stopping the Recursion (4)

```
void countDown(int num)
{
    if (num == 0)
        cout << "Blastoff!";
    else
    {
        cout << num << "... \n";
        countDown(num-1) ; // note that the value
                           // passed to recursive
    }                     // calls decreases by
                           // one for each call
}
```

Can you see the bug in this function?

```
void countDown(int num)
{
    if (num == 0)
        cout << "Blastoff!";
    else
    {
        cout << num << "... \n";
        countDown(num-1);
    }
}
```

- What input value would cause trouble?
 - What would the symptom(s) of the problem be?
 - Can you suggest a code change to guard against this occurrence?

Types of Recursion

- Direct
 - a function calls itself
- Indirect
 - function A calls function B, and function B calls function A
 - function A calls function B, which calls ..., which calls function A

The Recursive “Factorial” Function

Remember from Math class:

- The factorial function:

$$n! = n * (n-1) * (n-2) * \dots * 3 * 2 * 1 \quad \text{if } n > 0$$

$$n! = 1 \quad \text{if } n = 0$$

- We can compute factorial of **n** if the factorial of $(n-1)$ is known:

$$n! = n * (n-1)!$$

- $n = 0$ is the base case

The Recursive Factorial Function

```
int factorial (int num)
{
    if (num > 0) {
        return num * factorial(num-1);
    }
    else {
        return 1;
    }
}
```


Example: VerboseRecursion


- Prints intermediate results of the factorial calculation.
- Also prints the address of the local variable that holds each intermediate result.
- See also the sample program on Moodle.

Recursive Linked List Operations

- Recursive functions can be members of a linked list class
- Example applications:
 - Compute the size of (number of nodes in) a list.
 - Compute the total of all data values in the list.
 - Traverse the list in reverse order.

Counting the Nodes in a Linked List

- Uses a pointer to visit each node
- Algorithm:
 - Initially, the pointer starts at head of the list.
 - If the pointer is NULL, return 0 (base case).
 - If the pointer is not NULL, use a recursive call to advance to next node.
 - Upon returning from the recursive call, return $1 + (\text{whatever value the recursive call returned})$.
- That is, each return value is:
(the length of the *remaining* list) + 1.



Contents of a List in Reverse Order

- If you have a *singly-linked* list, then displaying the list contents in reverse order could be very messy *without* using recursion.
- Algorithm:
 - Initially, the pointer starts at head of the list.
 - If the pointer is NULL, return (base case)
 - If the pointer is not NULL, use a recursive call to advance to next node.
 - Upon returning from the recursive call, display contents of the current node.

Recursion vs. Iteration

- Benefits (+), disadvantages(-) of recursion:
 - + Models some algorithms most accurately
 - + Results in shorter, simpler functions
 - May execute very slowly, because of function-call overhead.
 - Often uses more memory, because of local variables that are present for *each* level of recursion.
- Benefits (+), disadvantages(-) for iteration:
 - + Usually executes more efficiently than recursion.
 - Sometimes harder to code or understand: if an algorithm is inherently recursive in nature, then a non-recursive implementation of the algorithm may be more complicated.

Recursion: Summary

- Any recursive function or program must have a “base case” to avoid an effective “endless loop”.
- The recursive logic must eventually reach the “base case”. That is, each recursive step should bring the program closer to the “base case”.
- Recursive algorithms are often *less* efficient than their iterative counterparts.
- The choice to use a recursive algorithm is usually based on simplicity.