

# CIT-237

# Command-Line Arguments

December 9, 2019

**NOTICE to Students:** Portions of these lecture slides are

Copyright 2018 Pearson Education, Inc.

We have a license to use this material *only* in the context of this course.

There is NO PERMISSION to share these lecture slides with anyone not taking the course.

There is NO PERMISSION to post these lecture slides on the Internet.

# Reminder / Announcement

- Quiz 8 will be on Wednesday, December 11.
- The material covered on Quiz 8 will be:
  - The Lectures of November 25, 27, and December 2.
  - Chapters 19, 20 and 21.
- The EXTENDED Due date for Project 3 is TODAY (Monday, December 9).
- Our last day of class is Monday, December 16.
  - Obviously, that is the last day to demonstrate the solutions to Lab Exercises.
  - We will NOT have a Final Exam.

# Command-line Environment (1)

- While we are accustomed to using our computers with the “point-and-click” graphical user interface, there are some occasions when a program needs to be invoked from a “command-line” environment.
- The Windows Operating System allows us to open a command-line interface by running a special tool:
  - In Windows 7, the “default” command-line interface was the “cmd” tool.
  - In Windows 10, the “default” command-line interface is the “Power Shell” tool.
- There is a rich set of command-line operations that the operating system supports.
  - To view a summary of these operations, open a “cmd” tool and type “help”, followed by the ENTER key:

`help`
  - If you wish to save a copy of this “help” information for browsing later, type the following (followed by the ENTER key):

`help > help.txt`

## Command-line Environment (2)

- To view more detailed documentation about a particular command, type “help”, followed by the command name, followed by the ENTER key.
  - Several examples:

```
help dir
```

```
help cd
```

```
help set
```

- This detailed documentation can also be saved in a text file, if desired. For example:

```
help dir > dir.txt
```

```
help cd > cd.txt
```

```
help set > set.txt
```

# Command-line Environment (3)

- Many details of how the system behaves can be altered by modifying *environment variables*.
  - This is described in the documentation for the “set” command.
  - To view the **current** value of all environment variables, run the “set” command with no arguments:

```
set > envirVars.txt
```

- There is a convenient way to start the command-line interface at a particular location :
  1. Use the *File Explorer* tool to navigate to a particular folder.
  2. Point the mouse at an “empty” column of the display,
  3. Hold down the SHIFT key,
  4. Press the right mouse button, and
    - For Windows 7, select the “**Open Command Window Here**” menu.
    - For Windows 10, select the “**Open Power Shell Window Here**” menu.

# Windows 10 Command-Line Environment

- As previously noted, the Operating System I currently run at home is Windows 7.  
(I have deferred upgrading until this semester is over.)
- Most students today run Windows 10 on their personal computers.
- There are numerous online tutorials about the Windows 10 command-line environment.

# C++ Command-line Arguments

- In a C++ program, command-line arguments may be passed to the “main” function in the form of optional calling parameters:

```
int main(int argc, char *argv[])
```

- The **argc** parameter contains the number of items that were typed on the command line, including the name of the program.
- The `argv` parameter is an array of char pointers.
  - In the function header, the brackets are empty because `argv` is an external array of unknown size.
  - The number that is stored in `argc`, however, is the number of elements in the `argv` array.
  - Each pointer in the `argv` array points to a C-string holding one command line argument.

# Command-line Arguments Example

```
#include <iostream>
using namespace std;

int main(int argc, char *argv[])
{
    cout << "You entered " << (argc - 1);
    cout << " command line arguments.\n";
    if (argc > 1)
    {
        cout << "Here they are:\n";
        for (int count = 1; count < argc; count++)
            cout << argv[count] << endl;
    }
    return 0;
}
```



## Adding a List of Numbers (1)

- Another example is a program to add a list of numbers, where the numbers are listed on the command line.
- One nice feature of this is that the program will add as many numbers as the user chooses to type on the command line.

# Adding a List of Numbers (2)

```
#include <iostream>
#include <cmath>    // Needed for atof
using namespace std;

int main(int argc, char *argv[])
{
    double total = 0;

    if (argc > 1)
    {
        for (int count = 1; count < argc; count++) {
            total += atof(argv[count]);
        }
        cout << total << endl;
    }
    return 0;
}
```

# Appendix Document on Moodle

As I indicated in the previous class, I have been unable to locate the Appendices for the 9<sup>th</sup> edition of the textbook on the publisher's website.

- The document I have placed on Moodle is from the 8<sup>th</sup> edition.