Geometria Computacional

Círculos: problemas resolvidos

Prof. Edson Alves

2018

Faculdade UnB Gama


Sumário

- 1. UVA 10221 Satellites
- 2. UVA 10209 Is This Integration?

UVA 10221 - Satellites

Problema

The radius of earth is 6440 Kilometer. There are many Satellites and Asteroids moving around the earth. If two Satellites create an angle with the center of earth, can you find out the distance between them? By distance we mean both the arc and chord distances. Both satellites are on the same orbit (However, please consider that they are revolving on a circular path rather than an elliptical path).



E = Earth S = Satellite

Entrada e saída

Input

The input file will contain one or more test cases.

Each test case consists of one line containing two-integer s and a, and a string 'min' or 'deg'. Here s is the distance of the satellite from the surface of the earth and a is the angle that the satellites make with the center of earth. It may be in minutes (') or in degrees (°). Remember that the same line will never contain minute and degree at a time.

Output

For each test case, print one line containing the required distances i.e. both arc *distance* and *chord distance* respectively between two satellites in Kilometer. The distance will be a floating-point value with six digits after decimal point.

Exemplo de entradas e saídas

Sample Input

500 30 deg 700 60 min 200 45 deg

Sample Output

3633.775503 3592.408346 124.616509 124.614927 5215.043805 5082.035982

Solução

- A primeira etapa da solução é uniformizar as unidades de medida
- \bullet Sabendo que um grau tem 60 minutos, a conversão de x minutos para y graus é

$$y = \frac{x}{60}$$

• Sabendo que π radianos correspondem a 180°, segue que o ângulo α , em radianos, será de

$$\alpha = \frac{a\pi}{180}$$

ullet O comprimento c do arco será dado por

$$c = \alpha R$$
,

onde R é o raio até o satélite, isto é, r+s

ullet A corda terá comprimento L igual a

$$L = 2R\sin(\frac{\alpha}{2})$$

 \bullet Com estas informações, a solução terá complexidade O(T) , onde T é o número de casos de teste

```
1 #include <iostream>
2 #include <cmath>
4 using namespace std;
6 const int R { 6440 };
7 const double PI = acos(-1.0);
9 double arc(double s, double a)
10 {
      auto r = s + R;
      return r*a;
14 }
16 double chord(double s, double a)
17 {
      auto r = s + R:
18
      return 2*r*sin(a/2);
21 }
```


```
23 int main()
24 {
      double s, a;
25
      string unit;
26
      while (cin >> s >> a >> unit)
28
      {
           if (unit[0] == 'm')
30
               a /= 60;
32
           if (a > 180)
               a = 360 - a:
34
35
           a *= (PI/180.0);
36
           printf("%.6f %.6f n", arc(s, a), chord(s, a));
38
39
40
      return 0;
41
42 }
```

UVA 10209 - Is This

Integration?

Problema

In the image below you can see a square ABCD, where $AB = \mathbf{D}$ BC = CD = DA = a. Four arcs are drawn taking the four vertexes A, B, C, D as centers and aas the radius. The arc that is drawn taking A as center, starts at neighboring vertex B and ends at neighboring vertex D. All other arcs are drawn in a similar fashion. Regions of three different shapes are created in this fashion. You will have to determine the total area these different shaped regions.



Entrada e saída

Input

The input file contains a floating-point number $a(0 \le a \le 10000)$ in each line which indicates the length of one side of the square. Input is terminated by end of file.

Output

For each line of input, output in a single line the total area of the three types of region (filled with different patterns in the image above).

These three numbers will of course be floating point numbers with three digits after the decimal point. First number will denote the area of the striped region, the second number will denote the total area of the dotted regions and the third number will denote the area of the rest of the regions.

Exemplo de entradas e saídas

Sample Input

- 0.1
- 0.2
- 0.3

Sample Output

- 0.003 0.005 0.002
- 0.013 0.020 0.007
- 0.028 0.046 0.016

Solução

- Observe, inicialmente, que a área tracejada é composta por um quadrado cujo lado é o comprimento da corda c gerada por um ângulo igual a um terço de $\pi/2$, somado a quatro segmentos g
- Assim, $A_T = c^2 4g$, onde

$$c = 2a \sin\left(\frac{\pi}{6}\right)$$

$$s = \frac{a+a+c}{2}$$

$$T = \sqrt{(s-a)(s-a)(s-c)}$$

$$S = \frac{\pi a^2}{12}$$

$$g = S - T$$

• Já a área pontilhada é a metade do que resta quando subtraída, da área de um semi-círculo de raio a, a área de um quadrado de lado a e a área tracejada

Solução

Portanto,

$$A_P = \frac{\pi a^2}{2} - a^2 - A_T$$

- Por fim, a área restante A_R é o que sobra da diferença entre a área de um quadrado de lado a e as duas áreas já computadas
- Logo,

$$A_R = a^2 - A_T - A_P$$

 \bullet As expressões apresentadas permitem a implementação de uma solução O(T), onde T é o número de casos de teste

```
1 #include <iostream>
2 #include <cmath>
4 using namespace std;
6 const double PI { acos(-1.0) };
8 struct Circle
9 {
      double r;
10
      double arc(double theta) const
          return theta * r;
14
      double chord(double a) const
18
          return 2 * r * sin(a/2);
20
```

```
double sector(double theta) const
           return (theta * r * r)/2;
25
26
      double segment(double a) const
28
          auto c = chord(a);
29
           auto s = (r + r + c)/2.0;
30
           auto T = sqrt(s*(s - r)*(s - r)*(s - c));
31
32
           return sector(a) - T;
34
35 };
36
```

```
37 int main()
38 {
      double a:
40
      while (scanf("%lf", &a) == 1)
41
          Circle circle { a };
44
          double c = circle.chord(PI/6);
          double g = circle.segment(PI/6);
46
          double stripped = c * c + 4*g;
48
          double dotted = 4*(-stripped + (PI/2.0 - 1.0)*a*a)/2.0;
          double rest = a*a - stripped - dotted:
50
51
          printf("%.3f %.3f %.3f\n", stripped, dotted, rest);
52
      return 0;
55
56 }
```

Referências

- 1. UVA 10221 Satellites
- 2. UVA 10209 Is This Integration?