

Category Theory for Programmers

Homework (Session 5)


Bruno Vandekerkhove

Contents

Pushout in C++	1
Limit of the identity functor	1
Pullback, pushout, ... in Set	1
Coequalizer	2
Pullback towards terminal object	2
Pushout from initial object	2

Pushout in C++

We talked about products and co-products in posets before, where the term supremum and infimum applied. In this more general case applied on C++ types a diagram of a pushout D is as follows :



Any superclass E of B and C is a superclass of D . Which means that D corresponds to a superclass that encompasses all the functionality that the subclasses have in common¹.

Limit of the identity functor


The identity functor Id maps a category to itself. The initial object is the object for which there's exactly one morphism to every object. When constructing the limit for Id any apex will correspond to an initial object (or there wouldn't be a natural transformation from Δ_c to Id). If there are many apexes (or initial objects) there

¹One has to consider all possible superclasses of B and C . Then D inherits from all of those. Some superclasses may only declare a part of the functionality that's present in both the classes B and C , yet together they declare all of it and nothing more or some wouldn't be superclasses.

will be unique transformations between them. Indeed, initial objects are unique up to isomorphism, which we knew already.

Pullback, pushout, ... in **Set**

Starting from the diagram depicted on the previous page and applying analogous reasoning we can see that D is the smallest superset of both B and C . In the opposite category we get :



Here, D is the largest subset (every other set that's a subset of B and C ought to be a subset of D). A trellis visualises this and the terms supremum and infimum are in order.

As for the initial - and terminal object, they (trivially) correspond to the empty set and the set on which the category is based.

Coequalizer

can you guess what coequalizer is?

Pullback towards terminal object

should be product (prove)

Pushout from initial object

should be coproduct (prove)