

Doors

Bruno Carvalho up201606517 and Amadeu Pereira up201605646

Faculdade de Engenharia da Universidade do Porto

Abstract. In this paper we describe and explore a simple restraint logic programming solution for the logic problem *Doors*.

Keywords: doors · logic puzzle · rooms

1 Examples

4	2	4	2
5	3	5	3
4	3		4
2	3	2	4

2 Problem Description

The logic problem *Doors* is a puzzle on a rectangular board whose cells are either empty or contain natural numbers. The board is thought of like a *house*. Each cell is a *room*, and two adjacent cells are separated by a *wall* with one *door*. That door may be either open or closed. If it is open, then the cell can see its adjacent room through the doorway. A man standing in a room can look in all four directions — north, east, west, south — and count the number of *visible rooms*.

The puzzle consists in discovering an assignment of open and closed doors to the walls of the board such that the natural number in each non-empty cell is how many rooms are visible from that cell (including itself). There may be multiple solutions, or none at all.

3 Representation

A puzzle of size $n \times m$ is represented internally by three matrices (list of lists): *Board*, of size $n \times m$, holding the cell numbers; *Vertical*, of size $n \times (m-1)$, holding the vertical walls; and *Horizontal*, of size $(n-1) \times m$, holding the horizontal walls.

For each cell (R, C) , $R = 1, 2, \dots, n$, $C = 1, 2, \dots, m$, indices in *Board*, the left wall has index $(R, C-1)$ in *Vertical*, the right wall has index (R, C) in *Vertical*, the top wall has index $(R-1, C)$ in *Horizontal*, the bottom wall has index (R, C) in *Horizontal*. Each wall in the board is assigned the number 0 for closed door and 1 for open door.

4 Restrictions

When solving a puzzle *Board* is fully instantiated, while *Vertical* and *Horizontal* contain domain variables (domain $\{0,1\}$). Empty cells in the *Board* are represented by a 0, as it is never a valid visible room counter.

1	<i>T</i>	?	?	?	?	?	2
<i>X</i>	<i>A</i>	<i>B</i>	<i>C</i>	<i>D</i>	<i>E</i>	<i>F</i>	<i>G</i>
?	<i>M</i>	?	?	?	?	?	?
?	<i>N</i>	?	?	?	?	?	?

Consider the puzzle above. The horizontal range $A - G$ consists of 7 rooms and 6 vertical doors: let $\{b, c, d, e, f, g\}$ be these vertical doors, from left to right.

Focus on room *A*. If $b = 0$ then *A* sees no rooms to its right. If $b = 1$ and $c = 0$ then *A* sees only room *B*. A general formula can be deduced by noticing that closed doors behave as zero elements.

Let e_A be the total number of rooms *A* sees to its right (east), then

$$e_A = b + b(c + c(d + d(e + e(f + f(g + g \cdot 0)))))) \quad (1)$$

Now, if we analogously define w_A for west, n_A for north and s_A for south, then we find that the number in cell *A* must be $e_A + w_A + n_A + s_A + 1$.

Implementing these restrictions in PROLOG is surprisingly simple. We start with a predicate to compute formula (1):

```
calculate_value([], 0).
calculate_value([H|T], V) :-
    calculate_value(T, V1),
    V #= H + H*V1.
```

Then, for each non-zero cell (R, C) on the *Board*, we retrieve as a list the four ranges of doors to the right, left, top and bottom of (R, C) , apply the formula for each list, and finally the restriction:

```
restrict_cell(Board, _, _, [R,C]) :-
    matrixnth1([R,C], Board, 0), !. % empty cell
restrict_cell(Board, Vertical, Horizontal, [R,C]) :-
    matrixnth1([R,C], Board, Value),
    right_total(Vertical, [R,C], Right),
    left_total(Vertical, [R,C], Left),
    top_total(Horizontal, [R,C], Top),
    bot_total(Horizontal, [R,C], Bot),
    Right + Left + Top + Bot + 1 #= Value.
```

References

1. Author, F.: Article title. *Journal* **2**(5), 99–110 (2016)
2. Author, F., Author, S.: Title of a proceedings paper. In: Editor, F., Editor, S. (eds.) *CONFERENCE 2016, LNCS*, vol. 9999, pp. 1–13. Springer, Heidelberg (2016). <https://doi.org/10.10007/1234567890>
3. Author, F., Author, S., Author, T.: Book title. 2nd edn. Publisher, Location (1999)
4. Author, A.-B.: Contribution title. In: *9th International Proceedings on Proceedings*, pp. 1–2. Publisher, Location (2010)
5. LNCS Homepage, <http://www.springer.com/lncs>. Last accessed 4 Oct 2017