

Performance Tuning

A CEREBRUM Research Publication (v1.2.4)

Bryan Alexander Buchorn
Independent Researcher

Abstract

Overview: This guide provides a conceptual entry point into the CEREBRUM framework. It is designed for practitioners and researchers seeking to understand the core reasoning signals of Framework Implementation Guide.

0.1 CEREBRUM Performance Tuning Guide

Version: v1.1.0

This guide covers the key parameters affecting query latency, throughput, reasoning quality, and memory usage — and how to tune them for your specific workload.

The Performance Levers (Quick Reference)

Parameter	Default	Affects	Tune When
beam_width	10	Latency, recall	Graph is large or queries are slow
max_hop	3	Latency, recall depth	Questions require deeper reasoning
n_trials (DSCF)	5	Community quality, startup time	Startup is slow or Q is low
q_drift_threshold	0.05	Rebalance frequency	Graph updates are frequent
warm_start_strength	0.0	First-hop variance	Probabilistic mode on sparse graphs
window_size (stream)	10,000	Memory, temporal context	High-volume ingest
batch_size (stream)	50	Ingest throughput, latency	High-frequency event streams
CEREBRUM_WORKERS	4	Concurrent query throughput	Multi-user deployments

1. Query Latency

beam_width

The single most impactful parameter for latency. Beam width controls how many candidates are evaluated at each hop.

beam_width	Latency (21-node)	Latency (10K-node)	H@10 (MetaQA-3hop)
3	0.9ms	2.1ms	0.271
5	1.2ms	3.4ms	0.294
10	1.8ms	6.3ms	0.248
20	3.1ms	14.8ms	0.331
50	7.4ms	48.2ms	0.339

Rule of thumb: beam_width=10 is the quality/latency sweet spot for most graphs. Increase to 20–50 only for high-stakes queries where latency budget is relaxed (>50ms acceptable).

max_hop

Each additional hop multiplies the search space by approximately $\text{beam_width} \times \text{avg_degree}$.

Total candidates	$\text{beam_width}^{\text{max_hop}}$
------------------	--

For a graph with avg_degree=5 and beam_width=10:

- max_hop=2: 100 candidates
- max_hop=3: 1,000 candidates
- max_hop=4: 10,000 candidates (consider increasing beam_width instead)

Recommendation: Start at max_hop=3. Increase to 4 only if 3-hop recall is inadequate on your specific queries.

—

2. Community Detection Quality vs. Speed

n_trials (DSCF)

DSCF is stochastic; running multiple trials and selecting the highest-modularity result improves Q.

n_trials	Avg Q (toy_graph)	Startup time
1	0.38	Fast
3	0.41	Moderate
5	0.43	Recommended
10	0.44	Slow

For production, compute communities once at startup or cache them. Communities only need recomputation when the graph changes substantially (triggered by GlobalRebalancer).

Algorithm selection

Algorithm	Q	Speed	Use when
dscf	Highest	Moderate	Default – best reasoning quality
leiden	High	Moderate	Large graphs where DSCF is slow
lpa	Lower	Fast	Very large graphs (>1M nodes) where startup time matters

—

3. Streaming Ingest Throughput

batch_size and flush_interval_ms

Events are batched before commit to amortize graph write cost.

```
StreamAdapter(  
    base_adapter=adapter,  
    batch_size=50,           # events per commit      increase for high-  
        volume ingest  
    flush_interval_ms=100,   # max wait before commit    decrease for low-  
        latency  
    window_size=10_000,     # recency buffer size      reduce to save  
        memory  
)
```

Scenario	batch_size	flush_interval_ms	Throughput
Low-latency IoT	10	20	500 events/s
General streaming	50	100	2,000 events/s
High-throughput ingest	200	500	8,000 events/s

Memory: Each event in the sliding window uses 200 bytes. `window_size=10,000` → 2MB.

GlobalRebalancer tuning

```
GlobalRebalancer(  
    adapter,  
    q_drift_threshold=0.05,  # lower = more frequent rebalancing (higher  
        quality, more CPU)  
    min_interval_s=30.0,    # minimum seconds between rebalances  
)
```

Rebalancing is expensive ($O(N \log N)$). For high-ingest deployments, set `min_interval_s=120` to prevent rebalance storms during burst traffic.

—

4. Probabilistic Mode (Bayesian Beam Search)

Probabilistic mode adds Thompson sampling overhead (15% latency increase) but improves quality on sparse graphs and provides confidence intervals.

```
BeamTraversal(  
    probabilistic=True,  
    warm_start_strength=5.0,  # 0.0 = uniform prior (cold), 5.0 = CSA-seeded  
        (warm)  
)
```

warm_start_strength guidance:

- 0.0 — standard uniform Beta(1,1) prior (v0.4.0 behavior)
- 2.0 — mild warm-start (reduces first-hop variance 40%)
- 5.0 — strong warm-start (reduces first-hop variance 85%, recommended for sparse graphs)

- 10.0 — aggressive seeding (can reduce diversity; use only on very sparse graphs)

5. Embedding Choice

Engine	Semantic quality	Speed	Use when
<code>RandomEngine(dim=64)</code>	None (structural only)	Fastest	Graph topology dominates; no text labels
<code>RandomEngine(dim=128)</code>	None	Fast	Larger graphs needing more embedding capacity
<code>SentenceEngine</code>	High	Slow (GPU-accelerated)	Entity names carry semantic meaning
<code>RotateEngine</code> (trained)	Relational	Medium (after training)	Rich relation diversity

For pure structural reasoning (graphs where entity names are opaque IDs), `RandomEngine` achieves the same H@10 as `SentenceEngine` because the community consensus term (β) dominates over semantic similarity (α).

6. ResourceGovernor Budgets

```
from core.hardware import ResourceGovernor

governor = ResourceGovernor(
    max_cpu_percent=80,          # cap CPU usage across all queries
    max_memory_mb=2048,         # hard memory limit
    query_timeout_ms=5000,      # abort queries exceeding this
    rem_cpu_budget=0.15,        # fraction of CPU reserved for REM cycle
)
```

For latency-critical deployments, set `rem_cpu_budget=0.05` to give more CPU to query processing and reduce REM cycle priority.

7. Memory Optimization

Component	Memory	Reduction strategy
Embedding matrix	$N \times \text{dim} \times 4 \text{ bytes}$	Reduce <code>dim</code> (64→32 halves memory)
Community map	$N \times 8 \text{ bytes}$	Minimal — unavoidable
Sliding window buffer	$W \times 200 \text{ bytes}$	Reduce <code>window_size</code>
Materialized path store	Variable	Call <code>adapter.clear_path_cache()</code>
InsightEvent graph	Capped at 10K nodes	Reduce <code>meta_insight_engine.max_events</code>

For a 100K-node graph with `dim=64`: embedding matrix $\approx 25\text{MB}$. For 1M nodes: $\approx 250\text{MB}$.

8. Benchmark Your Deployment

```
# Run the synthetic benchmark
python benchmarks/synthetic_eval.py --nodes 1000 --edges 5000 --queries 100

# Run baseline comparison
python benchmarks/baseline_comparison.py --algorithm dscf --beam-width 10

# Profile a specific configuration
python -m cProfile -s cumulative benchmarks/synthetic_eval.py 2>&1 | head -30
```

See `benchmarks/README.md` for full benchmark documentation.

— **Copyright © 2026 Bryan Alexander Buchorn. All Rights Reserved.**

Project CEREBRUM — March 2026 — Hardened Enterprise Security (v1.2.4)