


## Metal Film Resistors

# General Type

## Normal & Miniature Style [ MFR Series ]



### INTRODUCTION


The MFR Series Metal Film Resistors are manufactured using a vacuum sputtering system to deposit multiple layers of mixed metal alloys and passivative materials onto a carefully treated high grade ceramic substrate. After a helical groove has been cut in the resistive layer, tinned connecting leads of electrolytic copper are welded to the end-caps. The resistors are coated with layers of blue color lacquer.

### FEATURES

Power Rating	1/6W, 1/4W, 1/2W, 1W, 2W, 3W
Resistance Tolerance	±0.5%, ±1%, ±2%, ±5%
T.C.R.	±50ppm/°C, ±100ppm/°C


### DERATING CURVE

For resistors operated in ambient temperatures above 70°C, power rating must be derated in accordance with the curve below.



### DIMENSIONS

Unit: mm



STYLE		DIMENSION			
Normal	Miniature	L	øD	H	ød
MFR-12	MFR25S	3.4±0.3	1.9±0.2	28±2.0	0.45±0.05
MFR-25	MFR50S	6.3±0.5	2.4±0.2	28±2.0	0.55±0.05
MFR-50	MFR1WS	9.0±0.5	3.3±0.3	26±2.0	0.55±0.05
MFR100	MFR2WS	11.5±1.0	4.5±0.5	35±2.0	0.8±0.05
MFR200	MFR3WS	15.5±1.0	5.0±0.5	33±2.0	0.8±0.05

Note:

## ELECTRICAL CHARACTERISTICS

STYLE	MFR-12	MFR25S	MFR-25	MFR50S	MFR-50	MFR1WS	MFR100	MFR2WS	MFR200	MFR3WS
Power Rating at 70°C	1/6W	1/4W		1/2W		1W		2W		3W
Maximum Working Voltage	200V		250V	300V	350V	400V	500V			
Maximum Overload Voltage	400V		500V	600V	700V	800V	1,000V			
Voltage Proof on Insulation	300V	400V	500V			700V	1,000V			
Resistance Range	1Ω - 4M7Ω & for E24 & E96 series value									
Operating Temp. Range	-55°C to +155°C									
Temperature Coefficient	±50ppm/°C, ±100ppm/°C									

Note: Special value is available on request

## ENVIRONMENTAL CHARACTERISTICS

PERFORMANCE TEST	TEST METHOD		APPRAISE
Short Time Overload	IEC 60115-1 4.13	2.5 times RCWV for 5 sec. (Not more than maximum Overload Voltage)	±0.25%+0.05Ω
Voltage Proof on Insulation	IEC 60115-1 4.7	In V-Block for 60 sec., test voltage as above table	No Breakdown
Temperature Coefficient	IEC 60115-1 4.8	Between -55°C to +155°C	By type
Insulation Resistance	IEC 60115-1 4.6	in V-block for 60 Sec.	>10,000MΩ
Solderability	IEC 60115-1 4.17	245±5°C for 3±0.5 Sec.	95% Min. coverage
Solvent Resistance of Marking	IEC 60115-1 4.30	IPA for 5±0.5 Min. with ultrasonic	No deterioration of coatings and markings
Robustness of Terminations	IEC 60115-1 4.16	Direct load for 10 Sec. in the direction of the terminal leads	≥2.5kg (24.5N)
Periodic-pulse Overload	IEC 60115-1 4.39	4 times RCWV 10,000 cycles (1 Sec. on, 25 Sec. off)	±1.0%+0.05Ω
Damp Heat Steady State	IEC 60115-1 4.24	40±2°C, 90-95% RH for 56 days, loaded with 0.1 times RCWV	±1.5%+0.05Ω
Endurance at 70°C	IEC 60115-1 4.25	70±2°C at RCWV (or Umax., Whichever less) for 1,000 Hr. (1.5Hr: on, 0.5Hr: Off)	±1.5%+0.05Ω
Temperature Cycling	IEC 60115-1 4.19	-55°C ⇒ Room Temp. ⇒ +155°C ⇒ Room Temp. (5 cycles)	±0.75%+0.05Ω
Resistance to Soldering Heat	IEC 60115-1 4.18	260±3°C for 10±1 Sec., immersed to a point 3±0.5mm from the body	±0.25%+0.05Ω

Note: RCWV(Rated Continuous Working Voltage) =  $\sqrt{\text{Power Rating} \times \text{Resistance Value}}$  or Max. working voltage listed above, whichever less.

Revision: 2020

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Yageo:

[MFR-25FTF52-39K2](#) [MFR-50FTE52-1K2](#) [MFR-25FRF52-12R](#) [MFR-50FTE52-237R](#) [MFR-25FRE52-887K](#)  
[MFR25SFRF52-392R](#) [MFR-25FRE52-64K9](#) [MFR100FTF73-200K](#) [MFR-50FRF52-2K](#) [MFR-25FRE52-806K](#)  
[MFR25SFRF52-200R](#) [MFR25SFTF52-8K25](#) [MFR-50FRE52-8K25](#) [MFR25SFTF52-390R](#) [MFR-25FRE52-174K](#) [MFR-](#)  
[25FRE52-442R](#) [MFR-50FRE52-3K3](#) [MFR-50FRE52-470K](#) [MFR25SFRF52-274R](#) [MFR100FTE52-510R](#) [MFR-](#)  
[25FTF52-40R2](#) [MFR-25FTF52-5K11](#) [MFR25SFTF52-8K2](#) [MFR-25FRE52-1K37](#) [MFR-25FTF52-30R1](#) [MFR-25FTE52-](#)  
[2M37](#) [MFR-25FTE52-38R3](#) [MFR25SFRF52-24K3](#) [MFR25SFTF52-475K](#) [MFR-25FRE52-3K24](#) [MFR-25FRE52-6K98](#)  
[MFR-12FRF52-29K4](#) [MFR-50FRF52-909K](#) [MFR25SFTF52-340R](#) [MFR-25FRE52-2K67](#) [MFR25SFTF52-80R6](#)  
[MFR100FTE52-6K8](#) [MFR25SFTF52-39K](#) [MFR-25FTF52-22R1](#) [MFR-25FTF52-215K](#) [MFR-50FRE52-1M](#)  
[MFR25SFRF52-1K37](#) [MFR-12FRF52-2K](#) [MFR-50FTE52-3K](#) [MFR25SFTF52-4K12](#) [MFR100FTF73-12R](#) [MFR-](#)  
[25FRE52-1K4](#) [MFR-25FTF52-665R](#) [MFR-25FRE52-39K](#) [MFR-50FRE52-5K6](#) [MFR-25FTF52-43R](#) [MFR25SFRF52-](#)  
[29K4](#) [MFR-12FTF52-20K5](#) [MFR50SFTF52-1M](#) [MFR25SFTF52-3K01](#) [MFR-50FRF52-2K21](#) [MFR-25FTF52-14K3](#)  
[MFR25SFTF52-4K64](#) [MFR-25FRE52-5K62](#) [MFR25SFRF52-562K](#) [MFR-50FRF52-38K3](#) [MFR-50FRF52-75K](#) [MFR-](#)  
[25FTF52-12R7](#) [MFR25SFTF52-68R](#) [MFR-25FTF52-6K81](#) [MFR-25FTF52-680K](#) [MFR100FTE52-62R](#) [MFR-50FRF52-](#)  
[475K](#) [MFR-25FRF52-5M49](#) [MFR25SFTF52-2K67](#) [MFR-25FTF52-82K5](#) [MFR-25FTF52-274R](#) [MFR-50FRE52-280K](#)  
[MFR-50FRF52-1K62](#) [MFR-12FTE52-7K5](#) [MFR25SFRF52-51K1](#) [MFR100FRF73-13K3](#) [MFR-25FTF52-133K](#) [MFR-](#)  
[50FTE52-220R](#) [MFR25SFTF52-5K23](#) [MFR100FTF52-120R](#) [MFR25SFTF52-62K](#) [MFR25SFTF52-15K](#) [MFR-](#)  
[25FTF52-26K7](#) [MFR-25FRE52-402R](#) [MFR100FTF52-820K](#) [MFR-50FTE52-280K](#) [MFR-25FRE52-5K11](#)  
[MFR25SFTF52-68K1](#) [MFR-25FRE52-536K](#) [MFR-25FRE52-357R](#) [MFR100FTE52-82K](#) [MFR-25FRE52-118K](#) [MFR-](#)  
[25FTF52-48R7](#) [MFR25SFTF52-124R](#) [MFR25SFRF52-4K32](#) [MFR100FTF73-47R](#) [MFR-25FTF52-300K](#)  
[MFR25SFTF52-200K](#) [MFR25SFTF52-2K26](#)