

# Telco ADB Automation – Installation & User Guide (v1.0.0)

This guide covers the exact steps to install and run the **Telco ADB Automation** desktop suite on Windows and Ubuntu, followed by a concise user manual describing day-to-day operations (device onboarding, module runs, workflow execution, and troubleshooting).

---

## 1. Architecture Recap

- **Desktop shell:** Electron 28 (Node.js 18) bootstrapping the React frontend and FastAPI backend (`simple-server.py`).
- **Frontend:** React 18 + Vite, Material UI, TypeScript (living under `mon-projet/src/frontend`).
- **Backend:** FastAPI + Pydantic + Python 3.11, modules orchestrate ADB scripts (`mon-projet/src/backend` and `modules/telco_modules.py`).
- **Runtime requirements:** Android Debug Bridge (`adb`), Node.js, Python, and device USB drivers.

Keep this structure in mind when installing; each platform section ensures both Node/Electron and Python/ADB pieces are configured.

---

## 2. Windows Installation

### 2.1 Prerequisites

Requirement	Recommended Version	Notes
Windows	10 21H2+ / 11	64-bit
Node.js	18.x LTS	Required for Electron + React build
npm	Bundled with Node	Used for dependency install
Python	3.11.x	Backend ( <code>simple-server.py</code> )
pip	Latest	<code>python -m pip install --upgrade pip</code>
ADB / Platform Tools	r34+	Install via Android SDK or packaged zip
USB Drivers	OEM specific	Samsung, Google, etc.

Ensure node, npm, python, and adb are all resolvable from PowerShell (Get-Command node etc.).

## 2.2 Clone / Update the Repository

```
git clone https://github.com/<org>/ADB-automation-tool.git
cd ADB-automation-tool\mon-projet
```

If already cloned, pull latest: `git pull`.

## 2.3 Backend Setup

```
python -m venv .venv
.venv\Scripts\Activate.ps1
python -m pip install --upgrade pip
pip install -r requirements-mongodb.txt
```

The requirements file bundles FastAPI, uvicorn, Pydantic, and telco module dependencies. Repeat `pip install -r requirements.txt` if you maintain an alternate lock file.

## 2.4 Frontend / Electron Setup

```
# From mon-projet/
npm install
npm run build --prefix src/frontend # builds React assets
npm run build                       # optional: compile TypeScript/Electron preload
```

## 2.5 Running in Development

Two options exist:

### 1. One-shot helper script

```
./launch-app.ps1 # starts backend + Electron renderer
```

### 2. Manual steps

```
# Terminal 1
cd mon-projet
. .venv\Scripts\Activate.ps1
python simple-server.py

# Terminal 2
cd mon-projet/src/frontend
npm start # Vite dev server (optional)

# Terminal 3
cd mon-projet
npx electron .
```

## 2.6 Packaging (Optional)

To produce an installer:

```
npm run dist # invokes electron-builder (see package.json)
```

Artifacts land under mon-projet/dist/ (NSIS) and mon-projet/build/.

---

## 3. Ubuntu Installation

### 3.1 Prerequisites

```
sudo apt update
```

```
sudo apt install -y curl git build-essential python3.11 python3.11-venv python3-pip adb
```

Install Node.js 18 (via NodeSource):

```
curl -fsSL https://deb.nodesource.com/setup_18.x | sudo -E bash -
```

```
sudo apt install -y nodejs
```

Confirm versions: node -v, npm -v, python3.11 -V, adb version.

### 3.2 Clone Repo

```
git clone https://github.com/<org>/ADB-automation-tool.git
```

```
cd ADB-automation-tool/mon-projet
```

### 3.3 Backend Setup

```
python3.11 -m venv .venv
```

```
source .venv/bin/activate
```

```
pip install --upgrade pip
```

```
pip install -r requirements-mongodb.txt
```

### 3.4 Frontend / Electron Setup

```
npm install
```

```
cd src/frontend && npm install && npm run build && cd ../..
```

### 3.5 Development Run

```
# Terminal 1 - backend
```

```
source .venv/bin/activate
```

```
python simple-server.py # listens on 0.0.0.0:8007 by default
```

```
# Terminal 2 - Electron (uses built frontend if present)
```

```
npx electron .
```

If you prefer Vite hot reload:

```
cd src/frontend
npm run dev -- --host
```

Launch Electron with `npm run electron-dev` (see `package.json` scripts) to point at the dev server.

### 3.6 Packaging

Electron Builder can produce AppImage/DEB on Ubuntu:

```
npm run dist:linux
```

Configure `electron-builder.yml` (or `package.json > build`) for Linux targets before distributing.

---

## 4. User Manual (v1.0.0)

### 4.1 First Launch

1. Connect target Android devices via USB with USB debugging enabled.
2. Start the app (`launch-app.ps1`, `start-app.bat`, or `npx electron .`).
3. Wait for the backend banner: `Uvicorn running on http://0.0.0.0:8007`. The dashboard then populates within ~3 seconds.

### 4.2 Dashboard

- **Device cards/table** display `Serial` `Alias` `FriendlyName`.
- Click the **edit icon** to rename alias; changes persist via API.
- Quick actions (Ping, Call, Airplane) are available per device.
- **Start Workflow** button opens workflow selector with the currently highlighted devices.

### 4.3 Device Manager

- Shows all devices ever connected (active + historical).
- Each row offers: status, tags, last seen timestamp, and a **notebook icon** that opens the activity timeline (modules/workflows run with timestamps).
- Use filters/search to locate QA collections. (Pinned/Collections widgets were removed for clarity in this release.)

#### 4.4 Modules Page

- Lists each telco module with description and parameter form.
- **RUN behavior:** When you click RUN on Ping, button turns green for the full backend execution (no modal). Other modules show inline status chips.
- Failures are logged in device history; watch the console for backend traces if needed (`mon-projet/simple-server.py`).

#### 4.5 Workflows

1. Drag modules from the left palette to the workflow canvas (drag-and-drop works L R).
2. Arrange modules; double-click to edit parameters.
3. Press **Start Workflow**:
  - The runner ensures module `n+1` waits until module `n` reports success (fix for multi-call sequences).
  - Progress indicator highlights only the truly running module.
  - Use **Stop Workflow** to cancel; UI halts progression when backend acknowledges the abort.

#### 4.6 Live Activity & Logs

- Device history captures: module/workflow name, result, timestamp, device serial.
- To inspect backend logs, check the Electron console or the terminal running `simple-server.py`.
- Known behavior: we intentionally suppress toast popups such as “Airplane Mode On – latest results...” to avoid clutter; refer to history instead.

#### 4.7 Troubleshooting

Symptom	Fix
Device takes long to appear/disappear	Ensure adb server running ( <code>adb kill-server &amp;&amp; adb start-server</code> ); app already polls faster (1s connect / 2s disconnect).

Symptom	Fix
Ping shows “Failed” instantly	Check that device responds to <code>adb shell ping</code> ; verify module script in <code>modules/telco_modules.py</code> .
Stop workflow ignored	Confirm backend log shows <code>Received stop signal</code> ; if not, ensure WebSocket connection alive or restart backend.
Electron “Renderer entry not found”	Run <code>npm run build --prefix src/frontend</code> so <code>src/frontend/build/index.html</code> exists before launching Electron prod mode.
Pydantic validator warning	Current backend still uses V1 validators; warning is harmless but upgrade path is documented in backlog.

#### 4.8 Shutdown

- Use **Stop Workflow** to halt all executions.
- Quit via system tray or **Ctrl+C** on backend terminal.
- Disconnect devices only after workflow completion to preserve log continuity.

## 5. Appendices

- **Scripts of interest:**
  - `launch-app.ps1`, `start-app.bat`, `launch-without-node.ps1` (Windows helpers)
  - `simple-server.py` (FastAPI)
  - `modules/` directory for telco-specific automation
  - `docs/exports/` for PDF/DOCX deliverables
- **Command summary:**

*# Windows*

`.\launch-app.ps1`

*# Ubuntu*

```
source .venv/bin/activate && python simple-server.py  
npx electron .
```

- **Support:** Log issues in the repo's tracker with backend logs + device history screenshots for faster triage.

---

*Last updated: 2025-12-12 (aligned with v1.0.0 feature set)*