

HW 2

Bryan Mui - UID 506021334

2025-01-29

Problem 1

1a, create a simulated dataset

simulate()
generate 100 UIDs starting from 100000000
Create homework 1-5 and quiz 1-7, using floor and runif to get a randomized value between 1-100

```
source("./506021334_stats102a_hw2.R")
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.4      v readr      2.1.5
## v forcats    1.0.0      v stringr   1.5.1
## v ggplot2    3.5.1      v tibble    3.2.1
## v lubridate  1.9.4      v tidyr     1.3.1
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
data <- simulate_data()
data
```

```
## # A tibble: 100 x 13
##       UID Homework1 Homework2 Homework3 Homework4 Homework5 Quiz1 Quiz2 Quiz3
##   <dbl>   <dbl>   <dbl>   <dbl>   <dbl>   <dbl> <dbl> <dbl> <dbl>
## 1 100000000      79      13      23      25      16     20     91     27
## 2 100000001      64      41      28      55      69     46     98     30
## 3 100000002       9      45      68      97       3     31     19     60
## 4 100000003      14      71      81      69      97       2     54     74
## 5 100000004      14      87      83      33      71     97     23     49
## 6 100000005      49      45      39      10       0     45     53       9
## 7 100000006      24      25      90      93      35     52     12     35
## 8 100000007      63      93      25       6     45     96     11     77
## 9 100000008      10       8      56      78      70       7     75     71
## 10 100000009      48      95       1      96       2     35     92     27
## # i 90 more rows
## # i 4 more variables: Quiz4 <dbl>, Quiz5 <dbl>, Quiz6 <dbl>, Quiz7 <dbl>
```