

GROUP I HANDSPRING/ YAMASHITA			GROUP II HANDSPRING with or without 1/1 TURN → SALTO FORWARD /BACKWARD		GROUP III TSUKAHARA or ½ on → SALTO FORWARD /BACKWARD with or without TURN		GROUP IV Round-off, Flic-flac → SALTO FORWARD /BACKWARD with or without LA TURN			GROUP V Round-off, Flic-flac (½ or 1/1) → HANDSPRING or SALTO FWD/BWD with or without LA TURN			
1.101	Handspring	8.5			All Group 3 vaults allow a 90° to 180° LA turn in the first flight		4.101 RO, FF → Repulsion 7.0 4.102 RO, FF → Repulsion ½ 7.7 4.201 RO, FF → 1/1 twist 9.1 4.202 RO, FF → 1½ twist 9.3			Group 5 vaults described as a Flic-flac with a 1/1 (360°) turn on: allow a ¾ (270°) to 1/1 (360°) LA turn in the first flight 5.101 RO, FF ½ → Hsp 8.9 5.102 RO, FF ½ → Hsp ½ off 9.1 5.107 RO, FF 1/1 → Hsp ½ off 9.2 5.108 RO, FF 1/1 → Repulsion 8.2			
1.102	Hsp → ½	8.6											
1.103	Yamashita	8.5											
1.104	Yami → ½	8.6											
1.105	½ → ½	8.6											
OR ¼ → ¾													
1.106	¼ - ½ → Repulsion	7.0											
1.109	FHS onto board, → Repulsion	8.6											
1.110	FHS onto board, → Hsp ½	8.7											
1.111	FHS onto board, ¼ -½→ Repulsion	7.1											
1.201	Hsp -→1/1	9.0											3.201 Tsukahara Tuck 9.6
1.202	Hsp → 1½	9.4											
1.203	Yami → 1/1	9.0											
1.205	½ → 1½	9.3											
OR ¼ → 1¾													
1.206	½ → 1/1	8.9											
OR ¼ → 1¼													
1.207	1/1 → H/Y	9.0											
1.208	1/1 → ½	9.3											
1.209	FHS onto board, Hsp → 1/1	9.1											
1.211	FHS onto board, ½ → ½ OR ¼ → ¾	8.7											
1.301	Hsp → 2/1	10.0	2.301 Hsp → Front Tuck 10.0		3.301 FHS onto board- ¼ to ½ → B. Tuck 9.7 3.302 Tsuk Tuck 1/1 10.0 3.303 Tsuk Pike 9.7 3.304 Tsuk Layout 10.0 3.305 FHS onto board, ¼ to ½ → B. Pike 9.8 3.306 ½ → ½, Fr. Tuck 10.0 OR ¼ → ¼, Fr. Tuck (land facing out) OR Tsuk Tuck ½ 3.308 ½ → ½, Fr. Tuck ½ 10.0 OR ¼ → ¾, Fr. Tuck ½			4.301 RO, FF → 2/1 twist 9.8 4.303 RO, FF → B. Tuck 1/1 10.0 4.304 RO, FF → B. Pike 9.7 4.305 RO, FF → B. Layout 10.0 4.307 RO, FF → ½ off, Fr. Tuck 10.0 OR RO, FF → B. Tuck ½ 4.407 RO, FF → ½ turn, Fr. Tuck ½ 10.0			5.301 RO, FF ½ → Front Tuck 10.0 5.312 RO, FF ½ → 2/1 twist off 10.0		
1.306	½ → 2/1 OR ¼ → 2¼	9.8	2.302 Hsp → Front Tuck ½ 10.0										
1.307 1/1 → 1/1 9.8 1.311 FHS onto board, ½ → 1/1 OR ¼ → 1¼ 9.0		2.304 Hsp → Front Pike 10.0											
		2.310 FHS onto board, Hsp → Fr. Tuck 10.0											
		2.311 FHS onto board, Hsp→ Fr. Pike 10.0											