

**PROGRAMACIÓN WEB II**  
**Mtra. Liliana Gámez Zavala**

**PRACTICA 1: (Verificar el funcionamiento de mysql)**

1. Enciende el xampp control para iniciar el servicio de apache y mysql
2. Accesa a la siguiente ruta: C:\xampp\mysql\bin
3. Una vez que te aparezca el prompt de mysql, teclea lo siguiente:  
mysql -h localhost -u root -p
4. Como password no es necesario teclear ningún dato y oprime enter
5. Prueba los siguientes comandos:
  - select now();
  - select version ();
  - show databases;
6. Una vez que hayas mostrado las bases de datos existentes, teclea el siguiente comando:  
use mysql;
7. utiliza el comando "show tables;" y verifica las tablas que están contenidas en la base de datos seleccionada.
8. Muestra los campos que se encuentran en la tabla users con el siguiente comando:  
show fields from user;

```
mysql> show fields from user;
```

Field	Type	Null	Key	Default	Extra
Host	char(60)	NO	PRI		
User	char(16)	NO	PRI		
Password	char(41)	NO			
Select_priv	enum('N','Y')	NO		N	
Insert_priv	enum('N','Y')	NO		N	
Update_priv	enum('N','Y')	NO		N	
Delete_priv	enum('N','Y')	NO		N	
Create_priv	enum('N','Y')	NO		N	
Drop_priv	enum('N','Y')	NO		N	
Reload_priv	enum('N','Y')	NO		N	
Shutdown_priv	enum('N','Y')	NO		N	
Process_priv	enum('N','Y')	NO		N	
File_priv	enum('N','Y')	NO		N	
Grant_priv	enum('N','Y')	NO		N	
References_priv	enum('N','Y')	NO		N	
Index_priv	enum('N','Y')	NO		N	
Alter_priv	enum('N','Y')	NO		N	
Show_db_priv	enum('N','Y')	NO		N	
Super_priv	enum('N','Y')	NO		N	
Create_tmp_table_priv	enum('N','Y')	NO		N	
Lock_tables_priv	enum('N','Y')	NO		N	
Execute_priv	enum('N','Y')	NO		N	
Repl_slave_priv	enum('N','Y')	NO		N	
Repl_client_priv	enum('N','Y')	NO		N	
Create_view_priv	enum('N','Y')	NO		N	
Show_view_priv	enum('N','Y')	NO		N	
Create_routine_priv	enum('N','Y')	NO		N	
Alter_routine_priv	enum('N','Y')	NO		N	
Create_user_priv	enum('N','Y')	NO		N	
Event_priv	enum('N','Y')	NO		N	
Trigger_priv	enum('N','Y')	NO		N	
ssl_type	enum('', 'ANY', 'X509', 'SPECIFIED')	NO			
ssl_cipher	blob	NO		NULL	
x509_issuer	blob	NO		NULL	
x509_subject	blob	NO		NULL	
max_questions	int(11) unsigned	NO		0	
max_updates	int(11) unsigned	NO		0	
max_connections	int(11) unsigned	NO		0	
max_user_connections	int(11) unsigned	NO		0	

39 rows in set (0.07 sec)

**PRACTICA 2: (Crear una base de datos)**

Teclea la siguiente secuencia de comandos y realiza una tabla resumen en la que indiques que es lo que hace cada línea de código sql separado por punto y coma:

1. create database discosnet;
2. show databases;
3. use discosnet;
4. CREATE TABLE discos  
(  
id disco INT unsigned auto\_increment not null primary key,  
nombre tinytext,  
interprete tinytext,  
cds tinyint unsigned,  
precio float,  
stock smallint unsigned) ;
5. describe discos;
6. rename table discos to discosbackup;
7. show tables;
8. describe discosbackup;
9. create table prueba (id\_prueba int);
10. show tables;
11. insert into prueba (id\_prueba) values (1);
12. insert into prueba (id\_prueba) values (2);
13. insert into prueba (id\_prueba) values (3);
14. select \* from prueba;

```
mysql> show tables;
+-----+
| Tables_in_discosnet |
+-----+
| discosbackup         |
| prueba              |
+-----+
2 rows in set (0.00 sec)

mysql> insert into prueba (id_prueba) values (1);
Query OK, 1 row affected (0.00 sec)

mysql> insert into prueba (id_prueba) values (2);
Query OK, 1 row affected (0.00 sec)

mysql> insert into prueba (id_prueba) values (3);
Query OK, 1 row affected (0.00 sec)

mysql> select * from prueba;
+-----+
| id_prueba |
+-----+
| 1         |
| 2         |
| 3         |
+-----+
3 rows in set (0.00 sec)

mysql>
```

- 15.drop table prueba;
- 16.drop table discos;
- 17.drop database discosnet;

Database
information_schema
controlesc
ejercicio1
ejercicio5
jardineria
library
mysql
phpmyadmin
tienda
tienda_elec
ventas
veterinaria

### PRACTICA 3: (Crear e importar desde un script)

Coloca todos los comandos siguientes en un block de notas:

```
CREATE DATABASE EJERCICIO1;  
USE EJERCICIO1;  
CREATE TABLE departamentos (  
  dept_no TINYINT(2) NOT NULL,  
  dnombre VARCHAR(15),  
  loc VARCHAR(15)  
);
```

```
INSERT INTO departamentos VALUES (10,'CONTABILIDAD','SEVILLA');  
INSERT INTO departamentos VALUES (20,'INVESTIGACIÓN','MADRID');  
INSERT INTO departamentos VALUES (30,'VENTAS','BARCELONA');  
INSERT INTO departamentos VALUES (40,'PRODUCCIÓN','BILBAO');  
DESCRIBE DEPARTAMENTOS;
```

y guardalos en un archivo "archivo.sql en la carpeta raíz de tu memoria o disco duro, luego en mysql teclea "source c:\archivo.sql"

Verifica que se haya ejecutado. Envía por blackboard tu archivo sql y la pantalla de Windows en donde se ejecutó el script de sql.

```
mysql> source E:\archivo.sql;  
ERROR:  
Unknown command '\a'.  
Query OK, 1 row affected (0.04 sec)  
  
Database changed  
Query OK, 0 rows affected (0.11 sec)  
  
Query OK, 1 row affected (0.01 sec)  
  
Query OK, 1 row affected (0.00 sec)  
  
Query OK, 1 row affected (0.00 sec)  
  
Query OK, 1 row affected (0.00 sec)  
  
+-----+-----+-----+-----+-----+-----+  
| Field | Type      | Null | Key | Default | Extra |  
+-----+-----+-----+-----+-----+-----+  
| dept_no | tinyint(2) | NO   |     | NULL    |       |  
| dnombre | varchar(15) | YES  |     | NULL    |       |  
| loc     | varchar(15) | YES  |     | NULL    |       |  
+-----+-----+-----+-----+-----+-----+  
3 rows in set (0.04 sec)  
  
mysql> use ejercicio1  
Database changed  
mysql>  
mysql> select * from departamentos;  
+-----+-----+-----+  
| dept_no | dnombre      | loc      |  
+-----+-----+-----+  
| 10      | CONTABILIDAD | SEVILLA  |  
| 20      | INVESTIGACI | MADRID   |  
| 30      | VENTAS       | BARCELONA |  
| 40      | PRODUCCI    | BILBAO   |  
+-----+-----+-----+  
4 rows in set (0.00 sec)
```

Windows PowerShell

Copyright (C) Microsoft Corporation. Todos los derechos reservados.

Prueba la nueva tecnología PowerShell multiplataforma <https://aka.ms/pscore6>

```
PS C:\Users\182934> cd..
PS C:\Users> cd ..
PS C:\> E:
PS E:\> cd .\WEB_2\
PS E:\WEB_2> cd .\xampplite\
PS E:\WEB_2\xampplite> cd .\xampplite\
PS E:\WEB_2\xampplite\xampplite> cd .\mysql\
PS E:\WEB_2\xampplite\xampplite\mysql> cd .\bin\
PS E:\WEB_2\xampplite\xampplite\mysql\bin> ls
```

Directorio: E:\WEB\_2\xampplite\xampplite\mysql\bin

Mode	LastWriteTime	Length	Name
-a----	12/20/2009 1:00 AM	1649808	bug25714.exe
-a----	12/20/2009 1:00 AM	1353360	comp_err.exe
-a----	12/20/2009 1:00 AM	59024	echo.exe
-a----	12/20/2009 1:00 AM	1695888	libmysql.dll
-a----	8/18/2023 9:05 AM	5796	my.ini
-a----	12/20/2009 1:00 AM	1340048	my_print_defaults.exe
-a----	12/20/2009 1:00 AM	1494160	myisam_ftdump.exe
-a----	12/20/2009 1:00 AM	1618064	myisamchk.exe
-a----	12/20/2009 1:00 AM	1514128	myisamlog.exe
-a----	12/20/2009 1:00 AM	1533584	myisampack.exe
-a----	12/20/2009 1:00 AM	1744016	mysql.exe
-a----	12/20/2009 1:00 AM	2009232	mysql_client_test.exe
-a----	12/20/2009 1:00 AM	1396368	mysql_upgrade.exe
-a----	12/20/2009 1:00 AM	1683088	mysqladmin.exe
-a----	12/20/2009 1:00 AM	1735312	mysqlbinlog.exe
-a----	12/20/2009 1:00 AM	1678480	mysqlcheck.exe
-a----	12/20/2009 1:00 AM	6095504	mysqld.exe
-a----	12/20/2009 1:00 AM	1732240	mysqldump.exe
-a----	12/20/2009 1:00 AM	1675408	mysqlimport.exe
-a----	12/20/2009 1:00 AM	1729168	mysqlmanager.exe
-a----	12/20/2009 1:00 AM	1676944	mysqlshow.exe
-a----	12/20/2009 1:00 AM	1691792	mysqlslap.exe
-a----	12/20/2009 1:00 AM	1812624	mysqltest.exe
-a----	12/20/2009 1:00 AM	1314960	perror.exe
-a----	12/20/2009 1:00 AM	1334416	replace.exe
-a----	12/20/2009 1:00 AM	1309840	resolveip.exe

```
PS E:\WEB_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p
```

Enter password:

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 1

Server version: 5.1.41 Source distribution

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
mysql> select now();
```

```
+-----+  
| now() |  
+-----+  
| 2023-08-29 10:03:34 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> select version();
```

```
+-----+  
| version() |  
+-----+  
| 5.1.41 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> show databases
```

```
-> ;  
+-----+  
| Database |  
+-----+  
| information_schema |  
| controlesc |  
| ejercicio1 |  
| ejercicio5 |  
| jardineria |  
| library |  
| mysql |  
| phpmyadmin |  
| tienda |  
| tienda_elec |  
| ventas |  
| veterinaria |  
+-----+  
12 rows in set (0.10 sec)
```

```
mysql> use mysql
```

Database changed

```
mysql> show tables
```

```
-> ;  
+-----+  
| Tables_in_mysql |  
+-----+  
| columns_priv |  
| db |  
| event |  
| func |  
| general_log |  
| help_category |
```

```
| help_keyword      |
| help_relation    |
| help_topic       |
| host              |
| ndb_binlog_index |
| plugin           |
| proc             |
| procs_priv       |
| servers          |
| slow_log         |
| tables_priv      |
| time_zone        |
| time_zone_leap_second |
| time_zone_name   |
| time_zone_transition |
| time_zone_transition_type |
| user             |
```

+-----+  
23 rows in set (0.06 sec)

mysql> show fields from user;

Field	Type	Null	Key	Default	Extra
Host	char(60)	NO	PRI		
User	char(16)	NO	PRI		
Password	char(41)	NO			
Select_priv	enum('N','Y')	NO		N	
Insert_priv	enum('N','Y')	NO		N	
Update_priv	enum('N','Y')	NO		N	
Delete_priv	enum('N','Y')	NO		N	
Create_priv	enum('N','Y')	NO		N	
Drop_priv	enum('N','Y')	NO		N	
Reload_priv	enum('N','Y')	NO		N	
Shutdown_priv	enum('N','Y')	NO		N	
Process_priv	enum('N','Y')	NO		N	
File_priv	enum('N','Y')	NO		N	
Grant_priv	enum('N','Y')	NO		N	
References_priv	enum('N','Y')	NO		N	
Index_priv	enum('N','Y')	NO		N	
Alter_priv	enum('N','Y')	NO		N	
Show_db_priv	enum('N','Y')	NO		N	
Super_priv	enum('N','Y')	NO		N	
Create_tmp_table_priv	enum('N','Y')	NO		N	
Lock_tables_priv	enum('N','Y')	NO		N	
Execute_priv	enum('N','Y')	NO		N	
Repl_slave_priv	enum('N','Y')	NO		N	
Repl_client_priv	enum('N','Y')	NO		N	
Create_view_priv	enum('N','Y')	NO		N	
Show_view_priv	enum('N','Y')	NO		N	
Create_routine_priv	enum('N','Y')	NO		N	
Alter_routine_priv	enum('N','Y')	NO		N	
Create_user_priv	enum('N','Y')	NO		N	

Event_priv	enum('N','Y')	NO	N		
Trigger_priv	enum('N','Y')	NO	N		
ssl_type	enum('', 'ANY', 'X509', 'SPECIFIED')	NO			
ssl_cipher	blob	NO	NULL		
x509_issuer	blob	NO	NULL		
x509_subject	blob	NO	NULL		
max_questions	int(11) unsigned	NO	0		
max_updates	int(11) unsigned	NO	0		
max_connections	int(11) unsigned	NO	0		
max_user_connections	int(11) unsigned	NO	0		

-----+-----+-----+-----+  
39 rows in set (0.07 sec)

mysql> exit;

Bye

PS E:\WEB\_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p

Enter password:

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 2

Server version: 5.1.41 Source distribution

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql> create databases discosnet;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'databases discosnet' at line 1

mysql> create database discosnet;

Query OK, 1 row affected (0.06 sec)

mysql> use discosnet;

Database changed

mysql> create table discos(iddisco INT unsigned auto\_increment not null primary key,

-> nombre tinytext,

-> interprete tinytext,

-> cds tinyint unsigned,

-> precio float,

-> stock smallint unsigned;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'auto\_increment not null primary key,

nombre tinytext,

interprete tinytext,

cds' at line 1

mysql> create table discos(iddisco INT unsigned auto\_increment not null primary key,

-> ;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'auto\_increment not null primary key,' at line 1

mysql> 4.CREATE TABLE discos

-> (

-> iddisco INT unsigned auto\_increment not null primary key,

-> nombre tinytext,

-> interprete tinytext,



```

-> cds tinyint unsigned,
-> precio float,
-> stock smallint unsigned) ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '4.CREATE TABLE discos
(
iddisco INT unsigned auto_increment not null primary key' at line 1
mysql> CREATE TABLE discos
-> (
-> iddisco INT unsigned auto_increment not null primary key,
-> nombre tinytext,
-> interprete tinytext,
-> cds tinyint unsigned,
-> precio float,
-> stock smallint unsigned) ;
Query OK, 0 rows affected (0.13 sec)

```

```

mysql> describes discos;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'describes discos' at line 1
mysql> describe discos;

```

Field	Type	Null	Key	Default	Extra
iddisco	int(10) unsigned	NO	PRI	NULL	auto_increment
nombre	tinytext	YES		NULL	
interprete	tinytext	YES		NULL	
cds	tinyint(3) unsigned	YES		NULL	
precio	float	YES		NULL	
stock	smallint(5) unsigned	YES		NULL	

6 rows in set (0.07 sec)

```

mysql> rename table discos to discosbackup;
Query OK, 0 rows affected (0.05 sec)

```

```

mysql> show tables;
+-----+
| Tables_in_discosnet |
+-----+
| discosbackup        |
+-----+
1 row in set (0.00 sec)

```

```

mysql> describe discosbackup;

```

Field	Type	Null	Key	Default	Extra
iddisco	int(10) unsigned	NO	PRI	NULL	auto_increment
nombre	tinytext	YES		NULL	
interprete	tinytext	YES		NULL	
cds	tinyint(3) unsigned	YES		NULL	
precio	float	YES		NULL	

```
| stock      | smallint(5) unsigned | YES | | NULL | |
+-----+-----+-----+-----+-----+
6 rows in set (0.05 sec)
```

```
mysql> create table prueba(id_prueba int);
Query OK, 0 rows affected (0.13 sec)
```

```
mysql> show tables;
+-----+
| Tables_in_discosnet |
+-----+
| discosbackup        |
| prueba              |
+-----+
2 rows in set (0.00 sec)
```

```
mysql> insert into prueba (id_prueba) values (1);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into prueba (id_prueba) values (2);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> insert into prueba (id_prueba) values (3);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from prueba;
+-----+
| id_prueba |
+-----+
| 1         |
| 2         |
| 3         |
+-----+
3 rows in set (0.00 sec)
```

```
mysql> drop table prueba;
Query OK, 0 rows affected (0.08 sec)
```

```
mysql> drop table discos;
ERROR 1051 (42S02): Unknown table 'discos'
mysql> drop table discosbackup;
Query OK, 0 rows affected (0.04 sec)
```

```
mysql> drop database discosnet;
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> show databases
-> ;
+-----+
| Database |
+-----+
| information_schema |
| controlesc        |
```

```
| ejercicio1 |
| ejercicio5 |
| jardineria |
| library |
| mysql |
| phpmyadmin |
| tienda |
| tienda_elec |
| ventas |
| veterinaria |
+-----+
```

12 rows in set (0.00 sec)

mysql> source E:\archivo.sql;

ERROR:

Unknown command '\a'.

ERROR 1007 (HY000): Can't create database 'ejercicio1'; database exists

Database changed

ERROR 1050 (42S01): Table 'departamentos' already exists

Query OK, 1 row affected (0.02 sec)

Query OK, 1 row affected (0.00 sec)

Query OK, 1 row affected (0.00 sec)

Query OK, 1 row affected (0.00 sec)

```
+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| dept_no | tinyint(2) | NO   |     | NULL    |       |
| dnombre | varchar(15) | YES  |     | NULL    |       |
| loc     | varchar(15) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```

3 rows in set (0.05 sec)

mysql> use ejercicio1

Database changed

mysql> show tables;

```
+-----+
| Tables_in_ejercicio1 |
+-----+
| departamentos        |
+-----+
```

1 row in set (0.00 sec)

mysql> select \* from departamentos;

```
+-----+-----+-----+
| dept_no | dnombre      | loc      |
+-----+-----+-----+
| 10 | CONTABILIDAD | SEVILLA |
| 20 | INVESTIGACI | MADRID  |
| 30 | VENTAS       | BARCELONA |
```

```
| 40 | PRODUCCI | ðN | BILBAO |
| 10 | CONTABILIDAD | SEVILLA |
| 20 | INVESTIGACI | ðN | MADRID |
| 30 | VENTAS | BARCELONA |
| 40 | PRODUCCI | ðN | BILBAO |
```

```
+-----+-----+-----+
```

8 rows in set (0.00 sec)

```
mysql> drop database ejercicio1;
Query OK, 1 row affected (0.10 sec)
```

```
mysql> source E:\archivo.sql;
ERROR:
Unknown command '\a'.
Query OK, 1 row affected (0.04 sec)
```

```
Database changed
Query OK, 0 rows affected (0.11 sec)
```

```
Query OK, 1 row affected (0.01 sec)
```

```
Query OK, 1 row affected (0.00 sec)
```

```
Query OK, 1 row affected (0.00 sec)
```

```
Query OK, 1 row affected (0.00 sec)
```

```
+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| dept_no | tinyint(2) | NO   |     | NULL    |       |
| dnombre | varchar(15) | YES  |     | NULL    |       |
| loc     | varchar(15) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```

3 rows in set (0.04 sec)

```
mysql> use ejercicio1
Database changed
mysql>
mysql> select * from departamentos;
```

```
+-----+-----+-----+
| dept_no | dnombre      | loc    |
+-----+-----+-----+
| 10 | CONTABILIDAD | SEVILLA | |
| 20 | INVESTIGACI | ðN | MADRID |
| 30 | VENTAS      | BARCELONA |
| 40 | PRODUCCI | ðN | BILBAO |
+-----+-----+-----+
```

4 rows in set (0.00 sec)

```
mysql> show databases
-> ;
```

```
+-----+
```

```
| Database      |
+-----+
| information_schema |
| controlesc      |
| ejercicio1      |
| ejercicio5      |
| jardineria      |
| library         |
| mysql           |
| phpmyadmin      |
| tienda          |
| tienda_elec     |
| ventas          |
| veterinaria     |
+-----+
12 rows in set (0.00 sec)
```

```
mysql> Windows PowerShell
-> Copyright (C) Microsoft Corporation. Todos los derechos reservados.
->
-> Prueba la nueva tecnología PowerShell multiplataforma https://aka.ms/pscore6
->
-> PS C:\Users\182934> cd..
ERROR:
Unknown command '\U'.
ERROR:
Unknown command '\1'.
-> PS C:\Users> cd ..
ERROR:
Unknown command '\U'.
-> PS C:\> E:
ERROR:
Unknown command '\>'.
-> PS E:\> cd .\WEB_2\
ERROR:
Unknown command '\>'.
Show warnings enabled.
-> PS E:\WEB_2> cd .\xampplite\
Show warnings enabled.
ERROR:
Unknown command '\x'.
-> PS E:\WEB_2\xampplite> cd .\xampplite\
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
-> PS E:\WEB_2\xampplite\xampplite> cd .\mysql\
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
```

```
ERROR:
Unknown command '\m'.
-> PS E:\WEB_2\xampplite\xampplite\mysql> cd .\bin\
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\m'.
ERROR:
Unknown command '\b'.
-> PS E:\WEB_2\xampplite\xampplite\mysql\bin> ls
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\m'.
ERROR:
Unknown command '\b'.
->
->
-> Directorio: E:\WEB_2\xampplite\xampplite\mysql\bin
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\m'.
ERROR:
Unknown command '\b'.
->
->
-> Mode                LastWriteTime         Length Name
-> ----                -
-> -a----      12/20/2009  1:00 AM       1649808 bug25714.exe
-> -a----      12/20/2009  1:00 AM       1353360 comp_err.exe
-> -a----      12/20/2009  1:00 AM         59024 echo.exe
-> -a----      12/20/2009  1:00 AM       1695888 libmysql.dll
-> -a----       8/18/2023  9:05 AM         5796 my.ini
-> -a----      12/20/2009  1:00 AM       1340048 my_print_defaults.exe
-> -a----      12/20/2009  1:00 AM       1494160 myisam_ftdump.exe
-> -a----      12/20/2009  1:00 AM       1618064 myisamchk.exe
-> -a----      12/20/2009  1:00 AM       1514128 myisamlog.exe
-> -a----      12/20/2009  1:00 AM       1533584 myisampack.exe
-> -a----      12/20/2009  1:00 AM       1744016 mysql.exe
-> -a----      12/20/2009  1:00 AM       2009232 mysql_client_test.exe
-> -a----      12/20/2009  1:00 AM       1396368 mysql_upgrade.exe
-> -a----      12/20/2009  1:00 AM       1683088 mysqladmin.exe
-> -a----      12/20/2009  1:00 AM       1735312 mysqlbinlog.exe
```

# UNIVERSIDAD POLITÉCNICA DE SAN LUIS POTOSÍ

```
-> -a---- 12/20/2009 1:00 AM 1678480 mysqlcheck.exe
-> -a---- 12/20/2009 1:00 AM 6095504 mysqld.exe
-> -a---- 12/20/2009 1:00 AM 1732240 mysqldump.exe
-> -a---- 12/20/2009 1:00 AM 1675408 mysqlimport.exe
-> -a---- 12/20/2009 1:00 AM 1729168 mysqlmanager.exe
-> -a---- 12/20/2009 1:00 AM 1676944 mysqlshow.exe
-> -a---- 12/20/2009 1:00 AM 1691792 mysqlslap.exe
-> -a---- 12/20/2009 1:00 AM 1812624 mysqltest.exe
-> -a---- 12/20/2009 1:00 AM 1314960 perror.exe
-> -a---- 12/20/2009 1:00 AM 1334416 replace.exe
-> -a---- 12/20/2009 1:00 AM 1309840 resolveip.exe
->
->
-> PS E:\WEB_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\m'.
ERROR:
Unknown command '\b'.
ERROR:
Unknown command '\m'.
-> Enter password:
-> Welcome to the MySQL monitor. Commands end with ; or \g.
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Windows PowerShell
Copyright (C) Microsoft Corporation. Todos los derechos reser' at line 1
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'or' at line 1
-> Your MySQL connection id is 1
-> Server version: 5.1.41 Source distribution
->
-> Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
->
-> mysql> select now();
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '.
Your MySQL connection id is 1
Server version: 5.1.41 Source distribution

Type' at line 1
mysql> +-----+
-> | now()      |
-> +-----+
-> | 2023-08-29 10:03:34 |
-> +-----+
-> 1 row in set (0.00 sec)
->
-> mysql> select version();
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '+-----+

```
| now() |
+-----+
| 2023-0' at line 1
mysql> +-----+
-> | version() |
-> +-----+
-> | 5.1.41 |
-> +-----+
-> 1 row in set (0.00 sec)
->
-> mysql> show databases
-> -> ;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '+-----+

```
| version() |
+-----+
| 5.1.41 |
+-----+
1 row in s' at line 1
mysql> +-----+
-> | Database |
-> +-----+
-> | information_schema |
-> | controlesc |
-> | ejercicio1 |
-> | ejercicio5 |
-> | jardineria |
-> | library |
-> | mysql |
-> | phpmyadmin |
-> | tienda |
-> | tienda_elec |
-> | ventas |
-> | veterinaria |
-> +-----+
-> 12 rows in set (0.10 sec)
->
-> mysql> use mysql
-> Database changed
-> mysql> show tables
-> -> ;
```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '+-----+

```
| Database |
+-----+
| informati' at line 1
mysql> +-----+
-> | Tables_in_mysql |
-> +-----+
-> | columns_priv |
-> | db |
```



```

-> | event          |
-> | func           |
-> | general_log    |
-> | help_category  |
-> | help_keyword   |
-> | help_relation  |
-> | help_topic     |
-> | host           |
-> | ndb_binlog_index |
-> | plugin         |
-> | proc           |
-> | procs_priv     |
-> | servers        |
-> | slow_log       |
-> | tables_priv    |
-> | time_zone      |
-> | time_zone_leap_second |
-> | time_zone_name |
-> | time_zone_transition |
-> | time_zone_transition_type |
-> | user           |

```

```

-> +-----+
-> 23 rows in set (0.06 sec)

```

```

->
-> mysql> show fields from user;

```

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '+-----+'  
| Tables\_in\_mysql |

```

+-----' at line 1
mysql>

```

```

mysql> +-----+
-> | Field          | Type          | Null | Key | Default | Extra |
-> +-----+-----+-----+-----+-----+-----+
-> | Host           | char(60)      | NO   | PRI |         |       |
-> | User           | char(16)      | NO   | PRI |         |       |
-> | Password       | char(41)      | NO   |     |         |       |
-> | Select_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Insert_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Update_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Delete_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Create_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Drop_priv      | enum('N','Y') | NO   |     | N       |       |
-> | Reload_priv    | enum('N','Y') | NO   |     | N       |       |
-> | Shutdown_priv  | enum('N','Y') | NO   |     | N       |       |
-> | Process_priv   | enum('N','Y') | NO   |     | N       |       |
-> | File_priv      | enum('N','Y') | NO   |     | N       |       |
-> | Grant_priv     | enum('N','Y') | NO   |     | N       |       |
-> | References_priv | enum('N','Y') | NO   |     | N       |       |
-> | Index_priv     | enum('N','Y') | NO   |     | N       |       |
-> | Alter_priv     | enum('N','Y') | NO   |     | N       |       |
-> | Show_db_priv   | enum('N','Y') | NO   |     | N       |       |
-> | Super_priv     | enum('N','Y') | NO   |     | N       |       |
-> | Create_tmp_table_priv | enum('N','Y') | NO   |     | N       |       |
-> | Lock_tables_priv | enum('N','Y') | NO   |     | N       |       |

```

# UNIVERSIDAD POLITÉCNICA --- DE SAN LUIS POTOSÍ

```

-> | Execute_priv      | enum('N','Y')          | NO | | N | | |
-> | Repl_slave_priv   | enum('N','Y')          | NO | | N | | |
-> | Repl_client_priv  | enum('N','Y')          | NO | | N | | |
-> | Create_view_priv  | enum('N','Y')          | NO | | N | | |
-> | Show_view_priv    | enum('N','Y')          | NO | | N | | |
-> | Create_routine_priv | enum('N','Y')          | NO | | N | | |
-> | Alter_routine_priv | enum('N','Y')          | NO | | N | | |
-> | Create_user_priv   | enum('N','Y')          | NO | | N | | |
-> | Event_priv        | enum('N','Y')          | NO | | N | | |
-> | Trigger_priv      | enum('N','Y')          | NO | | N | | |
-> | ssl_type           | enum('', 'ANY', 'X509', 'SPECIFIED') | NO | | | | |
-> | ssl_cipher         | blob                   | NO | | NULL | | |
-> | x509_issuer        | blob                   | NO | | NULL | | |
-> | x509_subject       | blob                   | NO | | NULL | | |
-> | max_questions     | int(11) unsigned       | NO | | 0 | | |
-> | max_updates        | int(11) unsigned       | NO | | 0 | | |
-> | max_connections   | int(11) unsigned       | NO | | 0 | | |
-> | max_user_connections | int(11) unsigned      | NO | | 0 | | |
-> +-----+-----+-----+-----+-----+
-> 39 rows in set (0.07 sec)
->
-> mysql> exit;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+-----+-----+-----+-----+
-----+-----+-----+-----' at line 1
mysql> Bye
-> PS E:\WEB_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p
Show warnings enabled.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\x'.
ERROR:
Unknown command '\m'.
ERROR:
Unknown command '\b'.
ERROR:
Unknown command '\m'.
-> Enter password:
-> Welcome to the MySQL monitor. Commands end with ; or \g.
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Bye
PS E:\WEB_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p' at line 1
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'or' at line 1
-> Your MySQL connection id is 2
-> Server version: 5.1.41 Source distribution
->
-> Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
->
-> mysql> create databases discosnet;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '

```

Your MySQL connection id is 2  
Server version: 5.1.41 Source distribution

Type' at line 1

mysql> ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'databases discosnet' at line 1

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'ERROR 1064 (42000): You have an error in your SQL syntax' at line 1

-> mysql> create database discosnet;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'the manual that corresponds to your MySQL server version for the right syntax to' at line 1

mysql> Query OK, 1 row affected (0.06 sec)

->

-> mysql> use discosnet;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'Query OK, 1 row affected (0.06 sec)

mysql> use discosnet' at line 1

mysql> Database changed

-> mysql> create table discos(iddisco INT unsigned auto\_increment not null primary key,

-> -> nombre tinytext,

-> -> interprete tinytext,

-> -> cds tinyint unsigned,

-> -> precio float,

-> -> stock smallint unsigned;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'Database changed

mysql> create table discos(iddisco INT unsigned auto\_incrementen' at line 1

mysql> ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'auto\_increment not null primary key,

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'ERROR 1064 (42000): You have an error in your SQL syntax' at line 1

'> nombre tinytext,

'> interprete tinytext,

'> cds' at line 1

-> mysql> create table discos(iddisco INT unsigned auto\_increment not null primary key,

-> -> ;

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'the manual that corresponds to your MySQL server version for the right syntax to' at line 1

mysql> ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'auto\_increment not null primary key,' at line 1

ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'ERROR 1064 (42000): You have an error in your SQL syntax' at line 1

-> mysql> 4.CREATE TABLE discos

-> -> (

```

-> -> iddisco INT unsigned auto_increment not null primary key,
-> -> nombre tinytext,
-> -> interprete tinytext,
-> -> cds tinyint unsigned,
-> -> precio float,
-> -> stock smallint unsigned) ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'the manual that corresponds to your
MySQL server version for the right syntax to' at line 1
mysql> ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near '4.CREATE TABLE
discos
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'ERROR 1064 (42000): You have an
error in your SQL syntax' at line 1
'> (
'> iddisco INT unsigned auto_increment not null primary key' at line 1
-> mysql> CREATE TABLE discos
-> -> (
-> -> iddisco INT unsigned auto_increment not null primary key,
-> -> nombre tinytext,
-> -> interprete tinytext,
-> -> cds tinyint unsigned,
-> -> precio float,
-> -> stock smallint unsigned) ;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'the manual that corresponds to your
MySQL server version for the right syntax to' at line 1
mysql> Query OK, 0 rows affected (0.13 sec)
->
-> mysql> describes discos;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.13 sec)

mysql> describes discos' at line 1
mysql> ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that
corresponds to your MySQL server version for the right syntax to use near 'describes discos' at line
1
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'ERROR 1064 (42000): You have an
error in your SQL syntax' at line 1
-> mysql> describe discos;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'the manual that corresponds to your
MySQL server version for the right syntax to' at line 1
mysql> +-----+-----+-----+-----+-----+-----+
-> | Field      | Type                | Null | Key | Default | Extra          |
-> +-----+-----+-----+-----+-----+-----+
-> | iddisco    | int(10) unsigned    | NO   | PRI | NULL    | auto_increment |
-> | nombre     | tinytext            | YES  |     | NULL    |                |
-> | interprete | tinytext            | YES  |     | NULL    |                |
-> | cds        | tinyint(3) unsigned | YES  |     | NULL    |                |
-> | precio     | float               | YES  |     | NULL    |                |

```

```

-> | stock      | smallint(5) unsigned | YES | | NULL | |
-> +-----+-----+-----+-----+-----+-----+
-> 6 rows in set (0.07 sec)
->
-> mysql> rename table discos to discosbackup;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+-----+-----+-----+
+-----+-----+
| ' at line 1
mysql> Query OK, 0 rows affected (0.05 sec)
->
-> mysql> show tables;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.05 sec)

mysql> show tables' at line 1
mysql> +-----+
-> | Tables_in_discosnet |
-> +-----+
-> | discosbackup      |
-> +-----+
-> 1 row in set (0.00 sec)
->
-> mysql> describe discosbackup;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+
| Tables_in_discosnet |
+-----+
| discos' at line 1
mysql> +-----+-----+-----+-----+-----+-----+
-> | Field      | Type                | Null | Key | Default | Extra      |
-> +-----+-----+-----+-----+-----+-----+
-> | iddisco    | int(10) unsigned    | NO   | PRI | NULL    | auto_increment |
-> | nombre     | tinytext            | YES  |     | NULL    |                |
-> | interprete | tinytext            | YES  |     | NULL    |                |
-> | cds        | tinyint(3) unsigned | YES  |     | NULL    |                |
-> | precio     | float               | YES  |     | NULL    |                |
-> | stock      | smallint(5) unsigned | YES  |     | NULL    |                |
-> +-----+-----+-----+-----+-----+-----+
-> 6 rows in set (0.05 sec)
->
-> mysql> create table prueba(id_prueba int);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+-----+-----+-----+
+-----+-----+
| ' at line 1
mysql> Query OK, 0 rows affected (0.13 sec)
->
-> mysql> show tables;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.13 sec)

mysql> show tables' at line 1

```

```
mysql> +-----+
-> | Tables_in_discosnet |
-> +-----+
-> | discosbackup      |
-> | prueba            |
-> +-----+
-> 2 rows in set (0.00 sec)
->
-> mysql> insert into prueba (id_prueba) values (1);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+'
| Tables_in_discosnet |
+-----+
| discos' at line 1
mysql> Query OK, 1 row affected (0.00 sec)
->
-> mysql> insert into prueba (id_prueba) values (2);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 1 row affected (0.00 sec)

mysql> insert into prueba (id_prueba) value' at line 1
mysql> Query OK, 1 row affected (0.00 sec)
->
-> mysql> insert into prueba (id_prueba) values (3);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 1 row affected (0.00 sec)

mysql> insert into prueba (id_prueba) value' at line 1
mysql> Query OK, 1 row affected (0.00 sec)
->
-> mysql> select * from prueba;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 1 row affected (0.00 sec)

mysql> select * from prueba' at line 1
mysql> +-----+
-> | id_prueba |
-> +-----+
-> |      1 |
-> |      2 |
-> |      3 |
-> +-----+
-> 3 rows in set (0.00 sec)
->
-> mysql> drop table prueba;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+'
| id_prueba |
+-----+
|      1 |
|      2 |
|      ' at line 1
mysql> Query OK, 0 rows affected (0.08 sec)
```

```
->
-> mysql> drop table discos;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.08 sec)
```

```
mysql> drop table discos' at line 1
mysql> ERROR 1051 (42S02): Unknown table 'discos'
-> mysql> drop table discosbackup;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'ERROR 1051 (42S02): Unknown
table 'discos'
mysql> drop table discosbackup' at line 1
mysql> Query OK, 0 rows affected (0.04 sec)
```

```
->
-> mysql> drop database discosnet;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.04 sec)
```

```
mysql> drop database discosnet' at line 1
mysql> Query OK, 0 rows affected (0.05 sec)
```

```
->
-> mysql> show databases
-> ->;
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near 'Query OK, 0 rows affected (0.05 sec)
```

```
mysql> show databases
->' at line 1
mysql> +-----+
-> | Database      |
-> +-----+
-> | information_schema |
-> | controlesc      |
-> | ejercicio1      |
-> | ejercicio5      |
-> | jardineria      |
-> | library         |
-> | mysql           |
-> | phpmyadmin      |
-> | tienda          |
-> | tienda_elec     |
-> | ventas          |
-> | veterinaria     |
-> +-----+
-> 12 rows in set (0.00 sec)
->
-> mysql> source E:\archivo.sql;
```

```
ERROR:
Unknown command '\a'.
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds
to your MySQL server version for the right syntax to use near '+-----+
| Database      |
+-----+
```



| informati' at line 1

mysql> ERROR:

-> Unknown command '\a'.

-> ERROR 1007 (HY000): Can't create database 'ejercicio1'; database exists

'> Database changed

'> ERROR 1050 (42S01): Table 'departamentos' already exists

'> Query OK, 1 row affected (0.02 sec)

'>

'> Query OK, 1 row affected (0.00 sec)

'>

'> Query OK, 1 row affected (0.00 sec)

'>

'> Query OK, 1 row affected (0.00 sec)

'>

'> +-----+-----+-----+-----+-----+

'> | Field | Type | Null | Key | Default | Extra |

'> +-----+-----+-----+-----+-----+

'> | dept\_no | tinyint(2) | NO | | NULL | |

'> | dnombre | varchar(15) | YES | | NULL | |

'> | loc | varchar(15) | YES | | NULL | |

'> +-----+-----+-----+-----+-----+

'> 3 rows in set (0.05 sec)

'>

'> mysql> use ejercicio1

'> Database changed

'> mysql> show tables;

'> +-----+

'> | Tables\_in\_ejercicio1 |

'> +-----+

'> | departamentos |

'> +-----+

'> 1 row in set (0.00 sec)

'>

'> mysql> select \* from departamentos;

'> +-----+-----+-----+

'> | dept\_no | dnombre | loc |

'> +-----+-----+-----+

'> | 10 | CONTABILIDAD | SEVILLA |

'> | 20 | INVESTIGACI | ðN | MADRID |

'> | 30 | VENTAS | BARCELONA |

'> | 40 | PRODUCCI | ðN | BILBAO |

'> | 10 | CONTABILIDAD | SEVILLA |

'> | 20 | INVESTIGACI | ðN | MADRID |

'> | 30 | VENTAS | BARCELONA |

'> | 40 | PRODUCCI | ðN | BILBAO |

'> +-----+-----+-----+

'> 8 rows in set (0.00 sec)

'>

'> mysql> drop database ejercicio1;

'> Query OK, 1 row affected (0.10 sec)

'>

'> mysql> source E:\archivo.sql;

'> ERROR:



```

> Unknown command '\a'.
ERROR:
Unknown command '\a'.
> Query OK, 1 row affected (0.04 sec)
>
> Database changed
> Query OK, 0 rows affected (0.11 sec)
>
> Query OK, 1 row affected (0.01 sec)
>
> Query OK, 1 row affected (0.00 sec)
>
> Query OK, 1 row affected (0.00 sec)
>
> Query OK, 1 row affected (0.00 sec)
>
> +-----+-----+-----+-----+-----+
> | Field | Type      | Null | Key | Default | Extra |
> +-----+-----+-----+-----+-----+
> | dept_no | tinyint(2) | NO   |     | NULL    |      |
> | dnombre | varchar(15) | YES  |     | NULL    |      |
> | loc     | varchar(15) | YES  |     | NULL    |      |
> +-----+-----+-----+-----+-----+
> 3 rows in set (0.04 sec)
>
> mysql> use ejercicio1
> Database changed
> mysql>
> mysql> select * from departamentos;
> +-----+-----+-----+
> | dept_no | dnombre      | loc      |
> +-----+-----+-----+
> | 10 | CONTABILIDAD | SEVILLA |
> | 20 | INVESTIGACI | MADRID  |
> | 30 | VENTAS       | BARCELONA |
> | 40 | PRODUCTOS   | BILBAO  |
> +-----+-----+-----+
> 4 rows in set (0.00 sec)
>
> mysql> show databases
> -> ;
> +-----+
> | Database |
> +-----+
> | information_schema |
> | controlesc         |
> | ejercicio1         |
> | ejercicio5         |
> | jardineria         |
> | library            |
> | mysql              |
> | phpmyadmin         |
> | tienda            |

```

```
'> | tienda_elec      |  
'> | ventas           |  
'> | veterinaria       |  
'> +-----+  
'> 12 rows in set (0.00 sec)
```

```
'>  
'> mysql>
```

```
'>  
'>  
'>  
'> ;  
'>  
'>  
'>  
'>  
'>  
'>  
'>  
'>
```

```
'> Ctrl-C -- exit!
```

Bye

PS E:\WEB\_2\xampplite\xampplite\mysql\bin> .\mysql.exe -h localhost -u root -p

Enter password:

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 3

Server version: 5.1.41 Source distribution

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

mysql>