

# **MAI 5100: Fundamentals of Artificial Intelligence**

Instructor: Dr. Christopher Clarke

## Overview & Agenda (week 4)

- **Reminder:** HW0 is due on Mar 25 @ 11:59 PM
- **Last week:** Constraint Satisfaction Problems
  - Backtracking Search
  - Forward Checking
  - Arc Consistency

# Overview & Agenda (week 4)

- **This week** Constraint Satisfaction Problems Continued
  - Variable Ordering
    - Minimum Remaining Values (MRV)
    - Least Constraining Value (LCV)
  - K Consistency
  - Structured CSPs
    - Tree-Structured CSPs
    - Non-Tree-Structured CSPs

# Overview & Agenda (week 4)


- **Tentative:**

- Another makeup class on March 24, No class on March 29
  - Will try to avoid so you can focus on HW0 but if I cannot find another time, we will have to do it
- Local Search
  - Hill Climbing
  - Simulated Annealing
  - Genetic Algorithms
- Adversarial Search
  - Minimax
  - Alpha-Beta Pruning

# Reminder: CSPs


- CSPs:

- Variables
- Domains
- Constraints
  - Implicit (provide code to compute)
  - Explicit (provide a list of the legal tuples)
  - Unary / Binary / N-ary



- Goals:

- Here: find any solution
- Also: find all, find best, etc.



# Backtracking Search

```
function BACKTRACKING-SEARCH(csp) returns solution/failure
  return RECURSIVE-BACKTRACKING({ }, csp)

function RECURSIVE-BACKTRACKING(assignment, csp) returns soln/failure
  if assignment is complete then return assignment
  var ← SELECT-UNASSIGNED-VARIABLE(VARIABLES[csp], assignment, csp)
  for each value in ORDER-DOMAIN-VALUES(var, assignment, csp) do
    if value is consistent with assignment given CONSTRAINTS[csp] then
      add {var = value} to assignment
      result ← RECURSIVE-BACKTRACKING(assignment, csp)
      if result ≠ failure then return result
      remove {var = value} from assignment
  return failure
```


# Improving Backtracking

- General-purpose ideas give huge gains in speed
  - ... but it's all still NP-hard
- Filtering: Can we detect inevitable failure early?
- Ordering:
  - Which variable should be assigned next? (MRV)
  - In what order should its values be tried? (LCV)
- Structure: Can we exploit the problem structure?



# Arc Consistency and Beyond



---





# Arc Consistency of an Entire CSP

- A simple form of propagation makes sure **all** arcs are simultaneously consistent:



- Arc consistency detects failure earlier than forward checking
- Important: If X loses a value, neighbors of X need to be rechecked!
- Must rerun after each assignment!

*Remember: Delete  
from the tail!*

# Enforcing Arc Consistency in a CSP

```
function AC-3(csp) returns the CSP, possibly with reduced domains
inputs: csp, a binary CSP with variables  $\{X_1, X_2, \dots, X_n\}$ 
local variables: queue, a queue of arcs, initially all the arcs in csp

while queue is not empty do
     $(X_i, X_j) \leftarrow \text{REMOVE-FIRST}(\textit{queue})$ 
    if REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) then
        for each  $X_k$  in NEIGHBORS[ $X_i$ ] do
            add  $(X_k, X_i)$  to queue



---





function REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) returns true iff succeeds
    removed  $\leftarrow$  false
    for each  $x$  in DOMAIN[ $X_i$ ] do
        if no value  $y$  in DOMAIN[ $X_j$ ] allows  $(x, y)$  to satisfy the constraint  $X_i \leftrightarrow X_j$ 
            then delete  $x$  from DOMAIN[ $X_i$ ]; removed  $\leftarrow$  true
    return removed
```

- Runtime:  $O(n^2d^3)$ , can be reduced to  $O(n^2d^2)$
- ... but detecting all possible future problems is NP-hard – why?

# Limitations of Arc Consistency

- After enforcing arc consistency:
  - Can have one solution left
  - Can have multiple solutions left
  - Can have no solutions left (and not know it)
- Arc consistency still runs inside a backtracking search!



*What went  
wrong here?*

# Ordering




# Ordering: Minimum Remaining Values

- Variable Ordering: Minimum remaining values (MRV):
  - Choose the variable with the fewest legal left values in its domain





- Why min rather than max?
- Also called “most constrained variable”
- “Fail-fast” ordering



# Ordering: Least Constraining Value

- Value Ordering: Least Constraining Value
  - Given a choice of variable, choose the *least constraining value*
  - I.e., the one that rules out the fewest values in the remaining variables
  - Note that it may take some computation to determine this! (E.g., rerunning filtering)
- Why least rather than most?
- Combining these ordering ideas makes 1000 queens feasible




# Demo: Coloring -- Backtracking + Forward Checking + Ordering

---

# K-Consistency



---





# K-Consistency

- Increasing degrees of consistency
  - 1-Consistency (Node Consistency): Each single node's domain has a value which meets that node's unary constraints
  - 2-Consistency (Arc Consistency): For each pair of nodes, any consistent assignment to one can be extended to the other
  - K-Consistency: For each k nodes, any consistent assignment to k-1 can be extended to the k<sup>th</sup> node.
- Higher k more expensive to compute
- (You need to know the k=2 case: arc consistency)




# Strong K-Consistency

---


- Strong k-consistency: also k-1, k-2, ... 1 consistent
- Claim: strong n-consistency means we can solve without backtracking!
- Why?
  - Choose any assignment to any variable
  - Choose a new variable
  - By 2-consistency, there is a choice consistent with the first
  - Choose a new variable
  - By 3-consistency, there is a choice consistent with the first 2
  - ...
- Lots of middle ground between arc consistency and n-consistency! (e.g. k=3, called path consistency)

# Structure




# Problem Structure

- Extreme case: independent subproblems
  - Example: Tasmania and mainland do not interact
- Independent subproblems are identifiable as connected components of constraint graph
- Suppose a graph of  $n$  variables can be broken into subproblems of only  $c$  variables:
  - Worst-case solution cost is  $O((n/c)(d^c))$ , linear in  $n$
  - E.g.,  $n = 80$ ,  $d = 2$ ,  $c = 20$
  - $2^{80} = 4$  billion years at 10 million nodes/sec
  - $(4)(2^{20}) = 0.4$  seconds at 10 million nodes/sec




# Tree-Structured CSPs




- Theorem: if the constraint graph has no loops, the CSP can be solved in  $O(n d^2)$  time
  - Compare to general CSPs, where worst-case time is  $O(d^n)$
- This property also applies to probabilistic reasoning (later): an example of the relation between syntactic restrictions and the complexity of reasoning

# Tree-Structured CSPs

- Algorithm for tree-structured CSPs:
  - Order: Choose a root variable, order variables so that parents precede children




- Remove backward: For  $i = n : 2$ , apply  $\text{RemoveInconsistent}(\text{Parent}(X_i), X_i)$
  - Assign forward: For  $i = 1 : n$ , assign  $X_i$  consistently with  $\text{Parent}(X_i)$
- Runtime:  $O(n d^2)$  (why?)



# Tree-Structured CSPs

- Claim 1: After backward pass, all root-to-leaf arcs are consistent
- Proof: Each  $X \rightarrow Y$  was made consistent at one point and  $Y$ 's domain could not have been reduced thereafter (because  $Y$ 's children were processed before  $Y$ )




- Claim 2: If root-to-leaf arcs are consistent, forward assignment will not backtrack
- Proof: Induction on position
- Why doesn't this algorithm work with cycles in the constraint graph?
- Note: we'll see this basic idea again with Bayes' nets

# Improving Structure





# Nearly Tree-Structured CSPs



- Conditioning: instantiate a variable, prune its neighbors' domains
- Cutset conditioning: instantiate (in all ways) a set of variables such that the remaining constraint graph is a tree
- Cutset size  $c$  gives runtime  $O((d^c)(n-c)d^2)$ , very fast for small  $c$


# Cutset Conditioning

Choose a cutset

Instantiate the cutset  
(all possible ways)


Compute residual CSP  
for each assignment

Solve the residual CSPs  
(tree structured)





# Cutset Quiz

- Find the smallest cutset for the graph below.




# Tree Decomposition\*

- Idea: create a tree-structured graph of mega-variables
- Each mega-variable encodes part of the original CSP
- Subproblems overlap to ensure consistent solutions




# Iterative Improvement




# Iterative Algorithms for CSPs

- Local search methods typically work with “complete” states, i.e., all variables assigned
- To apply to CSPs:
  - Take an assignment with unsatisfied constraints
  - Operators *reassign* variable values
  - No fringe! Live on the edge.
- Algorithm: While not solved,
  - Variable selection: randomly select any conflicted variable
  - Value selection: min-conflicts heuristic:
    - Choose a value that violates the fewest constraints
    - I.e., hill climb with  $h(n)$  = total number of violated constraints




# Example: 4-Queens



- States: 4 queens in 4 columns ( $4^4 = 256$  states)
- Operators: move queen in column
- Goal test: no attacks
- Evaluation:  $c(n)$  = number of attacks

# Video of Demo Iterative Improvement – n Queens


---





# Video of Demo Iterative Improvement – Coloring



---



# Performance of Min-Conflicts


- Given random initial state, can solve n-queens in almost constant time for arbitrary n with high probability (e.g., n = 10,000,000)!
- The same appears to be true for any randomly-generated CSP *except* in a narrow range of the ratio

$$R = \frac{\text{number of constraints}}{\text{number of variables}}$$



# Summary: CSPs

- CSPs are a special kind of search problem:
  - States are partial assignments
  - Goal test defined by constraints
- Basic solution: backtracking search
- Speed-ups:
  - Ordering
  - Filtering
  - Structure
- Iterative min-conflicts is often effective in practice




# Local Search

---



# Local Search

- Tree search keeps unexplored alternatives on the fringe (ensures completeness)
- Local search: improve a single option until you can't make it better (no fringe!)
- New successor function: local changes




- Generally much faster and more memory efficient (but incomplete and suboptimal)

# Hill Climbing


- Simple, general idea:
  - Start wherever
  - Repeat: move to the best neighboring state
  - If no neighbors better than current, quit
- What's bad about this approach?
  - Complete?
  - Optimal?
- What's good about it?



# Hill Climbing Diagram



# Hill Climbing Quiz



Starting from X, where do you end up ?

Starting from Y, where do you end up ?

Starting from Z, where do you end up ?




# Simulated Annealing

- Idea: Escape local maxima by allowing downhill moves
  - But make them rarer as time goes on


```
function SIMULATED-ANNEALING(problem, schedule) returns a solution state
  inputs: problem, a problem
           schedule, a mapping from time to “temperature”
  local variables: current, a node
                   next, a node
                   T, a “temperature” controlling prob. of downward steps

  current ← MAKE-NODE(INITIAL-STATE[problem])
  for t ← 1 to ∞ do
    T ← schedule[t]
    if T = 0 then return current
    next ← a randomly selected successor of current
     $\Delta E \leftarrow \text{VALUE}[\textit{next}] - \text{VALUE}[\textit{current}]$ 
    if  $\Delta E > 0$  then current ← next
    else current ← next only with probability  $e^{\Delta E / T}$ 
```





# Simulated Annealing

- Theoretical guarantee:
  - Stationary distribution:  $p(x) \propto e^{-\frac{E(x)}{kT}}$
  - If T decreased slowly enough, will converge to optimal state!
- Is this an interesting guarantee?
- Sounds like magic, but reality is reality:
  - The more downhill steps you need to escape a local optimum, the less likely you are to ever make them all in a row
  - People think hard about *ridge operators* which let you jump around the space in better ways




# Genetic Algorithms



- Genetic algorithms use a natural selection metaphor
  - Keep best N hypotheses at each step (selection) based on a fitness function
  - Also have pairwise crossover operators, with optional mutation to give variety
- Possibly the most misunderstood, misapplied (and even maligned) technique around


# Example: N-Queens



- Why does crossover make sense here?
- When wouldn't it make sense?
- What would mutation be?
- What would a good fitness function be?

# CS 188: Artificial Intelligence


## Adversarial Search




Instructors: Dan Klein and Pieter Abbeel  
University of California, Berkeley

# Game Playing State-of-the-Art

- **Checkers:** 1950: First computer player. 1994: First computer champion: Chinook ended 40-year-reign of human champion Marion Tinsley using complete 8-piece endgame. 2007: Checkers solved!
- **Chess:** 1997: Deep Blue defeats human champion Gary Kasparov in a six-game match. Deep Blue examined 200M positions per second, used very sophisticated evaluation and undisclosed methods for extending some lines of search up to 40 ply. Current programs are even better, if less historic.
- **Go:** Human champions are now starting to be challenged by machines, though the best humans still beat the best machines. In go,  $b > 300$ ! Classic programs use pattern knowledge bases, but big recent advances use Monte Carlo (randomized) expansion methods.
- **Pacman**




# Behavior from Computation



# Video of Demo Mystery Pacman


---






# Adversarial Games

---




# Types of Games

- Many different kinds of games!
- Axes:
  - Deterministic or stochastic?
  - One, two, or more players?
  - Zero sum?
  - Perfect information (can you see the state)?
- Want algorithms for calculating a **strategy (policy)** which recommends a move from each state




# Deterministic Games

- Many possible formalizations, one is:
  - States:  $S$  (start at  $s_0$ )
  - Players:  $P=\{1\dots N\}$  (usually take turns)
  - Actions:  $A$  (may depend on player / state)
  - Transition Function:  $S \times A \rightarrow S$
  - Terminal Test:  $S \rightarrow \{t, f\}$
  - Terminal Utilities:  $S \times P \rightarrow R$
- Solution for a player is a **policy**:  $S \rightarrow A$



# Zero-Sum Games




## ■ Zero-Sum Games

- Agents have opposite utilities (values on outcomes)
- Lets us think of a single value that one maximizes and the other minimizes
- Adversarial, pure competition


## ■ General Games

- Agents have independent utilities (values on outcomes)
- Cooperation, indifference, competition, and more are all possible
- More later on non-zero-sum games

# Adversarial Search




# Single-Agent Trees



# Value of a State

Value of a state:  
The best achievable  
outcome (utility)  
from that state




Non-Terminal States:

$$V(s) = \max_{s' \in \text{children}(s)} V(s')$$

Terminal States:

$$V(s) = \text{known}$$

# Adversarial Game Trees






# Minimax Values

States Under Agent's Control:

$$V(s) = \max_{s' \in \text{successors}(s)} V(s')$$

States Under Opponent's Control:


$$V(s') = \min_{s \in \text{successors}(s')} V(s)$$



Terminal States:


$$V(s) = \text{known}$$

# Tic-Tac-Toe Game Tree



# Adversarial Search (Minimax)

- **Deterministic, zero-sum games:**
  - Tic-tac-toe, chess, checkers
  - One player maximizes result
  - The other minimizes result
- **Minimax search:**
  - A state-space search tree
  - Players alternate turns
  - Compute each node's **minimax value**: the best achievable utility against a rational (optimal) adversary



# Minimax Implementation

def max-value(state):


    initialize  $v = -\infty$

    for each successor of state:

$v = \max(v, \text{min-value}(\text{successor}))$

    return  $v$

$$V(s) = \max_{s' \in \text{successors}(s)} V(s')$$



def min-value(state):

    initialize  $v = +\infty$

    for each successor of state:

$v = \min(v, \text{max-value}(\text{successor}))$

    return  $v$

$$V(s') = \min_{s \in \text{successors}(s')} V(s)$$

# Minimax Implementation (Dispatch)

```
def value(state):
```

if the state is a terminal state: return the state's utility

if the next agent is MAX: return max-value(state)

if the next agent is MIN: return min-value(state)

```
def max-value(state):
```

initialize  $v = -\infty$

for each successor of state:

$v = \max(v, \text{value}(\text{successor}))$

return  $v$

```
def min-value(state):
```

initialize  $v = +\infty$


for each successor of state:

$v = \min(v, \text{value}(\text{successor}))$

return  $v$


# Minimax Example

---






# Minimax Efficiency

- How efficient is minimax?
  - Just like (exhaustive) DFS
  - Time:  $O(b^m)$
  - Space:  $O(bm)$
- Example: For chess,  $b \approx 35$ ,  $m \approx 100$ 
  - Exact solution is completely infeasible
  - But, do we need to explore the whole tree?



# Minimax Properties




Optimal against a perfect player. Otherwise?




# Video of Demo Min vs. Exp (Min)

---



# Video of Demo Min vs. Exp (Exp)

---




# Resource Limits



# Resource Limits

- Problem: In realistic games, cannot search to leaves!
- Solution: Depth-limited search
  - Instead, search only to a limited depth in the tree
  - Replace terminal utilities with an evaluation function for non-terminal positions
- Example:
  - Suppose we have 100 seconds, can explore 10K nodes / sec
  - So can check 1M nodes per move
  - $\alpha$ - $\beta$  reaches about depth 8 – decent chess program
- Guarantee of optimal play is gone
- More plies makes a BIG difference
- Use iterative deepening for an anytime algorithm




# Depth Matters

- Evaluation functions are always imperfect
- The deeper in the tree the evaluation function is buried, the less the quality of the evaluation function matters
- An important example of the tradeoff between complexity of features and complexity of computation




# Video of Demo Limited Depth (2)

---




# Video of Demo Limited Depth (10)

---



# Evaluation Functions


---





# Evaluation Functions

- Evaluation functions score non-terminals in depth-limited search




- Ideal function: returns the actual minimax value of the position
- In practice: typically weighted linear sum of features:

$$Eval(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

- e.g.  $f_1(s) = (\text{num white queens} - \text{num black queens})$ , etc.


# Evaluation for Pacman




[Demo: thrashing  $d=2$ , thrashing  $d=2$  (fixed evaluation function), smart ghosts coordinate (L6D6,7,8,10)]

# Video of Demo Thrashing (d=2)

---



# Why Pacman Starves




- A danger of replanning agents!

- He knows his score will go up by eating the dot now (west, east)
- He knows his score will go up just as much by eating the dot later (east, west)
- There are no point-scoring opportunities after eating the dot (within the horizon, two here)
- Therefore, waiting seems just as good as eating: he may go east, then back west in the next round of replanning!


# Video of Demo Thrashing -- Fixed ( $d=2$ )

---




# Video of Demo Smart Ghosts (Coordination)

---




# Video of Demo Smart Ghosts (Coordination) – Zoomed In

---




# Game Tree Pruning






# Minimax Example

---




# Minimax Pruning



# Alpha-Beta Pruning

- General configuration (MIN version)
  - We're computing the MIN-VALUE at some node  $n$
  - We're looping over  $n$ 's children
  - $n$ 's estimate of the childrens' min is dropping
  - Who cares about  $n$ 's value? MAX
  - Let  $a$  be the best value that MAX can get at any choice point along the current path from the root
  - If  $n$  becomes worse than  $a$ , MAX will avoid it, so we can stop considering  $n$ 's other children (it's already bad enough that it won't be played)
- MAX version is symmetric



# Alpha-Beta Implementation


$\alpha$ : MAX's best option on path to root  
 $\beta$ : MIN's best option on path to root

```
def max-value(state,  $\alpha$ ,  $\beta$ ):  
    initialize  $v = -\infty$   
    for each successor of state:  
         $v = \max(v, \text{value}(\text{successor}, \alpha, \beta))$   
        if  $v \geq \beta$  return  $v$   
         $\alpha = \max(\alpha, v)$   
    return  $v$ 
```


```
def min-value(state,  $\alpha$ ,  $\beta$ ):  
    initialize  $v = +\infty$   
    for each successor of state:  
         $v = \min(v, \text{value}(\text{successor}, \alpha, \beta))$   
        if  $v \leq \alpha$  return  $v$   
         $\beta = \min(\beta, v)$   
    return  $v$ 
```

# Alpha-Beta Pruning Properties


- This pruning has **no effect** on minimax value computed for the root!
- Values of intermediate nodes might be wrong
  - Important: children of the root may have the wrong value
  - So the most naïve version won't let you do action selection
- Good child ordering improves effectiveness of pruning
- With “perfect ordering”:
  - Time complexity drops to  $O(b^{m/2})$
  - Doubles solvable depth!
  - Full search of, e.g. chess, is still hopeless...
- This is a simple example of **metareasoning** (computing about what to compute)



# Alpha-Beta Quiz



# Alpha-Beta Quiz 2



# Next Time: Uncertainty!

---