



**PRECISION STEEL GROUTS**




## Features



**Excellent Early  
Strengthening**



**Non-shrink Grout**




**Self-compactable**

**SG 2 FLOWABLE**  
**HIGH PERFORMANCE GROUT**

## AREAS OF APPLICATION


**JSW Steel Grout SG 2** is a cementitious highly flow-able non shrink high strength grout for precision application like repair RCC Structures, heavy machinery foundations etc.



Turbine Generator Bearings



Boiler Foundations



Columns in precast crane

## 8 BENEFITS

- High early strength and highly flow able
- Highly Durable
- Non Expansive
- Non Shrink
- High Compressive, flexural & Tensile Strength
- Early loading
- Self-Compacting
- High Bond Strength

## BEST BEFORE

6 months from the date of manufacturing if stored in unopened original packing, under shaded area in dry and moisture free conditions.

## COVERAGE & CLASS

- Yield about 11 litre per 25 kg bag
- 80 MPa Grout complying to ASTM C 1107/1107M: 20 & CRD-C-621-83

## Compressive Strength, MPa (IS 4031 Part 6)

1 Day	Minimum 25
3 Days	Minimum 50
7 Days	Minimum 65
28 Days	Minimum 80
Expansion	Nil

## TECHNICAL SPECIFICATIONS

Properties	Results
Appearance	Free Flowing Powder
Color	Cementitious Grey
Water/ Powder Ratio	0.13 – 0.15
Flow on Table @ 30°C in mm	Min. 260 mm
Fresh Wet Density, Kg/m <sup>3</sup>	2200 – 2400
Initial Setting Time, Minutes	> 200
Final Setting Time, Minutes	< 600
Pot Life @ 30°C	45 – 60 minutes

## PACK SIZE

25 kg



**JSW Cement**

World's No.1 Eco Friendly Cement Company

MARKETED BY: JSW Green Cement Pvt. Ltd.

Babukhan Millenium Centre, 6-3-1099/1100, No. 702, Block-A, Somajiguda, Hyderabad, Telangana, India, Pincode - 500 082.

Email: [info@jswcement.in](mailto:info@jswcement.in) | Website: [www.jswcement.in](http://www.jswcement.in) | Toll free - 18002662661

SCAN HERE FOR TDS



SCAN HERE



SG 2 FLOWABLE

PRECISION STEEL GROUTS